Demo Client · DEMO-0013
13 November 2026 · v1.0

Agent specification

> Demonstration: the evaluation used a simulated model; the specification is the one a client receives.

Agent: message triage for customer email triage and replies · **Model:** `claude-opus-5-5` at effort `low` · **Confidence bar:** 0.90

1. The job, in one line

Read one customer message, name the request, copy the order number, flag urgency and draft a reply; never send anything itself.

2. Input

The message text after masking: e-mail addresses, phone numbers, card numbers and bank accounts are replaced by `[EMAIL]`, `[PHONE]`, `[CARD]` and `[IBAN]` before the request leaves the client's platform. No customer name or account is sent.

3. Output

One JSON object, enforced by the API's structured output against this schema:

Field	Type	Meaning
`intent`	string	order_status, return_request, refund_status, product_question, complaint, invoice_request, address_change, cancel_order, other
`confidence`	number	0 to 1: how sure the intent is right
`order_id`	string	The order number as written (SO-123456), or empty
`urgent`	boolean	
`language`	string	ISO code of the customer's language
`summary`	string	One sentence for the person who reads it next
`reply_draft`	string	A reply in the customer's language; never promises money, dates or exceptions

4. What happens next (the policy)

The route is decided by fixed rules on the platform, in this order: an engine error, refusal or unreadable answer goes to a manager; an unknown request goes to the owning team; an urgent message goes to a manager; otherwise the request type's own route applies, and an automatic reply below the confidence bar becomes a draft for review.

Request type	The customer	Route
order_status	asks where an order is or when it arrives	auto

Request type	The customer	Route
return_request	wants to send an item back	review
refund_status	asks about a refund already due	review
product_question	asks about a product before or after buying	auto
complaint	is unhappy with the service and wants it put right	escalate
invoice_request	asks for an invoice or tax document	auto
address_change	asks to change a delivery address	review
cancel_order	asks to cancel an order	review
other	anything else	route

5. The instructions the model reads

```
You read one customer message for an online retailer and return a JSON answer that a routing step will act

Choose exactly one intent:
- order_status: the customer asks where an order is or when it arrives
- return_request: the customer wants to send an item back
- refund_status: the customer asks about a refund already due
- product_question: the customer asks about a product before or after buying
- complaint: the customer is unhappy with the service and wants it put right
- invoice_request: the customer asks for an invoice or tax document
- address_change: the customer asks to change a delivery address
- cancel_order: the customer asks to cancel an order
- other: the customer anything else

Set confidence honestly: below 0.9 whenever the message could reasonably be another intent, mixes two reques
Mark urgent when the customer is angry, threatens to complain elsewhere, or reports being charged wrongly.
Copy the order number exactly as written (for example SO-123456); leave it empty if there is none. Never inv
Personal details in the message have been replaced by tags such as [EMAIL] or [PHONE]; never ask the custome

The reply draft:
- Reply in the customer's language, in three sentences or fewer, polite and plain.
- Never promise a refund, a delivery date, compensation or an exception; say a colleague will confirm.
- Never give legal, medical or financial advice.
- If the message is a complaint, apologise and say a manager will contact them today.
```

6. Request settings

- Structured output (`output_config.format` , JSON schema above); effort `low` ; the instructions are cached between calls.
- Server-side refusal fallback (`server-side-fallback-2026-07-01` , `fallbacks: "default"`): if the model declines on policy grounds, the API retries on a fallback model; a final refusal goes to a manager.
- The API key is the client's own, stored in the platform's credential store, never in a file of this pack.

7. If the AI is switched off

`fallback/rules.json` routes messages by keywords alone. Nothing is answered automatically in that mode; every message reaches a person or a team with its request type.

8. Files in the automation pack

- `README.md`
- `fallback/mask.js`
- `fallback/masking_patterns.json`
- `fallback/rules.json`
- `golden_set.csv`
- `make/BUILD_GUIDE.md`
- `n8n/ai_triage_workflow.json`
- `policy.yaml`
- `power_automate/BUILD_GUIDE.md`
- `prompt/output_schema.json`
- `prompt/request_body.json`
- `prompt/system_prompt.txt`
- `zapier/BUILD_GUIDE.md`

9. Changing the agent

Any change to the instructions, the model, the effort or the confidence bar is re-tested on `golden_set.csv` first, and goes live only if every go-live test still passes.