

National University of Computer and Emerging Sciences, Lahore Campus



Course:	Computer Programming	Course Code:	CS103
Program:	BS(Computer Science)	Semester:	Fall 2018
Duration:	45 Minutes	Total Marks:	30
Paper Date:	21-Dec-2018	Weight	10
Section:	All	Page(s):	3
Exam:	Final – Part I	Roll No:	
		Section	

- Instructions:**
- Attempt Part I in the space provided in this sheet.
 - Questions during exam are not allowed. Take reasonable assumptions where needed.

Question [10x3 = 30 Marks] For the code segments given below, determine the output/error(s). If there is any error, highlight the exact line that will cause the error.

Part(i)

```
class Date{
private:
    static int day;
    static int month;
    static int year;
public:
    Date(int d=1, int m =1 , int y = 2000){
        day = d; month = m; year = y;
    }
    void Print(){
        cout<<day<<" - "<<month<<" - "<<year<<endl;
    }
}; //end of Date class

class Student{
private:
```

```
void Print()
{
    cout<<name<<"\t";
    dateOfBirth.Print();
    for(int i=0 ; i<5; i++){
        cout<<marks[i]<<"
";
    }
    cout<<endl;
}

~Student(){
    if(marks != 0)
        delete[] marks;
}

}; //end of student class

int Date::day = 1;
```

<pre> char name[20]; Date dateOfBirth; static int* marks; public: Student(char* n = "", int d=1, int m=1, int y=2000, int* _marks = 0):dateOfBirth(d,m,y) { strcpy(name, n); if(_marks != 0){ marks = new int[5]; for(int i=0 ; i<5; i++){ marks[i] = _marks[i]; } } else marks = 0; } </pre>	<pre> int Date::month = 1; int Date::year = 2000; int* Student::marks = 0; void main() { int size = 5; int marks1[5] = {90, 80, 20, 30 , 60}; int marks2[5] = {40, 50, 60, 70 , 80}; Student s1("Ali", 20,2,1999, marks1); Student s2("Hamza", 5,1,1998, marks2); s1.Print(); s2.Print(); } </pre>
--	--

Output/Error:

Ali 5-1-1998

40 50 60 70 80

Hamza 5-1-1998

40 50 60 70 80

Error:

- 1- Line: delete[] marks; // Static data being deleted multiple times
- 2- Line: marks = new int[5]; // Memory Leakage

Part(ii)

<pre> class B{ private: int* bptr; public: B(int b=10){bptr = new int(b);} virtual int GetValue(){ return *bptr; } virtual ~B(){ cout<<"~B() "; if(bptr != 0) delete bptr; } }; class D1 : public B{ private:` int* dptr1; public: D1(int d1=20){dptr1 = new int(d1);} int GetValue(){ return (B::GetValue() + *dptr1); } void Print(){ cout<<"*dptr1 = "<<*dptr1<<endl; } ~D1(){ cout<<"~D1() "; if(dptr1 != 0) delete dptr1; } }; </pre>	<pre> GC(int gc=40) :*{ gcPtr = new int(gc); } int GetValue(){ return (D1::GetValue() + *gcPtr); } void Print(){ cout<<"*gcptr = "<<*gcPtr<<endl; } ~GC(){ cout<<"~GC() "; if(gcPtr != 0) delete gcPtr; } }; void main() { B* arr[4]; arr[0] = new B(1); arr[1] = new D1(2); arr[2] = new D2(3); arr[3] = new GC(4); for(int i=0; i<4 ; i++) { cout<<arr[i]->GetValue()<<" , "; } cout<<endl; for(int i = 0 ; i<4 ; i++) { </pre>
---	---

<pre> class D2 : public B { private: int* dptr2; public: D2(int d2=30){ dptr2 = new int(d2); } int GetValue(){ return (B::GetValue() + *dptr2); } ~D2(){ cout<<"~D2() "; if(dptr2 != 0) delete dptr2; } }; class GC : public D1{ private: int* gcPtr; public: </pre>	<pre> delete arr[i]; cout<<endl; } cout<<"-----\n"; D1* arr2[2]; arr2[0] = new D1(100); arr2[1] = new GC(500); for(int i = 0 ; i<2 ; i++) arr2[i]->Print(); for(int i = 0 ; i<2 ; i++) { delete arr2[i]; cout<<endl; } } </pre>
--	--

Output/Error:

1, 12, 13, 28

~B()

~D1() ~B()

~D2() ~B()

~GC() ~D1() `B()

*dptr1 = 100

*dptr1 = 510

~D1() ~B()

~GC() ~D1() ~B()

Part(iii)

```
void RecFun(int* arr, int start, int end)
{
    if(end > start+1)
    {
        int mid = (start+end)/2; //int(4.5) = 4
        cout<<"mid = "<<mid<<"\t arr[mid] = "<<arr[mid]<<endl;
        if(arr[mid]%2 == 0)
        {
            RecFun(arr, start, mid-1);
            cout<<"Value = "<<arr[mid]<<endl;
            return;
        }
        else
        {
            RecFun(arr, mid+1, end);
        }
        for(int i=start; i<mid; i++)
            cout<<arr[i]<<",";
        cout<<endl;
    }
}

void main()
{
    int arr1[] = {1,2,6,9,5,7,12,8,9,10};
    RecFun(arr1, 0, 9);
}
```

Output/Error:

```
Mid = 4          arr[mid] = 5
Mid = 7          arr[mid] = 8
Value = 8
```

1, 2, 6, 9