


CS 302 DESIGN AND ANALYSIS OF ALGORITHMS**MID 1 FALL 2016****Date: 19th Sept, 2016.****Total Marks: 40****Time: 60 min**

NOTE: Answer in the provided space. You can get extra sheets only for rough work. They will NOT be collected.

QUESTION 1 [4*5 = 20 marks] Following is a modified version of merge sort. It uses the same merge function as studied in class.

```
void mergeSort(int A, int p, int s){
    if(p<s){
        int one3rd=(s-p+1)/3;
        int q=p+one3rd;
        int r=p+2*one3rd;
        mergeSort(A,p,q);
        mergeSort(A,q+1,r);
        mergeSort(A,r+1,s);
        merge(A,p,q,r);
        merge(A,p,r,s);
    }
}
```

- a) Draw a tree to show the division of the problem by this algorithm. Show the values of parameters p and s at each call. The first call in the main is: mergeSort(A, 0, 26)



- b) Write down a recurrence relation $T(n)$, with base case $T(1)$ to describe the running time of this modified version of merge sort.

- c) Solve the recurrence in (b) to get an asymptotic upper bound (big-Oh bound).

- d) Based on the result in (c), if you were given a choice to use either regular merge sort or this version, which one will you choose and why? An answer without a reason will not get any points.

Roll Number: _____

Section: _____

QUESTION 2 [20 marks] Write an algorithm to take union of two sets of numbers, i.e. two arrays A, B of integers. Since these are sets, the numbers are distinct in each array, however, they could contain common elements. Make your algorithm as asymptotically efficient as possible.

Algorithm (in English):

C++ code