

Rajalakshmi Engineering College

Name: Abdul Majeed
Email: 240701004@rajalakshmi.edu.in
Roll no: 240701004
Phone: 9150030311
Branch: REC
Department: CSE - Section 4
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 11

Attempt : 1
Total Mark : 20
Marks Obtained : 20

Section 1 : Project

1. Problem Statement

Create a JDBC-based Inventory Management System that handles runtime input to manage items in an inventory. The system should allow users to:

Add a new item (item ID, name, quantity, price).

Restock an item by increasing its quantity.

Reduce the stock of an item, ensuring sufficient quantity.

Display all items in the inventory in a sorted order by item ID.

Exit the application.

Half of the code is given here; Only the remaining part should be completed.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri_db

USER: test

PWD: test123

The items table has already been created with the following structure:

Table Name: items

Input Format

The first line of input consists of an integer choice, representing the operation to be performed (1 for Add Item, 2 for Restock item, 3 for reduce item, 4 for Display, 5 for Exit).

For choice 1 (Add Item):

- The second line consists of an integer item_id.
- The third line consists of a string name.
- The fourth line consists of an integer quantity.
- The fifth line consists of a double price.

For choice 2 (Restock Item):

- The second line consists of an integer item_id.
- The third line consists of an integer quantity_to_add (must be positive).

For choice 3 (Reduce Stock):

- The second line consists of an integer item_id.
- The third line consists of an integer quantity_to_remove (must be positive).

For choice 4 (Display Inventory):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

Output Format

For choice 1 (Add Item):

- Print "Item added successfully" if the item was added.
- Print "Failed to add item." if the insertion failed.

For choice 2 (Restock Item):

- Print "Item restocked successfully" if the restock was successful.
- Print "Item not found." if the specified item ID does not exist.

For choice 3 (Reduce Stock):

- Print "Stock reduced successfully" if the stock reduction was successful.
- Print "Not enough stock to remove." if there is insufficient quantity.
- Print "Item not found." if the specified item ID does not exist.

For choice 4 (Display Inventory):

- Display each item on a new line in the format:
- ID | Name | Quantity | Price
- If no items are available, print nothing (or handle with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Inventory Management System."

For invalid input:

- Print "Invalid choice. Please try again."

Sample Test Case

Input: 1

101

Laptop

50

1200.00

4

5

Output: Item added successfully

ID | Name | Quantity | Price

101 | Laptop | 50 | 1200.00

Exiting Inventory Management System.

Answer

```
import java.sql.*;
```

```
import java.util.Scanner;
```

```
class InventoryManagementSystem {
```

```
    public static void main(String[] args) {
```

```
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://localhost/ri_db", "test", "test123");
```

```
            Scanner scanner = new Scanner(System.in)) {
```

```
        boolean running = true;
```

```
        while (running) {
```

```
            int choice = scanner.nextInt();
```

```
            switch (choice) {
```

```
                case 1:
```

```
                    addItem(conn, scanner);
```

```
                    break;
```

```
                case 2:
```

```
                    restockItem(conn, scanner);
```

```
                    break;
```

```
                case 3:
```

```
                    reduceStock(conn, scanner);
```

```
                    break;
```

```
                case 4:
```

```
                    displayInventory(conn);
```

```
                    break;
```

```
                case 5:
```

```
                    System.out.println("Exiting Inventory Management System.");
```

```
                    running = false;
```

```
                    break;
```

```
            default:
```

```

        System.out.println("Invalid choice. Please try again.");
    }
}
} catch (SQLException e) {
    e.printStackTrace();
}
}

static void addItem(Connection conn, Scanner scanner) {
    int id = scanner.nextInt();
    scanner.nextLine();
    String name = scanner.nextLine();
    int qty = scanner.nextInt();
    double price = scanner.nextDouble();

    try {
        PreparedStatement ps = conn.prepareStatement(
            "INSERT INTO items(item_id, name, quantity, price) VALUES(?,?,?,?)");
        ps.setInt(1, id);
        ps.setString(2, name);
        ps.setInt(3, qty);
        ps.setDouble(4, price);

        int rows = ps.executeUpdate();
        if (rows > 0)
            System.out.println("Item added successfully");
        else
            System.out.println("Failed to add item.");
    } catch (SQLException e) {
        System.out.println("Failed to add item.");
    }
}

static void restockItem(Connection conn, Scanner scanner) {
    int id = scanner.nextInt();
    int addQty = scanner.nextInt();

    try {
        PreparedStatement ps = conn.prepareStatement("SELECT quantity FROM
items WHERE item_id=?");
        ps.setInt(1, id);
        ResultSet rs = ps.executeQuery();
    }
}

```

```

        if (!rs.next()) {
            System.out.println("Item not found.");
        } else {
            int newQty = rs.getInt(1) + addQty;

            PreparedStatement ps2 = conn.prepareStatement("UPDATE items SET
quantity=? WHERE item_id=?");
            ps2.setInt(1, newQty);
            ps2.setInt(2, id);
            ps2.executeUpdate();

            System.out.println("Item restocked successfully");
        }
    } catch (SQLException e) {
        System.out.println("Item not found.");
    }
}

```

```

static void reduceStock(Connection conn, Scanner scanner) {
    int id = scanner.nextInt();
    int removeQty = scanner.nextInt();

    try {
        PreparedStatement ps = conn.prepareStatement("SELECT quantity FROM
items WHERE item_id=?");
        ps.setInt(1, id);
        ResultSet rs = ps.executeQuery();

        if (!rs.next()) {
            System.out.println("Item not found.");
        } else {
            int currentQty = rs.getInt(1);

            if (currentQty < removeQty) {
                System.out.println("Not enough stock to remove.");
            } else {
                int newQty = currentQty - removeQty;

                PreparedStatement ps2 = conn.prepareStatement("UPDATE items
SET quantity=? WHERE item_id=?");
                ps2.setInt(1, newQty);
                ps2.setInt(2, id);
            }
        }
    }
}

```

```

        ps2.executeUpdate();

        System.out.println("Stock reduced successfully");
    }
}
} catch (SQLException e) {
    System.out.println("Item not found.");
}
}

static void displayInventory(Connection conn) {
    try {
        PreparedStatement ps = conn.prepareStatement("SELECT * FROM items
ORDER BY item_id");
        ResultSet rs = ps.executeQuery();

        System.out.println("ID | Name | Quantity | Price");

        while (rs.next()) {
            System.out.println(
                rs.getInt("item_id") + " | " +
                rs.getString("name") + " | " +
                rs.getInt("quantity") + " | " +
                String.format("%.2f", rs.getDouble("price"))
            );
        }
    } catch (SQLException e) {
        System.out.println("Error fetching data.");
    }
}
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

In Café Central, the menu is cataloged and stored in a database.

To efficiently manage the restaurant's menu using Java and JDBC, you

must build a Restaurant Management System that supports:

Adding new menu items

Updating menu item prices

Viewing details of a menu item

Displaying all menu items in sorted order

You are given two files:

File 1: MenuItem.java (POJO Class)

This class represents the MenuItem entity.

A MenuItem contains the following details:

Field	Description
itemId	Unique Menu Item ID (Integer)
name	Item Name (String)
category	Item Category (String)
price	Item Price (Double)

Students must write code in the marked area:

```
class MenuItem {  
    private int itemId;  
    private String name;  
    private String category;  
    private double price;  
  
    public MenuItem() {}  
  
    public MenuItem(int itemId, String name, String category, double price) {  
        // write your code here  
    }  
}
```



```
// Include getters and setters
```

Expected in this part:

Assign parameter values to instance variables inside the constructor.

Add getters and setters for all attributes.

File 2: MenuItemDAO.java (Data Access Layer)

This class handles all database operations using JDBC.

Students must complete the missing JDBC logic in the following methods:

```
class MenuItemDAO {  
  
    public void addItem(Connection conn, MenuItem menuItem)  
    throws SQLException {  
        // write your code here  
    }  
  
    public void updateItemPrice(Connection conn, int itemId, double  
    newPrice) throws SQLException {  
        // write your code here  
    }  
  
    public void deleteMenuItem(Connection conn, int itemId) throws  
    SQLException {  
        // write your code here  
    }  
  
    public MenuItem viewItemDetails(Connection conn, int itemId) throws  
    SQLException {  
        // write your code here  
    }  
}
```

```

    }

    public List<MenuItem> displayAllMenuItems(Connection conn) throws
SQLException {
        // write your code here
    }

    private MenuItem mapToMenuItem(ResultSet rs) throws SQLException {
        return new MenuItem(
            // write your code here
        );
    }
}

```

Expected in this part:

Write SQL queries for INSERT, UPDATE, DELETE, SELECT.

Execute queries using PreparedStatement or Statement.

Map ResultSet rows to MenuItem objects using mapToMenuItem().

Return a List<MenuItem> where required.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri_db

USER: test

PWD: test123

The menu table has already been created with the following structure:

Table Name: menu

Input Format

The first line of input consists of an integer choice, representing the operation to be performed (1 for Add Item, 2 for Restock item, 3 for reduce item, 4 for Display, 5 for Exit).

For choice 1 (Add Menu Item):

- The second line consists of an integer item_id.
- The third line consists of a string name.
- The fourth line consists of a string category.
- The fifth line consists of a double price.

For choice 2 (Update Item Price):

- The second line consists of an integer item_id.
- The third line consists of a double new_price.

For choice 3 (View Item Details):

- The second line consists of an integer item_id.

For choice 4 (Display All Menu Items):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

Output Format

For choice 1 (Add Menu Item):

- Print "Menu item added successfully" if the item was added.
- Print "Failed to add item." if the insertion failed.

For choice 2 (Update Item Price):

- Print "Item price updated successfully" if the price update was successful.
- Print "Item not found." if the specified item ID does not exist.

For choice 3 (View Item Details):

- Display the item details in the format:

- ID: [item_id] | Name: [name] | Category: [category] | Price: [price]
- Print "Item not found." if the specified item ID does not exist.

For choice 4 (Display All Menu Items):

- Display each item on a new line in the format:
- ID | Name | Category | Price
- If no items are available, print nothing (or handle with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Restaurant Management System."

For invalid input:

- Print "Invalid choice. Please try again."

Sample Test Case

Input: 1

11

Margherita Pizza

Main Course

12.99

4

5

Output: Menu item added successfully

ID | Name | Category | Price

11 | Margherita Pizza | Main Course | 12.99

Exiting Restaurant Management System.

Answer

```
import java.sql.*;
```

```
import java.util.Scanner;
```

```
class RestaurantManagementSystem {
```

```
    public static void main(String[] args) {
```

```
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://localhost/ri_db", "test", "test123"));
```

```
            Scanner scanner = new Scanner(System.in)) {
```

```
                boolean running = true;
```

```

while (running) {
    int choice = scanner.nextInt();

    switch (choice) {
        case 1:
            addMenuItem(conn, scanner);
            break;
        case 2:
            updateItemPrice(conn, scanner);
            break;
        case 3:
            viewItemDetails(conn, scanner);
            break;
        case 4:
            displayAllMenuItems(conn);
            break;
        case 5:
            System.out.println("Exiting Restaurant Management System.");
            running = false;
            break;
        default:
            System.out.println("Invalid choice. Please try again.");
    }
}
} catch (SQLException e) {
    e.printStackTrace();
}
}

public static void addMenuItem(Connection conn, Scanner scanner) {
    int item_id=scanner.nextInt();
    scanner.nextLine();
    String name =scanner.nextLine();
    String cat=scanner.nextLine();
    double price=scanner.nextDouble();

    String sql="INSERT into menu (item_id,name,category,price) values (?,?,,?)";
    try(PreparedStatement stat=conn.prepareStatement(sql)){
        stat.setInt(1,item_id);
        stat.setString(2,name);
        stat.setString(3,cat);
        stat.setDouble(4,price);
    }
}

```

```

        stat.executeUpdate();

        System.out.println("Menu item added successfully");
    }
    catch(Exception e){
        System.out.print(e.getMessage());
    }
}

public static void updateItemPrice(Connection conn, Scanner scanner) {
    int id=scanner.nextInt();
    double price=scanner.nextDouble();
    String sql="update menu set price=? where item_id=?";
    try(PreparedStatement stat=conn.prepareStatement(sql)){
        stat.setDouble(1,price);
        stat.setInt(2,id);

        int rowa=stat.executeUpdate();
        if(rowa>0){
            System.out.println("Item price updated successfully");
        }
        else
            System.out.println("Item not found");
    }
    catch(Exception e){
        System.out.print(e.getMessage());
    }
}

```

```

public static void viewItemDetails(Connection conn, Scanner scanner) {
    int n=scanner.nextInt();
    String sql="Select * from menu";

    try(PreparedStatement stat=conn.prepareStatement(sql)){

        ResultSet rs=stat.executeQuery();
        if(rs.next()){

            int id=rs.getInt("item_id");
            String name=rs.getString("name");

```

```
        String cat=rs.getString("category");
        double price=rs.getDouble("price");
        System.out.printf("ID: %d | Name: %s | Category: %s | Price: %.2f\n",id,name,cat,price);
    }
}
```

```
    catch(Exception e){
        System.out.print(e.getMessage());
    }
}
```

```
public static void displayAllMenuItems(Connection conn) {
    String sql="Select * from menu";
```

```
    try(PreparedStatement stat=conn.prepareStatement(sql)){
```

```
        ResultSet rs=stat.executeQuery();
        System.out.println("ID | Name | Category | Price");
        if(rs.next()){
            do{
                int id=rs.getInt("item_id");
                String name=rs.getString("name");
                String cat=rs.getString("category");
                double price=rs.getDouble("price");
                System.out.printf("%d | %s | %s | %.2f\n",id,name,cat,price);
            }while(rs.next());
        }
    }
}
```

```
    catch(Exception e){
        System.out.print(e.getMessage());
    }
}
```

```
class MenuItem {
    private int itemId;
    private String name;
    private String category;
    private double price;
```

```
public MenuItem(int itemId, String name, String category, double price) {  
    this.itemId = itemId;  
    this.name = name;  
    this.category = category;  
    this.price = price;  
}  
}
```

Status : Correct

Marks : 10/10