

<

Maze

MEDIUM

DIFFICULTY RATING

60 POINTS

NO CONNECTION REQUIRED

INFORMATION

ACTIVITY

CHANGELOG

REVIEWS

WALKTHROUGHS

SHARE RESULTS

Download Files

Necessary files to play the challenge.

ZIP PASSWORD

hackthebox

SHA-256

0e162616a252046e07390a2187ae2432e4609e4cb34c59238269d2567d14512a

Submit Flag

Submit a flag to this challenge.

Add To-Do List

Add this challenge to your list.

Review Challenge

Rate and send your feedback.

CHALLENGE DESCRIPTION

I am stuck in a maze. Can you lend me a hand to find the way out?

☆

4.5

CHALLENGE RATING

👤

432

USER SOLVES

↶↷

Reversing

CATEGORY

📅

531 Days

RELEASE DATE

!! d3vnu11

CHALLENGE CREATOR

GIVE RESPECT

📄

Challenge Flag

INCOMPLETE

🔪

0H 50M 43S

📦 rrrmpwn

FIRST BLOOD

Attached files : maze.exe , enc_maze.zip , maze.png

Step-by-Step Solution

1. Extract Python Files from Executable

Why: The executable is a PyInstaller bundle containing Python bytecode we need to analyze.

How:

```
# Use pyinstxtractor to unpack the executable
python3.8 pyinstxtractor.py maze.exe

# Output: Creates 'maze.exe_extracted' directory
```

2. Decompile Python Bytecode

Why: We need to recover the original Python logic.

How:

```
# Decompile main script
uncompyle6 maze.exe_extracted/maze.pyc > maze.py

# Decompile obfuscated module
uncompyle6 maze.exe_extracted/PYZ-00.pyz_extracted/obf_path.pyc > obf_path.py
```

Step	How	What made me try this
Identify the packer	`strings maze.exe	head` shows “PYZ” <i>and</i> “py” magic: dead giveaway it’s PyInstaller
Unpack	python pyinstxtractor.py maze.exe → creates maze.exe_extracted/ with tons of .pyc files	pyinstxtractor is my go-to because it keeps time-stamps and directory layout intact.
Decompile	uncompyle6 maze.pyc > maze.py and the same for obf_path.pyc	Reading source is faster than reading byte-code; plus I’m after hard-coded secrets.

Key Findings in maze.py :

- Password for ZIP: Y0u_Ar3_W4lkiNG_t0_Y0uR_D34TH
- Decryption logic modifies every 10th byte:
 1. Add 80 (mod 256)
 2. XOR with key (initially zeros)

3. Unpack Obfuscated Code

1. **Dump the blob** – I saved it as BLOB in obf_crack.py .
2. **Look for compression headers** – BLOB.find(b'\xfd7zXZ') locates an LZMA stream .
3. **LZMA → zlib → marshal** – The three-stage decompress recipe in obf_crack.py yields readable Python code .

Why: obf_path.py contains a marshaled blob we need to unpack.

How: Use obf_crack.py :

```
import lzma, zlib

BLOB = b'\xe3\x00...' # Full blob from obf_path.py

# Find LZMA header and decompress
start = BLOB.find(b'\xfd7zXZ')
lzma_block = BLOB[start:]
lzma_decompressed = lzma.decompress(lzma_block)

# ZLIB decompress
final_payload = zlib.decompress(lzma_decompressed)

with open("dec-obf_path.py", "wb") as f:
    f.write(final_payload)
```

Output: Heavily obfuscated Python with another marshaled blob.

4. Analyze Second Obfuscation Layer

Why: The new script contains critical seed logic.

How: Use `obf_crack2.py` to disassemble (use python3.8 again):

```
import marshal, dis

STAGE5 = b'\xe3\x00...' # Blob from dec_obf_path.py
code = marshal.loads(STAGE5)

def try_dis(obj, level=0):
    if isinstance(obj, types.CodeType):
        dis.dis(obj) # Disassemble bytecode
        # Recursively process constants
        for const in obj.co_consts:
            try_dis(const, level+1)

try_dis(code)
```

Key Findings:

1. Reads `maze.png`
2. Computes seed from bytes at offsets:
 - 4817
 - 2624
 - 2640
 - 2720
3. Seed = sum of these bytes

5. Compute the Seed

Why: The seed generates the decryption key.

How:

```
with open('maze.png', 'rb') as f:
    data = f.read()
    seed = data[4817] + data[2624] + data[2640] + data[2720]
print(seed) # Output: 493
```

6. Decrypt the Maze Binary

Why: The extracted `maze` file is encrypted.

How:

```
import random, pyzipper

# 1. Extract maze file from ZIP
with pyzipper.AESZipFile('enc_maze.zip') as zf:
    zf.pwd = b'Y0u_Ar3_W4lkiNG_t0_Y0uR_D34TH'
    zf.extract('maze')

# 2. Generate key using seed
random.seed(493)
key = [random.randint(32, 125) for _ in range(300)] # 300-byte key

# 3. Decrypt the binary
with open('maze', 'rb') as f:
    data = bytearray(f.read())

for i in range(0, len(data), 10):
    data[i] = (data[i] + 80) % 256 # First operation
    data[i] = (data[i] ^ key[i % 300]) % 256 # Second operation

with open('dec_maze.elf', 'wb') as f:
    f.write(data) # Output: Valid ELF binary
```

Why those two passes?

The original script added 80 before XORing with an all-zero key—a deliberate sabotage so the players thinks the algorithm is pointless. Re-inserting the proper key flips the switch and the output turns into a bona-fide ELF header (7F 45 4C 46).

7. Extract Encrypted Flag from ELF

Why: The flag is hidden in the binary's data section.

How:

```
with open('dec_maze.elf', 'rb') as f:
    elf = f.read()

# Find flag array using known header values
pattern = b'\xde\x00\x00\x00\x11\x01\x00\x00' # 222, 273 in little-endian
pos = elf.find(pattern)

# Extract 4-byte integers until invalid value
encrypted_flag = []
for i in range(0, 100*4, 4):
    val = int.from_bytes(elf[pos+i:pos+i+4], 'little')
    if val < 96 or val > 378: break # Valid range: 32*3 to 126*3
    encrypted_flag.append(val)
```

8. Reconstruct the Flag

Why: The flag is derived from triple-character sums.

How:

```
flag = [72, 84, 66] # 'H','T','B'

for i in range(1, len(encrypted_flag)):
    # Calculate next char: S[i] = flag[i] + flag[i+1] + flag[i+2]
    next_char = encrypted_flag[i] - flag[i] - flag[i+1]
    flag.append(next_char)

print('').join(chr(c) for c in flag) # Full flag
```

Final Solution Script

```
import pyzipper
import random
import struct

# Step 1: Extract maze file
with pyzipper.AESZipFile('enc_maze.zip') as zf:
    zf.pwd = b'Y0u_Ar3_W4lkiNG_t0_Y0uR_D34TH'
    zf.extract('maze')

# Step 2: Compute seed from maze.png
with open('maze.png', 'rb') as f:
    data = f.read()
seed = data[4817] + data[2624] + data[2640] + data[2720] # = 493

# Step 3: Generate key
random.seed(seed)
key = [random.randint(32, 125) for _ in range(300)]

# Step 4: Decrypt binary
with open('maze', 'rb') as f:
    data = bytearray(f.read())

for i in range(0, len(data), 10):
    data[i] = (data[i] + 80) % 256
    data[i] = (data[i] ^ key[i % len(key)]) % 256

with open('dec_maze.elf', 'wb') as f:
    f.write(data)

# Step 5: Extract flag array from ELF
with open('dec_maze.elf', 'rb') as f:
    elf = f.read()

pattern = b'\xde\x00\x00\x00\x11\x01\x00\x00' # 222, 273
pos = elf.find(pattern)
encrypted_flag = []

for i in range(0, 100*4, 4):
    if pos+i+4 > len(elf): break
    val = struct.unpack('<I', elf[pos+i:pos+i+4])[0]
    if val < 96 or val > 378: break
    encrypted_flag.append(val)

# Step 6: Reconstruct flag
flag = [72, 84, 66] # "HTB"

for i in range(1, len(encrypted_flag)):
    next_char = encrypted_flag[i] - flag[i] - flag[i+1]
    if not 32 <= next_char <= 126: break # Printable ASCII check
    flag.append(next_char)

print('FLAG:', ''.join(chr(c) for c in flag))
```

Output: HTB{w0W_Y0u_C0uld_E5c4p3_Th1s_M4Z33!!}

Maze

MEDIUM

DIFFICULTY RATING

50 POINTS

NO CONNECTION REQUIRED

INFORMATION

ACTIVITY

CHANGELOG

REVIEWS

WALKTHROUGHS

SHARE RESULTS

Download Files

Necessary files to play the challenge.

Submit Flag

Submit a flag to this challenge.

Add To-Do List

Add this challenge to your list.

Review Challenge

Rate and send your feedback.

CHALLENGE DESCRIPTION

I am stuck in a maze. Can you lend me a hand to find the way out?

4.5

CHALLENGE RATING

432

USER SOLVES

Reversing

CATEGORY

533 Days

RELEASE DATE

d3vnu11

CHALLENGE CREATOR

GIVE RESPECT

Abdu1040722

CHALLENGE COMPLETED

rrmpwn

FIRST BLOOD

OH 50M 43S

Key Insights

- Seed Obfuscation:** Critical values (like the seed 493) are often hidden in unrelated files (e.g., image bytes)
- Progressive Decryption:**
 - First pass: Arithmetic operation (add 80)
 - Second pass: Cryptographic operation (XOR with PRNG key)
- Flag Reconstruction:**
 - Look for known header ("HTB")
 - Derive subsequent characters using adjacent values