



Lab Number 03

CoppeliaSim EDU – Translation, Rotation and Transformation

Introduction:

CoppeliaSim uses different languages such as Lua, python or MATLAB etc. In this lab we will study Lua programming. Since Lua programming is used in many industrial grade robots.

Software Used:

CoppeliaSim EDU v4.7

Programming Language:

LUA

Basics can be learnt from the website: www.tutorialspoint.com/lua/

Objectives of the Lab:

- To learn basics of LUA programming
- To use revolute and prismatic joints

Programming basics:

Syntax is almost same as C language.

Data Types → nil, Boolean, number, string, tables

Variable declaration → assignment

Function call with variable arguments

print("test") displays test in the output console.

Keywords:

and	break	do	else
elseif	end	false	for
function	if	in	local
nil	not	or	repeat
return	then	true	until
while			



Example:

-- Variable definition:

local a, b

-- Initialization

a = 10

b = 30

print("value of a:", a)

print("value of b:", b)

-- Swapping of variables

b, a = a, b

print("value of a:", a)

print("value of b:", b)

f = 70.0/3.0

print("value of f", f)

Loops:

while(true)

do

 print("This loop will run forever.")

end

Functions:

function max(num1, num2)

 if (num1 > num2) then

 result = num1;

 else

 result = num2;

 end

 return result;

end

-- calling a function

print("The maximum of the two numbers is ",max(10,4))

print("The maximum of the two numbers is ",max(5,6))

Strings:



```
string1 = "Lua"  
print("\String 1 is\\"",string1)
```

```
string2 = 'Tutorial'  
print("String 2 is",string2)
```

```
string3 = ["Lua Tutorial"]  
print("String 3 is",string3)
```

Arrays:

```
array = {"Lua", "Tutorial"}
```


```
for i = 0, 2 do  
    print(array[i])  
end
```

Modules:

```
-- Assuming we have a module printFormatter  
-- Also printFormatter has a funtion simpleFormat(arg)  
-- Method 1  
require "printFormatter"  
printFormatter.simpleFormat("test")  
  
-- Method 2  
local formatter = require "printFormatter"  
formatter.simpleFormat("test")  
  
-- Method 3  
require "printFormatter"  
local formatterFunction = printFormatter.simpleFormat  
formatterFunction("test")
```

Matrices and Vectors will be discussed in the script made in CoppeliaSim as they provide major role in transformations. First of all create a new script in the scene.

ADDING A SCRIPT IN CoppeliaSim EDU:



Function `sysCall_init` is used to initialize the handles (robots or objects) that are to be used. Function `sysCall_actuation` is used when you have to actuate something in the scene. Such as actuating a revolute joint as motors.

ROTATION MATRIX:

Write the code inside `sysCall_init ()`

```
function sysCall_init()  
    sim = require('sim')
```

```
    A = Matrix3x3:rotz(math.pi/2) -- rotation matrix (rotated around z axis by angle pi/2)  
    Matrix.print(A)                -- Print the matrix  
    -- do some initialization here  
end
```



TRANSLATIONAL VECTOR:

Now translational vector will be printed as follows

```
t = vector3({2,3,4})
```

```
Matrix.print(t)
```

TRANSFORMATION MATRIX:

```
A = Matrix4x4({1,0,0, 1,      - - Add a transformation Matrix
                0,2,0, -2,
                1,2,0, 3,
                0,0,0, 1})
```


```
Matrix.print(A)          - - print the matrix A
print(Matrix4x4:torotation(A)) - - print the rotation from transformation matrix
print(Matrix4x4:toeuler(A)) - - print the euler angles
print(Matrix4x4:toposition(A)) - - print the translation of the transformation matrix
```

Now visualizing the frames in CoppeliaSim.

Add the two reference frames from model browser

Model browser → other → reference frame

Name them as R0 and R1






HOMOGENOUS TRANSFORM:

Write down the code in the script's sysCall_init ()

```
function sysCall_init()
    sim = require('sim')          -- module sim

    R0 = sim.getObjectHandle('/R0') -- initialize an object R0 (reference frame)
    R1 = sim.getObjectHandle('/R1') -- initialize an object R1
    R = Matrix3x3:rotx(math.pi/4)  -- Make a rotation matrix to rotate the frame R1 by
                                    pi/4 relative to R0
    t = Vector3({0, 0.1, 0.2})      -- Make a vector such that to translate R1 by t relative
                                    to R0
    A1 = Matrix4x4:fromrt(R,t)      -- Make the transformation matrix by concatenating R
                                    and t to make a 4x4 matrix
    sim.setObjectMatrix(R1,R0,A1:data()) -- set object position and orientation
end
```



Now we will print a homogeneous transformation matrix of R1 relative to R0. Adding the following line in the code already done will make homogeneous transformation matrix as shown below:

```
A1m = Matrix (3,4, sim.getObjectMatrix(R1,R0))
A2 = Matrix:vertcat(A1m,Matrix(1,4,{0,0,0,1}))
Matrix.print(A2)
```



USING THE AXIS METHOD:

Using the Axis method to compute the rotation matrix R from the given transformation matrix such that it is rotated by angle “Y”.

```
Q = A2:axis("y")
```

```
T = Matrix3x3:fromaxisangle(Q,math.pi/4)
```

```
Matrix.print(T)
```

By adding the above code we get the rotation matrix when rotated by 45 degrees around Y axis.

```
Matrix.print(T:inv( )) - - takes the inverse of the matrixs
```