



Pakistan State Oil Company Limited

PSO House, Khayaban-e-Iqbal, Clifton, Karachi-75600, Pakistan
Telephone (021) 9203866-85 Fax (021) 9203796

PAGE

1	OF	3
RFQ No	LT-20062IA	
DATE	30.09.2026	

REQUEST FOR QUOTATION

(THIS IS PRICE ENQUIRY-NOT AN ORDER)

SAP No.6100018431

Company PSO Dummy Vendor
PAKISTAN

QUOTATION REQUIRED

ON
(Date)

16.10.2026

BY
(Time)

2:15 PM

Please quote your best price for all items of following specifications. Please read the instructions attached herewith Rs. _____ EARNEST MONEY Fix %
PO/DD NO. _____

Title: Procurement of Gear Pumps with Motor for Bitumen Service LMT and Finished Lubricants Service LMPA.

S.No.	Description/Specifications	Location	Unit	Qty	Unit Price Rs.	Amount Rs.
1	Gear Pump Supply of Internal Gear Pump with Motor Package for Bitumen / Additives / Base Oil Transfer Service at the Blending LMT facility, complete with Heating Jacket, Mechanical Seal, Coupling/Motor Set, Baseplate, and Internal Pressure Relief (safety) Valve. Specification: - Pump Type: Positive Displacement, Self-Priming Internal Gear Pump. - Application: Bitumen. - Operating Temperature: 0 to 170°C. - Viscosity Range: 2 to 3,000 cSt @ 100°C; 10 to 100,000 cSt @ 40°C. - Required Flow Rate: 45,000#50,000 Lit per hr. - Seal: High-Temperature Resistant, Sulphur-Compatible Mechanical Seal. - Jacket: Steam or Electrically Heated Jacket, Front and Back. - Safety: Integral/Internal Adjustable Pressure Relief Valve. - Drive: Motor sized by manufacturer to meet specified duty. - Motor Supply: 400 VAC ±5%, 3-phase, 50/60 Hz. - Motor Type: TEFC, Squirrel-Cage Induction Motor. - Protection / Insulation: IP65 minimum; Class F Insulation.	LMT	EA	1		
2	Gear Pump Supply of Internal Gear Pump Package with Motor Additives / Base Oil Transfer Service at the LMPA Facility, complete with Mechanical Seal, Coupling/Motor Set, Baseplate, and Internal Pressure Relief (safety) Valve. Specification: - Pump Type: Positive Displacement, Self-Priming Internal Gear Pump, Horizontal Rotation Orientation, Foot-Mounted. - Application: Additives / Base Oil / Hydraulic Oil /Bright Stock. - Operating Temperature: 0 to 70°C. - Viscosity Range: up to 800 Cst. - Required Flow Rate: Minimum 800 L/min (48000 L/hour). - Differential Pressure: Approximately 8 bar max.### - Maximum Working Pressure: 6-7 bar.	LMPA (Blending)	EA	1		



Pakistan State Oil Company Limited

PSO House, Khayaban-e-Iqbal, Clifton, Karachi-75600, Pakistan
Telephone (021) 9203866-85 Fax (021) 9203796

PAGE

2	OF	3
RFQ No	LT-20062IA	
DATE	30.09.2026	

REQUEST FOR QUOTATION

(THIS IS PRICE ENQUIRY-NOT AN ORDER)

SAP No.6100018431

Company PSO Dummy Vendor
PAKISTAN

QUOTATION REQUIRED

ON
(Date)

16.10.2026

BY
(Time)

2:15 PM

Please quote your best price for all items of following specifications. Please read the instructions attached herewith Rs. _____ EARNEST MONEY Fix %
PO/DD NO. _____

Title: Procurement of Gear Pumps with Motor for Bitumen Service LMT and Finished Lubricants Service LMPA.

S.No.	Description/Specifications	Location	Unit	Qty	Unit Price Rs.	Amount Rs.
	- Internal Relief Pressure: As per vendor design (Keeping in view the given parameters). - Pump Speed: Depending on manufacturer design safety requirements and required pump specification (Flow rate, pressure etc.). - Casing: Cast Iron ASTM A48 Class 30 or Cast Carbon Steel ASTM A216 Gr.WCB. - Gears: Hardened Alloy Steel. - Shaft: Stainless Steel AISI 410/420 or equivalent.## - Bushes/Bearings: Bronze / Carbon Graphite / Heavy-Duty Anti-Friction Bearings. - Mechanical Seal: Carbon/Ceramic with NBR elastomers or equivalent suitable material for required application (Lubricants, Base Oil and Hydraulic Oil). - Gaskets / O-rings: NBR (Buna-N), suitable for Petroleum Products. ===== GENERAL REQUIREMENTS: - Both pump packages shall be brand new, unused and of latest available manufacture. - Pump and motor shall be factory-assembled, factory-aligned and factory-tested on a common baseplate, complete with coupling and coupling guard. - Supply shall include flexible coupling, coupling guard, common baseplate and foundation bolts, where applicable/required for the supplied package. - Integral/internal pressure relief valve shall be provided and suitably rated for the specified service and maximum working pressure. - Supplier shall submit manufacturer data sheets, certified/general arrangement (GA) drawings, dimensional drawings, technical datasheets and recommended operating parameters. - Supplier shall provide operation and maintenance manuals, minimum two (2) sets per pump/package. - Supplier shall provide MIL test, factory performance test certificate, where applicable. - Supplier shall provide serial numbers, nameplate details and original manufacturer documentation for the supplied pump and motor.					



Pakistan State Oil Company Limited

PSO House, Khayaban-e-Iqbal, Clifton, Karachi-75600, Pakistan
Telephone (021) 9203866-85 Fax (021) 9203796

PAGE

3	OF	3
RFQ No	LT-20062IA	
DATE	30.09.2026	

REQUEST FOR QUOTATION

(THIS IS PRICE ENQUIRY-NOT AN ORDER)

SAP No.6100018431

Company PSO Dummy Vendor
PAKISTAN

QUOTATION REQUIRED

ON
(Date)

16.10.2026

BY
(Time)

2:15 PM

Please quote your best price for all items of following specifications. Please read the instructions attached herewith Rs. _____ EARNEST MONEY Fix %
PO/DD NO. _____

Title: Procurement of Gear Pumps with Motor for Bitumen Service LMT and Finished Lubricants Service LMPA.

S.No.	Description/Specifications	Location	Unit	Qty	Unit Price Rs.	Amount Rs.
	- The bidder should be an authorized distributor/agent, documentary evidence of authorization shall be submitted with the offer. - Supplier shall provide documentary evidence of original manufacturer, country of origin and import/authorization documents. - Supplier shall have adequate after-sales service and technical support; manufacturer's authorization/support letter shall be submitted. - Supplier shall provide basic operation and troubleshooting orientation/training to PSO-nominated personnel, if required, at mutually agreed time. - Minimum Warranty: 12 months from date of receipt/acceptance of the supplied equipment by PSO, against defects in material. Warranty terms shall be clearly stated in the offer. - Supplier shall be responsible for warranty replacement/rectification of defective supplied components during the warranty period. - Delivery: Complete supply shall be delivered within 150 days from Purchase Order issuance. - Supplier shall clearly identify all deviations/exceptions against each technical requirement in the offer. - All dimensions, weights, motor ratings, connection sizes and other final package details shall be confirmed by the manufacturer and submitted for PSO review prior to dispatch. - Packing shall be suitable for safe transportation, handling and storage at site, with all components/accessories properly identified and protected. AMOUNT OF BID SECURITY: - RS. 100,000/-.					