```
Modality 1 - Thermal
Non Falls - 48, Falls - 173

Modality 2 - ONI_IR
Non Falls - 48, Falls - 173

Train Dataloader - 48
Test Dataloader - 173

Device Used - cuda

Model Used - MultiModal_3DCAE
Key Frame Extraction - False
Feature Extraction - True
Background Subtraction - True
Background Subtraction Algorithm - GMG
Data Augmentation - False
Spatial Temporal Loss - True
w1 - 1, w2 - 1e-05

Frame rate adjusted dataset - True
Synchronise Video - True
Video length adjustment method - Not Applicable

Window Length = 8
Stride = 1
Fair Comparison = True
Dropout = 0.25
Learning Rate = 0.0002
Num Epochs = 20
Chunk Size = 64
Forward Chunk Size = 8
Loss Fn = SmoothL1Loss()

Forward pass occuring
Forward pass completed

MultiModal_Thermal_T3_ONI_IR_T_2024-04-25-13-06-37

---------------------------------
STD Global Classification Results
TPR 0.894, FPR 0.217, Precision 0.053, Recall 0.894
tn 102640, fp 28482, fn 191, tp 1605
std_AUROC  0.913
---------------------------------
---------------------------------
Mean Global Classification Results
TPR 0.895, FPR 0.205, Precision 0.056, Recall 0.895
tn 104238, fp 26884, fn 189, tp 1607
mean_AUROC 0.921
---------------------------------
```

```
d:\Abdul Rasheed NITT\Academics\Eigth Semester\FYP\Implementation\FallDetection\Code\funct
ions.py:250: RuntimeWarning: Mean of empty slice
  final_performance_mean = np.nanmean(video_metrics, axis=0)  # get the mean performance a
cross all videos
c:\Users\abdul\anaconda3\envs\fyp_base_paper_2\lib\site-packages\numpy\lib\nanfunctions.p
y:1670: RuntimeWarning: Degrees of freedom <= 0 for slice.
  var = nanvar(a, axis=axis, dtype=dtype, out=out, ddof=ddof,
----------------------------------
STD Global Classification Results
TPR 0.898, FPR 0.172, Precision 0.067, Recall 0.898
tn 108633, fp 22489, fn 184, tp 1612
std_AUROC  0.919
----------------------------------
----------------------------------
Mean Global Classification Results
TPR 0.925, FPR 0.208, Precision 0.058, Recall 0.925
tn 103880, fp 27242, fn 134, tp 1662
mean_AUROC 0.897
----------------------------------
d:\Abdul Rasheed NITT\Academics\Eigth Semester\FYP\Implementation\FallDetection\Code\funct
ions.py:250: RuntimeWarning: Mean of empty slice
  final_performance_mean = np.nanmean(video_metrics, axis=0)  # get the mean performance a
cross all videos
c:\Users\abdul\anaconda3\envs\fyp_base_paper_2\lib\site-packages\numpy\lib\nanfunctions.p
y:1670: RuntimeWarning: Degrees of freedom <= 0 for slice.
  var = nanvar(a, axis=axis, dtype=dtype, out=out, ddof=ddof,
----------------------------------
STD Global Classification Results
TPR 0.919, FPR 0.214, Precision 0.055, Recall 0.919
tn 103008, fp 28114, fn 145, tp 1651
std_AUROC  0.926
----------------------------------
----------------------------------
Mean Global Classification Results
TPR 0.884, FPR 0.186, Precision 0.061, Recall 0.884
tn 106731, fp 24391, fn 209, tp 1587
mean_AUROC 0.923
----------------------------------
d:\Abdul Rasheed NITT\Academics\Eigth Semester\FYP\Implementation\FallDetection\Code\funct
ions.py:250: RuntimeWarning: Mean of empty slice
  final_performance_mean = np.nanmean(video_metrics, axis=0)  # get the mean performance a
cross all videos
c:\Users\abdul\anaconda3\envs\fyp_base_paper_2\lib\site-packages\numpy\lib\nanfunctions.p
y:1670: RuntimeWarning: Degrees of freedom <= 0 for slice.
  var = nanvar(a, axis=axis, dtype=dtype, out=out, ddof=ddof,
()
```


Receiver Operating Characteristic for STD of Reconstruction Error
True Positive Rate
False Positive Rate
ROC curve (area = 0.9129)
0.0
0.2
0.4
0.6
0.8
1.0


Precision Recall Curve for STD of Reconstruction Error
Precision
Recall
No Skill (area = 0.0135)
AUPR curve (area = 0.1030)
0.000
0.025
0.050
0.075
0.100
0.125
0.150
0.175
0.200
0.0
0.2
0.4
0.6
0.8
1.0


Receiver Operating Characteristic for Mean of Reconstruction Error
True Positive Rate
False Positive Rate
ROC curve (area = 0.9205)
0.0
0.2
0.4
0.6
0.8
1.0


Precision Recall Curve for Mean of Reconstruction Error
Precision
Recall
No Skill (area = 0.0135)
AUPR curve (area = 0.1305)
0.000
0.025
0.050
0.075
0.100
0.125
0.150
0.175
0.200
0.0
0.2
0.4
0.6
0.8
1.0


Receiver Operating Characteristic for STD of Reconstruction Error
True Positive Rate
False Positive Rate
ROC curve (area = 0.9187)
0.0
0.2
0.4
0.6
0.8
1.0


Precision Recall Curve for STD of Reconstruction Error
Precision
Recall
No Skill (area = 0.0135)
AUPR curve (area = 0.0903)
0.000
0.025
0.050
0.075
0.100
0.125
0.150
0.175
0.200
0.0
0.2
0.4
0.6
0.8
1.0


Receiver Operating Characteristic for Mean of Reconstruction Error
True Positive Rate
False Positive Rate
ROC curve (area = 0.8971)
0.0
0.2
0.4
0.6
0.8
1.0


Precision Recall Curve for Mean of Reconstruction Error
Precision
Recall
No Skill (area = 0.0135)
AUPR curve (area = 0.0678)
0.000
0.025
0.050
0.075
0.100
0.125
0.150
0.175
0.200
0.0
0.2
0.4
0.6
0.8
1.0


Receiver Operating Characteristic for STD of Reconstruction Error
True Positive Rate
False Positive Rate
ROC curve (area = 0.9260)
0.0
0.2
0.4
0.6
0.8
1.0


Precision Recall Curve for STD of Reconstruction Error
Precision
Recall
No Skill (area = 0.0135)
AUPR curve (area = 0.1286)
0.000
0.025
0.050
0.075
0.100
0.125
0.150
0.175
0.200
0.0
0.2
0.4
0.6
0.8
1.0


Receiver Operating Characteristic for Mean of Reconstruction Error
True Positive Rate
False Positive Rate
ROC curve (area = 0.9231)
0.0
0.2
0.4
0.6
0.8
1.0


Precision Recall Curve for Mean of Reconstruction Error
Precision
Recall
No Skill (area = 0.0135)
AUPR curve (area = 0.1295)
0.000
0.025
0.050
0.075
0.100
0.125
0.150
0.175
0.200
0.0
0.2
0.4
0.6
0.8
1.0