

Skipped Fall102
Skipped Fall106
Skipped Fall108
Skipped Fall110
Skipped Fall129
Skipped Fall131
Skipped Fall150
Skipped Fall151
Skipped Fall152
Skipped Fall153
Skipped Fall156
Skipped Fall157
Skipped Fall158
Skipped Fall159
Skipped Fall167
Skipped Fall170
Skipped Fall171
Skipped Fall182
Skipped Fall187
Skipped Fall188
Skipped Fall120
Skipped Fall1211
Skipped Fall1213
Skipped Fall1214
Skipped Fall123
Skipped Fall1230
Skipped Fall1231
Skipped Fall1232
Skipped Fall1233
Skipped Fall1234
Skipped Fall1235
Skipped Fall1236
Skipped Fall1237
Skipped Fall1238
Skipped Fall1239
Skipped Fall125
Skipped Fall126
Skipped Fall1264
Skipped Fall1267
Skipped Fall128
Skipped Fall129
Skipped Fall1290
Skipped Fall1291
Skipped Fall1292
Skipped Fall1293
Skipped Fall1294
Skipped Fall1295
Skipped Fall1296
Skipped Fall1297
Skipped Fall1298
Skipped Fall1299
Skipped Fall134
Skipped Fall137
Skipped Fall140
Skipped Fall141
Skipped Fall142
Skipped Fall143
Skipped Fall144
Skipped Fall145

Skipped Fall46
Skipped Fall47
Skipped Fall48
Skipped Fall49
Skipped Fall61
Skipped Fall67
Skipped Fall72
Skipped Fall74
Skipped Fall87
Skipped Fall91
Skipped Fall95
Skipped Fall98
Train Dataloader - 90
Test Dataloader - 187

Device Used - cuda

Model Used - Base_3DCAE
Window Length = 8
Stride = 1
Fair Comparison = False
Dropout = 0.25
Learning Rate = 0.0002
Num Epochs = 20
Chunk Size = 64
Forward Chunk = 8
Forward Chunk Size = 8
Loss Fn = MSELoss()

Training has Begun

epoch [1/20], loss:0.0012
epoch [2/20], loss:0.0007
epoch [3/20], loss:0.0005
epoch [4/20], loss:0.0005
epoch [5/20], loss:0.0004
epoch [6/20], loss:0.0004
epoch [7/20], loss:0.0004
epoch [8/20], loss:0.0003
epoch [9/20], loss:0.0003
epoch [10/20], loss:0.0003
epoch [11/20], loss:0.0003
epoch [12/20], loss:0.0003
epoch [13/20], loss:0.0003
epoch [14/20], loss:0.0003
epoch [15/20], loss:0.0003
epoch [16/20], loss:0.0003
epoch [17/20], loss:0.0002
epoch [18/20], loss:0.0002
epoch [19/20], loss:0.0002

```
c:\Users\abdul\anaconda3\envs\fyp_base_paper_2\lib\site-packages\numpy\lib\npyio.py:528: VisibleDeprecationWarning: Creating an ndarray from ragged nested sequences (which is a list-or-tuple of lists-or-tuples-or ndarrays with different lengths or shapes) is deprecated. If you meant to do this, you must specify 'dtype=object' when creating the ndarray.  
arr = np.asanyarray(arr)
```

epoch [20/20], loss:0.0002
Training has Completed

Forward pass occuring
Forward pass completed

Thermal_T3_2024-02-26-20-05-58

STD Global Classification Results
TPR 0.885, FPR 0.342, Precision 0.040, Recall 0.885
tn 47002, fp 24432, fn 132, tp 1014
std_AUROC 0.812

Mean Global Classification Results
TPR 0.760, FPR 0.278, Precision 0.042, Recall 0.760
tn 51585, fp 19849, fn 275, tp 871
mean_AUROC 0.803

d:\Abdul Rasheed NITT\Academics\Eigth Semester\FYP\Implementation\FallDetection\Code\functions.py:265: RuntimeWarning: Mean of empty slice
final_performance_mean = np.nanmean(
c:\Users\abdul\anaconda3\envs\fyp_base_paper_2\lib\site-packages\numpy\lib\nanfunctions.py:1670: RuntimeWarning: Degrees of freedom <= 0 for slice.
var = nanvar(a, axis=axis, dtype=dtype, out=out, ddof=ddof,





