```
Train Dataloader - 48
Test Dataloader - 173

Device Used - cuda

Model Used - Base_3DCAE_2
Feature Extraction - False
Data Augmentation - False
Spatial Temporal Loss - True
w1 - 1, w2 - 1e-05

Window Length = 8
Stride = 1
Fair Comparison = True
Dropout = 0.25
Learning Rate = 0.0002
Num Epochs = 20
Chunk Size = 64
Forward Chunk = 8
Forward Chunk Size = 8
Loss Fn = MSELoss()

Training has Begun
epoch [1/20], loss:0.0065
epoch [2/20], loss:0.0045
epoch [3/20], loss:0.0031
epoch [4/20], loss:0.0028
epoch [5/20], loss:0.0025
epoch [6/20], loss:0.0017
epoch [7/20], loss:0.0014
epoch [8/20], loss:0.0015
epoch [9/20], loss:0.0014
epoch [10/20], loss:0.0014
epoch [11/20], loss:0.0010
epoch [12/20], loss:0.0010
epoch [13/20], loss:0.0005
epoch [14/20], loss:0.0003
epoch [15/20], loss:0.0002
epoch [16/20], loss:0.0005
epoch [17/20], loss:0.0006
epoch [18/20], loss:0.0006
epoch [19/20], loss:0.0007
c:\Users\abdul\anaconda3\envs\fyp_base_paper_2\lib\site-packages\numpy\lib\npyio.py:528: VisibleDeprecationWarning: Creating an ndarray from ragged nested sequences (which is a list-or-tuple of lists-or-tuples-or ndarrays with different lengths or shapes) is deprecated. If you meant to do this, you must specify 'dtype=object' when creating the ndarray.
  arr = np.asanyarray(arr)
```

```
epoch [20/20], loss:0.0007
Training has Completed

Forward pass occuring
Forward pass completed

Thermal_T3_2024-03-20-03-07-33

----------------------------------
STD Global Classification Results
TPR 0.914, FPR 0.373, Precision 0.038, Recall 0.914
tn 41641, fp 24748, fn 92, tp 980
std_AUROC  0.812
----------------------------------
----------------------------------
Mean Global Classification Results
TPR 0.950, FPR 0.440, Precision 0.034, Recall 0.950
tn 37154, fp 29235, fn 54, tp 1018
mean_AUROC 0.819
----------------------------------
d:\Abdul Rasheed NITT\Academics\Eigth Semester\FYP\Implementation\FallDetection\Code\funct
ions.py:250: RuntimeWarning: Mean of empty slice
  final_performance_mean = np.nanmean(video_metrics, axis=0)  # get the mean performance a
cross all videos
c:\Users\abdul\anaconda3\envs\fyp_base_paper_2\lib\site-packages\numpy\lib\nanfunctions.p
y:1670: RuntimeWarning: Degrees of freedom <= 0 for slice.
  var = nanvar(a, axis=axis, dtype=dtype, out=out, ddof=ddof,
```




Precision Recall Curve for STD of Reconstruction Error
No Skill (area = 0.0159)
AUPR curve (area = 0.0555)
Precision
Recall
0.200
0.175
0.150
0.125
0.100
0.075
0.050
0.025
0.000
0.0
0.2
0.4
0.6
0.8
1.0


Receiver Operating Characteristic for Mean of Reconstruction Error
ROC curve (area = 0.8190)
True Positive Rate
False Positive Rate
1.0
0.8
0.6
0.4
0.2
0.0
0.0
0.2
0.4
0.6
0.8
1.0


Precision Recall Curve for Mean of Reconstruction Error
No Skill (area = 0.0159)
AUPR curve (area = 0.0562)
Precision
Recall
0.200
0.175
0.150
0.125
0.100
0.075
0.050
0.025
0.000
0.0
0.2
0.4
0.6
0.8
1.0