```
Modality 1 - Thermal
Non Falls - 48, Falls - 173
Modality 2 - ONI_IR
Non Falls - 48, Falls - 173
Train Dataloader - 48
Test Dataloader - 173
Device Used - cuda
Model Used - EarlyConcatenation_3DCAE
Key Frame Extraction - False
Feature Extraction - True
Background Subtraction - True
Background Subtraction Algorithm - GMG
Data Augmentation - False
Spatial Temporal Loss - False
Frame rate adjusted dataset - True
Synchronise Video - True
Video length adjustment method - Not Applicable
Window Length = 8
Stride = 1
Fair Comparison = True
Dropout = 0.25
Learning Rate = 0.0002
Num Epochs = 20
Chunk Size = 64
Forward Chunk Size = 8
Loss Fn = SmoothL1Loss()
Training has Begun
epoch [1/20], loss:0.0001
epoch [2/20], loss:0.0000
epoch [3/20], loss:0.0000
epoch [4/20], loss:0.0000
epoch [5/20], loss:0.0000
epoch [6/20], loss:0.0000
epoch [7/20], loss:0.0000
epoch [8/20], loss:0.0000
epoch [9/20], loss:0.0000
epoch [10/20], loss:0.0000
epoch [11/20], loss:0.0000
epoch [12/20], loss:0.0000
epoch [13/20], loss:0.0000
epoch [14/20], loss:0.0000
epoch [15/20], loss:0.0000
epoch [16/20], loss:0.0000
epoch [17/20], loss:0.0000
epoch [18/20], loss:0.0000
epoch [19/20], loss:0.0000
epoch [20/20], loss:0.0000
Training has Completed
Forward pass occuring
```

Forward pass completed

-----

STD Global Classification Results

TPR 0.919, FPR 0.214, Precision 0.055, Recall 0.919

tn 103017, fp 28105, fn 145, tp 1651

std\_AUROC 0.926

-----

Mean Global Classification Results

TPR 0.879, FPR 0.199, Precision 0.057, Recall 0.879

tn 105002, fp 26120, fn 217, tp 1579

mean\_AUROC 0.920

-----

d:\Abdul Rasheed NITT\Academics\Eigth Semester\FYP\Implementation\FallDetection\Code\funct
ions.py:250: RuntimeWarning: Mean of empty slice

final\_performance\_mean = np.nanmean(video\_metrics, axis=0) # get the mean performance a
cross all videos

c:\Users\abdul\anaconda3\envs\fyp\_base\_paper\_2\lib\site-packages\numpy\lib\nanfunctions.p
y:1670: RuntimeWarning: Degrees of freedom <= 0 for slice.</pre>

var = nanvar(a, axis=axis, dtype=dtype, out=out, ddof=ddof,

()

## Receiver Operating Characteristic for STD of Reconstruction Error









