

Train Dataloader - 48

Test Dataloader - 173

Device Used - cuda

Model Used - Base\_3DCAE

Feature Extraction - True

Background Subtraction - True

Background Subtraction Algorithm - GMG

Data Augmentation - False

Window Length = 8

Stride = 1

Fair Comparison = True

Dropout = 0.25

Learning Rate = 0.0002

Num Epochs = 20

Chunk Size = 64

Forward Chunk = 8

Forward Chunk Size = 8

Loss Fn = SmoothL1Loss()

Training has Begun

epoch [1/20], loss:0.5611

epoch [2/20], loss:0.5609

epoch [3/20], loss:0.5608

epoch [4/20], loss:0.5607

epoch [5/20], loss:0.5607

epoch [6/20], loss:0.5607

epoch [7/20], loss:0.5606

epoch [8/20], loss:0.5606

epoch [9/20], loss:0.5606

epoch [10/20], loss:0.5606

epoch [11/20], loss:0.5606

epoch [12/20], loss:0.5606

epoch [13/20], loss:0.5606

epoch [14/20], loss:0.5606

epoch [15/20], loss:0.5606

epoch [16/20], loss:0.5605

epoch [17/20], loss:0.5605

epoch [18/20], loss:0.5605

epoch [19/20], loss:0.5605

```
# https://docs.opencv.org/4.x/d1/d5c/classcv_1_1bgsegm_1_1BackgroundSubtractorGMG.html
def perform_background_subtraction_GMG(vid_total):
    background_subtracted_vid_total = []

    # Create background subtractor
    bg_subtractor = cv2.bgsegm.createBackgroundSubtractorGMG()
    kernel = cv2.getStructuringElement(cv2.MORPH_ELLIPSE, (3, 3))
    # bg_subtractor.setDecisionThreshold(0.8) # Default - 0.8
    # bg_subtractor.setLearningRate(0.025) # Default - 0.025
    bg_subtractor.setNumFrames(25) # Default - 120

    for frame in vid_total:
        frame = np.array(frame, dtype=np.float32)
        # print(frame.shape)
        # Perform background subtraction
        foreground_mask = bg_subtractor.apply(frame)
        foreground_mask = cv2.morphologyEx(foreground_mask, cv2.MORPH_OPEN, kernel)
        background_subtracted_vid_total.append(foreground_mask)

        ## To view the images
        # cv2.imshow("Original Frame", frame)
        # cv2.imshow("Foreground Mask - GMG", foreground_mask)
        # # Exit on 'q' press
        # k = cv2.waitKey(30) & 0xFF
        # if k == 27:
        #     break

    return background_subtracted_vid_total
```

c:\Users\abdul\anaconda3\envs\fyp\_base\_paper\_2\lib\site-packages\numpy\lib\ndarray.py:528: VisibleDeprecationWarning: Creating an ndarray from ragged nested sequences (which is a list-or-tuple of lists-or-tuples-or ndarrays with different lengths or shapes) is deprecated. If you meant to do this, you must specify 'dtype=object' when creating the ndarray.

```
arr = np.asanyarray(arr)
```

epoch [20/20], loss:0.5605  
Training has Completed

Forward pass occurring  
Forward pass completed

Thermal\_T3\_2024-03-14-01-46-48

-----  
STD Global Classification Results  
TPR 0.826, FPR 0.210, Precision 0.060, Recall 0.826  
tn 52438, fp 13951, fn 187, tp 885  
std\_AUROC 0.845  
-----

-----  
Mean Global Classification Results  
TPR 0.811, FPR 0.259, Precision 0.048, Recall 0.811  
tn 49214, fp 17175, fn 203, tp 869  
mean\_AUROC 0.821  
-----

```
d:\Abdul Rasheed NITT\Academics\Eigth Semester\FYP\Implementation\FallDetection\Code\functions.py:250: RuntimeWarning: Mean of empty slice
  final_performance_mean = np.nanmean(video_metrics, axis=0) # get the mean performance a
cross all videos
c:\Users\abdul\anaconda3\envs\fyp_base_paper_2\lib\site-packages\numpy\lib\nanfunctions.py:1670: RuntimeWarning: Degrees of freedom <= 0 for slice.
  var = nanvar(a, axis=axis, dtype=dtype, out=out, ddof=ddof,
```





