


EECS1022
MOBILE COMPUTING



CONTROL STRUCTURES

SELECTION

(SLIDES ADAPTED FROM PROF. H. ROUMANI)

PROF. Y. LESPÉRANCE


Dept. of Electrical Engineering & Computer Science

1


FLOW OF CONTROL

- What is control; how does it flow?
- Sequence versus Selection Flow

(a)




(b)



2

SELECTION: IF



```

Statement-S
if (condition)
{
    Statement-A1
    Statement-A2
    ...
}
Statement-X
        
```

3

EXAMPLE

Write a method that reads an int and out-puts its *abs* value without using `Math.abs`.

```

public int myAbs(int n)
{
    int result = n;
    if (n < 0)
    {
        result = -n;
    }
    return result;
}
        
```

4


PITFALL

What is wrong with this?

```
public int myAbs(int n)
{
    int result = n;
    if (n < 0);
    {
        result = -n;
    }
    return result;
}
```

5

SELECTION: IF-ELSE



6

EXAMPLE

Rewrite the **myAbs** body using if-else

```
int result;
if (n < 0)
{
    result = -n;
}
else
{
    result = n;
}
return result;
```

7

PITFALL

What is wrong with this?

```
if (n < 0)
{
    int result = -n;
}
else
{
    int result = n;
}
return result;
```

8

BUILDING THE CONDITION

- Relational Expression

```
if (k < 0)
```

- Boolean Variable

```
boolean b = k < 0
if (b)
```


- Boolean Expression

```
if (k < 0 || b && m > h)
```

Uses boolean operators: &&, ||, and !

9

OPERATOR PRECEDENCE



```
. ++ -- !
cast
* / %
+ -
< <= > >=
== !=
&&
||
= op=
```

10

EXAMPLE

- Express the condition $x \in [a, b]$

```
if (x >= a && x < b)
```

- Express the condition $x \notin [a, b]$

```
if (!(x >= a && x < b))
```

Can use deMorgan's Law to convert negated conjunctions to disjunctions.


```
if (x < a || x >= b)
```

11

EXAMPLE

Given two object references x and y , write a condition to determine if the objects they reference are equal.

Which one is correct and why:

- `if (x == y)` 
- `if (x.equals(y))`
- `if (x.equals(y) && x != null)`
- `if (x != null && x.equals(y))`


12

EXERCISES


Implement these methods:

- `public boolean isOdd(int n)`
Returns true if n is odd else returns false.
- `public char getFullGrade(int mark)`
Returns the full letter grade (A,B,C,D,E,F) given the mark (out of 100) in a course.
- `public boolean isLeap(int year)`
Returns true if the year is a leap else returns false.
A leap year is divisible by 4 and if it is divisible by 100 then it must also be divisible by 400; e.g. 2016 is, 2000 is, but 2100 is not.

13



EECS1022
MOBILE COMPUTING




CONTROL STRUCTURES

ITERATION

(SLIDES ADAPTED FROM PROF. H. ROUMANI)


PROF. Y. LESPÉRANCE
Dept. of Electrical Engineering & Computer Science

1



ITERATION: FOR

Flow:



Syntax:

```

Statement-S
for (initial; condition; bottom)
{
    body;
}
Statement-X
                    
```

Algorithm:

1. Start the for scope
2. Execute initial
3. If condition is false go to 9
4. Start the body scope {
5. Execute the body
6. End the body scope }
7. Execute bottom
8. If condition is true go to 4
9. End the for scope

3

EXAMPLE

Output a table of square roots in [0,9].

```

for (int i = 0; i < 10; i = i + 1)
{
    double root = Math.pow(i, 0.5);
    System.out.print(i);
    System.out.print("\t");
    System.out.println(root);
}
                    
```

4


for (initial; condition; bottom)

```
for (int i = 0; i < MAX; i = i + 1)
{
    ...
}
```

```
int i = 0;
for (; i < MAX; i = i + 1)
{
    ...
}
```


5

for (initial; condition; bottom)

- Can it be omitted?
- Can it be set to the literal `true`? 
- What if it were false at the beginning?
- Is it monitored throughout the body?

6

for (initial; condition; bottom)

- Can be any statement.
- Can be omitted.
- Will the loop become infinite if it is omitted? 

7

EXAMPLE

Write a fragment to output the exponents of all powers of 2 that are smaller than a million.

Correct output:

```
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19
```

```
final int MILLION = 1000000;
for (int expo = 0; Math.pow(2, expo) < MILLION; expo++)
{
    System.out.print(expo);
    System.out.print(" ");
}
System.out.println();
```

8

EXAMPLE

Rewrite the fragment so it only outputs the exponent of the greatest power of 2 that is smaller than a million.

```
int expo = 0;
for (; Math.pow(2, expo) < MILLION; expo++)
{
}
System.out.println(expo - 1);
```



```
int expo = 0;
for (; Math.pow(2, expo) < MILLION; expo++);
System.out.println(expo - 1);
```

9

NESTED LOOPS

- Must be fully nested
- Nested structures imply nested scopes

```
for (int i = 0; i < 10; i++)
{
    for (int j = 0; j < 10; j++)
    {
        System.out.println(i + " " + j);
    }
}
```

10

EXERCISES

Implement these methods:

- `public boolean isPrime(int n)`
Returns true if n is prime, else returns false.
- `public int log2 (int n)`
Returns the number of repeated division of n by 2 until the result of the division is 1
- `public double factorial(int n)`
Returns n!
- `public double oddRecipSum (int n)`
Returns the sum of the reciprocals of odd integers with alternating signs between 1 and 10^6 (should around $\pi/4$)

11