



1

## Statements

- Program to execute
  - Ended with a ;
- Expression statement (ch2)
  - `i+1; i++; x = 4;`
- Function call statement (ch4)
  - `printf("the result is %d");`
- Control flow statement (ch3)
  - `if else, for(), while, do while, switch`

Same in Java

2

2

## Summary and future work

- Type, operators and expressions (Chapter 2) :
  - Types and sizes
    - Basic types, their sizes and constant values (literals)
      - ✓ char: `x > 'a' && x < 'z';`    `x > '0' && x < '9'`
      - ✓ int:    122, 0122, 0x12F    convert between Decimal, Bin, Oct, Hex
    - Arrays (one dimension) and strings (Ch1.6,1.9)
      - ✓ "hello" has size 6 byte 

H	e	l	l	o	\0
---	---	---	---	---	----
  - Expressions
    - Basic operators (arithmetic, relational and logical)
      - ✓ `y=x++;`    `y=++x;`
      - ✓ `if (x = 2)`
    - Type conversion and promotion
    - Other operators (bitwise, bit shifting , compound assignment, conditional)
      - ✓ Bit: `|`, `&`, `~`, `^`, `<<` `>>`
      - ✓ Compound: `x += 10;`    `x >>= 10;`    `x += y + 3`
    - Precedence of operators
- <sup>3</sup> Functions and Program Structure (Chapter 4)

Last week

today

3

## Expression

- Formed by combining **operands** (variable, constants and function calls) using **operators** (+ - \* % > < == != )
- Has return values -- always
  - `x+1`
  - `i < 20`    false: 0    true: 1    `printf("%d", i<20);`
  - `sum (i+j)`
  - `x = 5`    = is an operator in C (and Java)! Return value 5
  - `x = k + sum(i,j)`    `printf("%d", x=5);`

*"whenever a value is needed, any expression of the same type will do"*

- `printf("sum is %d\n", i*y+2)`
- `printf("sum is %d\n", sum(i+j))`

4

## C Types and sizes

Text book:

4 basic types: char, int, float, double

3 qualifiers: short, long, unsigned

- Variables and values have types
- There are two basic types in ANSI-C: integer, and floating point
  - Integer type**
    - char** - **character**, single byte (8 bits)
    - short (int)** - **short integer**, 1 or 2 bytes (8 or 16 bits)
    - int** - **integer**, usually 2 or 4 bytes (16 or 32 bits)
    - long (int)** - **long integer**, usually 4 or 8 bytes (32 or 64 bits)
  - Floating point**
    - float** - single-precision, usually 4 bytes (32 bits)
    - double** - double-precision, usually 8 bytes (64 bits)
    - long double** - extended-precision




5

5

## Qualifiers (modifiers) for integer type

- signed, unsigned** qualifiers can be applied to integer types
  - Signed: **default**. **Left most bit signifies sign** 0: positive 1: negative
  - Unsigned: **positive**. Left most bit contributes to magnitude
- (signed) char
- (signed) int
- (signed) short int
- (signed) long int
- unsigned char
- unsigned int
- unsigned short int
- unsigned long int



Java: no direct support for unsigned int. Always signed



(signed) int	$-2^{31} \sim 2^{31}-1$	-2145483648 ~ 2147483647	$2^{32}$ values
unsigned int	$0 \sim 2^{32}-1$	0 ~ 4294967295	$2^{32}$ values

6


Max: signed 01111111....11111

Unsigned: 11111111....11111

6

## Qualifiers (modifiers) for integer type

- **signed/unsigned** can be applied to char
  - **signed** char  $-2^7 \sim 2^7-1$  /\* -128 ~ 127 \*/
  - **unsigned** char  $0 \sim 2^8-1$  /\* 0 ~ 255 \*/



### Unsigned potentially save bits

E.g., Count # student in our class (about 150)

- If declared **signed short**, max 127, 8 bits not enough
- If declared **unsigned**, then 8 bits are enough.

```
unsigned short counter;
```

7

Bits	Unsigned value	2's complement value
00000000	0	0
00000001	1	1
00000010	2	2
01111110	126	126
01111111	127	127
10000000	128	-128
10000001	129	-127
10000010	130	-126
11111110	254	-2
11111111	255	-1
0 ~ 2 <sup>n</sup> -1		-2 <sup>n-1</sup> ~ -2 <sup>n-1</sup> -1
2 <sup>n</sup> =256 values		2 <sup>n</sup> =256 values

7

## Summary

- Integer types:

signed char	unsigned char
(signed) short	unsigned short
(signed) int	unsigned int
(signed) long	unsigned long

- There are three types of floating points:

float	/* single-precision */
double	/* double precision */
long double	/* extended-precision */

- C99 added:

(signed) long long int
unsigned long long int

8

Java defines

Type
int
short
long
byte
float
double
char
boolean

8


# Outline

- Types and sizes
  - Types
    - **Constant values (literals)**
      - **char**
      - int
      - float
- Array and “strings”
- Expressions
  - Basic operators
  - Type promotion and conversion
  - Other operators
  - Precedence of operators

9

9

## Internal representation of characters



```
int i = 43;
```

```
char a = 'A';
```



## How to represent 'A' using 0s and 1s

10

10

01100101					01101100					01101100					01101111					00000000				
Dec Hx Oct Char					Dec Hx Oct Htm1 Chr					Dec Hx Oct Htm1 Chr					Dec Hx Oct Htm1 Chr									
0	0	000	NUL (null)		32	20	040	Space		64	40	100	64		96	60	140	96						
					33	21	041	!		65	41	101	A		97	61	141	a						
					34	22	042	"		66	42	102	B		98	62	142	b						
					35	23	043	#		67	43	103	C		99	63	143	c						
					36	24	044	\$		68	44	104	D		100	64	144	d						
					37	25	045	%		69	45	105	E		101	65	145	e						
					38	26	046	&		70	46	106	F		102	66	146	f						
					39	27	047	'		71	47	107	G		103	67	147	g						
					40	28	050	(		72	48	110	H		104	68	150	h						
					41	29	051	)		73	49	111	I		105	69	151	i						
					42	2A	052	*		74	4A	112	J		106	6A	152	j						
					43	2B	053	+		75	4B	113	K		107	6B	153	k						
					44	2C	054	,		76	4C	114	L		108	6C	154	l						
					45	2D	055	-		77	4D	115	M		109	6D	155	m						
					46	2E	056	.		78	4E	116	N		110	6E	156	n						
					47	2F	057	/		79	4F	117	O		111	6F	157	o						
					48	30	060	0		80	50	120	P		112	70	160	p						
					49	31	061	1		81	51	121	Q		113	71	161	q						
					50	32	062	2		82	52	122	R		114	72	162	r						
					51	33	063	3		83	53	123	S		115	73	163	s						
					52	34	064	4		84	54	124	T		116	74	164	t						
					53	35	065	5		85	55	125	U		117	75	165	u						
					54	36	066	6		86	56	126	V		118	76	166	v						
					55	37	067	7		87	57	127	W		119	77	167	w						
					56	38	070	8		88	58	130	X		120	78	170	x						
					57	39	071	9		89	59	131	Y		121	79	171	y						
					58	3A	072	:		90	5A	132	Z		122	7A	172	z						
					59	3B	073	;		91	5B	133	[		123	7B	173	{						
					60	3C	074	<		92	5C	134	\		124	7C	174							
					61	3D	075	=		93	5D	135	]		125	7D	175	}						
					62	3E	076	>		94	5E	136	^		126	7E	176	~						
					63	3F	077	?		95	5F	137	_		127	7F	177	DEL						

11

## Characters

- `chars` are treated in C as small integers, `char` variables and constants are identical to `int` in arithmetic expressions:
  - `char c` is converted to its encoding (index in the character set table)

```
char aChar = '5'; // encoding 53
aChar + 12 // expression with value 53+12 = 65
```

same in Java

- Same for other expressions. In relational expression, characters can be compared directly, comparing their indexes/encodings

```
aChar == 'H' // index == 72? → expr with value 0 (false)

aChar == '/n' // index = 10? → exp with value 0 (false)

'5' < 'H' // 53 < 72? Earlier in table? → expr with 1 (true)
```

12

## Characters

- Since **chars** are just small integers, **char** variables and constants are identical to **int** in arithmetic expressions:
  - char c** is converted to its encoding (index in the character set table)

45	2D	055	0#45:
46	2E	056	0#46: .
47	2F	057	0#47: /
48	30	060	0#48: 0
49	31	061	0#49: 1
50	32	062	0#50: 2
51	33	063	0#51: 3
52	34	064	0#52: 4
53	35	065	0#53: 5
54	36	066	0#54: 6
55	37	067	0#55: 7
56	38	070	0#56: 8
57	39	071	0#57: 9
58	3A	072	0#58: :
59	3B	073	0#59: ;
60	3C	074	0#60: <
61	3D	075	0#61: =
62	3E	076	0#62: >
63	3F	077	0#63: >

```
char aCh = '6'; // same as char aCh = 54;
printf("value is %c\n", aCh ); // char 6
printf("value is %d\n", aCh ); // numerical 54
                                // print encoding

printf("value is %d\n", aCh + 2 ); //numerical 56
printf("value is %c\n", aCh + 2 ); // char 8

printf("value is %d\n", aCh-'0' ); // 54-48
                                //numerical 6
```

13

same in Java

13

## Characters

- Since **chars** are just small integers, **char** variables and constants are identical to **ints** in arithmetic expressions: take advantage of this

45	2D	055	0#45:
46	2E	056	0#46: .
47	2F	057	0#47: /
48	30	060	0#48: 0
49	31	061	0#49: 1
50	32	062	0#50: 2
51	33	063	0#51: 3
52	34	064	0#52: 4
53	35	065	0#53: 5
54	36	066	0#54: 6
55	37	067	0#55: 7
56	38	070	0#56: 8
57	39	071	0#57: 9
58	3A	072	0#58: :
59	3B	073	0#59: ;
60	3C	074	0#60: <

```
if(c >= '0' && c <= '9') /*index 48~57, is a digit */
                        Located after '0' and before '9'

if(c >='a' && c <= 'z') /* low case letter*/

if(c >='A' && c <= 'Z') /*upper case letter*/

if(c >='0' && c <= '9') // c<= 48 c>=57 isdigit(c)
printf("c is a digit\n");
printf("numerical value is %d\n", c-'0');
```

14

same in Java

14

## Example

- Upper case letters before lower case letters.
- Encoding difference of 'a' and 'A' is 32, so does 'b' and 'B', 'c' and 'C', 'd' and 'D'...

```
#include<stdio.h>

/*copying input to output with
converting upper-case to lower-case letters */
main(){
    int c; int lowC;
    c= getchar();
    while (c != EOF)
    {
        if (c >= 'A' && c <= 'Z') /* 65~90 upper case letter*/
            lowC = c + 'a' - 'A'; /* c + 'b' - 'B' */
                                   /* c + 'c' - 'C' */
        putchar(lowC);           /* c = tolower(c) */

        c = getchar(); // read again
    }
    return 0;
}
```

**c + 32** works in the lab but not good for portability. Avoid that!

64	40	100	65	A	96	60	140	96	a
65	41	101	66	B	97	61	141	97	b
66	42	102	67	C	98	62	142	98	c
67	43	103	68	D	99	63	143	99	d
68	44	104	69	E	100	64	144	100	e
69	45	105	70	F	101	65	145	101	f
70	46	106	71	G	102	66	146	102	g
71	47	107	72	H	103	67	147	103	h
72	48	108	73	I	104	68	148	104	i
73	49	109	74	J	105	69	149	105	j
74	50	110	75	K	106	70	150	106	k
75	51	111	76	L	107	71	151	107	l
76	52	112	77	M	108	72	152	108	m
77	53	113	78	N	109	73	153	109	n
78	54	114	79	O	110	74	154	110	o
79	55	115	80	P	111	75	155	111	p
80	56	116	81	Q	112	76	156	112	q
81	57	117	82	R	113	77	157	113	r
82	58	118	83	S	114	78	158	114	s
83	59	119	84	T	115	79	159	115	t
84	60	120	85	U	116	80	160	116	u
85	61	121	86	V	117	81	161	117	v
86	62	122	87	W	118	82	162	118	w
87	63	123	88	X	119	83	163	119	x
88	64	124	89	Y	120	84	164	120	y
89	65	125	90	Z	121	85	165	121	z
90	66	126	91	[	122	86	166	122	{
91	67	127	92	\	123	87	167	123	
92	68	128	93	^	124	88	168	124	~
93	69	129	94	_	125	89	169	125	
94	70	130	95	`	126	90	170	126	
95	71	131	96	{	127	91	171	127	
96	72	132	97		128	92	172	128	
97	73	133	98	~	129	93	173	129	
98	74	134	99		130	94	174	130	
99	75	135	100		131	95	175	131	



15

## Outline

- Types and sizes
  - Types
  - Constant values (literals)
    - char** treated as small int
    - int** different bases
    - float
- Array and "strings"
- Expressions
  - Basic operators
  - Type promotion and conversion
  - Other operators
  - Precedence of operators



16

16



0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

  
 Stored always binary      $2^2 \ 2^1 \ 2^0$

## Integer Constants

- Integer constants can be expressed in three different ways:
  1. **Decimal** [base 10]
 

▪ `int x = 31`

same in Java
  2. **Octal** [base 8]
 

▪ Start with zero 0

▪ `int x = 037` (31 in decimal)

same in Java
  3. **Hexadecimal** [base 16]
 

▪ Start with 0x or 0X

▪ `int x = 0x1F` (31 in decimal)

same in Java

*Ways for people to write numbers.*

*No effect on how the numbers are stored --- always binary.*

Java also has the 4<sup>th</sup>: binary  
`int x = 0b00011111`

17

## Others To decimal

• 3 2 8  
 $10^2 \ 10^1 \ 10^0$

➔

$3 \cdot 10^2 + 2 \cdot 10^1 + 8 \cdot 10^0 =$   
 $300 + 20 + 8 = 328$

Decimal 328

• 1 0 1  
 $2^2 \ 2^1 \ 2^0$

➔

$1 \cdot 2^2 + 0 \cdot 2^1 + 1 \cdot 2^0 =$   
 $4 + 0 + 1 = 5$

000000000101

  
 Binary

• 3 4 5  
 $8^2 \ 8^1 \ 8^0$

➔

$3 \cdot 8^2 + 4 \cdot 8^1 + 5 \cdot 8^0 =$   
 $192 + 32 + 5 = 229$

Octal 0345

• 3 4 F  
 $16^2 \ 16^1 \ 16^0$

➔

$3 \cdot 16^2 + 4 \cdot 16^1 + F \cdot 16^0 =$   
 $3 \cdot 256 + 4 \cdot 16 + 15 \cdot 1 =$   
 $768 + 64 + 15 = 847$

Hex 0x34F  
 0X34f

*You should know these conversions.*

18

## Binary to others -- why Hex and Oct

I know I want an int with representation 01001100, how to code it in C?

In Java, can do binary `int a = 0b01001100`

• 0 1 0 0 1 1 0 0 →  $1 \cdot 2^6 + 1 \cdot 2^3 + 1 \cdot 2^2 =$  Decimal

$2^7 \ 2^6 \ 2^5 \ 2^4 \ 2^3 \ 2^2 \ 2^1 \ 2^0$  64 + 8 + 4 **int a = 76**

• 01 001 100  
1 1 4  
int a = 0114 Octal

- ```
int a = 0x4C
```

```
int a = 0x4c
```

Hex

19 You should know these conversions (both ways).



19

# Outline

- Types and sizes
  - Types
  - Constant values (literals)
    - char
    - int
    - float
- **Array and “strings” (Ch1.6,1.9)**
- Expressions
  - Basic operators
  - Type promotion and conversion
  - Other operators
  - Precedence of operators



20

20

## Declaring Arrays

- Declare and initialize (how to do in Java?)

```
int k[5]; /* each element get some garble value*/
        -5 122 45623 85 58
```

```
int k[5] = {1,5,3,2,25}; 1 5 3 2 25
```

```
int k[5] = {1,5}; 1 5 0 0 0
```

```
int k[] = {1,5,3,2,25}; 1 5 3 2 25
```

`sizeof k?` 20 // assuming 4 bytes int

`sizeof(k)/sizeof(k[0]) = 20/4 = 5`



21

## An example involving array and chars

What does this program do?

```
/*counting digits*/
#include <stdio.h>
#define N 10
int main () {
    int c, i;
    int digit[N];

    for (i=0; i< N; i++)
        digit[i]=0;

    c = getchar();
    while (c != EOF)
    {
        if ( c>= '0' && c <= '9' ){
            int pos = c - '0';
            digit[pos] ++; // digit[c] ++ X
        }
        c = getchar(); // read again
    }

    for (i=0; i< N; i++)
        printf ("%d: %d ", i, digit[i]);
}
```

```
45 20 055 0#45: -
46 2E 056 0#46: .
47 2F 057 0#47: /
48 30 060 0#48: 0
49 31 061 0#49: 1
50 32 062 0#50: 2
51 33 063 0#51: 3
52 34 064 0#52: 4
53 35 065 0#53: 5
54 36 066 0#54: 6
55 37 067 0#55: 7
56 38 070 0#56: 8
57 39 071 0#57: 9
58 3A 072 0#58: :
59 3B 073 0#59: ;
60 3C 074 0#60: <
```



22

## Strings ↔ Character Arrays !

- There is no separate “string” type in C
- Strings are just **arrays of char** that end with **'\0'**

```
char s[] = "Hello";
char s[6] = "Hello";
```



|     |     |     |     |     |      |
|-----|-----|-----|-----|-----|------|
| 'H' | 'e' | 'l' | 'l' | 'o' | '\0' |
|-----|-----|-----|-----|-----|------|

\0 added for you

```
01001000 01100101 01101100 01101100 01101111 00000000
```

- What's the **size** of s in memory? **sizeof (s)? 6×1 bytes**



```
char s[5] = "Hello";
```

```
char s[8] = "Hello";      sizeof s? 8×1 bytes
```

|     |     |     |     |     |      |      |      |
|-----|-----|-----|-----|-----|------|------|------|
| 'H' | 'e' | 'l' | 'l' | 'o' | '\0' | '\0' | '\0' |
|-----|-----|-----|-----|-----|------|------|------|

- What is the **length** of s?

23

```
strlen(s) = 5
```

later



23

## Accessing Arrays/Strings

- In C, you can only assign to array members
  - This means you **cannot assign to an array**:

```
int i, k[4], j[4];
for (i=0; i<4; i++)
    j[i] = 0;      /* another way? int j[4]={0} */
```

```
k = j;  /* invalid */ /* perfectly valid in Java */
```

- Also **cannot compare directly**

```
if (k == j)      /* invalid */
if (k == "quit") /* invalid, as in Java */
```

```
if (c == 'Q')    /* valid, comparing encodings */
while (arr[i] != '\0') /* valid */
```

24



24

## An example involving reading char arrays

```
#include<stdio.h>
int length (char []);

main() {
    char my_strg[100];
    int a;

    printf("Enter a word and a int by blank>");
    scanf("%s %d", my_strg, &a);
    printf("%d", length(my_strg));
}

int length(char arr[]){
    int i = 0;
    while (arr[i] != '\0')
        i++;
    return i;
}
```

No need to give size

No & needed!  
A big topic. Talk about that later

No [].  
Same in Java

No need to give size

25

## Outline

- Types and sizes
  - Types
  - Constant values (literals)
    - char
    - int
    - float
- Array and “strings” (Ch1.6,1.9)
- **Expressions**
  - **Basic operators (arithmetic, relational and logical)**
  - Type promotion and conversion
  - Other operators (bitwise, bit shifting , compound assignment, conditional)
  - Precedence of operators

26

26

## Expressions

- Expressions are made up of *operands* (things we operate upon) and *operators* (things that do the operations: + - \* % > < )
  - `x+y/2, i>=0, x==y, i++,...`
- Operands* can be constants, variables, array elements, function calls and other expressions
- Every expression has a return value.
  - `x+2` has return value 3 if `x` was 1
  - `i < 20` has return value true or false -- 1 or 0
- In C/Java, `=` is an operator, so *assignment is also an expression*
  - `variable = expression`
  - `x = 2+3` has return value 5      `printf("%d", x=2+3) // 5`
  - Assignment expression can be an operand in other expressions
    - `y = x = 2;`
    - `while ((c=getchar()) != EOF )`

27 *"whenever a value is needed, any expression of the same type will do"*      `printf("sum is %d\n", i*y+2);`

27

## Expressions

- Some of the common operators:
  - `+, -, *, /, %, ++, --` (basic arithmetic)
  - `<, >, <=, >=` (relational operators)
  - `==, !=` (equality operators)
  - `&&, ||, !` (logical operators)
  - `=, +=, -=` (assignment & compound assignment)
- Others: bitwise `& | ~`, bit shifting `<< >>`, conditional `?:`

28

28

## Arithmetic (unary) Increment/Decrement Operators

- **++** increment
- **--** decrement

same in Java

- May come before (prefix) or after the operand (postfix)
  - ++x** increment x, result of expression is new value (pre-increment)
  - x++** increment x, result of expression is old value (post-increment)
  - x** decrement x, result of expression is new value (pre-decrement)
  - x--** decrement x, result of expression is old value (post-decrement)

|                                                                                                                      |                                                                                          |
|----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| <pre> while (x &lt; 10) {     .....     x++; // increment later,            before next statement     ..... } </pre> | <pre> while (x &lt; 10) {     .....     ++x; // increment immediately     ..... } </pre> |
|----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|

29

Same effects

29

## Arithmetic (unary) Increment/Decrement Operators

- **++** increment
- **--** decrement

same in Java

- May come before (prefix) or after the operand (postfix)
  - ++x** increment x, result of expression is new value (pre-increment)
  - x++** increment x, result of expression is old value (post-increment)
  - x** decrement x, result of expression is new value (pre-decrement)
  - x--** decrement x, result of expression is old value (post-decrement)

|                                                                                              |                                                                                               |
|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| <pre> x = 2; y = x++; // increment after            assignment printf("%d %d", x, y); </pre> | <pre> x = 2; y = ++x; // increment before            assignment printf("%d %d", x, y); </pre> |
|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|

30

x:2 y:3    x:3    y:2                      x:3    y:3

30

## A common use

```

/*initialize to 0 */

#include <stdio.h>
#define N 10

int main () {

    int i=0;
    int digit[N];

    while (i< N)
    {
        digit[i]=0;
        i++;
    }
}

```

// succinct code

```

while ( i< N)
{
    digit[i++]=0;
}

```

→

31

same in Java

31

## A common use

```

/*copy 4 elements from pos 10 of arrB to arrA */

#include <stdio.h>
#define N 10
int main () {
    int i,j;
    ....

    i=0; j=10;
    while (i<4 && j<14...)
    {
        arrA[i] = arrB[j];
        i++;
        j++;
    }
}

```

// succinct code

```

while (i<4 && j<14...)
{
    arrA[i++] = arrB[j++];
}

```

→

32

same in Java

Stopped here last time

32



## Summary and future work

- Type, operators and expressions (Chapter 2 ) :
  - Types and sizes
    - Basic types, their size and constant values (literals)
      - ✓ char: `x > 'a' && x < 'z';`    `x > '0' && x < '9'`
      - ✓ int:    122, 0122, 0x12F    convert between Decimal, Bin, Oct, Hex
    - Arrays (one dimension) and strings (Ch1.6,1.9)
      - ✓ "hello" has size 6 byte 

|   |   |   |   |   |    |
|---|---|---|---|---|----|
| H | e | l | l | o | \0 |
|---|---|---|---|---|----|
  - Expressions
    - Basic operators (arithmetic, relational and logical)
      - ✓ `y=x++;`    `y=++x;`
      - ✓ `if (x = 2)`
    - Type conversion and promotion
    - Other operators (bitwise, bit shifting , compound assignment, conditional)
      - ✓ Bit: `|`, `&`, `~`, `^`, `<<` `>>`
      - ✓ Compound: `x += 10;`    `x >>= 10;`    `x += y + 3`
    - Precedence of operators
- <sup>33</sup> Functions and Program Structure (Chapter 4)

Last week

today

33

## Expressions

- Some of the common operators:
  - `+`, `-`, `*`, `/`, `%`, `++`, `--`                      (basic arithmetic)
  - `<`, `>`, `<=`, `>=`                                              (relational operators)
  - `==`, `!=`                                                      (equality operators)
  - `&&`, `||`, `!`                                                      (logical operators)
  - `=`    `+=`    `-=`                                              (assignment & compound assignment)
- Others: bitwise `&` `|` `~`, bit shifting `<<` `>>`, conditional `?` :  
                  `sizeof`

34

34

## Relational and logical Operators

<, >, <=, >=, ==, != (relational and equality operators)

&&, ||, ! (logical operators)

- Value of a relational or logical expression is `Boolean`

0 when *false*

1 when *true*

In C,  
0 means *false*  
non-zero means *true*

```
int x = 3;
x > 4      0      printf("%d", x<4);
x == 3     1
x != 4     1
```

```
if (x == 5)    not true
```

```
while (1)      if (5)
```

```
35 if (x = 5)    ?
```



35

## Relational and logical Operators

- Not as safe as Java -- probably why Java introduce Boolean

```
int x = 2;
if (x = 1)
.....
else if (x=2) ...
.....
```

```
int x = 2;
while(x = 3)
.....
```

```
indigo 311 % javac Hello.java
Hello.java:13: incompatible types
found   : int
required: boolean
           if (x = 1){
                   ^
1 error
```



36

## Relational and logical Operators (cont.)

| And |     |             | Or  |     |            |
|-----|-----|-------------|-----|-----|------------|
| $p$ | $q$ | $p \cdot q$ | $p$ | $q$ | $p \vee q$ |
| $T$ | $T$ | $T$         | $T$ | $T$ | $T$        |
| $T$ | $F$ | $F$         | $T$ | $F$ | $T$        |
| $F$ | $T$ | $F$         | $F$ | $T$ | $T$        |
| $F$ | $F$ | $F$         | $F$ | $F$ | $F$        |

- **!** Logical negation

**!**0 returns 1, **!** (any non-zero value) returns 0      **! -4**

Not valid in Java

- **||** logical or, **&&** logical and

▪ **&&** returns 1 if both non-zero. Otherwise 0      3 **&&** -2

▪ **||** returns 1 if either non-zero. Otherwise 0      3 **||** 5

- **Short-circuit** (lazy) evaluation stops when we have an answer

```
int x = 1, y = 1
```

```
if (x == 0 && y == 0) ...;
```

same in Java

Java example:

```
if ( object != null && object.data > 9)
```

37

37

## Outline

- Types and sizes
  - Types
  - Constant values (literals)
    - char
    - int
    - float
- Array and “strings” (Ch1.6,1.9)
- Expressions
  - Basic operators (arithmetic, relational and logical)
  - **Type promotion and conversion**
  - Other operators (bitwise, bit shifting, compound assignment, conditional)
  - Precedence of operators

38

38

## Type conversion – 4 scenarios

1. Given an expression with operands of mixed types, C converts (promotes) the types of values to do calculations
2. Conversion may happens on assignment
3. May happens on function call arguments
4. May happens on function return type





39



39

## Type conversion – scenario 1

```
int x = 5, y = 2;
float f = 2.0
```

- What is the type of expression  $x/y$  or  $y/x$  
- What is the result of expression  $x/y$  or  $y/x$  
- What is the type of  $x/f$  or  $f/x$ ? 
- What is the result of  $x/f$  or  $f/x$ ? 

40



40

## Scenario 1 -- Type conversion (Promotion)

- Given an expression with operands of mixed types, C converts (**promotes**) the types of values to do calculations
  - Promotes: converts to a **more precise** type
  - Result is the **promoted** type.

```
int x = 5, y = 2;
float f = 2.0
```

same in Java

- E.g., for  $x/f$   $x$  is `int`,  $f$  is `float`
- $x$ 's value is read, converted to a float and then used in division (i.e.,  $5 \Rightarrow 5.0$ )
  - $5 / 2.0 = 5.0 / 2.0 = 2.5$
  - return type `float`


41



41

## Type Promotion converts to a **more precise** type

- Informal rules ( from K&R p. 44)
  - if either operand is "long double"
    - convert to "long double"
  - else if either operand is "double"
    - convert to "double"
  - else if either operand is "float"
    - convert to "float"
  - else
    - convert char and short to int
    - if either operand is long, convert to long



Examples:



42

short ⇒ int ⇒ long ⇒ float ⇒ double ⇒ long double  
char

### Mixed type arithmetic

- Given an expression with operands of mixed types, C converts (**promotes**) the types of values to do calculations
- $17 / 5$ 
  - 3
- $'k' + 32$ 
  - $75 + 32 = 107$
  - Return type int
- $17.0 / 5$ 
  - $17.0 / 5.0 = 3.4$
  - Return type double
- $9 / 2 * 3.0 / 4$ 
  - $9/2 = 4$  type int
  - $4 * 3.0 = 4.0 * 3.0 = 12.0$  double
  - $12.0 / 4 = 12.0 / 4.0 = 3.0$  double
- $3.0 * 9 / 2 / 4$ 
  - $3.0 * 9 = 3.0 * 9.0 = 27.0$  double
  - $27.0 / 2.0 = 13.5$  double
  - $13.5 / 4.0 = 3.375$  double

same in Java

43      2 conversions      Associativity: left to right      3 conversions

43

## Scenarion 2: Conversions across assignments

- The value of the **right** side is converted to the type of the **left**, which is the type of the result

```
int i = 512
float f;
f = i;  /*value of i is converted to float 512.0 */
        /* return type float, return value 512.0 */
```

same in Java

- If the left side is of smaller range or precision, information may be lost (should avoid)
  - Longer integers converted to shorter ones or chars by dropping the excess high-order bits
  - float/double to int truncates any fractional part.

```
float f = 512.3;
int i = f;  /* f is converted to int 512 */
```

```
java:10: error: incompatible types: possible lossy conversion from float to int
int i = f;
    ^
```

Not valid in Java

44      UNIVERSITÉ

44

## Type Conversion - Examples

arithmetic (scenario1) and assignment (scenario2)

same in Java

```
int x=5, y=2;
double q = 2;    // conversion on assignment q=2.0

int w = x/y;      // no conversions w=2

double z = x/y;   // z=2.0 conversion on assignment

double z = x/q;   // z=5.0/2=2.5 conversion on /

int w = x/q;
// conversion on / and then on assignment
// w = 5.0/2.0 = 2.5 = 2

char x = 'k' + 32; // conversion on + and then on =
// x = 75 + 32 = 107 = 'K'
```

45

45

## Scenario 3,4 Conversions across function

- arguments
- returns

```
#include <stdio.h>

/* function declaration */
int sum(int, int);

main()
{
    int x = 4; double y= 3.9;
    int su = sum(x,y); // sum receives 4, and 3.9 → 3
    printf( "Sum is %d\n", su); // 7
}

/* function definition */
int sum (int i, int j){
    return i+j; // 4 + 3
}
```

UNIVERSITY

46

## Scenario 3,4 Conversions across function

- arguments
- returns

```
#include <stdio.h>

/* function declaration */
double sum(double, double);

main()
{
    int x = 4; double y= 3.9;
    double su = sum(x,y); // sum receives 4 → 4.0 and 3.9
    printf("Sum is %f\n", su); // 7.9
}

/* function definition */
double sum (double i, double j){
    return i+j;    // 4.0 + 3.9
}
```

47

## Scenario 3,4 Conversions across function

- arguments
- returns

```
type function () {
    return expr;
}
```

- If `expr` is not of type `type`, compiler
  - produces a warning
  - converts `expr` (as if by assignment) to the return `type` of the function
  - should avoid
 

```
int function () {
    double x;
    return x;    /* return (int)x if you have to
                  tell the compiler you know
                  what you are doing (losing) */
```

48

48



## Scenario 3,4 Conversions across function

- arguments
- returns

```
#include <stdio.h>

/* function declaration */
double aFun();

main()
{
    aFun(); // return type double, value 7.0
}

/* function definition */
double aFun () {
    int i = 3;
    int j = 4;
    return i + j; /* i+j of type int, converted to double*/
}                /* 7 → 7.0 */
```

49

## Scenario 3,4 Conversions across function

- arguments
- returns

```
#include <stdio.h>

/* function declaration */
int aFun();

main()
{
    aFun(); // return type double, value 7.0
}

/* function definition */
int aFun () {
    double i = 3.6;
    int j = 4;
    return i + j; /* i+j of type double, converted to int */
}                /* 7.6 → 7 */
```

50

## Explicit Conversion (Type Casting)

- We can also explicitly change type
- Type cast operator; **(type-name) operand**

```
int a = 9, b = 2;
```

```
float f;
```

```
f = a / b;           /* f is 4.0 */
```

```
f = a / (float) b    /* f is 4.5 */
```

```
f = (float) (a/b) ?
```

Doesn't change the value of b,  
Just changes the type to float

```
int d = (int)f
```

Needed in Java



51

51

## Outline

- Types and sizes
  - Types
  - Constant values (literals)
    - char
    - int
    - float
- Array and “strings” (Ch1.6,1.9)
- **Expressions**
  - Basic operators (arithmetic, relational and logical)
  - Type promotion and conversion
  - **Other operators (bitwise, bit shifting, compound assignment, conditional)**
  - Precedence of operators



52

52

## Bitwise operators

C (and Java) allows us to easily manipulate individual bits in integer types (**char**, **short**, **int**, **long**)

- bitwise **&** **|** **~** **^**

| And      |          |             | Or       |          |            | Not      |          |
|----------|----------|-------------|----------|----------|------------|----------|----------|
| <i>p</i> | <i>q</i> | $p \cdot q$ | <i>p</i> | <i>q</i> | $p \vee q$ | <i>p</i> | $\sim p$ |
| <i>T</i> | <i>T</i> | <i>T</i>    | <i>T</i> | <i>T</i> | <i>T</i>   | <i>T</i> | <i>F</i> |
| <i>T</i> | <i>F</i> | <i>F</i>    | <i>T</i> | <i>F</i> | <i>T</i>   | <i>F</i> | <i>T</i> |
| <i>F</i> | <i>T</i> | <i>F</i>    | <i>F</i> | <i>T</i> | <i>T</i>   |          |          |
| <i>F</i> | <i>F</i> | <i>F</i>    | <i>F</i> | <i>F</i> | <i>F</i>   |          |          |

- bit shifting **<<** **>>**

01001000 01100101 01101100 01101100 01101111 00000000

53

## Bitwise Operators

| Or       |          |            |
|----------|----------|------------|
| <i>p</i> | <i>q</i> | $p \vee q$ |
| <i>T</i> | <i>T</i> | <i>T</i>   |
| <i>T</i> | <i>F</i> | <i>T</i>   |
| <i>F</i> | <i>T</i> | <i>T</i>   |
| <i>F</i> | <i>F</i> | <i>F</i>   |

|        |   |   |   |   |
|--------|---|---|---|---|
| Lhs    | 0 | 0 | 1 | 1 |
| Rhs    | 0 | 1 | 0 | 1 |
| Result | 0 | 1 | 1 | 1 |

- |** – bitwise “or”
  - Calculates the “or” of all bits in both operands
  - either bit is 1 → the result is 1 (set) 0: keep whatever other,

- e.g.

**z = 145 | 41**

145 = 000...10010001  
 41 = 000...00101001  
 000...10111001 = 185 (decimal)  
 0271 (oct)  
 0xb9 (hex)

54

same in Java

# Bitwise Operators

| And |   |             |
|-----|---|-------------|
| P   | q | $P \cdot q$ |
| T   | T | T           |
| T   | F | F           |
| F   | T | F           |
| F   | F | F           |

|        |   |   |   |   |
|--------|---|---|---|---|
| Lhs    | 0 | 0 | 1 | 1 |
| Rhs    | 0 | 1 | 0 | 1 |
| Result | 0 | 0 | 0 | 1 |

- **&** - bitwise “and”
  - Calculates ‘and’ of all bits in both operands
  - (both bits must be 1 to result in 1)
  - **Either is 0: 0 (off) 1: keep whatever the other**
- e.g.
 

$z = 145 \ \& \ 41$   
  
 $z = 1$

$145 = 000...10010001$   
 $41 = 000...00101001$   


---

 $000...00000001 = 1 \text{ (decimal)}$


55

same in Java



55

# Bitwise Operators



| A | B | Output |
|---|---|--------|
| 0 | 0 | 0      |
| 0 | 1 | 1      |
| 1 | 0 | 1      |
| 1 | 1 | 0      |

|        |   |   |   |   |
|--------|---|---|---|---|
| Lhs    | 0 | 0 | 1 | 1 |
| Rhs    | 0 | 1 | 0 | 1 |
| Result | 0 | 1 | 1 | 0 |

- **^** - “xor” (“exclusive-or”)
  - like “or” except when both bits are 1, the result is 0)
  - **If two bits are different, the result is 1; otherwise 0.**

e.g.  $z = 145 \ \wedge \ 41$

$145 = 000...10010001$   
 $41 = 000...00101001$   


---

 $000...10111000 = 184 \text{ (decimal)}$

$0270 \text{ (oct)}$   
 $0xb8 \text{ (hex)}$

56

same in Java

56

## Bitwise Operators

| Not |          |
|-----|----------|
| $P$ | $\sim P$ |
| $T$ | $F$      |
| $F$ | $T$      |

|        |   |   |
|--------|---|---|
| Rhs    | 0 | 1 |
| Result | 1 | 0 |

•  $\sim$

- one's complement (bit inversion)
- flips all bits in its operand

- e.g.(assuming unsigned char)

$z = \sim 145$        $145 = 10010001$

$01101110 = 110$  (decimal)

$0156$  (oct)

$0X6E$  (hex)

57

same in Java



57

## Bit Shifting

01001000 01100101 01101100 01101100 01101111 00000000

- Shifting bits:  $\ll$  (left shift),  $\gg$  (right shift)
  - $x \ll n$  means "take  $x$  and shift it  $n$  bits to the left"
  - $x \gg n$  means "take  $x$  and shift it  $n$  bits to the right"
  - Result is an int value (but **does not change  $x$** )

**What goes Out?** bits pushed "off the end" on the end

**What comes in?**  $\gg$   $\ll$  different

58


58

## Bit Shifting <<

- Suppose  $z$  is an int

▪ e.g.

- $z = 26 \ll 3$
- shift left 3 bits
- $z = 208$   
0320  
0XD0



What goes Out? bits pushed “off the end” on the left end

What comes in? we add 0 on the right

59

$z = x \ll 3$  does not change  $x$



59


## Bit Shifting >>

- What if we shift right?  $>>$  complicated.
- For “unsigned” types – all bits are magnitude -- add 0 on left

- e.g. ( assume these are all unsigned)

$z = 154 \gg 3$

shift left 3 bits



$z = x \gg 3$  does not change  $x$

60



60

## Bit Shifting- What Comes In >>

- What about “signed” values?
  - It’s undefined -meaning?
  - On some platforms it’s logical ( 0’s –like unsigned values)
  - On others it’s arithmetic (whatever the leftmost bit is)
- e.g.( 8-bit signed values using 2’s complement)
  - 94 >>3                      -94= 10010010
  - logical                       $\Rightarrow$                       00010010= 18
  - arithmetic                       $\Rightarrow$                       11110010= -14



61

61

## Bit Shifting- What Comes In >>

- What about “signed” values?
  - It’s undefined -meaning?
  - On some platforms it’s logical ( 0’s –like unsigned values)
  - On others it’s arithmetic (whatever the leftmost bit is)

C does not define which method is used  
The moral:

*Avoid right bit-shifting signed values!*

Java address right shift by introducing >>>  
>> what ever leftmost is  
>>> always 00...



62

62

## But What Is It Useful?

- A common use: flags, masks
  - A flag is a boolean value (off=0, on=1) which describes a state, e.g., switches
  - We could use an “`int`” to describe a flag, but an `int` has a minimum of 16 bits (65536 values) - far more than we need
  - We can use bitwise operators to efficiently represent flags - each bit can be a flag
    - so one `int` can represent at least 16 flags.

00000100 01011000 00001100 11101111

One int -- 32  
'Boolean' flags



63

63

## Masking for bit manipulation

- Masking uses AND and OR operators
- Use OR ('|') to set bits to '1' with 1
- Use AND ('&') to set bits to 0 with 0
- Use XOR('^') to toggle bits (0 -> 1 and 1 -> 0)

| 1: turn on (set 1)  
& 0: turn off (set 0)  
| 0: keep value  
& 1: keep value

| OR |   |        |
|----|---|--------|
| A  | B | Output |
| 0  | 0 | 0      |
| 0  | 1 | 1      |
| 1  | 0 | 1      |
| 1  | 1 | 1      |

| AND |   |        |
|-----|---|--------|
| A   | B | Output |
| 0   | 0 | 0      |
| 0   | 1 | 0      |
| 1   | 0 | 0      |
| 1   | 1 | 1      |

| XOR |   |        |
|-----|---|--------|
| A   | B | Output |
| 0   | 0 | 0      |
| 0   | 1 | 1      |
| 1   | 0 | 1      |
| 1   | 1 | 0      |

64



64



## Flags (some idioms)

| 1: turn on  
 & 0: turn off  
 | 0: keep value  
 & 1: keep value


- Unsigned char `flags`;
  - `flags = flags | (1<<5)`
    - 00100000. Turn 6<sup>th</sup> bit on (set to 1) (lowest-bit is 1st bit)
  - `flags = flags & ~(1<< 5)`
    - 11011111. Turn 6<sup>th</sup> bit off (set to 0)
  - `flags = flags & (1<<5)`
    - 00100000. keep 6<sup>th</sup> bit only (other off)
  - `flags = flags & 0177`
    - ... 001 111 111. Set to zero all but the low-order 7 bits of flag
  - `flags = flags & ~077`
    - 000111111->111000000. Set last 6 bits to zero (turn off)

65

Practice in the lab. Revisit next time

65

## Some examples



- In Java, `getRGB()` packs 3 +1 values (0~255) into a 32 bit (4 bytes) int



- 00000000 11111101 01001000 10101011

^ Alpha    ^Red    ^Green    ^Blue

```
java.awt.Image
```

```
Class BufferedImage
```

```
java.lang.Object
```

```
java.awt.Image
```

```
java.awt.image.BufferedImage
```

```
getRGB
```

```
public int getRGB()
```


66

Returns the RGB value representing the color in the default sRGB ColorModel. (Bits 24-31 are alpha, 16-23 are red, 8-15 are green, 0-7 are blue)

66

## Some examples

- I 1: turn on
- & 0: turn off
- I 0: keep value
- & 1: keep value



- In Java, getRGB() packS 3 +1 values into a 32 bit (4 bytes) int
- How to get blue value?

00001010 11111101 01001000 10101011

^ Alpha

^Red

^Green

^Blue

&

00000000 00000000 00000000 11111111

255 0377 0xFF

Turn off


keep value

00000000 00000000 00000000 10101011

- `int blue = (rgb_pack) & 0377; // rgb_pack not changed */`

67

## Some examples



- In Java, getRGB() packS 3 +1 values into a 32 bit (4 bytes) int

10101100 11111101 01001000 11111111

^ Alpha

^Red

^Green

^Blue

How to get red value?

- First shift to the right end. 00000000 00000000 10101100 11111101

- Then need 000 ..... 11111111 to turn off 9~32 bits -- mask

68

Select Command Prompt

```

Connection-specific DNS Suffix  . :
Wireless LAN adapter Wireless Network Connection:
    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::81c8:be2f:99d:2c
    IPv4 Address. . . . . : 130.63.199.163
    Subnet Mask . . . . . : 255.255.254.0
    Default Gateway . . . . . : 130.63.178.1
Ethernet adapter Local Area Connection:
    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . : cs.yorku.ca
Tunnel adapter isatap.{4C22CACA-FD21-424B-91FD-614F471D1709} :

```

Example: ip address 192.168.18.55, subnet mask: 255.255.255.0

11000000 10101000 00010010 00110111

11111111 11111111 11111111 00000000

Address: 11000000 10101000 00010010 00110111  
Subnet Mask: 11111111 11111111 11111111 00000000  
AND -----  
Network ID: 11000000 10101000 00010010 00000000

NET\_ID is 192.168.18

For your information

**YORK**  
UNIVERSITY

69

## Expressions

- Some of the common operators:
  - `+, -, *, /, %, ++, --` (basic arithmetic)
  - `<, >, <=, >=` (relational operators)
  - `==, !=` (equality operators)
  - `&&, ||, !` (logical operators)
  - `= += -=` (assignment & compound assignment)
- Others: bitwise `& | ~`, bit shifting `<< >>`, conditional `?:`

70

70

## Somethings to Think About

- `|` looks similar to `||` Both do “OR”
- `&` looks similar to `&&` Both do “AND”
- `|` and `&` applies to bits, `||` and `&&` apply to whole values
- Can you substitute `|` for `||`?
- Can you substitute `&` for `&&`?

```
int x=1, y=2;
```

```
x & y ? 0
```

```
x && y ? 1
```

```
x | y ? 3
```

```
x || y ? 1
```

71

| And      |          |             | Or       |          |            |
|----------|----------|-------------|----------|----------|------------|
| <i>p</i> | <i>q</i> | $p \cdot q$ | <i>p</i> | <i>q</i> | $p \vee q$ |
| <i>T</i> | <i>T</i> | <i>T</i>    | <i>T</i> | <i>T</i> | <i>T</i>   |
| <i>T</i> | <i>F</i> | <i>F</i>    | <i>T</i> | <i>F</i> | <i>T</i>   |
| <i>F</i> | <i>T</i> | <i>F</i>    | <i>F</i> | <i>T</i> | <i>T</i>   |
| <i>F</i> | <i>F</i> | <i>F</i>    | <i>F</i> | <i>F</i> | <i>F</i>   |

71

## Outline

- Types and sizes
  - Types
  - Constant values (literals)
    - char
    - int
    - float
- Array and “strings” (Ch1.6,1.9)
- **Expressions**
  - Basic operators (arithmetic, relational and logical)
  - Type promotion and conversion
  - **Other operators (bitwise, bit shifting , compound assignment, conditional)**
  - Precedence of operators

72

72

## (Compound) Assignment Operators

- C (and Java) provides other “short-hand” assignment operators (we’ve seen ++ and --)

- e.g.

▪ `x += 5;`      `<-->`      `x = x + 5`  
 ▪ `x *= 5;`      `<-->`      `x = x * 5`

73



73

## Assignment Op. & Expressions

- Assignment operator: “op=”  
`exp1 op= exp2` is equivalent to  
`exp1 =(exp1) op (exp2)`
  - `exp1` and `exp2` are expressions



- `op` can be:  
`+` `-` `*` `/` `%` `<<` `>>` `&` `^` `|`

- Thus, we can have  
`+=`, `-=`, `*=`, `/=`, `%=`, `<<=`, `>>=`, `&=`, `^=`, `|=`

`flags = flags | (1<<5)`  $\Leftrightarrow$  `flag |= (1 << 5)`

74



74

## Assignment Op. -- Examples

- `x *= y + 1` is equivalent to `x = x * (y + 1)`

- Because `*` has low precedence than `+`

- `x=2; y=2; x *= y + 1 + 5;`  
`x` has value  $2 * (2 + 1 + 5) = 16$

same in Java

unsigned int x;

- `x = 24; x >>= 2;`      `00011000`    `24 -> 6`  
`x` is `00000110`
- `x = 24; x <<= 2;`      `00011000`    `24 -> 96`  
`x` is `01100000`
- `x = 24; x |= 0x02;`      `00011000 |`  
                               `00000010`  
`x` is `00011010`    `24 -> 26`    Turn on 2<sup>nd</sup> bit



75

75

## Conditional operator

- `exp1 ? exp 2: exp 3`
  - If `exp1` is true, the value of the conditional expression is `exp2`; otherwise, `exp3`
- ```

z = (a > b) ? a : b; /* z = max (a,b) */
if (a>b)
    z=a;
else z=b;

```

76

## Java vs. C, types and operators

	Java	C
<b>Boolean</b>	<code>boolean</code>	<code>int 0/1</code>
<b>Integer types</b>	<code>byte</code> // 8 bits <code>short</code> // 16 bits <code>int</code> // 32 bits <code>long</code> // 64 bits	<code>char</code> <code>unsigned char</code> <code>short</code> <code>unsigned short</code> <code>int</code> <code>unsigned int</code> <code>long</code> <code>unsigned long</code>
<b>String type</b>	<code>String s1 = "Hello";</code> <code>String s2 = new</code> <code>String("hello");</code>	<code>char s1[] = "Hello";</code> <code>char s2[6];</code> <code>strcpy( s2, "hello" );</code>
<b>String concatenate</b>	<code>s1 + s2</code>	<code>#include &lt;string.h&gt;</code> <code>strcat( s1, s2 );</code>
<b>Logical</b>	<code>&amp;&amp;,   , !</code>	<code>&amp;&amp;,   , !</code>
<b>Compare</b>	<code>=, !=, &gt;, &lt;, &gt;=, &lt;=</code>	<code>=, !=, &gt;, &lt;, &gt;=, &lt;=</code>
<b>Arithmetic</b>	<code>+, -, *, /, %, unary -</code>	<code>+, -, *, /, %, unary -</code>
<b>Bit-wise ops</b>	<code>&gt;&gt;, &lt;&lt;, &gt;&gt;&gt;, &amp;,  , ^</code>	<code>&gt;&gt;, &lt;&lt;, &amp;,  , ^</code>
<b>Assignments</b>	<code>=, *=, /=, +=, -=, &lt;&lt;=,</code> <code>&gt;&gt;=, &gt;&gt;&gt;=,  =, ^=, %=</code>	<code>=, *=, /=, +=, -=, &lt;&lt;=,</code> <code>&gt;&gt;=,  =, ^=, %=</code>

77

## Outline

- Types and sizes
  - Types
  - Constant values (literals)
    - char
    - int
    - float
- Array and “strings” (Ch1.6,1.9)
- **Expressions**
  - Basic operators (arithmetic, relational and logical)
  - Type promotion and conversion
  - Other operators (bitwise, bit shifting , compound assignment, conditional)
  - **Precedence of operators**

78

78

## Precedence

- How do we interpret:
  - `a && b || c && d`
  - `i << 2 + 1      flag | 1 << 4`
  - `i *= y+1`
  - `(int) f1/f2`
- Rules of precedence tell us what gets evaluated first:
  - `a && b` `||` `c && d`
  - `i << 2 + 1      flag | 1 << 4`
  - `i *= y + 1`
  - `(int) f1` `/` `f2`
- Precedence should be familiar from basic math:
  - Given "`x+y*5`", you evaluate "`y*5`" first:
    - `x + (y*5)`

79

79

## Precedence

```
#include <stdio.h>
```

```
main(){
  int c;
  c = getchar();
  while(c != EOF)
  {
    putchar(c);
    c = getchar(); /*read next*/
  }
}
```



Succinct code

```
#include <stdio.h>

main(){
  int c;

  while( c = getchar() != EOF )
  {
    putchar(c);
  }
}
```



80

80



## Precedence and Associativity p53

- Observe that:

- Parentheses first
- Negation(!,~) next
- Arithmetic before Relational
- Arithmetic: /, \*, % before +-
- Relational before Logical
- Logical: && before ||
- Bit shift << >> before bitwise & ^ |
- Assignment = += very low

```
if ( a&&b || c && d)
while( (c=getchar()) == EOF)
i << 2 + 1 // i = i << 3
if (a==2 || a<4)
i *= y + 1 // i=i*(y+1)
(*p).data
```

- When in doubt – use parentheses
  - Also for clarity
- Don't need to memorize
  - 81▪ Will be provided in tests
  - But know how to use them

Similar in Java

Operator Type	Operator
Primary Expression Operators	() [] . -> expr++ expr--
Unary Operators	* & + - ! ~ ++expr --expr (typecast) sizeof
Binary Operators	* / % arithmetic
	+ - arithmetic
	>> << bit shift
	<< >> <= >= relational
	= != relational
	& bitwise
	^ bitwise
	bitwise
	&& logical
	logical
Ternary Operator	?:
Assignment Operators	= += -= *= /= %= >>= <<=
Comma	,

81

## Summary and future work

- Type, operators and expressions (Chapter 2) :
  - Types and sizes
    - Basic types, their size and constant values (literals)
      - ✓ char: x > 'a' && x < 'z'; x > '0' && x < '9'
      - ✓ int: 122, 0122, 0x12F convert between Decimal, Bin, Oct, Hex
    - Arrays (one dimension) and strings (Ch1.6,1.9)
      - ✓ "hello" has size 6 byte 

H	e	l	l	o	\0
---	---	---	---	---	----
  - Expressions
    - Basic operators (arithmetic, relational and logical)
      - ✓ y=x++; y=++x;
      - ✓ if (x = 2)
    - Type conversion and promotion
    - Other operators (bitwise, bit shifting , compound assignment, conditional)
      - ✓ Bit: |, &, ~, ^, << >>
      - ✓ Compound: x += 10; x >>= 10; x += y + 3
    - Precedence of operators

- 82 Next: Functions and Program Structure (Chapter 4)

82