

Prediction of Chronic Disease Risk in Older
Adults using Nutrition, Lifestyle & Clinical Data
from The Irish Longitudinal Study on Ageing
(TILDA)



Abderahman Haouit

CSIS Research Centre

Department of Computer Science and Information Systems

Faculty of Science and Engineering

University of Limerick

Submitted to the University of Limerick for the degree of

Artificial Intelligence (MSc) 2026

-
1. Supervisor: Dr. Alison O'Connor
Computer Science & Information Systems
University *of* Limerick
Ireland

Abstract

Background: Chronic diseases such as Cardiovascular Disease (CVD), Diabetes Mellitus (DM), Frailty (FR), and obesity represent major contributors to morbidity in older adults. While traditional prediction models focus heavily on clinical and functional indicators, the contribution of nutritional and lifestyle factors to early risk detection remains underexplored.

Methods: This thesis applies machine learning techniques to data from The Irish Longitudinal Study on Ageing (TILDA), a national representative longitudinal study of older adults. Five waves of socio-demographic, clinical, nutritional, psychological, and behavioural data, with selected variables from the externally produced Research and Development Corporation (RAND) + Harmonised TILDA dataset, together were systematically cleaned and standardised using a multi-stage preprocessing pipeline. Predictive models, including (*models x , y , z*) were developed to estimate the risk of chronic disease and FR related outcomes. Model performance was evaluated using (*mention examples*), and feature importance was used to assess predictive value.

Results: TBD

Conclusions: TBD

Keywords: ageing, (Artificial Intelligence (AI)), Machine Learning (ML), predictive modelling, Frailty (FR), chronic disease, nutrition, The Irish Longitudinal Study on Ageing (TILDA)

Declaration

I Abderahman Haouit declare that I have produced this thesis without the prohibited assistance of third parties and without making use of aids other than those specified; notions taken over directly or indirectly from other sources have been identified as such. This thesis has not previously been presented in identical or similar form to any other Irish or foreign examination board.

The thesis work was conducted from 2025 to 2026 under the supervision of Dr. Alison O'Connor at University of Limerick.

Limerick, 2026

Acknowledgements

I would like to acknowledge my supervisor, Dr. Alison O'Connor, for her guidance, support, and for providing a well organised environment throughout the implementation of this project.

I would also like to thank the University of Limerick (UL) Science and Engineering Research Ethics Committee for approving the ethical aspects of this research. Special thanks to the Irish Social Science Data Archive (ISSDA) team for facilitating access to the TILDA dataset, collected by Trinity College Dublin.

Your dedication goes here. Open the dedication.tex file found at:
0_frontmatter/dedication.tex

Contents

List of Tables	vi
List of Figures	viii
List of Abbreviations	ix
1 Introduction	1
1.1 Research problem and motivation	2
1.2 Research aims and objectives	3
1.3 Contributions of the research	4
1.4 Thesis outline	4
2 Literature Review	6
2.1 Search strategy and study selection	6
2.1.1 Database search and query development	7
2.1.2 Quality and relevance evaluation	9
2.1.3 Synthesis and integration	10
2.2 Frailty and physical function	12
2.2.1 Probabilistic interpretation of frailty	12
2.2.2 Bayesian updating of frailty risk	13
2.3 Mental health in older adults	13
2.4 Nutrition and biological ageing	14
2.4.1 Bayesian perspective on nutritional biomarkers	15
2.4.2 Contextual and integrative considerations	15
2.5 Machine Learning in ageing and chronic disease	16
2.5.1 Models used in machine learning	16

CONTENTS

2.5.2	Performance and validation	17
2.5.3	Explainability in machine learning for ageing	17
2.6	Gaps in the literature	17
2.7	Chapter summary	19
3	Methodology	21
3.1	Study population and design	21
3.2	TILDA data collection and screening	22
3.3	Thematic domains	23
3.4	Manual variable filtering workflow	24
3.5	Reduced dataset overview	29
3.6	Retained variable distribution by domain	30
4	Technical Implementation	33
4.1	Automated cleaning engine	33
4.1.1	Stage 1: Variable scenario mapping and validation	34
4.1.2	Stage 2: Deterministic six step cleaning sequence	35
4.1.3	Feature engineering within the cleaning pipeline	39
4.1.4	Cross wave semantic verification	39
4.2	Validation on the cleaning pipeline	41
4.2.1	Internal feature relationships	42
4.2.2	Model based validation	43
5	Empirical Evaluation	50
5.1	Modelling and evaluation framework	50
5.1.1	Outcome definitions (Track A and Track B)	51
5.1.2	Modelling designs	52
5.1.3	Participant level data splitting and leakage prevention	56
5.1.4	Evaluation protocol and decision metrics	57
5.2	Main results	57
5.2.1	Track A: Any disease onset	58
5.2.1.1	Design 1 performance:	58
5.2.1.2	Design 2 performance:	58
5.2.1.3	Design 3 performance:	59

CONTENTS

5.2.2	Cross design comparison	59
5.2.3	Model comparison	60
5.2.4	Track B: Disease specific	61
5.3	Model interpretability and feature importance	61
5.4	Robustness checks and sensitivity	61
5.5	Error analysis	61
5.6	Summary of findings	61
6	Conclusion	62
6.1	Summary	62
6.2	Conclusions	62
6.2.1	Data availability Statement	62
6.2.2	Ethics Statement	62
6.3	Contributions	63
6.4	Future Work	63
A	Python code for exporting PMF metadata to CSV	64
B	Scenario: Cleaning Pipeline Tables	67
C	First Stage: Scenario Variable Mapping	70
D	Step 6: Scenario ‘Multi class categorical’ Cleaning Function	75
E	Second Stage: Deterministic <i>six step</i> Cleaning Pipeline	87
F	MD Dictionary: Scenario Grouping and Transformation Function	89
G	MD Dictionary: Scenario Grouping and Transformation Audit Outputs	92
	References	97

List of Tables

2.1	Database searches and number of studies per database 2.3 [1]. . .	8
2.2	Quality evaluation of Systematic Literature Review (SLR)s [2]. . .	10
2.3	Summary of selected studies on ageing using TILDA.	11
3.1	Dimensions of raw TILDA and harmonised datasets version 5.5 (prior to cleaning in Section 4.1).	23
3.2	Pseudonymised Microdata File (PMF) v5.5 derived variable pre- fixes [3].	25
3.3	Input shape for cleaning pipeline (post manual filtering workflow 3.1). . .	29
3.4	Thematic domain grouping of longitudinal features.	32
4.1	Inconsistent category ordering for the same feature <i>ph009</i> (self rated health compared to other people your age) across waves and its impact on positional (order based) label encoding.	41
4.2	Directional validation of the 7 features explaining 95% of Gait Speed Reserve (GSR) variance as identified by [4].	45
5.1	Analysis samples by modelling design for Track A	52
5.2	Predictive performance across model families for D1 (baseline de- sign).	58
5.3	Predictive performance across model families for D2 (multi-wave design).	58
5.4	Predictive performance across model families for D3 (tuned design). . .	59
B.1	Initial Raw Feature Counts Categorised by Nine Scenarios (Pre Cleaning)	67

LIST OF TABLES

B.2	Scenario Count Progression: Post Step 1 (Empty / Blank Handling)	68
B.3	Scenario Count Progression: Post Step 2 (Sentinel Standardisation)	68
B.4	Scenario Count Progression: Post Step 3 (Numeric Cleaning) . . .	68
B.5	Scenario Count Progression: Post Step 4 (Censored / Ordinal Mapping)	69
B.6	Scenario Count Progression: Post Step 5 (Binary Classification) .	69
B.7	Final Dfs Cleaned: Post Step 6 (Multi-Class / Mixed Parsing) . .	69

List of Figures

2.1	Publications per year.	7
2.2	Preferred Reporting Items for Systematic reviews and Meta Analyses (PRISMA) chart for Systematic Review (SR)s showing the study selection process for the systematic mapping and integrative review [5].	9
3.1	Flowchart of the manual five-step workflow for variable screening and filtering. Placeholder (n) values represent the number of variables at each stage, illustrating the reduction from the raw dataset to the filtered dataset prior to automated preprocessing.	28
4.1	Flowchart of the final six-step cleaning pipeline applied to all TILDA waves. Detailed transformation tables are provided in Appendix B.7, and the corresponding implementation “.ipynb” script is documented in Appendix E at each scenario step.	36
4.2	Correlation heatmap for top 7 predictors (Wave 3).	44
4.3	ROC curves for mortality prediction using the cleaned 16 Frailty Index (FI) items under the Principal Component Analysis (PCA) informed mortality proxy. Separate models are shown for men and women, with and without age.	47
4.4	ROC curves for mortality prediction using the 6/16 recoded FI items aligned with [6]. Performance is shown separately for men and women, with and without age.	48

LIST OF FIGURES

5.1	Pipeline overview: shared pipeline → separation into Track A (Any chronic disease with D1/D2/D3) and Track B (disease specific, following D2/D3 design).	55
5.2	Train–test AUC generalisation gaps across models and designs. . .	60

LIST OF FIGURES

Chapter 1

Introduction

Ageing populations experience substantial changes across physical, nutritional, cognitive, and psychosocial domains, each shaping vulnerability to chronic disease and functional decline [7–9]. Understanding how these multidomain factors interact over time is essential for early risk identification.

The financial and societal burden is substantial. In Europe, poor diet is a major risk factor for non communicable diseases, contributing billions in health-care costs annually [10]. In Ireland, malnutrition alone is estimated to cost over €1.4 billion per year [11]. In response to these challenges, international public health frameworks, including the World Health Organization (WHO) *Global Action Plan* on noncommunicable diseases and Ireland’s *Healthy Ireland* framework, highlight nutrition and lifestyle factors as central components of disease prevention strategies.

European regulatory frameworks such as the General Data Protection Regulation (GDPR) and proposed European Union (EU) Artificial Intelligence (AI) Act emphasise transparency and highlight the need for interpretable Machine Learning (ML) models in healthcare.

Traditional risk prediction models have largely relied on clinical biomarkers such as Blood Pressure from Sphygmomanometer (BP) and lipid profiles. Yet, growing evidence shows that broader predictors, including nutrition [12], Physical Activity (PA) [13], Scales and Questions on Mental Health and Wellbeing (MH) [14], and Social Variables (SOC) [15] improve predictive performance. Es-

1. INTRODUCTION

timating the likelihood of developing a condition given certain risk factors helps quantify the influence of these predictors in clinical decision making.

The Irish Longitudinal Study on Ageing (TILDA)¹ provides a national representative cohort of adults aged 50+ in Ireland, surveyed repeatedly across multiple domains. For cross study comparability and methodological consistency in model development, selected variables from the externally produced Research and Development Corporation (RAND) Harmonised TILDA dataset (available for Waves 1 and 2) were included.

The harmonised dataset provides standardised variable definitions and documented construction rules, which are particularly relevant in a machine learning setting where models are trained and evaluated on partitioned data. Its inclusion supports robust feature engineering, reproducible train validation splits, and alignment with prior ageing related ML studies that adopt harmonised frameworks. The specific role of harmonised variables within the modelling pipeline is detailed in Chapter 3.

Despite these advantages, existing ML research on chronic disease prediction faces persistent limitations: over reliance on clinical predictors, limited incorporation of lifestyle and SOC variables, predominantly cross sectional study designs that fail to capture trajectories, and a lack of interpretability consistent with emerging AI governance standards.

This thesis addresses these gaps by leveraging longitudinal TILDA data across multiple domains, using interpretable ML methods to combine modifiable health behaviours, psychosocial factors, and established clinical measures to enhance prediction of ageing related outcomes.

1.1 Research problem and motivation

Despite increasing research and clinical interest in lifestyle, nutrition factors, and advances in ML methods, approaches to chronic disease prediction in older adults remain limited in several ways.

¹TILDA’s dataset are pseudonymised and accessed under license via Irish Social Science Data Archive (ISSDA). Use adheres to University of Limerick (UL) S&E ethics approval and data retention requirements.

- **Limited Integration of Multidomain Predictors:** Existing models focus primarily on clinical measurements and often neglect modifiable behavioural, dietary, and psychosocial factors [12, 16].
- **Underuse of Longitudinal Dynamics:** Few studies leverage repeated measures to capture developments of risk, such as Frailty (FR) progression [6]. Probabilistic reasoning can help estimate the likelihood of developing a condition at a future time given earlier measurements, for example, calculating the probability $P(\text{FR at wave 5} \mid \text{UGS at wave 1, Nutrition at wave 2})$.

This approach helps quantify how early indicators influence later outcomes and supports better feature selection and timing of interventions in predictive models.

- **Lack of Explainability:** Many ML models are not interpretable, limiting clinical adoption and failing to meet emerging regulatory requirements for trustworthy AI in healthcare [17].

Addressing these challenges is essential to improve predictive accuracy, support evidence based interventions, and ensure alignment with evolving policy and regulatory priorities.

1.2 Research aims and objectives

The goal of this thesis is to develop and validate ML models that integrate nutrition, lifestyle, and MH features with clinical data to improve prediction of chronic disease and ageing related outcomes in a representative cohort of older adults. This goal will be achieved through the following objectives:

- Review existing applications in ML for chronic disease prediction in ageing populations, with emphasis on gaps in lifestyle and nutrition integration.
- Develop a reproducible pipeline to preprocess and align TILDA waves 1–5, and engineer multidomain features (nutrition, activity, mobility, MH, clinical indicators).

1. INTRODUCTION

- Develop and compare baseline statistical models (e.g., logistic regression) with advanced interpretable ML methods such as Random Forest (RF) and Gradient Boosting Machine (GBM).
- Evaluate models using predictive classification performance metrics including Area Under the ROC Curve (AUC), calibration and error measures (accuracy, precision, Recall (true positive rate) (Recall), F1-score (harmonic mean of precision and recall) (F1)), perform ablation analyses to assess the incremental value of lifestyle and nutrition predictors.
- Identify actionable predictors (e.g., vitamin D status, UGS reserve) and highlight modifiable risk factors for intervention.
- Document ethical, governance, and reproducibility practices for handling longitudinal pseudonymised health data.

1.3 Contributions of the research

This research makes contributions at three levels:

- **Empirical:** Demonstrates how behavioural, dietary, and other MH features complement established clinical measures to enhance predictive performance.
- **Methodological:** Provides a reproducible pipeline for aligning longitudinal TILDA data across domains and integrating diverse features into ML workflows.
- **Clinical:** Highlights actionable modifiable factors alongside traditional clinical indicators for targeted interventions and policy.

1.4 Thesis outline

Chapter 2 presents a literature review on ML prediction of chronic disease in ageing populations, focusing on lifestyle, nutrition predictors and methodological

considerations. *Chapter 3* describes the data preparation process, including the TILDA study design, data collection, thematic domain structure, and the manual variable filtering workflow. In *Chapter 4*, the automated cleaning pipeline is presented, including the variable scenario detection system, the deterministic six-step cleaning sequence, and validation of the pipeline against established benchmarks. *Chapter 5* presents the experimental results, including model comparisons and feature importance analysis. *Chapter 6* discusses the implications and future directions of the research.

Chapter 2

Literature Review

This chapter reviews literature on ageing, chronic disease, and predictive modelling using TILDA (introduced in Chapter 1). It focuses on three interrelated domains central to later life health: FR, physical function, MH, and nutrition within the context of biological ageing. In line with the WHO healthy ageing framework, research using TILDA highlights FR, MH, and nutrition as interconnected determinants of later life outcomes.

2.1 Search strategy and study selection

Several methodological papers describe how systematic and integrative reviews are commonly carried out in fields such as software engineering, health, and education. This review followed key principles for systematic mapping. This included defining research questions, identifying relevant studies through structured database searches, applying inclusion and exclusion criteria, and categorising results as outlined [1]. The integrative literature review [18] helped structure and connect findings across studies, while [19, 20] guided the organisation of ideas. In related methodological work, [2] clarified how Systematic Review (SR)s can identify research gaps, and [21] showed how mapping and synthesis highlight trends and future directions. This combined guidance informed a structured yet flexible methodology suitable for ageing in AI, and health research.

2.1.1 Database search and query development

The main topic of interest was chronic disease prediction using nutrition, lifestyle, and clinical data from TILDA. Relevant databases (e.g., ScienceDirect, PubMed) were searched using combinations of keywords such as “Irish Longitudinal Study on Ageing”, “machine learning”, “chronic disease”, “nutrition”, “diet”, and “physical activity”, as shown in Table 2.1.

The search covered studies published from 2011 to 2025. Figure 2.1 summarises the number of studies identified per year, highlighting trends and gaps over time.




Figure 2.1: Publications per year.

Some search strings returned few or irrelevant entries, particularly for ML applications in TILDA, highlighting a key research gap. Iterations continued until suitable combinations consistently retrieved relevant studies. Duplicates were removed using Zotero’s reference management feature. The remaining studies were individually and manually checked for relevance to “ageing,” “chronic disease,” and ML. Using Zotero’s notes functionality, the initially created Table 2.3 captured key elements for each study, including model type, features used, and

2. LITERATURE REVIEW

Table 2.1: Database searches and number of studies per database 2.3 [1].

Database	Search	Results
Oxford Academic	(TILDA OR Irish Longitudinal Study on Ageing) AND (chronic disease OR diabetes OR cardiovascular) AND (nutrition OR diet OR "physical activity")	1081
	(TILDA OR "Irish Longitudinal Study on Ageing") AND ("machine learning" OR "predictive model" OR "risk prediction")	71
IEEE Xplore	TILDA OR "Irish Longitudinal Study on Ageing"	56
	(TILDA OR "Irish Longitudinal Study on Ageing") AND ("machine learning" OR "predictive model" OR "risk prediction")	7
ScienceDirect	(TILDA OR "Irish Longitudinal Study on Ageing") AND ("chronic disease" OR cardiovascular OR diabetes) AND (nutrition OR diet OR lifestyle OR "physical activity")	257
	(TILDA OR "Irish Longitudinal Study on Ageing") AND ("machine learning" OR "predictive model") AND ("chronic disease" OR diabetes) AND (nutrition OR "physical activity")	20
PubMed	(TILDA OR "Irish Longitudinal Study on Ageing") AND ("chronic disease" OR cardiovascular OR diabetes) AND (nutrition OR diet OR lifestyle OR "physical activity")	27
	(TILDA OR "Irish Longitudinal Study on Ageing") AND ("machine learning" OR "predictive model" OR "risk prediction")	9

2.1 Search strategy and study selection

main findings, as shown in the following Preferred Reporting Items for Systematic reviews and Meta Analyses (PRISMA) flow diagram (Figure 2.2).




Figure 2.2: PRISMA chart for SRs showing the study selection process for the systematic mapping and integrative review [5].

2.1.2 Quality and relevance evaluation

To systematically assess the quality of the included studies, a customised version of the Newcastle-Ottawa Scale (NOS) was applied (Table 2.2). The NOS evaluates studies across three domains: *selection* (S1–S4), *comparability* (C1–C2), and *outcome* (O1–O3). *Selection* criteria assess the representativeness of the sample, clarity of exposure measurement, and temporal alignment of outcomes. *Comparability* examines the control of key confounders (variables that may influence both the predictor and outcome), while *outcome* evaluates measurement validity, follow up adequacy, and completeness. Each domain is scored 0/1, recall the Bernoulli random variable (0 = criterion not met, 1 = criterion met), and the total score reflects the overall study quality.

This initial table guided a further refinement of the results into two sub tables: 1.studies critically related to TILDA, 2.studies using TILDA and ML for

2. LITERATURE REVIEW

predictive contexts, which revealed minimal to no integration with TILDA.

Table 2.2: Quality evaluation of Systematic Literature Review (SLR)s [2].

Reference	S1	S2	S3	S4	C1	C2	O1	O2	O3	Total
(Xu, 2023 [22])	1	1	1	1	1	1	1	1	1	9
(Donoghue, 2023 [17])	1	1	1	1	1	1	1	0	1	8
(Moguilner, 2021 [6])	1	1	1	1	1	0	1	1	1	8
(Davis, 2021 [7])	1	1	1	1	1	0	1	1	0	7
(Boyle, 2021 [23])	1	1	1	1	1	0	1	0	1	7
(Tzemah-Shahar, 2022 [24])	1	1	1	0	1	0	1	1	1	7
(A. Shirsath, 2024 [25])	1	1	1	1	1	1	1	0	1	8
(Romero-Ortuno, 2021 [26])	1	1	1	1	1	1	1	1	1	9
(Bardon, 2020 [27])	1	1	1	0	1	0	1	1	1	7
(Zhang, 2025 [28])	1	1	1	1	1	1	1	0	1	8
(Sutin, 2023 [29])	1	1	1	1	0	0	1	1	1	7

Table 2.3 summarises selected studies on ageing using TILDA and ML, reflecting key gaps and opportunities identified during systematic mapping. These steps were aligned with the research matrix created at the beginning, ensuring that the refinement of studies and synthesis of findings stayed closely tied to the original research goals.

2.1.3 Synthesis and integration

Using the NOS scores, each study was annotated in Zotero with details on dataset, key variables, analytical approach, and main findings, facilitating a consistent and systematic evaluation across studies. For the systematic component, data was systematically extracted and synthesised to identify trends (e.g., Markov models, logistic regression, 5-fold Cross Validation (CV)) and research gaps [2], complemented by *DoctoralWriting* resources [30, 31], which clarified how to define research questions and develop logical arguments.

The integration of a research matrix with systematic mapping and integrative synthesis ensured that the methodology was well suited to capturing the complexity of ageing, nutrition, chronic disease risk and predictive modelling studies focused primarily on TILDA based studies, but due to the limited number of

2.1 Search strategy and study selection

Table 2.3: Summary of selected studies on ageing using TILDA.

Theme	Author/year	Dataset	Variables/features	Methods/model type	Key Findings/outcome	Limitations
Frailty (FR)	Romero-Ortuno (2021) [26]	Wave 1–5	FR state, FR phenotype (FP) components (Exhaustion (EX), Unexplained weight loss (WL), Weakness (WK), Slowness (SL), Low physical activity (LA))	Multi state Markov model, longitudinal 8 year follow up	32% of pre frail to non frail; FR strongly predicted 31% mortality	Self report bias; observational design
Falls + Machine Learning (ML)	Donoghue (2023) [17]	Wave 1–3	Gait, mobility, medications, history of falls	Conditional inference forest; 5-fold CV; undersampling for imbalance	Accuracy up to 69.7%; for adults aged 50–64.	Area Under the Receiver Operating Characteristic Curve (AUROC) values were ≤ 0.69 and PRAUC ≤ 0.39 indicating low predictive accuracy; no external validation; cross sectional; Class imbalance
Fear of Falling (FOF)	Zarudsky (2014) [32]	Wave 1	Age, sex, fall history	Cross sectional prevalence analysis	23.3% prevalence; higher in women; 70% with Fear of Falling (FOF) had no recent falls in the last 12 months	Self reported; cross sectional
Functional Mobility	Huang (2019) [33]	Wave 1–2	Measured by Timed Up and Go (mobility test) (TUG), Hand Grip Strength (HGS), physical activity, vision, Body Mass Index (BMI), age	Linear regression, stratified analyses	Age modifies effects; PA and grip protect mobility; vision benefit only in middle aged (Beta = -0.032, P = 0.002)	Observational; 2 year follow up
Depression	Jacob (2023) [34]	Wave 1–2	Falls, FOF, HADS-A, Center for Epidemiologic Studies Depression Scale (CES-D)	Prospective logistic regression	Falls predicted incident anxiety Odds Ratio (OR)=1.58 and depression OR=1.43	Self reported falls; short follow up; mediation effect partially explored
	Laird (2023) [16]	Wave 1–5	Moderate-to-Vigorous Physical Activity (MVPA), walking, sociodemographics	Longitudinal regression; mixed model	Higher physical activity reduced depressive symptoms; dose response effect	Self reported PA; observational; limited causal inference
Nutrition	Murphy (2023) [12]	Wave 1–5	Plasma lutein, zeaxanthin	Linear/ordinal logistic regression	Higher carotenoids pre-linked to slower FR progression Lower odds of becoming frail (ORs = 0.57–0.89)	Observational; not predictive of longitudinal muscle changes
	Bardon (2020) [27]	Wave 1–2	Hospitalisation, functional status, SOC support, sex, falls	Logistic regression; sex stratified analyses	Functional decline, hospitalisation, poor support increased malnutrition risk; sex differences	Observational (short follow up (2 years)); limited generalisability >65 years, self reported
ML	Xu (2023) [22]	Wave 1–3	105 predictors from 40,000+ variables (SOC, clinical, mental, family)	Stacked ensemble: RF, XRT, GLM, GBM, Deep Neural Network (DNN); Shapley Additive Explanations (SHAP) explainability	AUC=0.854 for 2 year Diabetes Mellitus (DM) prediction; top predictors LDL, cirrhosis, sex	No external validation; short follow up; ensemble complexity limits deployment
	Davis (2021) [7]	Wave 3	Age, HGS, chair stands, BMI, cognitive tests	Histogram gradient boosting regression; SHAP	r^2 test: UGS $\approx$ 0.41, Maximum Gait Speed (MGS) $\approx$ 0.46, GSR $\approx$ 0.21	Modest predictive power; cross sectional; no external validation
	Zhang (2025) [28]	Longitudinal IMAGEN cohort	Psychopathology, personality, cognition, substance use, environment	Regularised logistic regression; diagnostic	Longitudinal AUC: ED=0.71, MDD=0.64, AUD=0.67; shared transdiagnostic predictors	Limited age range; no external replication
	Boyle (2021) [23]	Wave 3	Brain predicted age difference (brainPAD); processing speed; attention; cognitive flexibility; verbal fluency	Linear regression, correlation analyses	Higher brainPAD associated with lower cognitive performance across multiple domains	Cross sectional; no causal inference; limited sample

2. LITERATURE REVIEW

ML applications with TILDA, additional studies on older adult populations and chronic disease were included.

2.2 Frailty and physical function

FR reflects declining physiological reserve, providing a framework for understanding physical vulnerability in ageing. In TILDA, it is captured through both the FR phenotype and the FR index, with UGS, HGS, and mobility decline serving as practical predictors. These measures strongly predict hospitalisation and mortality.

2.2.1 Probabilistic interpretation of frailty

One can argue that from a probabilistic perspective, the chance of an adverse outcome (such as mortality, Y) given observed features (such as FR markers, X) is a conditional probability $P(Y | X)$. This allows us to deduce which FR features are most predictive of adverse outcomes. Features may be independent, dependent, or mutually exclusive.

The presence or absence of metabolic syndrome represents a mutually exclusive event that can inform risk models.

$$P(X_i \cap X_j) = P(X_i)P(X_j)$$

for independent features X_i and X_j , guiding feature selection and reducing redundancy in model inputs. This reflects the likelihood that an individual with certain FR characteristics will experience a particular outcome.

Evidence suggests that FR is dynamic, not irreversible. For example, multi state modelling showed that many prefrail adults transition back to non frail, although established FR strongly predicts mortality [26]. Metabolic syndrome accelerates the development of FR, suggesting a metabolic pathway of vulnerability [35]. The presence of metabolic syndrome modifies the conditional probability $P(\text{FR} | \text{Metabolic Syndrome})$ and may increase the likelihood of adverse outcomes over time. Age also plays an important role: obesity predicts mobility decline earlier in life, whereas later in life, traits that protect against this, including HGS, become more significant [33].

These findings partly conflict: FR appears both reversible and progressive, depending on risk context. This complexity highlights the need for probabilistic models that can update beliefs about risk as new features are observed, as formalised by Bayes theorem:

$$P(Y | X) = \frac{P(X | Y)P(Y)}{P(X)}$$

where $P(Y | X)$ is the posterior probability of outcome Y given features X .

2.2.2 Bayesian updating of frailty risk

Causal inference is limited by observational designs, and predictors are frequently examined separately, ignoring interactions. Most FR models have only been tested on the TILDA dataset, and with this study that focuses on the same TILDA but uses both longitudinal TILDA waves and harmonised variables to improve cross study comparability, enabling more robust train-validation splits in ML models, and exploring richer predictive patterns over time. These gaps point to the need for multidimensional approaches. Traditional regression models may not fully capture age dependent interactions, suggesting a role for more flexible methods such as machine learning techniques and models.

2.3 Mental health in older adults

MH, including depression, anxiety, loneliness, and SOC isolation, strongly shapes quality of life. Evidence from TILDA shows strong links to both physical and SOC factors. [36] found that participation in physical, SOC, and cognitive activities summarised by the Act-Belong-Commit (ABC) indicator was associated with lower depression and anxiety. This suggests SOC integration and lifestyle protect mental wellbeing. However, [37] reported that self reported measures may exaggerate such associations, raising concerns of bias. These two findings conflict: the effect of SOC engagement is strong when self reported and weaker when objectively assessed.

Objective data strengthen the case for activity. Accelerometer based measures show a dose response link between moderate to vigorous activity and lower

2. LITERATURE REVIEW

depressive symptoms [13]. Yet reverse pathways are also evident: incident falls and functional decline predict later depression, mediated by FOF [34]. Together, these results reveal a bidirectional relationship, MH both influences and is influenced by physical decline. Most studies rely on broad self report scales, such as CES-D or Hospital Anxiety and Depression Scale (HADS), with little biomarker or clinical validation.

This literature suggests MH in ageing cannot be modelled as a one way effect. It requires longitudinal, multidimensional approaches that can capture mutual pathways, an area where machine learning is well suited, especially when combined with probabilistic models that estimate the likelihood and posterior probability of MH outcomes given multiple interacting features.

For example, we can estimate:

$$P(\text{Depression} \mid \text{Activity, Falls, SOC Engagement}),$$

quantifying how these interacting features together influence MH outcomes. Probabilistic modelling helps determine which features have the strongest effect and which may be redundant for predictive purposes.

2.4 Nutrition and biological ageing

Nutrition interacts with both biological and psychosocial systems, shaping ageing trajectories and FR. Biomarkers like vitamin D, lutein, and zeaxanthin have been linked to physical and cognitive outcomes in TILDA. [12] showed that higher plasma lutein and zeaxanthin dietary carotenoids found in leafy vegetables were linked to slower FR progression. By contrast, [38] found vitamin D deficiency predicted DM, musculoskeletal decline, especially among adults with low sunlight exposure. These studies point to different nutritional mechanisms: antioxidant protection versus metabolic regulation.

2.4.1 Bayesian perspective on nutritional biomarkers

The effect of nutrition on ageing outcomes can be formalised probabilistically using Bayes theorem:

$$P(\text{Outcome} \mid \text{Nutritional Status}) = \frac{P(\text{Nutritional Status} \mid \text{Outcome})P(\text{Outcome})}{P(\text{Nutritional Status})},$$

where the likelihood function $P(\text{Nutritional Status} \mid \text{Outcome})$ quantifies how observed nutritional biomarkers relate to health states, and the posterior $P(\text{Outcome} \mid \text{Nutritional Status})$ captures updated beliefs about outcomes, including uncertainty in small sample studies. This helps identify which biomarkers are most informative for predicting ageing outcomes, which supports feature selection in ML models.

2.4.2 Contextual and integrative considerations

Malnutrition also reflects SOC and functional risks. [27] found that hospitalisation, functional loss, and poor SOC support increased malnutrition risk, with notable sex differences. This highlights a limitation in much nutritional research: biological markers are studied without integrating SOC context.

The difference between biological and chronological age is a major point of debate. Biomarker based metrics that better capture these cumulative exposures, like FR indices or epigenetic clocks, frequently vary from chronological age. McCarthy and Azizi link metabolic syndrome and nutritional deficits to accelerated biological ageing [39, 40]. Although the majority of the evidence is cross sectional and has little ability to capture changes over time, these indicators offer a more precise prediction of vulnerability. Reliability is also decreased in biomarker research with small sample sizes, which can be formalised through the likelihood function $P(\text{Data} \mid \theta)$ and its impact on posterior uncertainty in Bayesian inference.

Taken together, nutrition interacts with biological, metabolic, and SOC systems. Isolating single nutrients risks oversimplification. Integrative modelling that combines biomarkers, clinical factors, and SOC determinants supported by machine learning pipelines offers a more promising route. Models that estimate

2. LITERATURE REVIEW

the joint distribution of features and outcomes can better capture the complex dependencies relevant to biological ageing.

2.5 Machine Learning in ageing and chronic disease

ML is increasingly applied in ageing research because it can capture non linear and multidimensional relationships that traditional regression models, such as logistic regression, often miss [22, 23]. Studies using ML in ageing research include many types of predictors: clinical measures, sociodemographic factors, lifestyle habits, cognitive tests, and psychosocial variables.

A recurring pattern, however, is that models often over-rely on easily measured physical health data, such as comorbidity counts, mobility scores, or vital signs, while more complex but important predictors, including nutrition and SOC factors, are underrepresented [32]. This imbalance may limit the ability of models to capture the full complexity of chronic disease risk with ageing, especially considering that MH and nutrition exert independent and interacting effects on later life outcomes. Models that focus only on ready available clinical data risk reproducing the same biases seen in traditional regression approaches.

2.5.1 Models used in machine learning

The methodological approaches used in ageing research span both traditional and advanced models. Logistic regression and Markov models remain common baselines due to their interpretability and simplicity, yet they are often unable to capture non linearities or higher order interactions. More recent work has shifted towards ensemble methods such as RF, GBM, as well as DNNs, which generally achieve higher predictive accuracy.

Similarly, [41] evaluated mortality prediction using a standard logistic regression model with demographic, clinical, and functional predictors, achieving an AUC of 0.78, whereas ensemble methods in [22] reached 0.854 for DM prediction, showing how flexible, non linear models can better capture complex interactions among ageing related predictors.

2.5.2 Performance and validation

Predictive performance across studies is generally moderate to strong, with AUC values between 0.70 and 0.90 for outcomes like DM, UGS, depression, and mortality. This indicates that models can distinguish reasonably well between individuals who will or will not experience an outcome.

However, there are important limitations. Many studies rely only on internal validation, testing models on the same data used for training. This can inflate performance estimates and reduce confidence in applying the model to new populations. Furthermore, most studies are cross sectional, so causal or temporal effects cannot be assessed. When combined with the underuse of nutrition and SOC predictors, these issues indicate that current models may not fully represent the multidimensional nature of ageing and could produce context specific results rather than generalisable predictions [32].

2.5.3 Explainability in machine learning for ageing

As ML models become more complex, interpretability emerges as a critical challenge. Explainability tools like SHAP can highlight feature importance, but their use is inconsistent, particularly in deep learning models [4, 7, 22]. These methods improve transparency and can highlight unexpected drivers of outcomes, such as psychosocial variables being stronger predictors than biomedical ones, yet black box concerns remain, especially for deep learning models, where feature interactions are difficult to track. For ageing research, where clinical adoption requires both accuracy and trust, explainability is not optional but essential. Current efforts show promise but remain fragmented, with no consensus on best practice. This gap links directly to the broader methodological limits discussed in the next section on gaps in the literature.

2.6 Gaps in the literature

First, most studies rely on TILDA or similar cohorts of Irish and predominantly older adults (50+). This limits confidence in how well results transfer to other populations. This thesis focuses on TILDA studying ageing in depth but also

2. LITERATURE REVIEW

makes use of the harmonised dataset, which links TILDA with comparable UK and US cohorts. This helps place findings in a broader international context while retaining a core emphasis on older adults.

Second, there is an over reliance on physical health predictors such as co-morbidity counts and mobility measures, while nutrition, SOC, religious or spiritual, and environmental variables are often overlooked. As shown in [12], nutritional biomarkers like lutein and zeaxanthin are strong predictors of FR, yet these are rarely integrated into broader ML pipelines. By contrast, studies such as [27] highlight the role of SOC support and functional decline in malnutrition risk. Together, these examples show that excluding nutrition and SOC factors risks producing models that reinforce the same biomedical biases seen in regression heavy work. From a Bayesian viewpoint, the omission of key features reduces the explanatory power of the model and weakens the posterior probability $P(\text{Outcome} \mid \text{All Features})$ compared to $P(\text{Outcome} \mid \text{Limited Features})$. Including a richer set of features increases the likelihood that the model accurately reflects the true data generating process.

Third, methodological choices remain conservative. Regression models remain dominant, likely due to their interpretability and ease of implementation. However, they often fail to capture non linear interactions and higher order dependencies present in ageing related data. Comparisons with more advanced approaches such as DNNs or transformers are rarely explored. For instance, [41] achieved an AUC of 0.78 using logistic regression for mortality prediction in TILDA, whereas [22] reported an AUC of 0.854 with ensemble methods for DM incidence. This contrast illustrates that more flexible ML models can provide superior predictive performance while maintaining interpretability when combined with explainability techniques. Where ensembles or brainPAD approaches have been attempted, validation is almost always internal, with little cross cohort testing. Weak validation and limited feature sets reduce the generalisability of the estimated conditional probabilities and increase the risk of overfitting. Maximum likelihood estimation and Bayesian inference can provide a formal framework for assessing model fit and updating predictions as more diverse and representative data become available.

Fourth, many outcomes relevant to older adults such as pain, sleep quality, and subjective wellbeing remain underexplored. For example, [12] focused on plasma biomarkers for FR without assessing sleep or pain, and UGS models such as [7] similarly omit subjective quality of life. Omitting these outcomes limits the real world application of predictive models. Including broader outcomes in ML pipelines can better capture holistic ageing trajectories and improve interpretability for interventions targeting older adults.

Fifth, cross sectional bias and data handling weaken reliability. Much nutritional work, such as [12], relies on single time point biomarker data, which cannot capture longitudinal change. By contrast, studies applying multi wave TILDA data [26] demonstrate the added value of modelling temporal dynamics. Similarly, missing data are often handled through listwise deletion, as in [41], which risks biasing results toward healthier participants, whereas more robust imputation approaches remain underused. Missing or poorly handled data can distort the likelihood function and hence the posterior predictions, reducing confidence in the model’s outputs.

Finally, interpretability challenges persist. While tools like SHAP have been applied to highlight feature importance [4, 22], their use is inconsistent, and consensus on best practice has yet to emerge. Without transparent explanations, even accurate models may face barriers to clinical acceptance. Taken together, these examples show that ageing research continues to rely on narrow predictors, conservative models, and weak validation. Addressing these gaps requires integrative, diverse, and transparent approaches that link multidimensional predictors with explainable ML.

2.7 Chapter summary

This chapter reviewed evidence on ageing and chronic disease across three domains, FR, physical function, MH, nutrition, and biological ageing. We also examined how machine learning has been applied to predict later life outcomes. The findings showed that while FR is partly reversible, it remains strongly tied to mortality, that MH both shapes and is shaped by physical decline, and that

2. LITERATURE REVIEW

nutrition interacts with biological, metabolic, and SOC systems in ways that are often underestimated.

While machine learning has improved prediction accuracy in ageing research, challenges remain in integrating diverse predictors and ensuring interpretability and longitudinal validation.

Addressing these challenges requires the integrative, longitudinal, and transparent approaches that combine diverse predictors. These gaps motivated the data preparation and pipeline implementation described in Chapters 3 and 4, and the modelling strategies presented in Chapter 5.

Chapter 3

Methodology

3.1 Study population and design

TILDA provides longitudinal data across five waves (Waves 1–5) for community dwelling adults in Ireland. For benchmarking against international cohorts, an external harmonised TILDA dataset was also inspected and prepared. The harmonised dataset, which has been pre aligned to international standards e.g., the Gateway to Global Ageing Data (G2G), contains a subset of variables mapped to a common cross study format and thus differs from the raw TILDA files. Although the harmonised dataset was simpler to process, it was still subjected to the variable filtering and numerical standardisation steps developed as part of this research to ensure compatibility with the five wave cleaned datasets prior to modelling.

All participants who provided data in at least one TILDA wave were considered eligible. To maximise the available sample for machine learning, no exclusions were applied on the basis of age, medical conditions, mobility, cognitive status, or health centre attendance.

Participants were removed only in the rare case that, following manual variable filtering, no analytically usable variables remained for that individual. Filtering occurred primarily at the *variable level* during the manual screening stage, which excluded features with extreme missingness, lack of variation, or non informative structure. This approach preserves the largest possible sample while ensuring all

3. METHODOLOGY

retained inputs are analytically meaningful for downstream analysis and model development.

- **Participant inclusion:** All respondents who contributed data in at least one wave were included in the initial sample.
- **Usable data requirement:** Participants were excluded only if all retained variables were missing for that individual after manual variable screening.
- **Longitudinal retention:** Individuals were retained regardless of how many waves they contributed to, enabling initial maximum dataset utilisation.
- **No clinical exclusions:** No participant was removed due to medical diagnoses, cognitive scores, functional limitations, or non attendance at the health centre assessment.

This approach prioritises data integrity and sample size for machine learning applications, differing from exclusion heavy cohort definitions often used in traditional epidemiological studies [42].

3.2 TILDA data collection and screening

TILDA data collection occurred over five longitudinal waves (Table 3.1).

Each wave included three primary components:

1. **Computer Assisted Personal Interview (CAPI):** Home based, computer assisted personal interviews covering health, socio demographics, and family.
2. **Self Completion Questionnaire (SCQ):** Paper based self completion questionnaires capturing sensitive information on mental health, lifestyle, and wellbeing.
3. **Health Assessment:** Clinical and biomarker measurements conducted in dedicated centres or at home (Wave 1 and Wave 3).

All TILDA data were pseudonymised prior to release, meaning that personal identifiers such as names and addresses were removed or replaced with unique codes to protect participant confidentiality. Each participant received a unique identifier ('id'), along with household and cluster identifiers ('household', 'cluster'), allowing longitudinal linkage across waves without revealing individual identities.

Pseudonymisation ensures that analyses comply with data protection standards while retaining the structural and analytical integrity of the dataset. From a data cleaning and machine learning perspective, pseudonymised identifiers enable accurate merging of data across waves, preserve the longitudinal design, and support reproducible preprocessing and feature engineering. While these identifiers cannot be used for analyses of personal demographics like names or addresses, this limitation does not affect the modelling of health outcomes, lifestyle factors, or other variables of interest.

Table 3.1: Dimensions of raw TILDA and harmonised datasets version 5.5 (prior to cleaning in Section 4.1).

Dataset	Collection Period	Participants (N)	Raw Variables (N)
Wave 1 [43]	2009–2011	8501	1619
Wave 2 [44]	2012–2013	7206	724
Wave 3 [45]	2014–2015	6397	1029
Wave 4 [46]	2016	5713	990
Wave 5 [47]	2018–2019	4978	983
Harmonised [48]	2016 (release)	8501	572

3.3 Thematic domains

Variables were organised into seven thematic domains based on ageing literature and study objectives. Each variable's prefix, as defined in the Pseudonymised Microdata File (PMF) metadata (Table 3.2), indicates its source or research domain. This systematic assignment ensures that each thematic group contains conceptually related features and provides a clear structure for downstream automated preprocessing and machine learning.

3. METHODOLOGY

Each variable in TILDA was assigned a prefix indicating its data source or research domain. Home based CAPI variables use a two letter module code followed by a three digit question code (e.g., **ph121**). Variables with multiple responses or loops include an underscore and number to specify the response or iteration (e.g., **ph201_05**).

Variables from the self completion questionnaire are prefixed with SCQ, while derived variables constructed from either CAPI or SCQ data use uppercase codes corresponding to their research area (Table 3.2). These prefixes provide a consistent framework for categorising features and guiding the assignment into thematic domains for downstream analysis.

By categorising the raw variables into these seven thematic domains, a structured foundation was established for the technical dimensionality reduction and cleaning pipeline described in the following Section 3.4 and Chapter 4.

3.4 Manual variable filtering workflow

Prior to any data cleaning or modelling, a structured multi-stage workflow was implemented to screen and reduce the dimensionality of the raw TILDA datasets. As shown in Table 3.3 (for example, 1619 $\rightarrow$ 809 variables in Wave 1), the raw PMF files were reduced to a subset of variables of interest. This procedure also separated automated diagnostic profiling from manual variable exclusion, ensuring transparency in all selection decisions.

The process consisted of the following steps:

1. **Raw data loading:** Raw TILDA PMF files were loaded without cleaning or recoding. Waves 1–5 were loaded from Statistical Package for the Social Sciences (SPSS) (**.sav**) files, while the harmonised dataset was loaded from a (Stata) (**.dta**) file due to technical compatibility issues.
2. **Automated variable profiling (Python):** For every variable, summary statistics were computed programmatically, including data type, proportion of missing values, number of unique values, most frequent value, and frequency of the most frequent value. These summaries were exported to spreadsheet format for inspection.

3.4 Manual variable filtering workflow

Table 3.2: PMF v5.5 derived variable prefixes [3].

Variable Prefix	Research Area
1: Socio Demographic & Context	
INC	Income variables
SES	Social class
SOC	Social
2: Physical Health & Clinical Baseline	
BP	Blood pressure from sphygmomanometer
MD	Medication data
SCR	Screening tests
3: Functional Status & Frailty	
ADL	Activities of daily living
DIS	Disability, functional impairment, helpers
FR	Frailty, gait, exercise, falls and fractures
GRIP	Grip strength
IADL	Instrumental activities of daily living
4: Lifestyle & Behavioural	
BEH	Health behaviours
5: Nutrition & Metabolic Biomarkers	
BLOODS	Results of blood sample analysis
6: Psychological & Cognitive	
COG	Scales and questions on cognition
CRT	Choice reaction time (cognitive test)
MH	Scales and questions on mental health and wellbeing
Other / Administrative	
G2G	Gateway to Global Aging Data

3. METHODOLOGY

3. **Manual variable screening (spreadsheet based):** Using predefined rule based thresholds described below. Variables were manually reviewed and flagged for exclusion based on missingness, lack of variation, dominance of a single category, or administrative function.
4. **Creation of retained variable lists:** Variables not flagged for exclusion were programmatically concatenated in `.xlsx` and manually transferred into wave specific JavaScript Object Notation (JSON) files representing the retained variables of interest.
5. **Reloading filtered datasets:** The JSON files were then used to subset the original raw datasets, producing reduced datasets with identical rows but fewer variables. No cleaning, recoding, or imputation was applied at this stage.

Python scripts were used to profile all variables across each wave. For every variable, the following metrics were computed: data type, number of missing values, number of unique values, most frequent value, and frequency of the most frequent value. These summaries were exported to spreadsheet format to support structured manual review prior to variable dropping.

Manual filtering was applied according to the following criteria:

- **Missingness:** Drop variables with $> 80\%$ missing values. This threshold balances retaining sufficient feature coverage while ensuring statistical reliability. Variables exceeding this threshold provide limited information in most cases, increase imputation uncertainty, and reduce effective sample size, which is particularly critical in longitudinal machine learning analyses.
- **Unique values:** Drop variables with a single observed value, as they contain no discriminative information and cannot contribute to modelling or inference. Variables with low cardinality (2–4 unique values) were retained for review, as they frequently represent meaningful categorical responses (e.g., binary indicators or ordinal scales) relevant to ageing outcomes.
- **Dominant category (top value/frequency):** Variables where a single category (sample value) marked as the *topValue* occurs over $\approx > 90\%$

(*topFrequency*) of observations were flagged. Such dominance indicates limited variability, reducing analytical utility and predictive value. Variables exceeding this threshold were marked for review or exclusion.

- **Identifiers / administrative fields:** IDs, version tags, and sampling weights were identified using the PMF metadata. Variable names and descriptions were exported from each wave’s PMF file into Comma Separated Values (CSV) files (Appendix A) to systematically document and review features prior to filtering. These exports enabled structured manual inspection and traceability between raw PMF metadata and downstream feature selection decisions.

During manual screening and filtering, variables exceeding exclusion thresholds (e.g., high missingness, single value, dominant category, administrative identifiers) were visually flagged (e.g., marked in red). Non flagged variables were programmatically concatenated with double quotes and comma to separate each variable using spreadsheet formulas (e.g., `=TEXTJOIN(", ", TRUE, CHAR(34) & J2:Jn & CHAR(34))`) ready for the manual transfer into wave specific JSON files for each wave. These files represent the *variables of interest* retained after manual screening and filtering and serve as inputs for the upcoming automated data preprocessing and cleaning in Section 4.1.

The retained variables defined in JSON files were subsequently used to subset the raw datasets. As shown in Table 3.3, this process yielded a significant reduced dataset for each wave. For instance, in Wave 1, manual filtering reduced the feature space from 1,619 to 809 variables, a 50.03% reduction. When considering all five waves collectively, the total number of variables was reduced from 5,345 to 3,099 representing a count of 2,246 dropped features with an overall reduction average of 42.0%. This substantial drop highlights the elimination of non-contributory data (providing no predictive value to the model), ensuring only the *variables of interest* proceed to the automated cleaning engine.

Importantly, all variable exclusion decisions were completed at this stage. Subsequent preprocessing steps focus exclusively on numerical standardisation, recoding, and preparation for machine learning rather than further feature removal. With the variables of interest selected and the datasets reduced to a

3. METHODOLOGY




Figure 3.1: Flowchart of the manual five-step workflow for variable screening and filtering. Placeholder (n) values represent the number of variables at each stage, illustrating the reduction from the raw dataset to the filtered dataset prior to automated preprocessing.

manageable dimensionality, the next stage focuses on automated preprocessing, recoding, and preparation for ML modelling.

3.5 Reduced dataset overview

To further understand the characteristics of these retained variables, the datasets were profiled using an exploratory visualiser (`.ipynb`) file implemented with `pandas`, `numpy`, `matplotlib`, and `seaborn`. This step examined data types, missingness patterns, unique value distributions, and representative sample values across all waves. The purpose of this profiling stage was not transformation but to expose structural inconsistencies and latent formatting issues that would undermine direct numerical conversion.

Table 3.3: Input shape for cleaning pipeline (post manual filtering workflow 3.1).

Dataset	Row (N participants)	Column (N features)	% Reduction
Wave 1	8501	809	50.0%
Wave 2	7206	482	33.4%
Wave 3	6397	639	37.9%
Wave 4	5713	592	40.2%
Wave 5	4978	577	41.3%
Harmonised	8501	453	20.8%

For example, in wave 1, the visualiser detected 650 categorical columns, 150 (`float64`) columns, and 9 object columns, while the harmonised dataset contained 304 categorical columns, 148 `float32` columns, and several integer columns. Age distributions confirmed that the study population was restricted to older adults across waves, however, ages were bottom coded for participants younger than 50 years and top coded for those aged 65–85 years and above. Missing value summaries indicated substantial variation (e.g., mean missing values ranging from 4.7% in wave 4 to 35% in the harmonised dataset, with some variables exceeding 77% missing).

Despite this, the exploratory visualiser was limited because the raw data were not yet cleaned, many outputs were incorrect or nonsensical due to hybrid formats and inconsistent coding. For instance, inspection revealed that many variables

3. METHODOLOGY

across both the wave specific and harmonised datasets, while appearing numeric at first glance, in fact contained hybrid representations combining numeric prefixes with descriptive text (e.g., “1.Rarely or none of the time (less than 1 day)”, “4.All of the time (5–7 days)”, or prefixed labels such as “0.not coupled”, “1.coupled”). A trivial string stripping approach would therefore produce incorrect numeric values (for example, reducing “5–7 days” to 5) resulting in silently introducing semantic distortion. Similarly, numeric columns sometimes contained sentinel codes (e.g., -98, -99) or embedded symbols (‘\$’, ‘*cm*’, ‘%’) that skewed visual summaries.

These insights, revealed through systematic profiling, guided the development of the subsequent cleaning pipeline steps, ensuring consistent numeric logic representations (e.g., midpoints for ranges, standardised sentinel handling).

3.6 Retained variable distribution by domain

Using the PMF prefixes described in Table 3.2 as a guide, variables were assigned to seven thematic groups (Table 3.4), each capturing a conceptually coherent domain: physical, cognitive, social, and behavioural aspects of ageing. This structure supports reproducible preprocessing and helps machine learning models focus on meaningful, longitudinally robust features.

Specifically, the thematic grouping:

1. Provides a clear framework for automated cleaning and filtering rules.
2. Ensures that model input variables are conceptually aligned with study objectives.

The seven thematic groups integrate information from CAPI, SCQ, and derived variables, covering sociodemographic context, physical health, functional status, lifestyle behaviours, nutrition and metabolic biomarkers, psychological and cognitive measures, and administrative identifiers.

The gradient *heatmap* integrated at the bottom of Table 3.4 visually illustrates the relative dominance of each thematic domain across the five waves. Darker blue shading indicates domains with a higher number of variables, providing a

3.6 Retained variable distribution by domain

quick summary of domain coverage and prominence. This integrated visualisation supports interpretation by highlighting which domains contribute the most features to the dataset.

3. METHODOLOGY

Table 3.4: Thematic domain grouping of longitudinal features.

ID	Thematic Group	Description	Representative Variable Examples	Total Features
1	Socio-Demographic & Context	Baseline demographic and socioeconomic indicators	Age/Sex	844
			Education	
			Income	
			Marital status	
2	Physical Health & Clinical	Clinical and self reported health measures	Blood pressure	839
			BMI	
			Chronic disease status	
			Self rated health	
3	Functional Status & Frailty	Physical functioning and frailty markers	Activities of Daily Living (ADL)/Instrumental Activities of Daily Living (IADL)	174
			Grip strength	
			Gait speed	
4	Lifestyle & Behavioural	Health behaviours and activity patterns	Physical activity	120
			Smoking	
			Alcohol use	
5	Nutrition & Metabolic	Metabolic and biomarker indicators	C-Reactive Protein (CRP)	22
			Creatinine	
			Lipid markers	
6	Psychological & Cognitive	Cognitive performance and mental health	Mini-Mental State Examination (MMSE)	291
			Depressive symptoms	
			Stress scale	
7	Other / Administrative	Survey metadata and structural variables	Sampling weight	809
			Completion status	
			Contact names	

	SocioDemographic_Context	PhysicalHealth_Clinical	FunctionalStatus_Frailty	Lifestyle_Behavioural	Nutrition_Metabolic	Psychological_Cognitive	Other_Administrative	Total_Features
wave1	272	149	48	58	10	97	175	809
wave2	119	148	18	21	0	38	138	482
wave3	164	184	44	14	8	93	132	639
wave4	161	186	30	13	4	36	162	592
wave5	128	172	34	14	0	27	202	577
Total_per_Domain	844	839	174	120	22	291	809	3099

Thematic domain dominance across waves (higher n features per domain).

Chapter 4

Technical Implementation

4.1 Automated cleaning engine

The core challenge in converting heterogeneous variable types across the six datasets (Table 3.3) was achieving a single numerical standard suitable for downstream analysis. This required enforcing *numerical homogeneity*, defined here as representing all retained features using a single numerical representation (`float64`) with a unified missing or non response sentinel (`-1.0`).

The exploratory profiling across all waves showed that categorical variables were dominant overall (2,916 columns), while numeric variables were fragmented across multiple types, with `float64` being the most prevalent native numeric representation (462 columns), motivating its use as a common standard to ensure consistency and compatibility with downstream ML models, while accommodating decimal values arising from range midpoints, frequency normalisation, and ordinal scaling that cannot be reliably represented using integer types.

To address this, the solution was implemented as a two stage system. The first stage performs automated *variable scenario detection*, identifying the structural form of each variable based on observed value patterns using the `detect_column_scenario_map` function (Appendix C). This stage includes additional diagnostic categories used during development to surface unhandled edge cases.

The second stage applies a deterministic *six step numerical cleaning engine* (Appendix E). While nine scenario categories were initially defined during development, three served exclusively as validation fallbacks and were progressively

4. TECHNICAL IMPLEMENTATION

eliminated as detection coverage improved, with a full scenario to step mapping counts provided in Appendix B. The final pipeline therefore consists of six active transformation steps, applied sequentially and uniformly across all waves.

4.1.1 Stage 1: Variable scenario mapping and validation

Stage 1 focused on automatically identifying how each variable should be handled during cleaning. The automated detection function in Appendix C was developed to classify variables based on their observed value structure, including the presence of sentinel codes, numeric annotations, ordinal labels, and mixed string numeric formats. While multiple intermediate detection categories were used during development, these served solely as internal routing logic. Although all variables passed sequentially through the six step cleaning pipeline, most were fully resolved in the earlier steps (Steps 1–5). The final step (Step 6 in Appendix D) was applied only to residual variables that could not be deterministically resolved by earlier transformations.

The additional detection categories (e.g., “single value categorical”, “special symbol mixed”, and “unknown/complex”) were intentionally included as diagnostic fallbacks to surface unhandled edge cases due to the complexity and size of the data. As rules matured, variables initially defaulted to these fallback categories were progressively resolved into earlier, well defined scenarios, leaving none remaining for the final pipeline execution.

To ensure robustness, the classification output was immediately processed by a validation routine that generated a comprehensive dictionary of feature states before and after cleaning, including all representative sample values for each variable. This allowed direct inspection of how the same variable was represented across waves prior to cleaning, particularly in cases where identical semantic categories appeared in different orders or formats. By comparing these grouped samples before and after each cleaning step, classification errors and inconsistent mappings were identified and corrected prior to execution of subsequent transformations.

The dictionary generated inside the `show_grouped_vars_for_scenarios` function (Appendix F) was formatted to create an automatic friendly “.md” file for

rapid, surface level verification, which honed the final mapping dictionary (an example can be found in Appendix G) for all features across all waves. This process of using automated detection followed by visual, manual validation was essential for correcting errors in classification logic before the subsequent scenario transformations were executed in the pipeline.

4.1.2 Stage 2: Deterministic six step cleaning sequence

The nine input scenarios were processed sequentially by the *six step cleaning engine*, resolving simple and unambiguous cases first to maximise the proportion of clean numerical features before tackling more complex structures, particularly censored and multi class scenarios (Figure 4.1). With later steps progressively shifting from cleaning into semantic feature engineering, this deterministic sequence applied identical transformation and feature encoding logic to each wave, with later steps (particularly Steps 4–6) performing rule based feature engineering by deriving semantically meaningful numerical representations directly from observed category tokens at runtime. The methodological rationale and implications of this integrated engineering which reframes cleaning as semantic feature construction are detailed in Section 4.1.3. (See Appendix D for implementation).

This design reflects the empirical diversity of survey encodings, where a small subset of variables only reveal their semantic structure after simpler transformations have been applied.

The final cleaning pipeline consisted of six deterministic steps applied uniformly across all TILDA waves, with increasingly complex transformations handled in later stages. Steps 4–6 required particular attention due to hybrid, ordinal, or multi class formats. A summary of each step and examples is provided below.

1. **Empty / Blank Values:** All missing entries, empty strings, and whitespace were converted to the standard non-response sentinel (-1.0).
2. **Sentinel Values:** Wave specific non-response codes (e.g., -98, -99) and textual sentinels (e.g., "dk", "not applicable") were mapped to the unified (-1.0) placeholder.

4. TECHNICAL IMPLEMENTATION




Figure 4.1: Flowchart of the final six-step cleaning pipeline applied to all TILDA waves. Detailed transformation tables are provided in Appendix B.7, and the corresponding implementation “.ipynb” script is documented in Appendix E at each scenario step.

3. **Numeric Transformation:** Numeric like columns containing embedded units, symbols, or hybrid strings (e.g., 50+, <10, 1-2.5) were parsed using regex and converted to `float64`. For ranges, midpoints &/or boundary values were used. For censored or annotated values, appropriate upper/lower bounds were applied.
4. **Censored / Ordinal Variables:** This step addressed variables representing ordinal scales, bracketed numeric ranges, or frequency expressions (e.g., “2–3 days a week”, “daily”). Transformations included:
 - Converting textual ordinal labels and Likert scale responses to numeric equivalents.
 - Mapping calendar based frequency descriptors to numeric weekly equivalents.
 - Manual verification for low count or unusual variables, supported by the Markdown audit outputs (Appendix G), to ensure semantic meaning was preserved.
5. **Binary Categorical Variables:** Two level features (e.g., Yes/No, Male/Female) were dynamically encoded using mappings derived from the observed value set of each variable:
 - Semantic rules were applied e.g., (“no”, “not”, “female” $\rightarrow$ 0.0) and (“yes”, “male” $\rightarrow$ 1.0).
 - Count based detection verified that variables had exactly two non-missing unique values.
 - Features with more than two sample values were also analysed for sentinel presence:
 - If a variable had three observed values and one was a sentinel, it was treated as binary.
 - If a variable had four observed values and two were sentinels, it was treated as binary.
 - Sentinels were preserved as -1.0.

4. TECHNICAL IMPLEMENTATION

- This approach ensured order invariant encoding across waves, even when original labels or numeric prefixes differed.
- *Example (sentinel case)*: Feature `f1002_5` with pre transformed values `['NOT Getting in or out of bed', -1.0, 'Getting in or out of bed']` was encoded as `[0.0, -1.0, 1.0]`, demonstrating how a sentinel preserves binary semantics.

6. Multi-class / Mixed Variables (rule based feature engineering):

Variables with remaining multi class structure, mixed types, or unresolved string numeric hybrids after earlier transformations were processed in the final step.

Technical implementation details for this step are provided in Appendix D:

- Lexical parsing extracted numbers, ranges, units, percentages, and textual frequency descriptors into floats, yielding interpretable numerical feature representations.
- Sentinel handling ensured all known non-response codes mapped to `(-1.0)`.
- Original values were grouped and assigned numeric identifiers in first seen order, non numeric categorical labels were assigned integer codes above the highest observed numeric value to prevent collisions.
- Manual inspection using the Markdown audit file verified that semantic equivalence was maintained across waves.
- Step 6 was designed to be *order invariant*, dynamically interpreting category values within each wave rather than relying on predefined lookup tables shared across waves. This preserved consistent numeric representation regardless of variable ordering or wave specific encodings.
 - *Example*: Step 5 handled simple binary variables such as `CHRany_pain` (any pain reported) with pre transformed values `['pain', 'No pain']` and numeric mapping `[1.0, 0.0]`. In contrast, Step 6 dynamically processed multi class variables like `we114` (pre tax

wage/salary) many of which contained over 20 distinct pre transformed categories (e.g., -1.0, ‘200-299’, ‘Less than 100’, ..., ‘6,000-6,999’) into consistent numeric representations (e.g., -1.0, 249.5, 99, ..., 6499.5). This illustrates why Step 6 required wave specific, dynamic parsing to maintain semantic equivalence across diverse observed values.

4.1.3 Feature engineering within the cleaning pipeline

Although the six step pipeline is framed primarily as a numerical cleaning procedure, Steps 4-6 also perform explicit rule based feature engineering by interpreting heterogeneous categorical survey responses and converting them into semantically meaningful numerical representations. Rather than acting as a separate post processing stage, feature engineering is embedded directly within the cleaning logic, formalising ordinal structure, frequency, and magnitude encoded in text into directly modelable `float64` values suitable for downstream analysis.

Crucially, this process engineers the *representation* of each feature rather than expanding the feature space. For example, free text frequency responses such as “once or twice a week”, “a couple of times per month”, or “almost every day” are not treated as nominal categories. Instead, lexical cues (e.g., *once*, *twice*, *couple*) are resolved to numeric quantities and normalised onto a common temporal scale, yielding a continuous rate representation. Implicit semantic information such as ordering, intensity, and frequency is therefore preserved through deterministic parsing and normalisation without introducing additional variables. This design maintains the original dimensionality of the dataset while ensuring numerical homogeneity and semantic integrity, producing a compact and model ready representation of complex real world survey data.

4.1.4 Cross wave semantic verification

Given the absence of guaranteed category ordering across waves, preserving semantic equivalence during numerical encoding and feature representation was essential to avoid introducing distortions into downstream ML modelling. Pre

4. TECHNICAL IMPLEMENTATION

and post transformation values for each group were exported to a readable Mark-down (.md) file, as shown in Appendix G. This representation confirmed that features of known importance for downstream predictive models were preserved and correctly encoded. For example, features such as `ph001` (self rated general health), `ph009` (comparative self rated health), and `bh006` (smoking frequency) correspond to items identified by [6] as among the most influential predictors in mortality models by the Frailty Index (FI). Retaining these features from the manual filtering thresholds applied in (Section 3.4) and encoding them consistently across waves ensured that the cleaned dataset maintains coverage and semantic integrity, preventing distortions that could potentially compromise model performance.

A key challenge in cleaning the five TILDA waves was the lack of guaranteed ordering for categorical values of the same variable across different waves. Table 4.1 illustrates this for waves 4 and 5.

For example, gender (`sex`) variables appeared under different value encodings, with varied category orderings and numeric prefixes across waves. Values such as [`'Male'`, `'Female'`], [`'Female'`, `'Male'`], and prefixed forms like [`'1.male'`, `'2.female'`] were all mapped to a consistent numeric representation (1.0 for male, 0.0 for female). This ensured that semantic equivalence, rather than positional ordering or wave specific encoding, determined numerical assignment.

The variable `ph001` found in Appendix G corresponds to the survey question: “Now I would like to ask you some questions about your health. Would you say your health is...?”. Responses are ordinal (Poor to Excellent) with non-response categories.

The grouped Markdown representation reveals three critical points:

1. Semantically identical categories are correctly grouped even under different variable names (`ph001` vs `ph009`), enabling direct comparison of representations that would otherwise appear fragmented across waves.
2. Numerical encoding is invariant to category ordering, preserving ordinal meaning across waves. Without this approach, positional encoding would

4.2 Validation on the cleaning pipeline

assign inconsistent values, potentially distorting performance for downstream models.

3. For variables with a large and heterogeneous set of observed values (e.g., income bands, frequency ranges, or mixed numeric text responses), the grouped view provided essential visibility into how complex category spaces were being collapsed into stable numeric representations, supporting both validation and error detection at scale.

Table 4.1: Inconsistent category ordering for the same feature *ph009* (**self rated health compared to other people your age**) across waves and its impact on positional (order based) label encoding.

Pos	Wave 4		Wave 5	
	Category	Code	Category	Code
1	Good	3.0	Very Good	4.0
2	Fair	2.0	Fair	2.0
3	Poor	1.0	Excellent	5.0
4	Excellent	5.0	Good	3.0
5	DK	-1.0	Poor	1.0
6	Very Good	4.0	DK	-1.0
7	RF	-1.0	RF	-1.0

4.2 Validation on the cleaning pipeline

The purpose of the cleaning validation stage was to assess whether the automated numerical parsing and encoding pipeline preserved meaningful biological and statistical structure within the cleaned datasets. Rather than asserting correctness based solely on successful execution, validation was performed by evaluating whether known relationships reported in the literature could be recovered using the cleaned data under realistic data governance constraints.

4. TECHNICAL IMPLEMENTATION

Due to restricted access to certain outcome variables within TILDA, full end-to-end replication of all published models was not always feasible. In particular, access through the **Hotdesk Facility** for the official mortality outcomes is subject to additional governance requirements, including institutional GDPR training certification and approval by the TILDA data access committee [49].

As a result, validation focused on two complementary strategies:

- (i) Internal consistency checks against established biological and clinical relationships, and
- (ii) Constrained replication of published modelling frameworks using available predictors and the derived `8y_mortality_proxy` outcome.

Together, these validation steps demonstrate that the cleaning pipeline retains expected relational patterns and produces datasets appropriate for downstream modelling tasks.

4.2.1 Internal feature relationships

The first validation stage assessed whether cleaned predictors preserved biologically and clinically plausible relationships reported in prior TILDA studies. This analysis focused on predictors identified by [4] as accounting for approximately 95% of the explained variance in Gait Speed Reserve (GSR), defined as the difference between maximum and usual gait speed.

As GSR is not directly available in the public wave 3 dataset, validation was performed by examining the directional relationships between the 7 primary predictors themselves. This approach evaluates whether the numerical encoding process, including sentinel handling, missing value treatment, and ordinal mapping, retained the expected internal structure of the data rather than reproducing outcome specific performance.

Figure 4.2 presents the correlation matrix for the selected predictors following cleaning. Grip strength exhibited a negative association with both age and chair stand time, reflecting the inverse relationship between muscular strength and physical performance decline. Cognitive performance (Montreal Cognitive Assessment (MOCA)) demonstrated a moderate negative correlation with age

and a positive association with educational level, consistent with known patterns of cognitive reserve in older adults. Education correlated positively with cognitive performance, and BMI showed the expected weak negative association with age, reflecting reduced physiological reserve in older cohorts.

Table 4.2 summarises the expected and observed directional relationships between key predictor pairs. Notably, grip strength showed moderate negative correlations with both age ($r = -0.265$) and chair stand time ($r = -0.170$), reflecting the expected inverse relationship between muscular strength and physical performance decline. Cognitive performance (MOCA) displayed a moderate negative association with age ($r = -0.381$) and a positive association with education ($r = 0.367$), consistent with known patterns of cognitive reserve in older adults. BMI demonstrated the anticipated weak negative correlation with age ($r = -0.073$). These results confirm that the cleaning pipeline retained the expected numerical structure and relational patterns of the predictors, rather than introducing artificial associations.

4.2.2 Model based validation

To evaluate whether the cleaned dataset preserves predictive utility, a constrained replication of [6] was conducted. The resulting predictive performance for both model variants and sexes is shown in the following Figure 4.3. The study predicted 8-year mortality using 32 FI items. In the cleaned wave 1 dataset following the deterministic six step cleaning pipeline described in Section 4.1.2, only 16 of these 32 FI items remained following the manual variable filtering described in Section 3.4, which prioritised global numeric consistency across waves.

An ‘8y_mortality_proxy’ outcome was constructed to approximate the sex specific 8-year mortality rates reported in [6] (men: 14.9%, women: 11.1%), derived from linkage to Ireland’s Central Register Office records [50]. Due to access restrictions, the official mortality data were unavailable. Therefore, mortality status was first assigned by randomly selecting deceased participants from the wave 1 cohort aged 50 years or older to match the published sex specific mortality proportions observed at wave 5 follow up. An equal number of surviving participants were then randomly sampled within each sex to construct balanced

4. TECHNICAL IMPLEMENTATION




Figure 4.2: Correlation heatmap for top 7 predictors (Wave 3).

S

4.2 Validation on the cleaning pipeline

Table 4.2: Directional validation of the 7 features explaining 95% of Gait Speed Reserve (GSR) variance as identified by [4].

Predictor 1	Predictor 2	Expected Direction / Justification	Observed r
Grip Strength (GRIP)	Age	Negative (-): GRIP is a positive predictor of GSR, while age is a negative predictor.	-0.265
GRIP	Chair Stand Time	Negative (-): Higher strength (grip) is expected to correlate with faster (lower) performance time in physical tests.	-0.170
Montreal Cognitive Assessment (MOCA) Score	Age	Negative (-): Cognitive performance (MOCA) contributes positively to GSR, whereas increasing age is associated with reduced reserve.	-0.381
Education	MOCA Score	Positive (+): Third level education and cognitive scores are both cited as positive contributors to cognitive reserve and GSR.	0.367
Body Mass Index (BMI)	Age	Weak / Mixed: BMI and age both negatively impact GSR, though their internal correlation in older cohorts is typically weak.	-0.073

4. TECHNICAL IMPLEMENTATION

datasets for model training. The resulting random proxy datasets included 1,114 men (557 deceased) and 982 women (491 deceased), reflecting the baseline wave 1 population aged ≥ 50 years ($n = 8,172$: 3,743 men and 4,429 women).

Two variants of this proxy were implemented:

- (i) the purely random assignment described above, used as a structural baseline, and
- (ii) biologically informed probabilistic assignment that leverages latent frailty captured via Principal Component Analysis (PCA). This dual construction allowed separation of statistical artefact from biologically meaningful signal.

The random proxy provides an initial diagnostic benchmark, mortality labels were assigned using purely random sampling within each sex to match the published 8-year mortality proportions. While this preserves overall class balance, it does not encode any biological or frailty related information and therefore serves only as a structural validation baseline.

For the biologically informed proxy, the 16 available FI items were standardised to zero mean and unit variance using z-score transformation. PCA was then performed separately within each sex on complete case observations to extract the principal component representing the dominant latent frailty structure. The First Principal Component (PC1) was retained as a latent frailty score, and its direction was aligned such that higher PC1 scores correspond to higher frailty by enforcing a positive correlation with the calculated FI. This latent frailty score was subsequently combined with age to construct a probabilistic mortality assignment reflecting both biological vulnerability and time dependent risk.

Two model variants were tested for each sex:

1. **FI only model:** using the 16 available FI items, without age.
2. **FI + Age model:** including age as an additional predictor.

Model training and evaluation followed the procedure reported in [6] as closely as permitted by the available data. Features were min-max normalised prior to modelling. For each sex, data was split into training (80%) and testing (20%) sets. To mitigate overfitting and obtain robust estimates of model performance, 5-fold

4.2 Validation on the cleaning pipeline

stratified cross-validation was applied on the training data. AUC was selected as the primary evaluation metric due to its widespread use in prior TILDA and ML based studies (Figure 2.2) and its robustness to class imbalance.

For six FI items (mh0014, ph001, ph102, ph108, ph114, bh201), the cleaned dataset transformations differed from the scoring rules published in [6]. To align precisely with the original 16/32-item FI methodology, these items were recoded following the published ordinal and dichotomous mappings. This step was necessary to ensure that the six remapped FI items reflects the same interpretation of health deficits used in the literature and is consistent with standard FI construction principles [51]. Models were then re-evaluated using this partial remapping FI to assess sensitivity to feature encoding.

The resulting AUC values are reported separately for (i) cleaned (Figure 4.3) vs 6/16 recoded FI items (Figure 4.4), (ii) random vs PCA informed mortality assignment, (iii) FI only vs FI + Age models, and (iv) men and women.




Figure 4.3: ROC curves for mortality prediction using the cleaned 16 FI items under the PCA informed mortality proxy. Separate models are shown for men and women, with and without age.

These results highlight several key points:

4. TECHNICAL IMPLEMENTATION




Figure 4.4: ROC curves for mortality prediction using the 6/16 recoded FI items aligned with [6]. Performance is shown separately for men and women, with and without age.

1. **Random proxy baseline (cleaned vs recoded FI):** Under purely random mortality assignment, discrimination remained at chance level for both versions of the FI. For the cleaned 16 FI items, the FI only model achieved $AUC = 0.507$ (men) and 0.512 (women), increasing marginally to 0.516 (men) and 0.531 (women) when age was included. When six of the sixteen available deficits were recoded to align with the published FI scoring rules [6], the AUC values increased to 0.567 (men) and 0.537 (women) for the FI only model, and to 0.572 (men) and 0.605 (women) for the FI + Age model. Despite this increase relative to the fully cleaned encoding, discrimination remained close to chance under random label assignment.

These results confirm that, without embedding biological frailty structure into the outcome, predictive performance reflects statistical noise rather than meaningful signal, regardless of encoding refinement.

2. **PCA informed mortality proxy (cleaned vs recoded FI):** When mortality assignment incorporated the PCA derived frailty representation PC1, discrimination improved relative to the random baseline for both FI

constructions. For the 16 cleaned FI items, the FI only model achieved $AUC = 0.591$ (men) and 0.667 (women), increasing to 0.602 (men) and 0.660 (women) when age was included. When six of the sixteen deficits were recoded in accordance with the published scoring framework, the FI-only model achieved $AUC = 0.636$ (men) and 0.633 (women), while the FI + age model achieved 0.643 (men) and 0.652 (women).

This indicates that closer alignment with published ordinal deficit scoring improves discriminative stable performance relative to the simplified numeric encoding applied during initial cleaning.

3. **Comparison with published performance:** Absolute AUC values remain below those reported in [6] (approximately 0.70 for FI only and up to 0.80–0.90 when age is included), which is expected given the use of a constructed mortality proxy and only 16 of the original 32 FI items. However, the methodological sequence reported in the original study is preserved:

- (i) Random assignment yields chance level performance,
- (ii) Extracting latent frailty structure via PCA improves discrimination,
- (iii) Inclusion of age generally improved mortality prediction.

Importantly, the cleaned dataset maintains realistic sex distributions (45.8% men, 54.2% women) and mortality proportions consistent with published estimates, confirming that preprocessing preserved demographic and structural integrity required for downstream modelling.

Chapter 5

Empirical Evaluation

5.1 Modelling and evaluation framework

This section defines the modelling and evaluation setup used throughout this chapter, including model families and designs, analysis samples, outcome definitions, and evaluation procedures, building directly on the prepared datasets from Chapters 3 and 4.

The evaluation is based on participants aged between 50–80 years with a mean age of 57.8. To ensure that the task reflects incident *new onset* disease, individuals with the target condition present at the start of a transition were excluded, leaving only *at risk* observations for training and testing. This rule was applied consistently across all designs and for both Track A (composite outcome) and Track B (disease specific outcomes).

Final analysis samples differed by design and tracks due to data structure. The baseline design (D1) uses a single transition (Wave 1→Wave 5), a follow-up period of approximately 8 years. The pooled multi-wave designs (D2 and D3) aggregate all eligible consecutive transitions (W1→W2, W2→W3, W3→W4, W4→W5), each spanning approximately 2 years, thereby capturing shorter term dynamics.

Sample sizes and incident rates are summarised in Table 5.1. For Track B (disease specific), sample sizes vary by condition. An appendix table (Appendix incident_rate_PLACEHOLDER) provides the number of observations and incident rates for each disease specific model.

5.1.1 Outcome definitions (Track A and Track B)

Two complementary prediction tasks were defined.

Track A: Predicting any chronic disease onset. Track A uses a binary outcome indicating the first occurrence of any chronic disease during follow-up.

- In D1, the outcome was derived from a composite of self reported conditions recorded in Wave 1 (e.g., eye conditions (ph105_x), cardiovascular conditions (ph201_xx), diabetes related conditions (ph216_xx), general chronic conditions (ph301_xx), limiting long term illness (DISlongterm), and self reported chronic illness status (ph003)). Incident cases were defined using ICD10_ANY from the WHO *International Statistical Classification of Diseases and Related Health Problems 10th Revision* in Wave 5 (e.g., mental and behavioural disorders (ICD10_05), musculoskeletal diseases (ICD10_13)).
 - No single ICD10_ANY variable exists in Wave 1 to establish a clinical baseline. These clinical codes were recorded unevenly across the middle waves, with only three indicators available in Wave 2, two in Wave 3, and one in Wave 4, before a comprehensive set of 16 variables appeared at Wave 5.
 - PHYSICAL & COGNITIVE HEALTH (PH) variables are self reported responses that reflect prior doctor diagnoses (“has a doctor ever told you”), whereas ph003 captures a general self-assessment of long term illness without requiring clinical confirmation
 - All feature scoring schemes and labels are provided in Appendix PLACEHOLDER.
- In D2 and D3, ph003 was used to both define the outcome and identify the at risk cohort (ph003=0) at the start of each transition, as it is available in every wave and enables consistent application across all transitions.
- An analysis of Wave 5 data compared self reported illness (ph003) against clinical records (ICD10_ANY). While raw agreement reached 59.5%, the *Cohen’s Kappa for agreement beyond chance* (Kappa: 0.167) indicates poor

5. EMPIRICAL EVALUATION

consistency. This divergence reveals that 45% of individuals who perceived themselves as healthy possessed an objective clinical diagnosis, while 38% of those reporting illness had no corresponding hospital record. These results confirm that `ph003` serves as a distinct proxy for self perceived chronic illness status. It captures a subjective signal of health burden that exists independently of formal clinical markers, justifying its use when predicting the presence of any chronic disease in the pooled transitions.

Table 5.1: Analysis samples by modelling design for Track A

Design	Observations (n)	Incident cases (n)	Incidence rate (%)
D1: Baseline (W1→W5)	916	248	27.07
D2: Multi-wave pooled	14,296	3,212	22.5
D3: Top-20 (reduced)	14,296	3,212	22.5

Track B: Disease specific prediction. Track B targets individual chronic disease outcomes, e.g., circulatory disease (`ICD10_09`), diabetes (`ph726_01`), and functional decline (`DISlongterm`). For each task, the outcome was defined as the first recorded diagnosis of the specific condition, and participants were excluded if the condition was present at the baseline of the corresponding transition. Coding details for each disease specific outcome are provided in Appendix PLACEHOLDER.

5.1.2 Modelling designs

Four supervised learning algorithms were evaluated across all main Track A designs (D1, D2, D3) to compare linear and non-linear model families under the same evaluation framework.

- **Logistic Regression (LR)** – a linear baseline model to capture additive effects and provide interpretability through coefficients and odds ratios, with regularisation (e.g., L1/Lasso) to mitigate overfitting in high dimensional settings.

- **Extreme Gradient Boosting (XGB)** – a tree based gradient boosted model that captures non-linearities and interactions, with built in regularisation to mitigate overfitting and feature importance measures to identify key predictors.
- **RF** – a bagged ensemble of decision trees that captures complex patterns and is robust to noise and outliers through random feature selection and averaging over trees, with feature importance measures based on mean decrease in impurity or permutation importance.
- **Multi-Layer Perceptron (MLP)** – a feedforward neural network that captures complex non-linear relationships through multiple layers of abstraction, with regularisation techniques (e.g., dropout) to prevent overfitting and the ability to learn hierarchical feature representations, with reduced interpretability compared to tree based models.

The three primary modelling designs were implemented to address and assess the effect of baseline only prediction, pooled longitudinal prediction, and feature reduction, respectively.

- **D1 (Baseline):** Single transition from Wave 1 to Wave 5. Only participants free of the outcome at Wave 1 were included. Feature selection: SelectKBest ($k = 20$). All models were trained with default hyperparameters to establish a baseline performance for each model family.
- **D2 (Multi-wave pooled):** All eligible consecutive transitions (W1→W2, W2→W3, W3→W4, W4→W5) stacked together. A wave transition indicator was included as a feature. Feature selection: SelectKBest ($k = 100$) applied to the pooled dataset.
- **D3 (Top-20 features):** Same pooled structure as D2, but restricted to the 20 most informative predictors identified by XGB gain importance from D2. No additional feature selection was applied in D3 to allow the models to leverage the same reduced feature set. Hyperparameter optimisation was performed for all models in D3 using grid search within the same CV

5. EMPIRICAL EVALUATION

framework to ensure a fair comparison of optimised performance across model families.

Track B (disease specific) models followed either the D2 or D3 design, with XGB as the primary model family because it performed best in Track A (D2/D3). Each design was chosen to address specific research questions: D1 for baseline prediction, D2 for leveraging longitudinal information, and D3 for evaluating the impact of feature reduction with model hyperparameter optimisation.

Before model training, features with more than 50% missing values were removed to reduce sparsity. Remaining missing values were handled using median imputation. All model input pipeline steps, including feature filtering and imputation, were fitted on the training data only and then applied unchanged to validation and test sets to prevent information leakage.

This ensured that no information from held out data influenced feature engineering or model fitting. To account for class imbalance, model specific weighting strategies were applied: balanced class weights for LR and RF, `scale_pos_weight` for XGB, and sample weights for MLP. Standard scaling (zero mean, unit variance) was applied only to the features used by LR and MLP. Tree based models (XGB and RF) were trained on the raw imputed features without scaling. For D3, hyperparameter optimisation was performed using grid search within CV. For example, XGB was limited to a maximum depth of 3, and random forest used a maximum depth of 5 with a minimum of 10 samples per leaf.

5.1 Modelling and evaluation framework




Figure 5.1: Pipeline overview: shared pipeline → separation into Track A (Any chronic disease with D1/D2/D3) and Track B (disease specific, following D2/D3 design).

5. EMPIRICAL EVALUATION

Figure notes: 5.1

- (i) Shared pipeline steps (grey) applied to all data before branching into Track A and Track B.
- (ii) D1: single transition $W1 \rightarrow W5$; D2/D3: pooled transitions ($W1 \rightarrow W2$, $W2 \rightarrow W3$, $W3 \rightarrow W4$, $W4 \rightarrow W5$).
- (iii) Feature counts for Track A after missingness filter: D1: 570, D2/D3: 261 (due to pooling and additional missingness).
- (iv) D2 uses SelectKBest with $k = 100$ while D3 uses the top 20 features from D2 based on XGB gain importance, with no additional feature selection.
- (v) Track B excludes direct outcome proxies and uses XGB only due to its superior performance in Track A.
- (vi) Median imputation, variance threshold, and feature selection always fit on training data only to prevent leakage.
- (vii) Class imbalance handled via balanced class weights (LR/RF), `scale_pos_weight` (XGB), or sample weights (MLP) as appropriate for each model family.

5.1.3 Participant level data splitting and leakage prevention

To prevent identity based leakage where models memorise participant specific health signatures rather than learning general risk patterns, all splitting was performed at the **participant level**. Individuals were assigned exclusively to either the training, validation, or test set, ensuring no participant contributed data to more than one split. As Rumala [52] demonstrates in longitudinal brain Magnetic Resonance Imaging (MRI) analysis, this subject wise approach prevents overconfident performance and identity confounding, where models learn individual characteristics alongside diagnostic features, ensuring generalisation to truly unseen individuals.

Additional leakage prevention measures included:

- **Pipeline isolation:** All pipeline steps (median imputation, scaling, SelectKBest) were fitted using training data only and then applied to validation and test sets.
- **Temporal ordering:** Predictors were drawn only from baseline (start of a transition) *Wave n* predicts outcomes at follow-up *Wave n+1* eliminating look ahead bias.
- **Exclusion of direct proxies:** When predicting a specific disease (e.g., hypertension), variables that directly indicated the same condition (e.g., ph201_01) were removed from the predictor set.

5.1.4 Evaluation protocol and decision metrics

Model performance was assessed using a combination of discrimination, calibration, and classification metrics. The primary metric was the AUC, chosen for its robustness to class imbalance and its interpretability in risk prediction contexts. Model performance was estimated using 5-fold stratified CV on the training set, which was also used as the internal resampling strategy for model comparison across all designs. For models that required hyperparameter optimisation (D3), a grid search was conducted within the same CV framework.

Calibration was evaluated using the Brier score, which measures the accuracy of predicted probabilities, while classification performance was summarised using the F1 score, capturing the balance between precision and recall in the presence of class imbalance (e.g., 22–27% incidence). Additional metrics, including sensitivity, specificity, and confusion matrices, were used to support interpretation.

For the Track B add-on analysis, 95% confidence intervals for performance deltas were estimated via bootstrap resampling to ensure statistical significance.

5.2 Main results

This section presents the predictive performance for Track A (any disease onset) across the three modelling designs, followed by cross design and model level comparisons.

5. EMPIRICAL EVALUATION

5.2.1 Track A: Any disease onset

Results are presented for each modelling design (D1, D2, D3). Tables report discrimination (AUC), calibration (Brier score), and classification performance (F1), alongside training, validation, and test performance to assess generalisation.

5.2.1.1 Design 1 performance:

Table 5.2 summarises the performance of the four models on the single transition task (Wave 1 $\rightarrow$ Wave 5). Discrimination is weak (test AUC around 0.55–0.58), and tree based models show large gaps between training and test AUC, indicating overfitting.

Table 5.2: Predictive performance across model families for D1 (baseline design).

Model	CV AUC	Train AUC	Val AUC	Test AUC	Brier Score	F1 Optimal
LR	0.589	0.677	0.582	0.571	0.245	0.411
XGBoost	0.569	0.825	0.563	0.544	0.240	0.398
Random Forest	0.579	0.871	0.565	0.534	0.231	0.440
MLP	0.536	0.664	0.552	0.582	0.241	0.419

5.2.1.2 Design 2 performance:

Table 5.3 shows the results when using all consecutive transitions (pooled multi-wave design). All models improve markedly compared to D1 5.2.1.1, with test AUCs between 0.699 and 0.715.

Table 5.3: Predictive performance across model families for D2 (multi-wave design).

Model	CV AUC	Train AUC	Val AUC	Test AUC	Brier Score	F1 Optimal
LR	0.715	0.728	0.715	0.709	0.217	0.460
XGBoost	0.716	0.736	0.719	0.715	0.214	0.468
Random Forest	0.711	0.740	0.717	0.711	0.212	0.452
MLP	0.698	0.749	0.706	0.699	0.208	0.455

5.2.1.3 Design 3 performance:

Table 5.4 presents performance using only the 20 most informative predictors (derived from D2 5.2.1.2) with hyperparameter optimisation applied across all models. Discrimination remains effectively unchanged compared to D2 5.2.1.2, with test AUC values tightly clustered around 0.71.

Table 5.4: Predictive performance across model families for D3 (tuned design).

Model	CV AUC	Train AUC	Val AUC	Test AUC	Brier Score	F1 Optimal
LR	0.716	0.718	0.717	0.712	0.212	0.459
XGBoost	0.718	0.736	0.719	0.713	0.209	0.462
Random Forest	0.717	0.766	0.718	0.713	0.205	0.462
MLP	0.713	0.743	0.710	0.712	0.207	0.467

5.2.2 Cross design comparison

The best test AUC increased from 0.582 in D1 5.2.1.1 (achieved by MLP) to 0.715 in D2 5.2.1.2 by (XGB). Incorporating pooled temporal transitions substantially improves predictive performance (absolute gain of 0.133). Reducing the feature set to the top 20 predictors in D3 5.2.1.3 maintained this gain, with XGB achieving a test AUC of 0.713, only 0.002 lower than D2 5.2.1.2, confirming that most of the predictive signal is concentrated in a small subset of variables, and that performance is robust to feature reduction.

Across designs, CV performance also improves and stabilises:

- D1: 0.589 ± 0.072 (LR)
- D2: 0.716 ± 0.007 (XGB)
- D3: 0.718 ± 0.006 (XGB)

The reduction in standard deviation from D1 5.2.1.1 to D2 5.2.1.2 and D3 5.2.1.3 reflects improved stability associated with the pooled multi-wave design and more consistent learning signal across transitions, although differences in data structure across designs should be considered when interpreting cross design variability.

5. EMPIRICAL EVALUATION

5.2.3 Model comparison

Once temporal structure is introduced (D2 5.2.1.2 and D3 5.2.1.3), differences between model families are modest. Test AUCs cluster between (0.699–0.715), with no single model class dominating performance. XGB achieves the highest test AUC in both D2 5.2.1.2 (0.715) and D3 5.2.1.3 (0.713), but the margin over LR is at most (≤ 0.006). LR remains competitive (0.709 in D2 5.2.1.2 and 0.712 in D3 5.2.1.3), suggesting that linear effects capture much of the signal when features are well engineered. MLP slightly underperforms in D2 5.2.1.2 (0.699) but matched other models in D3 5.2.1.3 (0.712), indicating improved performance when the feature space is reduced to the most informative predictors.

Figure 5.2 compares generalisation gaps (Train–Test AUC) across all three designs. A clear reduction in overfitting is observed from D1 5.2.1.1 to D2 5.2.1.2 and D3 5.2.1.3, reflecting the benefit of pooled training data and improved feature representation. D1 5.2.1.1 exhibits the largest gaps, consistent with weaker signal and higher variance in estimates. In contrast, D2 5.2.1.2 and D3 5.2.1.3 show much smaller gaps, indicating improved stability. Tree based models (XGB and RF) consistently show slightly larger gaps than LR and MLP, reflecting their greater flexibility.




Figure 5.2: Train–test AUC generalisation gaps across models and designs.

5.3 Model interpretability and feature importance

The figure also highlights that model level differences in generalisation gap are more pronounced in D1 5.2.1.1, whereas D2 5.2.1.2 and D3 5.2.1.3 exhibit convergence across model families, suggesting that data structure plays a larger role than algorithmic choice in controlling overfitting.

5.2.4 Track B: Disease specific

5.3 Model interpretability and feature importance

5.4 Robustness checks and sensitivity

5.5 Error analysis

5.6 Summary of findings

Chapter 6

Conclusion

6.1 Summary

Models x, y, z

6.2 Conclusions

6.2.1 Data availability Statement

The data analysed in this study is subject to the following licenses/ restrictions:
The datasets generated during and/or analysed during the current study are not publicly available due to data protection regulations but are accessible at TILDA on reasonable request. Requests to access these datasets should be directed to <https://tilda.tcd.ie/data/accessing-data/>.

6.2.2 Ethics Statement

The studies involving human participants were reviewed and approved by Faculty of Health Sciences Research Ethics Committee at Trinity College Dublin, Ireland. The patients/ participants provided their written informed consent to participate in this study.

6.3 Contributions

6.4 Future Work

To use wave6 published on 15/12/2025, IDS and covid-19 datasets.

Appendix A

Python code for exporting PMF metadata to CSV

```
1 import pandas as pd
2 import pyreadstat
3 from pathlib import Path
4 import json
5
6 data_files = {
7     "wave1.json": "data/0053-01_TILDA_Wave1_2009-2011/0053-01
8         _TILDA_Wave1_Data/SPSS/0053-01_TILDA_Wave1_PMF_v1.12.sav",
9     "wave2.json": "data/0053-01_TILDA_Wave2_2012-2013/Data
10         /0053-02_TILDA_Wave2_PMF_v2.7.sav",
11     "wave3.json": "data/0053-01_TILDA_Wave3_2014-2015/Data
12         /0053-04_TILDA_Wave3_PMF_v3.6.sav",
13     "wave4.json": "data/0053-01_TILDA_Wave4_2016/Data/0053-05
14         _TILDA_Wave4_PMF_v4.4.sav",
15     "wave5.json": "data/0053-01_TILDA_Wave5_2018/Data/0053-06
16         _TILDA_Wave5_PMF_v5.5.sav",
17     "harmonized.json": "data/0053-06_TILDA_Harmonized_2016/Data
18         /0053-03_TILDA_Harmonized_v1.2.dta",
19 }
20
21 def load_df_with_var_of_interest(
22     var_dir="var_of_interest", data_files=data_files, verbose=
23     False
```

```

18 ):
19     dfs = {}
20     var_dir = Path(var_dir)
21
22     for json_name, data_path in data_files.items():
23         file = var_dir / json_name
24         with open(file, "r") as f:
25             vars_list = json.load(f).get("variables_of_interest")
26             if verbose:
27                 print(f"Variables_of_interest_from_{file.name}:_{vars_list[:10]}_...")
28
29             if data_path.endswith(".sav"):
30                 df_full, meta = pyreadstat.read_sav(
31                     data_path, encoding="latin1", apply_value_formats
32                     =True
33                 )
34                 df, _ = pyreadstat.read_sav(
35                     data_path,
36                     usecols=vars_list,
37                     encoding="latin1",
38                     apply_value_formats=True,
39                 )
40             else:
41                 df_full = pd.read_stata(data_path,
42                                         convert_categoricals=True)
43                 df = pd.read_stata(data_path, convert_categoricals=
44                                     True)[vars_list]
45
46             if verbose:
47                 print(
48                     f>Data_shape_(Original):_{df_full.shape[0]}_rows_
49                     x_{df_full.shape[1]}_columns"
50                 )
51                 print(f>Data_shape_(Cleaned):_{df.shape[0]}_rows_x_{
52                     df.shape[1]}_columns")
53                 print("
54                     -----")
55
56     dfs[file.stem] = df

```

Appendix

```
52     return dfs
53
54
55 if __name__ == "__main__":
56     for json_name, path_str in data_files.items():
57         path = Path(path_str)
58         wave_name = json_name.replace(".json", "")
59         if path_str.endswith(".sav"):
60             # SPSS
61             df, meta = pyreadstat.read_sav(
62                 path, encoding="latin1", apply_value_formats=True
63             )
64
65         else: # Stata .dta file
66             df, meta = pyreadstat.read_dta(path, encoding="latin1")
67
68         pd.DataFrame(
69             {"variable": meta.column_names, "label": meta.
70              column_labels}
71         ).to_csv(Path("output") / f"{wave_name}
72                  _variable_descriptions.csv", index=False)
73
74         print(f"-----wave_{path}-----")
75         print(df.shape)
76         print(df.columns[:20])
77         print(
78             "Variable/Feature_descriptions, csv file saved
79             successfully->dir=output/"
80         )
81         df.to_csv((Path("output") / f"{wave_name}.csv"), index=
82                   False)
83
84     dfs = load_df_with_var_of_interest(verbose=True)
```


Appendix B

Scenario: Cleaning Pipeline Tables

Table B.1: Initial Raw Feature Counts Categorised by Nine Scenarios (Pre Cleaning)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	9	0	7	0	9	0
Numeric with sentinel	187	59	143	60	100	141
Clean numeric	14	27	18	22	20	8
Censored / bracketed numeric	84	71	91	85	85	73
Binary categorical	248	159	177	220	207	187
Multi class categorical / mixed	267	166	203	205	156	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total Columns	809	482	639	592	577	453

Appendix

Table B.2: Scenario Count Progression: Post Step 1 (Empty / Blank Handling)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	81	31	42	32	75	15
Clean numeric	124	55	123	50	54	134
Censored / bracketed numeric	84	71	91	85	85	73
Binary categorical	251	159	179	220	207	187
Multi class categorical / mixed	269	166	204	205	156	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Table B.3: Scenario Count Progression: Post Step 2 (Sentinel Standardisation)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	0	0	0	0	0	0
Clean numeric	205	86	165	82	129	149
Censored / bracketed numeric	84	71	91	85	85	73
Binary categorical	251	159	179	220	207	187
Multi class categorical / mixed	269	166	204	205	156	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Table B.4: Scenario Count Progression: Post Step 3 (Numeric Cleaning)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	0	0	0	0	0	0
Clean numeric	263	117	215	124	172	149
Censored / bracketed numeric	16	23	17	16	17	73
Binary categorical	251	160	180	221	207	187
Multi class categorical / mixed	279	182	227	231	181	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Table B.5: Scenario Count Progression: Post Step 4 (Censored / Ordinal Mapping)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	0	0	0	0	0	0
Clean numeric	279	140	233	140	189	222
Censored / bracketed numeric	0	0	0	0	0	0
Binary categorical	251	160	180	221	207	187
Multi class categorical / mixed	279	182	226	231	181	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Table B.6: Scenario Count Progression: Post Step 5 (Binary Classification)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	0	0	0	0	0	0
Clean numeric	530	300	413	361	396	409
Censored / bracketed numeric	0	0	0	0	0	0
Binary categorical	0	0	0	0	0	0
Multi class categorical / mixed	279	182	226	231	181	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Table B.7: Final Dfs Cleaned: Post Step 6 (Multi-Class / Mixed Parsing)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	0	0	0	0	0	0
Clean numeric	809	482	639	592	577	453
Censored / bracketed numeric	0	0	0	0	0	0
Binary categorical	0	0	0	0	0	0
Multi class categorical / mixed	0	0	0	0	0	0
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Appendix C

First Stage: Scenario Variable Mapping

```
1 # Sentinel values (numeric and string)
2 # -1 and -1.0 is sentinel but will be used in the clean pipeline
3 standardised_sentinels = {'-1', '-1.0', -1, -1.0} # set ->
    duplicates removed -> counts correct -> single value detection
    is zero
4 numeric_sentinels = [-1, -1.0, -98, -98.0, -99, -99.0,
5                      95, 95.0, 96, 96.0, 98, 98.0, 99, 99.0]
6 string_sentinels = [str(x) for x in numeric_sentinels] + [f"_{x}"
7                   for x in numeric_sentinels] + \
8                   ['na', 'n/a', 'refused', 'missing', 'dk', 'rf', 'refused', "
9                   refuse", 'none', 'no_response', 'nan', 'not_answered', 'no
10                  _answer',
11                  'not_applicable', 'no_consent', 'dont_know', "don't_know", "didn
12                  _t_answer", 'prefer_not_to_say', 'task_not_done', '
13                  insufficient_sample', 'unable_to_record',
14                  '__', '*']
15 blanks = ['', ' ', '\t', '\n']
16
17 SCENARIOS = [
18     "Empty/_blank_values",
19     "Numeric_with_sentinel",
20     "Clean_numeric",
21     "Censored/_bracketed_numeric",
22     "Binary_categorical",
```

```

18     "Multi_class_categorical/_mixed",
19     "Single_value_categorical",
20     "Special_symbol/_mixed",
21     "Unknown/_complex_mixed"
22 ]
23
24
25 # flatten all dtypes across the waves to float and category
26 def flatten_column_types(df):
27     df_flat = df.copy()
28
29     for col in df_flat.columns:
30         if pd.api.types.is_numeric_dtype(df_flat[col]): # Numeric
31             columns
32             df_flat[col] = df_flat[col].astype(float) # Convert
33             to float
34         else:
35             df_flat[col] = ( # Convert to string, strip
36                 whitespace, lowercase, then category
37                 df_flat[col]
38                 .astype(str)
39                 .str.strip()
40                 .str.lower()
41                 .astype('category')
42             )
43
44     return df_flat
45
46 def detect_column_scenario_mapping(df, sample_size=10):
47     summary = []
48
49     # Regex patterns
50     special_symbols_pattern = r'^[A-Za-z0-9\s\.,\-\+&/()]' #
51         special symbols excluding common numeric formatting
52     bracketed_numeric_pattern = r"\d{1,3}(?:,\d{3})*[-/]\d{1,3}(?:,\d{3})*|\d+\s*[\< > + -]" # patterns like "10-20",
53         "30/40", ">=50"
54     sentinel_set = set(x.lower() for x in string_sentinels) #
55         Lowercase string sentinels for comparison
56
57     for col in df.columns:

```

C. FIRST STAGE: SCENARIO VARIABLE MAPPING

```
52     col_data = df[col].copy()
53     dtype = str(col_data.dtype) # get data type as string
54
55     # Convert to string for sentinel / blank detection
56     str_vals = col_data.astype(str).str.lower().str.strip() #
        lowercase and strip whitespace
57     clean_vals = col_data[~str_vals.isin(sentinel_set) & ~(
        str_vals.isin(blanks))] # remove sentinels and blanks
58
59     # Remove sentinels and blanks for scenario detection only
60     vals_no_sentinel = clean_vals[~clean_vals.astype(str).str
        .lower().isin(sentinel_set)
61                                     & ~clean_vals.astype(str).
        str.lower().isin(blanks)
        ].unique()
62     num_unique_no_sentinel = len(vals_no_sentinel)
63
64     # Check if any sentinel values are present
65     sentinel_present = str_vals.isin(sentinel_set).any()
66
67     # Detection flags
68     empty_detected = str_vals.isin(blanks).any() or len(
        col_data) == 0
69
70     # Numeric detection: coerce to numeric, NaNs for non-
        numeric
71     numeric_vals = pd.to_numeric(clean_vals, errors='coerce')
        # coerce non-numeric to NaN
72     numeric_like = numeric_vals.notna().all() and len(
        clean_vals) > 0 # all values are numeric-like after
        cleaning
73
74     sentinel_detected = str_vals[~str_vals.isin(
        standardised_sentinels)].isin(sentinel_set).any() # or
        col_data.eq(-1.0).any() # check for sentinel presence
75     censored_detected = clean_vals.astype(str).str.contains(
        bracketed_numeric_pattern).any() # check for bracketed
        numeric patterns
76
77     # Binary categorical detection (exactly 2 unique values
        after cleaning)
```

```

78     binary_categorical_detected = False
79     if dtype == 'category':
80         if num_unique_no_sentinel == 2:
81             binary_categorical_detected = True
82         elif num_unique_no_sentinel == 1 and sentinel_present
83             :
84             binary_categorical_detected = True
85
86     # Multi-class categorical (3+ unique values, object/
87     # category)
88     multi_class_categorical_detected = num_unique_no_sentinel
89     > 2 and dtype == 'category'
90
91     # Single value categorical
92     single_value_detected = num_unique_no_sentinel == 1 and
93     not binary_categorical_detected
94
95     # Special symbols detection (ignore numeric formatting)
96     symbol_detected = clean_vals.astype(str).str.contains(
97         special_symbols_pattern).any()
98
99     # Mixed types detection
100    mixed_detected = len(set(type(v) for v in col_data)) > 1
101    # more than one data type present
102
103    # Determine scenario in order of pipeline
104    if empty_detected:
105        scenario = SCENARIOS[0]
106        handling = "Replace numeric/categorical/empty/blank
107        with -1.0"
108    elif numeric_like and sentinel_detected:
109        scenario = SCENARIOS[1]
110        handling = "Replace numeric/sentinel values with -1.0
111        "
112    elif numeric_like and not sentinel_detected:
113        scenario = SCENARIOS[2]
114        handling = "Keep as numeric"
115    elif censored_detected:
116        scenario = SCENARIOS[3]
117        handling = "Convert numeric ranges to midpoints or
118        keep as categorical"

```

Appendix

```
110     elif binary_categorical_detected:
111         scenario = SCENARIOS[4]
112         handling = "Encode as 0/1 or keep as category"
113     elif multi_class_categorical_detected:
114         scenario = SCENARIOS[5]
115         handling = "One-hot encode, label encode, or keep as
116                     category"
117     elif single_value_detected:
118         scenario = SCENARIOS[6]
119         handling = "Keep as category / constant column"
120     elif symbol_detected:
121         scenario = SCENARIOS[7]
122         handling = "Inspect and preprocess based on context"
123     else:
124         scenario = SCENARIOS[8]
125         handling = "Inspect manually / complex mixed types"
126
127     sample_values = list(col_data.unique()[:sample_size]) #
128                     sample unique values
129
130     summary.append({
131         'Variable': col,
132         'DataType': dtype,
133         'UniqueValues': num_unique_no_sentinel,
134         'Scenario': scenario,
135         'SuggestedHandling': handling,
136         'SampleValues': sample_values
137     })
138
139     return pd.DataFrame(summary)
```


Appendix D

Step 6: Scenario ‘Multi class categorical’ Cleaning Function

```
1 def categorical_transform_S6(df): # Step6; Scenario -> Multi
    class categorical
2     df_cleaned = df.copy()
3     sent_set = set([str(x).lower() for x in string_sentinels]) |
        set([str(x).lower() for x in standardised_sentinels])
4     numeric_sentinel_set = set(float(x) for x in
        numeric_sentinels)
5
6     # Helper normaliser
7     def _norm(tok):
8         if tok is None:
9             return None
10        s = str(tok).strip().lower()
11        if s in blanks:
12            return ''
13        return s
14
15    # Words -> number map
16    word_num_map = {
17        'zero':0.0, 'one':1.0, 'two':2.0, 'three':3.0, 'four':4.0, '
18        five':5.0, 'six':6.0, 'seven':7.0, 'eight':8.0, 'nine'
        :9.0,
        'ten':10.0, 'eleven':11.0, 'twelve':12.0, 'thirteen':13.0, '
        fourteen':14.0, 'fifteen':15.0, 'twenty':20.0,
```

D. STEP 6: SCENARIO ‘MULTI CLASS CATEGORICAL’ CLEANING FUNCTION

```
19         'thirty':30.0, 'forty':40.0, 'fifty':50.0, 'sixty':60.0, '
20         seventy':70.0, 'eighty':80.0, 'ninety':90.0,
21         'a_few':2.0, 'a_couple':2.0, 'few':2.0, 'once':1.0, 'twice'
22         :2.0, 'several':3.0, 'couple':2.0
23     }
24
25     def words_to_num(token):
26         if token is None:
27             return None
28         token = token.strip().lower()
29         if token in word_num_map:
30             return word_num_map[token]
31         try:
32             return float(token)
33         except Exception:
34             return None
35
36     # Regexes for parsing
37     RE_TIME = re.compile(r'^\s*(\d{1,2}):(\d{2})\s*$')
38     RE_PERCENT = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*%\s*$')
39     RE_DIRECT_NUM = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*$')
40     RE_RANGE = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*[\--/]\s*(-?\d+(?:\.\d+)?)\s*$')
41     RE_RANGE_TO = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*(?:to|TO)\s*(-?\d+(?:\.\d+)?)\s*$')
42     RE_PLUS = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*\+\s*$')
43     RE_GT = re.compile(r'^\s*(?:>|=|>)\s*(-?\d+(?:\.\d+)?)\s*$')
44     RE_LT_ANCHOR = re.compile(r'^\s*(?:<|<=)\s*(-?\d+(?:\.\d+)?)\s*$')
45     RE_NUM_FIND = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*$')
46     RE_WORD_TOK = re.compile(r"[a-z']+(?:\s[a-z']+)?")
47     # RE_SURVEY_TIME = re.compile(r'^\s*(?:[a-z]+\s+)?(\d+(?:\.\d+)?\s*(?:month|week|year)s?\.?$', re.IGNORECASE)
48
49     def norm_return(v):
50         try:
51             vf = float(v)
52         except Exception:
53             return None
54         if vf in numeric_sentinel_set:
55             return 'SENTINEL'
56         return vf
```

```

55     def try_parse_token(x):
56         """Return float, SENTINEL, or None for unknown token x"""
57         if x is None:
58             return None
59
60         # preserve numeric pre transformed values
61         if isinstance(x, (int, float)):
62             if float(x) in numeric_sentinel_set:
63                 return 'SENTINEL'
64             return float(x)
65
66         s = _norm(x)
67         # Extending sentinel detection for categorical parsing
68         # scenario
69         if s == '':
70             return 'SENTINEL'
71         if 'not_applicable' in s or 'does_not_have' in s or "don'
72             t_receive" in s or "don\x92t_receive" in s or 'unknown
73             ' in s:
74             return 'SENTINEL'
75         if s in sent_set or re.fullmatch(r'[0-9a-z]+', s):
76             return 'SENTINEL'
77         if s in ('other', 'other_specify') or s.startswith('other
78             ') or s.endswith('(specify)':
79             return 'SENTINEL'
80
81         s0 = s.replace(',', ' ').replace('$', ' ').replace(EUR, ' ')
82             .replace('#', ' ')
83
84         s0 = re.sub(r'(\d+)-', r'\1-', s0)
85         s0 = re.sub(r'-(\d+)', r'-\1', s0)
86
87         RE_PREFIX_NUM = re.compile(r'^s*(-?\d+(?:\.\d+)?)\.\s*.$')
88
89         m = RE_PREFIX_NUM.match(s0)
90         if m:
91             # If the format is 'NUM. anything', return the number
92             # as the category value
93             return norm_return(float(m.group(1)))

```

D. STEP 6: SCENARIO ‘MULTI CLASS CATEGORICAL’ CLEANING FUNCTION

```
88
89     # time
90     m = RE_TIME.match(s0)
91     if m:
92         h, mi = float(m.group(1)), float(m.group(2))
93         return norm_return(h * 60.0 + mi)
94
95     # percent
96     m = RE_PERCENT.match(s0)
97     if m:
98         return norm_return(float(m.group(1)))
99
100    # direct numeric
101    if RE_DIRECT_NUM.match(s0):
102        return norm_return(s0)
103
104    # ranges
105    m = RE_RANGE.match(s0)
106    if m:
107        try:
108            a, b = float(m.group(1)), float(m.group(2))
109            return norm_return((a + b) / 2.0)
110        except Exception:
111            pass
112    m = RE_RANGE_T0.match(s0)
113    if m:
114        try:
115            a, b = float(m.group(1)), float(m.group(2))
116            return norm_return((a + b) / 2.0)
117        except Exception:
118            pass
119
120    # plus / greater than
121    m = RE_PLUS.match(s0) or RE_GT.match(s0)
122    if m:
123        nums = RE_NUM_FIND.findall(s0)
124        if nums:
125            return norm_return(nums[0])
126
127    # less than
128    if RE_LT_ANCHOR.search(s0) or 'less_than' in s0:
```

```

129         nums = RE_NUM_FIND.findall(s0)
130         if nums:
131             return norm_return(nums[0])
132
133     # or less / more
134     m = re.search(r'(-?\d+(?:\.\d+)?)\s*or\s*less', s0)
135     if m:
136         return norm_return(m.group(1))
137     m = re.search(r'(-?\d+(?:\.\d+)?)\s*or\s*more', s0)
138     if m:
139         return norm_return(m.group(1))
140
141     # "more than X but less than Y", "over X but less than Y"
142     m = re.search(r'(?:(more|than|over)\s*e?(-?\d+(?:\.\d+)?)\s*
143         s*(?:but\s*)?(?:less|than|under)\s*e?(-?\d+(?:\.\d+)?)
144         ', s0)
145     if m:
146         try:
147             a, b = float(m.group(1)), float(m.group(2))
148             return norm_return((a + b) / 2.0)
149         except Exception:
150             pass
151
152     # "between X and Y" / "between X - Y"
153     m = re.search(r'between\s*e?(-?\d+(?:\.\d+)?)\s*(?:and|[-
154         --/])\s*e?(-?\d+(?:\.\d+)?)', s0)
155     if m:
156         try:
157             a, b = float(m.group(1)), float(m.group(2))
158             return norm_return((a + b) / 2.0)
159         except Exception:
160             pass
161
162     # survey time based
163     time_map_weeks = {
164         'one|week': 1.0,
165         'two|weeks': 2.0,
166         'a|month|(4|weeks)': 4.0,
167         'a|month/4|weeks': 4.0,
168         'three|months|(13|weeks)': 13.0,
169         'three|months/13|weeks': 13.0,

```

D. STEP 6: SCENARIO ‘MULTI CLASS CATEGORICAL’ CLEANING FUNCTION

```
167         'six_months_(26_weeks)': 26.0,
168         'six_months/26_weeks': 26.0,
169         'one_year_(12_months/52_weeks)': 52.0,
170         'one_year/12_months/52_weeks': 52.0
171     }
172     if s0 in time_map_weeks:
173         return norm_return(time_map_weeks[s0])
174
175     # If a category is '3 months or more', try to extract the
176     # number and use upper bound
177     if 'months_or_more' in s0 and RE_NUM_FIND.search(s0):
178         nums = RE_NUM_FIND.findall(s0)
179         if nums:
180             months = float(nums[0])
181             return norm_return(months * 4.33) # Convert
182             # months to weeks (4.33 weeks per month)
183
184     # Frequency calendar based
185     if any(tok in s0 for tok in ('day', 'week', 'month', 'year',
186     'daily', 'never', 'almost_every_day', 'once', 'twice', '
187     thrice', 'three', 'several', 'couple')):
188         nums = RE_NUM_FIND.findall(s0)
189         if nums:
190             val = (float(nums[0]) + float(nums[1])) / 2.0 if
191             len(nums) >= 2 else float(nums[0])
192         else:
193             if 'once_or_twice' in s0:
194                 val = 1.5
195             else:
196                 val = None
197                 for w in RE_WORD_TOK.findall(s0):
198                     wn = words_to_num(w)
199                     if wn is not None:
200                         val = wn
201                         break
202     if val is not None:
203         if 'day' in s0:
204             if 'week' in s0:
205                 return norm_return(val * 4.33)
206             if 'month' in s0:
207                 return norm_return(val)
```

```

203         if 'daily' in s0 or 'every_day' in s0 or '
            almost_every_day' in s0:
204             return norm_return(val * 30.0)
205             return norm_return(val * 4.33)
206         if 'week' in s0:
207             return norm_return(val * 4.33)
208         if 'month' in s0:
209             return norm_return(val)
210         if 'year' in s0:
211             return norm_return(val / 12.0)
212         return norm_return(val)
213
214
215     likert_map = {
216         # Likert / ordinals (expanded with quintile/lowest/
            highest detection)
217         'strongly_disagree': 0.0, 'disagree': 1.0, 'neither_
            agree_nor_disagree': 2.0, 'neither': 2.0,
218         'agree': 3.0, 'strongly_agree': 4.0,
219         'very_poor': 0.0, 'poor': 1.0, 'fair': 2.0, 'good':
            3.0, 'very_good': 4.0, 'excellent': 5.0,
220         'none': 0.0, 'not_at_all': 0.0, 'hardly_ever': 0.0,
221         'a_little': 1.0, 'some': 2.0, 'a_lot': 3.0, 'alot':
            3.0, 'often': 3.0,
222         'yes': 1.0, 'no': 0.0, 'sometimes': 2.0, 'rarely':
            1.0, 'most_or_all_of_the_time': 4.0,
223         'pass': 2.0, 'fail': 1.0, '100': 100.0,
224         # Problem severity mappings
225         'no_problem': 1.0, 'minor_problem': 2.0, 'moderate_
            problem': 3.0, 'major_problem': 4.0,
226         # Concern level mappings
227         'not_at_all_concerned': 1.0, 'somewhat_concerned':
            2.0, 'fairly_concerned': 3.0, 'very_concerned': 4.0,
228         # Survey frequency mappings
229         'daily_/almost_daily': 7.0, 'once_a_week_or_more':
            6.0, 'twice_a_month_or_more': 5.0, 'about_once_a_
            month': 4.0,
230         'every_few_months': 3.0, 'about_once_or_twice_a_year'
            : 2.0, 'less_than_once_a_year': 1.0, 'never': 0.0,
231         'daily': 7.0, 'every_day': 7.0, 'almost_every_day':
            7.0, 'most_or_all_of_the_time': 7.0,

```

D. STEP 6: SCENARIO ‘MULTI CLASS CATEGORICAL’ CLEANING FUNCTION

```
232         'every_week': 6.0, 'once_a_week': 6.0, 'several_times_
233             per_week': 6.0,
234         'twice_a_month': 5.0, 'two_a_month': 5.0, 'several_
235             times_per_month': 5.0, 'once_or_twice_a_month':
236             5.0,
237         'once_a_month': 4.0, 'once_or_twice_a_year': 2.0, '
238             less_than_once_a_month': 1.0,
239     }
240
241     if s0 in likert_map:
242         return float(likert_map[s0])
243
244     # Quintile / ordinal like tokens: 'lowest', '2nd quintile
245     ', 'highest'
246     if 'quintile' in s0 or 'lowest' in s0 or 'highest' in s0
247     or 'middle' in s0 or 'median' in s0:
248         if 'lowest' in s0:
249             return norm_return(1.0)
250         if 'highest' in s0:
251             return norm_return(5.0)
252         if 'middle' in s0 or 'median' in s0:
253             return norm_return(3.0)
254         mq = re.search(r'(\d+)(?:st|nd|rd|th)?\s+quintile
255             ', s0)
256         if mq:
257             return norm_return(float(mq.group(1)))
258         nums = RE_NUM_FIND.findall(s0)
259         if nums:
260             return norm_return(nums[0])
261
262     if 'adjacent' in s0: # Adjacent boxes: keep semantic
263         average if present
264         nums = RE_NUM_FIND.findall(s0)
265         if len(nums) >= 2:
266             return norm_return((float(nums[0]) + float(nums
267                 [1])) / 2.0)
268         elif nums:
269             return norm_return(nums[0])
270         return None
271
272     # Fallback: first number
```

```

264     nums = RE_NUM_FIND.findall(s0)
265     if nums:
266         return norm_return(nums[0])
267
268     return None
269
270 def category_sort_key(u):
271     us = _norm(u) or ''
272     parsed = try_parse_token(us)
273     if isinstance(parsed, (int, float)):
274         return (0, float(parsed), us)
275     if us == 'no' or us.startswith('no_') or us.startswith('
not_'):
276         return (1, 0.0, us)
277     if 'yes' in us:
278         if 'both' in us or 'two' in us:
279             return (1, 2.0, us)
280         if 'one' in us:
281             return (1, 1.0, us)
282         return (1, 1.0, us)
283     amount_keywords = ['none', 'not_at_all', 'hardly_ever', '
a_little', 'some', 'a_lot', 'alot', 'often', '
sometimes', 'rarely']
284     for i, key in enumerate(amount_keywords):
285         if key in us:
286             return (2, float(i), us)
287     if 'adjacent_boxes' in us or 'adjacent_numbers' in us:
288         nums = RE_NUM_FIND.findall(us)
289         if len(nums) >= 2:
290             a, b = float(nums[0]), float(nums[1])
291             return (10, (a + b) / 2.0, us)
292         elif nums:
293             return (10, float(nums[0]), us)
294         return (10, 0, us)
295     return (99, 0, us)
296
297 # Operate only on categorical columns
298 cat_cols = df_cleaned.select_dtypes(include='category').
columns.tolist()
299 for col in cat_cols:

```

D. STEP 6: SCENARIO ‘MULTI CLASS CATEGORICAL’ CLEANING FUNCTION

```
300     uniques = list(dict.fromkeys(df_cleaned[col].tolist())) #
        Preserve original tokens with types (do NOT cast to
        str here)
301     normalised_pairs = [(u, _norm(u)) for u in uniques] #
        Build normalised pairs keeping original token too
302     # Keep tokens that are non sentinel and parseable (
        strings or numbers)
303     non_sentinel = [u for u, nu in normalised_pairs if (nu
        and nu not in sent_set and nu not in blanks and
        try_parse_token(nu) != 'SENTINEL')]
304
305     if not non_sentinel:
306         continue
307
308     # Computing parse results keyed by normalized string (but
        keep list of originals too)
309     parse_results = { _norm(u): try_parse_token(_norm(u)) for
        u in non_sentinel }
310
311     numeric_count = sum(1 for v in parse_results.values() if
        isinstance(v, (int, float)))
312     sentinel_parsed_count = sum(1 for v in parse_results.
        values() if v == 'SENTINEL')
313     all_parse_numeric = (numeric_count +
        sentinel_parsed_count == len(parse_results))
314
315     if all_parse_numeric:
316         # Map token string -> numeric (SENTINEL -> -1.0)
317         code_map = { k: (float(v) if isinstance(v, (int,
        float)) else -1.0) for k, v in parse_results.items
        () }
318
319     def map_to_numeric(x):
320         # Preserve the already numeric cells (except
        numeric sentinels)
321         if isinstance(x, (int, float)) and not pd.isna(x)
        :
322             if float(x) in numeric_sentinel_set:
323                 return -1.0
324             return float(x)
325         if pd.isna(x):
```

```

326         return -1.0
327     xs = _norm(x)
328     if not xs or xs in sent_set or xs in blanks or re
329         .fullmatch(r'[^0-9a-z]+', xs):
330         return -1.0
331     return float(code_map.get(xs, -1.0))
332
333 df_cleaned[col] = df_cleaned[col].apply(
334     map_to_numeric).astype(float)
335
336 else:
337     first_seen_norm = []
338     seen = set()
339     for u in non_sentinel:
340         nu = _norm(u)
341         if nu not in seen:
342             first_seen_norm.append(nu)
343             seen.add(nu)
344
345     parse_results = {nu: try_parse_token(nu) for nu in
346         first_seen_norm}
347     max_reserved_val = -1.0
348     for nu, val in parse_results.items():
349         if isinstance(val, (int, float)):
350             max_reserved_val = max(max_reserved_val, val)
351             # Assuming any parsed float is a reserved
352             # ID if it came from the map
353     start_i = int(max_reserved_val) + 1
354     if start_i == 0: # Ensure we never start at 0 if 0 is
355         a reserved category i.e for ('no')
356         start_i = 1
357     string_tokens = [nu for nu in first_seen_norm if not
358         isinstance(parse_results.get(nu), (int, float))]
359     sorted_strings = sorted(string_tokens, key=
360         category_sort_key)
361
362     code_map_strings = { norm_tok: i for i, norm_tok in
363         enumerate(sorted_strings, start=start_i) }
364
365     def map_mixed(x):

```

Appendix

```
357         if isinstance(x, (int, float)) and not pd.isna(x)
358             :# Preserve real numeric cell values
359             if float(x) in numeric_sentinel_set:
360                 return -1.0
361             return float(x)
362         if pd.isna(x):
363             return -1.0
364         xs = _norm(x)
365         if xs == '' or xs in sent_set or xs in blanks or
366             re.fullmatch(r'^0-9a-z+', xs):
367             return -1.0
368
369         parsed_val = try_parse_token(xs)
370         if parsed_val == 'SENTINEL':
371             return -1.0
372         if isinstance(parsed_val, (int, float)):#
373             Captures 'no' (0.0), 'yes' (1.0), and other
374             hardcoded likert values.
375             return float(parsed_val)
376         if xs in code_map_strings:
377             return float(code_map_strings[xs])
378         return -1.0
379
380     df_cleaned[col] = df_cleaned[col].apply(map_mixed).
381         astype(float)
382
383     # Final sweep on numeric columns
384     for c in df_cleaned.select_dtypes(include='float').columns:
385         df_cleaned[c] = df_cleaned[c].fillna(-1.0)
386         df_cleaned[c] = df_cleaned[c].replace(list(
387             numeric_sentinel_set), -1.0)
388
389     return df_cleaned
```

Appendix E

Second Stage: Deterministic *six step* Cleaning Pipeline

```
1 # Cleaning pipeline to all waves
2 dfs_cleaned = {}
3
4 # flattened dtype df
5 dfs_flat = {wave: flatten_column_types(df) for wave, df in dfs.
6             items()} # flatten dtypes
7
8 # Original df
9 display(scenario_count_table(dfs_flat).style.set_caption("
10     Original Table - pre cleaning")) # display original scenario
11     count table
12
13 # Step 1: Clean empty/missing values
14 dfs_step1 = {wave: clean_empty_missing(df) for wave, df in
15             dfs_flat.items()} # apply step 1 cleaning
16 display(scenario_count_table(dfs_step1).style.hide(axis="index").
17         set_caption("Step 1: Empty / Blank post cleaning"))
18
19 # Step 2: Clean sentinel values
20 dfs_step2 = {wave: clean_sentinel(df) for wave, df in dfs_step1.
21             items()} # apply step 2 cleaning
22 display(scenario_count_table(dfs_step2).style.hide(axis="index").
23         set_caption("Step 2: Sentinel post cleaning"))
24
```

Appendix

```
18 # Step 3: Numerical Transformation
19 dfs_step3 = {wave: numerical_transform(df) for wave, df in
    dfs_step2.items()} # apply step 3 cleaning
20 display(scenario_count_table(dfs_step3).style.hide(axis="index").
    set_caption("Step 3: Numeric Transformation - post cleaning"))
21
22 # Step 4: Categorical Transformation for censored scenario
23 dfs_step4 = {wave: categorical_transform_S4(df) for wave, df in
    dfs_step3.items()} # apply step 4 cleaning
24 display(scenario_count_table(dfs_step4).style.hide(axis="index").
    set_caption("Step 4: Category Transformation S4 - post
    cleaning"))
25
26 # Step 5: Categorical Transformation for binary values
27 dfs_step5 = {wave: categorical_transform_S5(df) for wave, df in
    dfs_step4.items()} # apply step 5 cleaning
28 display(scenario_count_table(dfs_step5).style.hide(axis="index").
    set_caption("Step 5: Category Transformation S5 - post
    cleaning"))
29
30 # Step 6: Categorical Transformation for multi class/mixed values
31 dfs_step6 = {wave: categorical_transform_S6(df) for wave, df in
    dfs_step5.items()} # apply step 6 cleaning
32 display(scenario_count_table(dfs_step6).style.hide(axis="index").
    set_caption("Step 6: Category Transformation S6 - post
    cleaning"))
33
34 dfs_cleaned = dfs_step6
```

Appendix F

MD Dictionary: Scenario Grouping and Transformation Function

```
1 def show_grouped_vars_for_scenarios(dfs_original, dfs_transformed
  , scenarios_to_show): # Function to show grouped variables per
  scenario across waves -> markdown format
2     """
3     Used to inspect the scenario variables/features that need
  handling for transformation/cleaning.
4     A pre and post cleaning helper function to identify variables
  that need specific handling and to
5     Inspect actual changes for a scenario from previous cleaning
  step to current step.
6     """
7
8     print("# Category Transformation Mapping")
9     # print(f"\n## Scenarios: {scenarios_to_show}") # Markdown
  mapping dictionary header
10    for wave in dfs_original.keys():
11        print(f"\n### ===== {wave.upper()} =====")
12
13        mapping_df = detect_column_scenario_mapping(
            dfs_transformed[wave]) # Get scenario mapping from
            transformed/cleaned to see overall changes for all
            variables
```

F. MD DICTIONARY: SCENARIO GROUPING AND TRANSFORMATION FUNCTION

```
14     # mapping_df = detect_column_scenario_mapping(  
15         dfs_original[wave]) # Get scenario mapping from  
16         original to see untransformed values  
17  
18     for scenario in scenarios_to_show:  
19         vars_in_scenario = mapping_df[mapping_df['Scenario']  
20             == scenario]['Variable'].tolist() # Variables in  
21             scenario  
22         print(f"\n---Scenario_{scenario}:_{len(  
23             vars_in_scenario)}_---") # Scenario header for  
24             pipeline git commit  
25         if not vars_in_scenario:  
26             print("\nNo_variables_found.")  
27             continue  
28  
29         # Dictionary: frozen set(values) -> list of variables  
30         groups = {}  
31  
32         for var in vars_in_scenario:  
33             unique_vals = list(dict.fromkeys(dfs_original[  
34                 wave][var].dropna())) # Preserve first seen  
35                 order from ORIGINAL  
36             key = tuple(unique_vals) # Use ordered tuple as  
37                 key  
38  
39             if key not in groups: # Initialise list if key  
40                 not present  
41                 groups[key] = []  
42             groups[key].append(var) # Append variable to the  
43                 group  
44  
45         # Print grouped variables in markdown format friendly  
46         for Notion -> mapping dictionary  
47         for value_set, var_list in groups.items():  
48             print("\n*Variables:*","" + ", ".join(var_list)  
49                 + "'_") # \n  
50             print(f"*Pre_transformed_values:_{list(value_set  
51                 )}_")  
52  
53         # Pull transformed values from dfs_cleaned /  
54         specific step using preserved order
```

```

40         try:
41             df_before = dfs_original[wave][var_list[0]]
42             df_after = dfs_transformed[wave][var_list[0]]
43
44             # Build transformed list in same order as
45             # original values
46             transformed_vals = []
47             for orig_val in value_set: # Iterate through
48                 # original values in order
49                 mask = df_before == orig_val
50                 if mask.any():
51                     trans_vals = df_after[mask].
52                     unique().tolist() # Get unique
53                     transformed values
54                     if trans_vals:
55                         transformed_vals.append(
56                             trans_vals[0]) # Append
57                             first transformed value
58
59         except Exception:
60             transformed_vals = []
61         print(f"*Transformed_numeric:*_{transformed_vals}
62             ")
63
64     scenarios_to_show = SCENARIOS
65     # scenarios_to_show = ["Clean numeric"]
66     # scenarios_to_show = ["Censored / bracketed numeric"]
67     # scenarios_to_show = ["Binary categorical"]
68     # scenarios_to_show = ["Multi class categorical / mixed"]
69
70     show_grouped_vars_for_scenarios(dfs, dfs_cleaned,
71                                     scenarios_to_show) # prev step == comparison to current step
72                 else current step transformed/cleaned for ready .md dictionary

```

Appendix G

MD Dictionary: Scenario Grouping and Transformation Audit Outputs

- **sex**: Binary biological sex indicator (e.g., **Male/Female**, **Female/Male**, pre-fixed encodings).
- **ph001**: Self-rated general health status measured on an ordinal scale. Survey question: *“Now I would like to ask you some questions about your health. Would you say your health is. . .”*. Responses range from *Poor* to *Excellent*, with additional ‘no response’ categories.
- **ph009**: Comparative self-rated health relative to people of the same age. Survey question: *“In general, compared to other people your age, would you say your health is. . .”*.
- **bh006**: Frequency based lifestyle variable combining numeric values, bounded ranges (e.g., 20-39), and textual descriptors (e.g., **Less than 10**, 30+). Survey question: *“How many cigarettes do/did you smoke on average per day?”*.

```
%-----%
%-----MARKDOWN_MAPPING_DICTIONARY-----%
%-----%
# Category Transformation Mapping
```

===== WAVE1 =====

--- Scenario Empty / blank values: 0 ---

No variables found.

--- Scenario Numeric with sentinel: 0 ---

No variables found.

--- Scenario Clean numeric: 809 ---

Variables: 'sex, gd002'

Pre transformed values: ['Male', 'Female']

Transformed numeric: '[1.0, 0.0]'

Variables: 'ph001'

Pre transformed values: ['Fair', 'Good', 'Very good', 'Excellent', 'Poor', 'I

Transformed numeric: '[2.0, 3.0, 4.0, 5.0, 1.0, -1.0]'

Variables: 'bh006'

Pre transformed values: ['20-39', 10.0, -1.0, 15.0, 5.0, '60+', "Don't Know"

Transformed numeric: '[29.5, 10.0, -1.0, 15.0, 5.0, 60.0, -1.0, 2.0, 8.0, 3.

--- Scenario Censored / bracketed numeric: 0 ---

No variables found.

--- Scenario Binary categorical: 0 ---

No variables found.

--- Scenario Multi class categorical / mixed: 0 ---

G. MD DICTIONARY: SCENARIO GROUPING AND TRANSFORMATION AUDIT OUTPUTS

No variables found.

--- Scenario Single value categorical: 0 ---

No variables found.

--- Scenario Special symbol / mixed: 0 ---

No variables found.

--- Scenario Unknown / complex mixed: 0 ---

No variables found.

===== WAVE2 =====

...

--- Scenario Clean numeric: 482 ---

Variables: 'gd002, sex'

Pre transformed values: ['Female', 'Male']

Transformed numeric: '[0.0, 1.0]'

Variables: 'bh006'

Pre transformed values: [-1.0, '10 - 19', '20 - 29', 'Less than 10', '30+', 'Don't know']

Transformed numeric: '[-1.0, 14.5, 24.5, 10.0, 30.0, -1.0]'

Variables: 'ph001'

Pre transformed values: ['Very good', 'Good', 'Fair', 'Excellent', 'Poor']

Transformed numeric: '[4.0, 3.0, 2.0, 5.0, 1.0]'

...

===== WAVE3 =====

...

--- Scenario Clean numeric: 639 ---

Variables: 'sex, gd002'

Pre transformed values: ['Female', 'Male']

Transformed numeric: '[0.0, 1.0]'

Variables: 'ph001, ph009'

Pre transformed values: ['Very Good', 'Good', 'Excellent', 'Fair', 'Poor', '']

Transformed numeric: '[4.0, 3.0, 5.0, 2.0, 1.0, -1.0]'

Variables: 'bh006'

Pre transformed values: [-1.0, '10 - 19', 'Less than 10', '20 - 29', '30+', '']

Transformed numeric: '[-1.0, 14.5, 10.0, 24.5, 30.0, -1.0, -1.0]'

...

===== WAVE4 =====

...

--- Scenario Clean numeric: 592 ---

Variables: 'bh006'

Pre transformed values: [-1.0, 'Less than 10', '20 - 29', '10 - 19', '30+', '']

Transformed numeric: '[-1.0, 10.0, 24.5, 14.5, 30.0, -1.0]'

Variables: 'gd002, sex'

Pre transformed values: ['Female', 'Male']

Transformed numeric: '[0.0, 1.0]'

Appendix

```
*Variables:* 'ph001'
*Pre transformed values:* ['Good', 'Fair', 'Poor', 'Excellent', 'Very Good', 'RF', 'D
*Transformed numeric:* '[3.0, 2.0, 1.0, 5.0, 4.0, -1.0, -1.0]'

...

### ===== WAVE5 =====

...

--- Scenario Clean numeric: 577 ---

*Variables:* 'bh006'
*Pre transformed values:* [-1.0, 'Less than 10', '20 - 29', '10 - 19', '30+', "Don't
*Transformed numeric:* '[-1.0, 10.0, 24.5, 14.5, 30.0, -1.0]'

*Variables:* 'gd002, sex'
*Pre transformed values:* ['Female', 'Male']
*Transformed numeric:* '[0.0, 1.0]'

*Variables:* 'ph001'
*Pre transformed values:* ['Very Good', 'Fair', 'Excellent', 'Good', 'Poor']
*Transformed numeric:* '[4.0, 2.0, 5.0, 3.0, 1.0]'

...
```

References

- [1] Kai Petersen, Sairam Vakkalanka, and Ludwik Kuzniarz. Guidelines for conducting systematic mapping studies in software engineering: An update. *Information and Software Technology*, 64:1–18, August 2015. ISSN 0950-5849. doi: 10.1016/j.infsof.2015.03.007. vi, 6, 8
- [2] Barbara Kitchenham, O. Pearl Brereton, David Budgen, Mark Turner, John Bailey, and Stephen Linkman. Systematic literature reviews in software engineering – A systematic literature review. *Information and Software Technology*, 51(1):7–15, January 2009. ISSN 09505849. doi: 10.1016/j.infsof.2008.09.009. vi, 6, 10
- [3] The Irish Longitudinal Study on Ageing. Tilda pseudonymised microdata file release guide v5.5. <https://tilda.tcd.ie/data/documentation/>, 2023. Accessed: 2025-10-09. vi, 25
- [4] James Davis, Silvin P. Knight, Rossella Rizzo, Orna A. Donoghue, Rose Anne Kenny, and Roman Romero-Ortuno. A linear regression-based machine learning pipeline for the discovery of clinically relevant correlates of gait speed reserve from multiple physiological systems. In *2021 29th European Signal Processing Conference (EUSIPCO)*, pages 1266–1270, August 2021. doi: 10.23919/EUSIPCO54536.2021.9616187. vi, 17, 19, 42, 45
- [5] Neal Haddaway, Matthew J Page, Chris C Pritchard, and Luke A McGuinness. PRISMA2020: An R package and Shiny app for producing PRISMA 2020-compliant flow diagrams, with interactivity for optimised digital transparency and Open Synthesis, 2022. viii, 9
- [6] Sebastian Moguilner, Silvin P. Knight, James R. C. Davis, Aisling M. O’Halloran, Rose Anne Kenny, and Roman Romero-Ortuno. The Importance of Age in the Prediction of Mortality by a Frailty Index: A Machine Learning Approach in the

REFERENCES

- Irish Longitudinal Study on Ageing. *Geriatrics (Basel)*, 6(3):84, August 2021. ISSN 2308-3417. doi: 10.3390/geriatrics6030084. viii, 3, 10, 40, 43, 46, 47, 48, 49
- [7] James R. C. Davis, Silvin P. Knight, Orna A. Donoghue, Belinda Hernández, Rossella Rizzo, Rose Anne Kenny, and Roman Romero-Ortuno. Comparison of Gait Speed Reserve, Usual Gait Speed, and Maximum Gait Speed of Adults Aged 50+ in Ireland Using Explainable Machine Learning. *Front Netw Physiol*, 1:754477, 2021. ISSN 2674-0109. doi: 10.3389/fnetp.2021.754477. 1, 10, 11, 17, 19
- [8] Patrick V. Moore, Kathleen Bennett, and Charles Normand. Counting the time lived, the time left or illness? Age, proximity to death, morbidity and prescribing expenditures. *Social Science & Medicine*, 184:1–14, 2017. ISSN 0277-9536. doi: 10.1016/j.socscimed.2017.04.038.
- [9] Ying Huang, Yuhao Su, Ying Jiang, and Meilan Zhu. Sex differences in the associations between blood pressure and anxiety and depression scores in a middle-aged and elderly population: The Irish Longitudinal Study on Ageing (TILDA). *Journal of Affective Disorders*, 274:118–125, September 2020. ISSN 0165-0327. doi: 10.1016/j.jad.2020.05.133. 1
- [10] World Health Organization Europe. New data: Noncommunicable diseases cause 1.8 million avoidable deaths and cost US\$ 514 billion every year, reveals new WHO/Europe report. <https://www.who.int/europe/news/item/27-06-2025-new-data-noncommunicable-diseases-cause-1-8-million-avoidable-deaths-and-cost-us-514-billion-USD-every-year-reveals-new-who-europe-report>, 2025. 1
- [11] Niamh Rice and Charles Normand. The cost associated with disease-related malnutrition in Ireland. *Public Health Nutr*, 15(10):1966–1972, October 2012. ISSN 1475-2727. doi: 10.1017/S1368980011003624. 1
- [12] Caoileann H. Murphy, Eoin Duggan, James Davis, Aisling M. O’Halloran, Silvin P. Knight, Rose Anne Kenny, Sinead N. McCarthy, and Roman Romero-Ortuno. Plasma lutein and zeaxanthin concentrations associated with musculoskeletal health and incident frailty in The Irish Longitudinal Study on Ageing (TILDA). *Experimental Gerontology*, 171:112013, 2023. ISSN 0531-5565. doi: 10.1016/j.exger.2022.112013. 1, 3, 11, 14, 18, 19
- [13] Eamon Laird, Charlotte Lund Rasmussen, Rose Anne Kenny, and Matthew P. Herring. Physical Activity Dose and Depression in a Cohort of Older Adults in

REFERENCES

- The Irish Longitudinal Study on Ageing. *JAMA Netw Open*, 6(7):e2322489, July 2023. ISSN 2574-3805. doi: 10.1001/jamanetworkopen.2023.22489. 1, 14
- [14] C. P. McDowell, R. K. Dishman, M. Hallgren, C. MacDonncha, and M. P. Herring. Associations of physical activity and depression: Results from the Irish Longitudinal Study on Ageing. *Experimental Gerontology*, 112:68–75, 2018. ISSN 0531-5565. doi: 10.1016/j.exger.2018.09.004. 1
- [15] Cathal McCrory, Ciaran Finucane, Celia O’Hare, John Frewen, Hugh Nolan, Richard Layte, Patricia M. Kearney, and Rose Anne Kenny. Social Disadvantage and Social Isolation Are Associated With a Higher Resting Heart Rate: Evidence From The Irish Longitudinal Study on Ageing. *J Gerontol B Psychol Sci Soc Sci*, 71(3):463–473, May 2016. ISSN 1079-5014. doi:10.1093/geronb/gbu163. 1
- [16] Eamon Laird, Matthew P. Herring, Brian P. Carson, Catherine B. Woods, Cathal Walsh, Rose Anne Kenny, and Charlotte Lund Rasmussen. Physical activity for depression among the chronically ill: Results from older diabetics in the Irish longitudinal study on ageing. *Psychiatry Research*, 326:115274, August 2023. ISSN 0165-1781. doi: 10.1016/j.psychres.2023.115274. 3, 11
- [17] Orna A Donoghue, Belinda Hernandez, Matthew D L O’Connell, and Rose Anne Kenny. Using Conditional Inference Forests to Examine Predictive Ability for Future Falls and Syncope in Older Adults: Results from The Irish Longitudinal Study on Ageing. *J Gerontol A Biol Sci Med Sci*, 78(4):673–682, April 2023. ISSN 1758-535X. doi: 10.1093/gerona/glac156. 3, 10, 11
- [18] Richard J. Torraco. Writing Integrative Literature Reviews: Guidelines and Examples. *Human Resource Development Review*, 4(3):356–367, September 2005. ISSN 1534-4843, 1552-6712. doi: 10.1177/1534484305278283. 6
- [19] Tonette S. Rocco and Maria S. Plakhotnik. Literature Reviews, Conceptual Frameworks, and Theoretical Frameworks: Terms, Functions, and Distinctions. *Human Resource Development Review*, 8(1):120–130, March 2009. ISSN 1534-4843, 1552-6712. doi: 10.1177/1534484309332617. 6
- [20] Andrew D Oxman and Gordon H Guyatt. Guidelines for reading literature reviews. *CMAJ: Canadian Medical Association Journal*, 148(10):1671–1676, May 1993. 6

REFERENCES

- [21] Muhammad Azeem Ashraf, Meijia Yang, Yufeng Zhang, Mouna Denden, Ahmed Tlili, Jiayi Liu, Ronghuai Huang, and Daniel Burgos. A Systematic Review of Systematic Reviews on Blended Learning: Trends, Gaps and Future Directions. *Psychology Research and Behavior Management*, 14:1525–1541, October 2021. ISSN null. doi: 10.2147/PRBM.S331741. 6
- [22] Xuezhong Xu, Xue Mingyang, Jie Yang, Hailong Zheng, and Zhifei Che. Tailored machine learning for evaluating the long-term diabetes risk in older individuals: Findings from the Irish Longitudinal Study on Ageing (TILDA). *BMJ Open*, 13(5):e072991, May 2023. ISSN 2044-6055. doi: 10.1136/bmjopen-2023-072991. 10, 11, 16, 17, 18, 19
- [23] Rory Boyle, Lee Jollans, Laura M. Rueda-Delgado, Rossella Rizzo, Görsev G. Yener, Jason P. McMorrow, Silvin P. Knight, Daniel Carey, Ian H. Robertson, Derya D. Emek-Savaş, Yaakov Stern, Rose Anne Kenny, and Robert Whelan. Brain-predicted age difference score is related to specific cognitive functions: A multi-site replication analysis. *Brain Imaging Behav*, 15(1):327–345, February 2021. ISSN 1931-7565. doi: 10.1007/s11682-020-00260-3. 10, 11, 16
- [24] Roy Tzemah-Shahar, Hagit Hochner, Khalil Iktilat, and Maayan Agmon. What can we learn from physical capacity about biological age? A systematic review. *Ageing Research Reviews*, 77:101609, May 2022. ISSN 1568-1637. doi: 10.1016/j.arr.2022.101609. 10
- [25] Morgana A. Shirsath, John D. O’Connor, Rory Boyle, Louise Newman, Silvin P. Knight, Belinda Hernandez, Robert Whelan, James F. Meaney, and Rose Anne Kenny. Slower speed of blood pressure recovery after standing is associated with accelerated brain ageing: Evidence from The Irish Longitudinal Study on Ageing (TILDA). *Cerebral Circulation - Cognition and Behavior*, 6:100212, January 2024. ISSN 2666-2450. doi: 10.1016/j.cccb.2024.100212. 10
- [26] Roman Romero-Ortuno, Peter Hartley, James Davis, Silvin P. Knight, Rossella Rizzo, Belinda Hernández, Rose Anne Kenny, and Aisling M. O’Halloran. Transitions in frailty phenotype states and components over 8 years: Evidence from The Irish Longitudinal Study on Ageing. *Archives of Gerontology and Geriatrics*, 95:104401, 2021. ISSN 0167-4943. doi: 10.1016/j.archger.2021.104401. 10, 11, 12, 19
- [27] Laura A Bardon, Melanie Streicher, Clare A Corish, Michelle Clarke, Lauren C Power, Rose Anne Kenny, Deirdre M O’Connor, Eamon Laird, Eibhlís M O’Connor,

REFERENCES

- Marjolein Visser, Dorothee Volkert, Eileen R Gibney, and MaNuEL Consortium. Predictors of Incident Malnutrition in Older Irish Adults from the Irish Longitudinal Study on Ageing Cohort—A MaNuEL study. *J Gerontol A Biol Sci Med Sci*, 75(2):249–256, January 2020. ISSN 1079-5006. doi: 10.1093/gerona/gly225. 10, 11, 15, 18
- [28] Zuo Zhang, Lauren Robinson, Robert Whelan, Lee Jollans, Zijian Wang, Frauke Nees, Congying Chu, Marina Bobou, Dongping Du, Ilinca Cristea, Tobias Banaschewski, Gareth J. Barker, Arun L. W. Bokde, Antoine Grigis, Hugh Garavan, Andreas Heinz, Rüdiger Brühl, Jean-Luc Martinot, Marie-Laure Paillère Martinot, Eric Artiges, Dimitri Papadopoulos Orfanos, Luise Poustka, Sarah Hohmann, Sabina Millenet, Juliane H. Fröhner, Michael N. Smolka, Nilakshi Vaidya, Henrik Walter, Jeanne Winterer, M. John Broulidakis, Betteke Maria van Noort, Argyris Stringaris, Jani Penttilä, Yvonne Grimmer, Corinna Insensee, Andreas Becker, Yuning Zhang, Sinead King, Julia Sinclair, Gunter Schumann, Ulrike Schmidt, and Sylvane Desrivières. Machine learning models for diagnosis and risk prediction in eating disorders, depression, and alcohol use disorder. *Journal of Affective Disorders*, 379:889–899, June 2025. ISSN 0165-0327. doi: 10.1016/j.jad.2024.12.053. 10, 11
- [29] Dr Angelina R. Sutin, Martina Luchetti, Damaris Aschwanden, Yannick Stephan, Amanda A. Sesker, and Antonio Terracciano. Sense of meaning and purpose in life and risk of incident dementia: New data and meta-analysis. *Archives of Gerontology and Geriatrics*, 105:104847, 2023. ISSN 0167-4943. doi: 10.1016/j.archger.2022.104847. 10
- [30] doctoralwriting. Creating the literature review: Research questions and arguments, February 2016. 10
- [31] doctoralwriting. Creating the literature review: Research questions and arguments (Part 3 of 4), February 2016. 10
- [32] A. A. Zarudsky and K. I. Prashchayeu. P277: One-legged balance test and falls in old patients with cardiovascular diseases. *European Geriatric Medicine*, 5:S171–S172, 2014. ISSN 1878-7649. doi: 10.1016/S1878-7649(14)70448-6. 11, 16, 17
- [33] Chuanying Huang, Shuqin Sun, Xiaocao Tian, Tong Wang, Tianyu Wang, Haiping Duan, and Yili Wu. Age modify the associations of obesity, physical activity, vision and grip strength with functional mobility in Irish aged 50 and older. *Archives of*

REFERENCES

- Gerontology and Geriatrics*, 84:103895, 2019. ISSN 0167-4943. doi: 10.1016/j.archger.2019.05.020. 11, 12
- [34] Louis Jacob, Karel Kostev, Jae Il Shin, Lee Smith, Hans Oh, Adel S. Abduljabbar, Josep Maria Haro, and Ai Koyanagi. Falls increase the risk for incident anxiety and depressive symptoms among adults aged ≥ 50 years: An analysis of the Irish longitudinal study on ageing. *Archives of Gerontology and Geriatrics*, 114:105098, 2023. ISSN 0167-4943. doi: 10.1016/j.archger.2023.105098. 11, 14
- [35] Kevin McCarthy, Eamon Laird, Aisling M. O’Halloran, Padraic Fallon, Román Romero Ortuño, and Rose Anne Kenny. Association between metabolic syndrome and risk of both prevalent and incident frailty in older adults: Findings from The Irish Longitudinal Study on Ageing (TILDA). *Experimental Gerontology*, 172:112056, 2023. ISSN 0531-5565. doi: 10.1016/j.exger.2022.112056. 12
- [36] Ziggi Ivan Santini, Ai Koyanagi, Stefanos Tyrovolas, Josep Maria Haro, Robert J. Donovan, Line Nielsen, and Vibeke Koushede. The protective properties of Act-Belong-Commit indicators against incident depression, anxiety, and cognitive impairment among older Irish adults: Findings from a prospective community-based study. *Experimental Gerontology*, 91:79–87, 2017. ISSN 0531-5565. doi: 10.1016/j.exger.2017.02.074. 13
- [37] A. L. Juola, M. P. Bjorkman, H. Kautiainen, S. Pylkkanen, U. H. Finne-Soveri, H. Soini, K. H. Pitkälä, and J. S. Bell. O1.17: Nursing staff education to reduce potentially harmful medication use among older people in assisted living facilities: Effects of randomized controlled trial on cognition and falls. *European Geriatric Medicine*, 5:S50–S51, 2014. ISSN 1878-7649. doi: 10.1016/S1878-7649(14)70100-7. 13
- [38] Kevin McCarthy, Eamon Laird, Aisling M. O’Halloran, Cathal Walsh, Martin Healy, Annette L. Fitzpatrick, James B. Walsh, Belinda Hernández, Padraic Fallon, Anne M. Molloy, and Rose Anne Kenny. Association between vitamin D deficiency and the risk of prevalent type 2 diabetes and incident prediabetes: A prospective cohort study using data from The Irish Longitudinal Study on Ageing (TILDA). *EClinicalMedicine*, 53:101654, November 2022. ISSN 2589-5370. doi: 10.1016/j.eclinm.2022.101654. 14
- [39] Kevin McCarthy, Aisling M. O’Halloran, Padraic Fallon, Rose Anne Kenny, and Cathal McCrory. Metabolic syndrome accelerates epigenetic ageing in older adults:

REFERENCES

- Findings from The Irish Longitudinal Study on Ageing (TILDA). *Experimental Gerontology*, 183:112314, 2023. ISSN 0531-5565. doi: 10.1016/j.exger.2023.112314. 15
- [40] Zahra Azizi, Rebecca J. Hirst, Alan O’ Dowd, Cathal McCrory, Rose Anne Kenny, Fiona N. Newell, and Annalisa Setti. Evidence for an association between allostatic load and multisensory integration in middle-aged and older adults. *Archives of Gerontology and Geriatrics*, 116:105155, 2024. ISSN 0167-4943. doi: 10.1016/j.archger.2023.105155. 15
- [41] Soraya Matthews, Mark Ward, Anne Nolan, Charles Normand, Rose Anne Kenny, and Peter May. Predicting mortality in The Irish Longitudinal Study on Ageing (TILDA): Development of a four-year index and comparison with international measures. *BMC Geriatr*, 22:510, June 2022. ISSN 1471-2318. doi: 10.1186/s12877-022-03196-z. 16, 18, 19
- [42] Ziad Obermeyer and Ezekiel J. Emanuel. Predicting the Future - Big Data, Machine Learning, and Clinical Medicine. *The New England Journal of Medicine*, 375(13):1216–1219, September 2016. ISSN 1533-4406. doi: 10.1056/NEJMp1606181. 22
- [43] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Wave 1, 2009-2011, 2025. URL <https://doi.org/10.7929/ISSDA/AWCUY3>. 23
- [44] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Wave 2, 2012-2013, 2025. URL <https://doi.org/10.7929/ISSDA/HSBNCU>. 23
- [45] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Wave 3, 2014-2015, 2025. URL <https://doi.org/10.7929/ISSDA/9Z4MFF>. 23
- [46] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Wave 4, 2016, 2025. URL <https://doi.org/10.7929/ISSDA/R4BZYX>. 23
- [47] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Wave 5, 2018-2019, 2025. URL <https://doi.org/10.7929/ISSDA/JCM06P>. 23
- [48] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Harmonized TILDA, 2016, 2025. URL <https://doi.org/10.7929/ISSDA/FHM5I8>. 23
- [49] Hot Desks - The Irish Longitudinal Study on Ageing (TILDA) - Trinity College Dublin. <https://tilda.tcd.ie/data/accessing-data/hotdesk/>, 2026. 42

REFERENCES

- [50] Mark Ward, Peter May, Robert Briggs, Triona McNicholas, Charles Normand, Rose Anne Kenny, and Anne Nolan. Linking death registration and survey data: Procedures and cohort profile for The Irish Longitudinal Study on Ageing (TILDA). *HRB open research*, 3:43, 2020. ISSN 2515-4826. doi: 10.12688/hrbopenres.13083.2. 43
- [51] Samuel D. Searle, Arnold Mitnitski, Evelyne A. Gahbauer, Thomas M. Gill, and Kenneth Rockwood. A standard procedure for creating a frailty index. *BMC Geriatrics*, 8(1):24, September 2008. ISSN 1471-2318. doi: 10.1186/1471-2318-8-24. 47
- [52] Dewinda Julianensi Rumala. How You Split Matters: Data Leakage and Subject Characteristics Studies in Longitudinal Brain MRI Analysis. volume 14242, pages 235–245. 2023. doi: 10.1007/978-3-031-45249-9_23. 56