

Predicting Chronic Disease Onset in Older Adults: A Machine Learning Study using The Irish Longitudinal Study on Ageing (TILDA)



Abderahman Haouit

CSIS Research Centre

Department of Computer Science and Information Systems

Faculty of Science and Engineering

University of Limerick

Submitted to the University of Limerick for the degree of

Artificial Intelligence (MSc) 2026

-
1. Supervisor: Dr. Alison O'Connor
Computer Science & Information Systems
University *of* Limerick
Ireland

Abstract

Background: Chronic disease and functional decline are major contributors to morbidity in older adults, yet the predictive contribution of accumulated self-reported health burden indicators across longitudinal transitions remains underexplored.

Methods: A longitudinal machine learning framework was developed using five waves of TILDA data. Variables were standardised through a multi-stage preprocessing pipeline, and four model families (Logistic Regression, XGBoost, Random Forest, Multi-Layer Perceptron) were evaluated across three modelling designs spanning single and pooled transitions. Performance, generalisation, and predictor contribution were assessed using Cross Validation (CV), bootstrapped confidence intervals, and predictor add-on analysis.

Results: Pooled multi wave modelling improved predictive performance and stability over the single wave transition baseline, increasing CV AUC from 0.589 ± 0.072 to 0.718 ± 0.006 . Reducing the feature set to the 20 most important predictors caused no measurable performance loss, while cognitive, psychosocial, nutritional, and behavioural add-on variables produced no statistically significant improvement.

Conclusions: Chronic disease risk prediction in this cohort using the publicly accessible TILDA dataset was driven primarily by accumulated self-reported and functional health measures rather than isolated domain specific risk factors. A compact set of survey derived indicators captured most predictive signal for risk assessment.

Keywords: ageing, Machine Learning (ML), predictive modelling, chronic disease, functional decline, health burden, The Irish Longitudinal Study on Ageing (TILDA), Extreme Gradient Boosting (XGB)

Acknowledgements

I would like to acknowledge my supervisor, Alison O'Connor, for her guidance, support, and for providing a well organised environment as well as the necessary resources throughout the journey of this project.

I would also like to thank the University of Limerick (UL) Science and Engineering Research Ethics Committee for approving the ethical aspects of this research. Special thanks to the Irish Social Science Data Archive (ISSDA) team for facilitating access to the The Irish Longitudinal Study on Ageing (TILDA) dataset, collected by Trinity College Dublin.

AI Declaration

Declaration I acknowledge the use of [AI tool or technology name] and [link] to generate.../ I have not used any AI tools or technologies to prepare this assessment. Prompt: I entered the following prompt/s... Use: I used the output to.../I modified the output to...

Example 1:

I acknowledge the use of [INSERT GEN AI PLATFORM] to generate an outline for an essay. I entered the following prompt: “Provide an outline for a 3000-word essay on the establishment of the University of Limerick.” I used the output at the initial stage of the assessment task to help plan my essay. I modified the outline generated, discarding several suggested body paragraphs and replacing them with my own ideas based on the research and reading I completed.

Example 2

Declaration I acknowledge the use of [INSERT GEN AI PLATFORM] to brainstorm topics for an assessment. I entered the following prompts: “Brainstorm ideas around the topic of the establishment of the University of Limerick.” I used the output as a starting point for initial research before narrowing down the topic for my assessment.

Limerick, 2026

Limerick, 2026

Your dedication goes here. Open the dedication.tex file found at:
0_frontmatter/dedication.tex

Contents

List of Tables	viii
List of Figures	x
List of Abbreviations	xi
1 Introduction	1
1.1 Research problem and motivation	2
1.2 Research aims and objectives	3
1.3 Contributions of the research	4
1.4 Thesis outline	4
2 Literature Review	5
2.1 Search strategy and study selection	5
2.1.1 Database search and query development	5
2.1.2 Quality and relevance evaluation	6
2.1.3 Synthesis and integration	8
2.2 Physical function and frailty	9
2.2.1 Probabilistic interpretation of frailty	9
2.3 Mental health in older adults	11
2.4 Nutrition and biological ageing	12
2.4.1 Contextual and integrative considerations	13
2.5 Machine Learning in ageing and chronic disease	13
2.5.1 Methodological approaches	14
2.5.2 Performance and validation	14
2.5.3 Explainability in machine learning for ageing	15

2.6	Gaps in the literature	15
2.7	Chapter summary	17
3	Methodology	18
3.1	Study population and design	18
3.2	TILDA data collection and screening	19
3.3	Thematic domains	20
3.4	Manual variable screening	20
3.5	Dataset characteristics after filtering	25
3.6	Retained variable distribution by domain	26
4	Technical Implementation	28
4.1	Automated cleaning engine	28
4.1.1	Stage 1: Variable scenario mapping and validation	28
4.1.2	Stage 2: Deterministic six step cleaning sequence	29
4.1.3	Feature engineering within the cleaning pipeline	33
4.1.4	Cross wave semantic verification	34
4.2	Validation on the cleaning pipeline	35
4.2.1	Internal feature relationships	36
4.2.2	Model based validation	37
5	Empirical Evaluation	43
5.1	Modelling and evaluation framework	43
5.1.1	Outcome definitions (Track A and Track B)	43
5.1.2	Modelling designs	45
5.1.3	Participant level data splitting and leakage prevention	50
5.1.4	Evaluation protocol and decision metrics	51
5.2	Main results	52
5.2.1	Track A: Any disease onset	52
5.2.1.1	Design 1 performance	52
5.2.1.2	Design 2 performance	52
5.2.1.3	Design 3 performance	53
5.2.2	Cross design comparison	53
5.2.3	Model comparison	54

CONTENTS

5.2.4	Track B: Disease specific	56
5.2.4.1	Outcome categories	56
5.2.4.2	Overall performance	57
5.2.4.3	Incidence and predictability	59
5.2.4.4	Overfitting and feature reduction	60
5.3	Model interpretability and feature importance	61
5.3.1	Design 1: Clinical biomarkers dominate	61
5.3.2	Design 2: Medication burden and self-rated health emerge	62
5.3.3	Cross model consistency and the D3 feature set	63
5.3.4	Predictor add-on analysis	64
5.4	Health burden correlation structure	68
5.4.1	Shared health burden signal	68
6	Conclusion	72
6.1	Summary	72
6.2	Conclusions	72
6.2.1	Data availability Statement	72
6.2.2	Ethics Statement	72
6.3	Contributions	73
6.4	Future Work	73
A	Python code for exporting PMF metadata to CSV	74
B	Scenario: Cleaning Pipeline Tables	77
C	First Stage: Scenario Variable Mapping	80
D	Step 6: Scenario ‘Multi class categorical’ Cleaning Function	85
E	Second Stage: Deterministic <i>six step</i> Cleaning Pipeline	97
F	MD Dictionary: Scenario Grouping and Transformation Function	99
G	MD Dictionary: Scenario Grouping and Transformation Audit Outputs	102

CONTENTS

H Cohort sample sizes by design for Track B	108
I Track A and Track B: Item index and scoring of individual features	110
J D1 and D2: Top 20 features	112
References	115

List of Tables

2.1	Database searches and number of studies per database 2.3 [1]. . .	7
2.2	Quality evaluation of included systematic literature reviews [2]. . .	9
2.3	Summary of selected studies on ageing using TILDA.	10
3.1	Dimensions of raw TILDA and harmonised datasets version 5.5 (prior to cleaning in Section 4.1).	19
3.2	Pseudonymised Microdata File (PMF) v5.5 derived variable pre- fixes [3].	21
3.3	Input shape for cleaning pipeline (post manual filtering workflow 3.1). . .	25
3.4	Thematic domain grouping of longitudinal features.	27
4.1	Inconsistent category ordering for the same feature <i>ph009</i> (self rated health compared to other people your age) across waves and its impact on positional (order based) label encoding.	35
4.2	Directional validation of the 7 features explaining 95% of Gait Speed Reserve (GSR) variance as identified by [4].	38
5.1	Cohort sample sizes by design for Track A	45
5.2	Predictive performance across model families for D1 (baseline de- sign).	52
5.3	Predictive performance across model families for D2 (multi-wave design).	53
5.4	Predictive performance across model families for D3 (tuned design). . .	53
5.5	Top-20 features from XGBoost gain in D2, applied in D3 and Track B. . .	64

LIST OF TABLES

B.1	Initial Raw Feature Counts Categorised by Nine Scenarios (Pre Cleaning)	77
B.2	Scenario Count Progression: Post Step 1 (Empty / Blank Handling)	78
B.3	Scenario Count Progression: Post Step 2 (Sentinel Standardisation)	78
B.4	Scenario Count Progression: Post Step 3 (Numeric Cleaning) . . .	78
B.5	Scenario Count Progression: Post Step 4 (Censored / Ordinal Mapping)	79
B.6	Scenario Count Progression: Post Step 5 (Binary Classification) .	79
B.7	Final Dfs Cleaned: Post Step 6 (Multi-Class / Mixed Parsing) . .	79
H.1	24-incident rates by disease specific for Track B, 10-year prediction window	109
I.1	40-items: and scoring of individual features	110

List of Figures

2.1	Publications per year.	6
2.2	Preferred Reporting Items for Systematic reviews and Meta Analyses (PRISMA) chart for systematic reviews showing the study selection process for the systematic mapping and integrative review [5].	8
3.1	Flowchart of the manual five step workflow for variable screening and filtering. Placeholder (n) values represent the number of variables at each stage, illustrating the reduction from the raw dataset to the filtered dataset prior to automated preprocessing.	24
4.1	Flowchart of the final six step cleaning pipeline applied to all TILDA waves. Detailed transformation tables are provided in Appendix B.7. The corresponding implementation “.ipynb” script is documented in Appendix E at each scenario step.	30
4.2	Correlation heatmap for top 7 predictors (Wave 3).	37
4.3	ROC curves for mortality prediction using the cleaned 16 frailty index items under the Principal Component Analysis (PCA) informed mortality proxy. Separate models are shown for men and women, with and without age.	41
4.4	ROC curves for mortality prediction using the 6/16 recoded frailty index items aligned with [6]. Performance is shown separately for men and women, with and without age.	41

LIST OF FIGURES

5.1	Pipeline overview: shared preprocessing applied to all data before branching into Track A (any chronic disease, D1/D2/D3) and Track B (disease specific, following D2/D3 structure). D3 is built directly on D2's cohort and wave structure, adding feature reduction and hyperparameter optimisation.	49
5.2	Train–Test generalisation gaps across models and designs. 0.05 marks a conventional heuristic threshold for acceptable error in Area Under the ROC Curve (AUC). Gaps below this level indicate that the model generalises well to unseen data.	55
5.3	Train AUC vs Test AUC for all Track B disease specific models, coloured by outcome category. Circle markers represent all feature models and cross markers represent top-20 feature models, with a line connecting the two feature strategies per disease. The diagonal dashed line marks perfect generalisation ($\text{Train} \approx \text{Test}$). Dashed lines at 0.5 on both axes indicate chance level discrimination. Confidence ellipses illustrate within category spread.	59
5.4	Bootstrapped 95% confidence intervals for test AUC delta (BASE+ADDON minus BASE) across all candidate features ($B = 2,000$ resamples). Features are sorted in ascending order by the midpoint of the delta interval. All intervals cross zero, indicating no statistically significant incremental contribution from any candidate.	67
5.5	Pairwise Spearman correlations among six health burden variables at wave 5 ($n = 4,978$). Self-reported long term illness and chronic health problem form an identical construct ($r = 1.00$), while ICD10_ANY shows consistently weak associations with all self-reported measures.	69
J.1	Top 20 features by importance for D1.	113
J.2	Top 20 features by importance for D2.	114

LIST OF FIGURES

Chapter 1

Introduction

Ageing populations experience substantial changes across physical, nutritional, cognitive, and psychosocial domains, each shaping vulnerability to chronic disease and functional decline [7–9]. Understanding how these multidomain factors interact over time is essential for early risk identification.

The financial and societal burden is substantial: lifestyle risk factors contribute billions in healthcare costs annually across Europe [10], and in Ireland, malnutrition alone is estimated to cost over €1.4 billion per year [11]. In response, frameworks including the World Health Organization (WHO) *Global Action Plan* and Ireland’s *Healthy Ireland* strategy identify modifiable health behaviours as central to disease prevention.

European regulatory frameworks such as the General Data Protection Regulation (GDPR) and proposed European Union (EU) Artificial Intelligence (AI) Act emphasise transparency and highlight the need for interpretable Machine Learning (ML) models in healthcare.

Traditional risk prediction models have largely relied on clinical biomarkers such as Blood Pressure from Sphygmomanometer (BP) and lipid profiles. Yet, growing evidence shows that broader predictors, including nutrition [12], Physical Activity (PA) [13], Scales and Questions on Mental Health and Wellbeing (MH) [14], and Social Variables (SOC) [15] improve predictive performance.

The Irish Longitudinal Study on Ageing (TILDA)¹ provides a national repre-

¹TILDA’s dataset are pseudonymised and accessed under license via Irish Social Science Data Archive (ISSDA). Use adheres to University of Limerick (UL) Science & Engineering

1. INTRODUCTION

sentative cohort of adults aged 50 and over in Ireland, surveyed repeatedly across multiple domains. An externally produced Research and Development Corporation (RAND) harmonised TILDA dataset (Waves 1–2) was inspected and pre-processed alongside the five core waves. Its potential for cross study replication is discussed in Chapter 6.

Despite these advantages, existing ML research on chronic disease prediction faces persistent limitations: over reliance on clinical predictors, limited incorporation of lifestyle and SOC variables, predominantly cross sectional study designs that fail to capture trajectories, and a lack of interpretability consistent with emerging AI governance standards.

This thesis addresses these gaps by leveraging longitudinal TILDA data across multiple domains, using interpretable ML methods to combine modifiable health behaviours, psychosocial factors, and established clinical measures to enhance prediction of ageing related outcomes.

1.1 Research problem and motivation

Despite increasing research and clinical interest in lifestyle, nutrition factors, and advances in ML methods, approaches to chronic disease prediction in older adults remain limited in several ways.

- **Limited Integration of Multidomain Predictors:** Existing models focus primarily on clinical measurements and often neglect modifiable behavioural, dietary, and psychosocial factors [12, 16].
- **Underuse of Longitudinal Dynamics:** Few studies leverage repeated measures to capture developments of risk, such as Frailty (FR) progression [6]. Probabilistic reasoning can help estimate the likelihood of developing a condition at a future time given earlier measurements, for example, calculating the probability $P(\text{FR at wave 5} \mid \text{UGS at wave 1, Nutrition at wave 2})$.

ethics approval and data retention requirements.

- **Lack of Explainability:** Many ML models are not interpretable, limiting clinical adoption and failing to meet emerging regulatory requirements for trustworthy AI in healthcare [17].

These gaps motivate the multi wave, multidomain approach taken in this thesis, which uses TILDA’s five longitudinal waves to test whether richer predictor sets and pooled designs improve chronic disease onset prediction.

1.2 Research aims and objectives

The goal of this thesis is to develop and evaluate longitudinal ML approaches that combine multidomain predictors from TILDA to predict chronic disease onset in older adults, while identifying the features and modelling designs that best support this task.

This goal will be achieved through the following objectives:

- Review existing applications in ML for chronic disease prediction in ageing populations, with emphasis on gaps in lifestyle and nutrition integration.
- Develop a reproducible pipeline to preprocess and align TILDA waves 1–5, deriving multidomain features across physical, functional, clinical, lifestyle, and psychosocial domains.
- Develop and compare a linear baseline (Logistic Regression (LR)) against tree ensemble and neural network families (Extreme Gradient Boosting (XGB), Random Forest (RF), Multi-Layer Perceptron (MLP)) across single wave and pooled longitudinal designs.
- Evaluate models using Area Under the ROC Curve (AUC), calibration, and classification metrics across all designs.
- Identify the most informative predictors of chronic disease onset and, through a predictor add-on analysis, assess whether domain specific features contribute independent predictive value beyond the core health burden set.
- Document ethical, governance, and reproducibility practices for handling longitudinal pseudonymised health data.

1. INTRODUCTION

1.3 Contributions of the research

This research makes contributions at three levels:

- **Empirical:** Demonstrates the value of longitudinal pooling for chronic disease onset prediction and identifies the health burden indicators that drive predictive signal in this cohort. Nutritional and psychosocial domain features did not contribute independent predictive value beyond this core set, a finding discussed in Chapter 5.
- **Methodological:** Provides a reproducible pipeline for aligning longitudinal TILDA data across domains and integrating diverse features into ML workflows.
- **Clinical:** Identifies the most informative predictors of chronic disease onset and evaluates the marginal contribution of domain specific features, providing a data driven basis for risk stratification.

1.4 Thesis outline

Chapter 2 reviews ML approaches to chronic disease prediction in ageing populations, with emphasis on lifestyle, nutrition, and methodological considerations. *Chapter 3* describes the data preparation process, including the TILDA study design, data collection, thematic domain structure, and the manual variable filtering workflow. In *Chapter 4*, the automated cleaning pipeline is presented, including the variable scenario detection system, the deterministic six step cleaning sequence, and validation of the pipeline against established benchmarks. *Chapter 5* presents the empirical evaluation, covering performance across three modelling designs, disease specific prediction, predictor add-on analysis, and an interpretation of the health burden correlation structure underlying the results. *Chapter 6* discusses the implications and future directions of the research.

Chapter 2

Literature Review

This chapter reviews literature on ageing, chronic disease, and predictive modelling using TILDA (introduced in Chapter 1). It covers four interrelated domains: physical function and FR, MH, nutrition and biological ageing, and ML applications for chronic disease prediction.

2.1 Search strategy and study selection

This review applied systematic mapping principles [1]: research questions were defined, relevant databases searched, inclusion and exclusion criteria applied, and findings synthesised through an integrative approach [2, 18]. The primary focus was chronic disease prediction in older adults using TILDA. Where ML applications specific to TILDA were limited, the scope was extended to include comparable ageing cohort studies.

2.1.1 Database search and query development

The main topic of interest was chronic disease prediction using nutrition, lifestyle, and clinical data from TILDA. Relevant databases (e.g., ScienceDirect, PubMed) were searched using combinations of keywords such as “Irish Longitudinal Study on Ageing”, “machine learning”, “chronic disease”, “nutrition”, “diet”, and “physical activity”, as shown in Table 2.1.

2. LITERATURE REVIEW

The search covered studies published from 2011 to 2025. Figure 2.1 summarises the number of studies identified per year, highlighting trends and gaps over time.




Figure 2.1: Publications per year.

Some search strings returned few or irrelevant entries, particularly for ML applications in TILDA, highlighting a key research gap. Iterations continued until suitable combinations consistently retrieved relevant studies. Duplicates were removed and the remaining studies screened individually for relevance to ageing, chronic disease, and ML. Key elements for each study, including model type, features used, and main findings, were recorded in Table 2.3. The full selection process is illustrated in the Preferred Reporting Items for Systematic reviews and Meta Analyses (PRISMA) diagram (Figure 2.2).

2.1.2 Quality and relevance evaluation

To systematically assess the quality of the included studies, a customised version of the Newcastle-Ottawa Scale (NOS) was applied (Table 2.2). The NOS evaluates studies across three domains: *selection* (S1–S4), *comparability* (C1–C2), and

2.1 Search strategy and study selection

Table 2.1: Database searches and number of studies per database 2.3 [1].

Database	Search	Results
Oxford Academic	(TILDA OR Irish Longitudinal Study on Ageing) AND (chronic disease OR diabetes OR cardiovascular) AND (nutrition OR diet OR “physical activity”)	1081
	(TILDA OR “Irish Longitudinal Study on Ageing”) AND (“machine learning” OR “predictive model” OR “risk prediction”)	71
IEEE Xplore	TILDA OR “Irish Longitudinal Study on Ageing”	56
	(TILDA OR “Irish Longitudinal Study on Ageing”) AND (“machine learning” OR “predictive model” OR “risk prediction”)	7
ScienceDirect	(TILDA OR “Irish Longitudinal Study on Ageing”) AND (“chronic disease” OR cardiovascular OR diabetes) AND (nutrition OR diet OR lifestyle OR “physical activity”)	257
	(TILDA OR “Irish Longitudinal Study on Ageing”) AND (“machine learning” OR “predictive model”) AND (“chronic disease” OR diabetes) AND (nutrition OR “physical activity”)	20
PubMed	(TILDA OR “Irish Longitudinal Study on Ageing”) AND (“chronic disease” OR cardiovascular OR diabetes) AND (nutrition OR diet OR lifestyle OR “physical activity”)	27
	(TILDA OR “Irish Longitudinal Study on Ageing”) AND (“machine learning” OR “predictive model” OR “risk prediction”)	9

2. LITERATURE REVIEW




Figure 2.2: PRISMA chart for systematic reviews showing the study selection process for the systematic mapping and integrative review [5].

outcome (O1–O3). Selection criteria assess the representativeness of the sample, clarity of exposure measurement, and temporal alignment of outcomes. Comparability examines the control of key confounders (variables that may influence both the predictor and outcome), while outcome evaluates measurement validity, follow up adequacy, and completeness. Each domain is scored binary (0 = criterion not met, 1 = criterion met), and the total reflects overall study quality.

This initial table guided refinement into two subsets: studies critically related to TILDA, and studies applying ML in TILDA for predictive modelling. The other revealed minimal integration between ML methods and TILDA data.

Table 2.3 summarises selected studies on ageing using TILDA and ML, reflecting key gaps and opportunities identified during systematic mapping.

2.1.3 Synthesis and integration

Data were extracted and synthesised to identify methodological trends (e.g., Markov models, LR, 5-fold Cross Validation (CV)) and gaps [2].

Given the limited number of ML studies using TILDA directly, the review

2.2 Physical function and frailty

Table 2.2: Quality evaluation of included systematic literature reviews [2].

Reference	S1	S2	S3	S4	C1	C2	O1	O2	O3	Total
(Xu, 2023 [19])	1	1	1	1	1	1	1	1	1	9
(Donoghue, 2023 [17])	1	1	1	1	1	1	1	0	1	8
(Moguilner, 2021 [6])	1	1	1	1	1	0	1	1	1	8
(Davis, 2021 [7])	1	1	1	1	1	0	1	1	0	7
(Boyle, 2021 [20])	1	1	1	1	1	0	1	0	1	7
(Tzemah-Shahar, 2022 [21])	1	1	1	0	1	0	1	1	1	7
(A. Shirsath, 2024 [22])	1	1	1	1	1	1	1	0	1	8
(Romero-Ortuno, 2021 [23])	1	1	1	1	1	1	1	1	1	9
(Bardon, 2020 [24])	1	1	1	0	1	0	1	1	1	7
(Zhang, 2025 [25])	1	1	1	1	1	1	1	0	1	8
(Sutin, 2023 [26])	1	1	1	1	0	0	1	1	1	7

was broadened to include relevant studies on chronic disease prediction in older adult populations more generally.

2.2 Physical function and frailty

FR reflects declining physiological reserve, providing a framework for understanding physical vulnerability in ageing. In TILDA, it is captured through both the FR phenotype and the FR index, with UGS, HGS, and mobility decline serving as practical predictors. These measures strongly predict hospitalisation and mortality.

2.2.1 Probabilistic interpretation of frailty

From a probabilistic perspective, the likelihood of an adverse outcome Y (such as mortality) given observed FR features X is expressed as a conditional probability $P(Y | X)$, and identifying which features carry the strongest predictive signal requires understanding how much unique information each contributes.

When features X_i and X_j are statistically independent,

$$P(X_i, X_j) = P(X_i) P(X_j),$$

2. LITERATURE REVIEW

Table 2.3: Summary of selected studies on ageing using TILDA.

Theme	Author/year	Dataset	Variables/features	Methods/model type	Key Findings/outcome	Limitations
Frailty (FR)	Romero-Ortuno (2021) [23]	Wave 1–5	FR state, FR phenotype (FP) components (Exhaustion (EX), Unexplained weight loss (WL), Weakness (WK), Slowness (SL), Low physical activity (LA))	Multi state Markov model, longitudinal 8 year follow up	32% of pre frail to non frail; FR strongly predicted 31% mortality	Self report bias; observational design
Falls + Machine Learning (ML)	Donoghue (2023) [17]	Wave 1–3	Gait, mobility, medications, history of falls	Conditional inference forest; 5-fold CV; undersampling for imbalance	Accuracy up to 69.7%; for adults aged 50–64.	AUC values were ≤ 0.69 and Precision Recall Area Under the Curve (PR-AUC) ≤ 0.39 indicating low predictive accuracy; no external validation; cross sectional; Class imbalance
Fear of Falling (FOF)	Zarudsky (2014) [27]	Wave 1	Age, sex, fall history	Cross sectional prevalence analysis	23.3% prevalence; higher in women; 70% with Fear of Falling (FOF) had no recent falls in the last 12 months	Self reported; cross sectional
Functional Mobility	Huang (2019) [28]	Wave 1–2	Measured by Timed Up and Go (mobility test) (TUG), Hand Grip Strength (HGS), physical activity, vision, Body Mass Index (BMI), age	Linear regression, stratified analyses	Age modifies effects; PA and grip protect mobility; vision benefit only in middle aged (Beta = -0.032, P = 0.002)	Observational; 2 year follow up
Depression	Jacob (2023) [29]	Wave 1–2	Falls, FOF, HADS-A, Center for Epidemiologic Studies Depression Scale (CES-D)	Prospective LR	Falls predicted incident anxiety Odds Ratio (OR)=1.58 and depression OR=1.43	Self reported falls; short follow up; mediation effect partially explored
	Laird (2023) [16]	Wave 1–5	Moderate-to-Vigorous Physical Activity (MVPA), walking, sociodemographics	Longitudinal regression; mixed model	Higher physical activity reduced depressive symptoms; dose response effect	Self reported PA; observational; limited causal inference
Nutrition	Murphy (2023) [12]	Wave 1–5	Plasma lutein, zeaxanthin	Linear/ordinal LR	Higher carotenoids linked to slower FR progression Lower odds of becoming frail (ORs = 0.57–0.89)	Observational; not predictive of longitudinal muscle changes
	Bardon (2020) [24]	Wave 1–2	Hospitalisation, functional status, SOC support, sex, falls	LR; sex stratified analyses	Functional decline, hospitalisation, poor support increased malnutrition risk; sex differences	Observational (short follow up (2 years)); limited generalisability >65 years, self reported
ML	Xu (2023) [19]	Wave 1–3	105 predictors from 40,000+ variables (SOC, clinical, mental, family)	Stacked ensemble: RF, Extreme randomised trees (XRT), General linear model (GLM), Gradient Boosting Machine (GBM), Deep Neural Network (DNN); Shapley Additive Explanations (SHAP) explainability	AUC=0.854 for 2 year Diabetes Mellitus (DM) prediction; top predictors LDL, cirrhosis, sex	No external validation; short follow up; ensemble complexity limits deployment
	Davis (2021) [7]	Wave 3	Age, HGS, chair stands, BMI, cognitive tests	Histogram gradient boosting regression; SHAP	r ² test: UGS≈0.41, Maximum Gait Speed (MGS)≈0.46, GSR≈0.21	Modest predictive power; cross sectional; no external validation
	Zhang (2025) [25]	Longitudinal IMAGEN cohort	Psychopathology, personality, cognition, substance use, environment	Regularised LR; diagnostic	Longitudinal AUC: ED=0.71, MDD=0.64, AUD=0.67; shared transdiagnostic predictors	Limited age range; no external replication
	Boyle (2021) [20]	Wave 3	Brain predicted age difference (brainPAD); processing speed; attention; cognitive flexibility; verbal fluency	Linear regression, correlation analyses	Higher brainPAD associated with lower cognitive performance across multiple domains	Cross sectional; no causal inference; limited sample

and each adds fully independent information to the model. In practice, however, FR related predictors such as gait speed, grip strength, and mobility limitation are often highly correlated, so the joint distribution does not factorise and the marginal gain from adding a second correlated predictor is reduced. This has direct implications for feature selection in ML, as discussed in Chapter 5.

Evidence suggests that FR is dynamic, not irreversible. For example, multi state modelling showed that many prefrail adults transition back to non frail, although established FR strongly predicts mortality [23]. Metabolic syndrome accelerates the development of FR, suggesting a metabolic pathway of vulnerability [30]. The presence of metabolic syndrome raises $P(\text{FR} \mid \text{Metabolic Syndrome})$ and is associated with greater risk of adverse outcomes over time [30]. Age also plays an important role: obesity predicts mobility decline earlier in life, whereas later in life, traits that protect against this, including HGS, become more significant [28].

These findings partly conflict: FR appears both reversible and progressive, depending on risk context. This complexity motivates probabilistic models that can update beliefs about risk as new observations arrive, as formalised by Bayes theorem:

$$P(Y \mid X) = \frac{P(X \mid Y)P(Y)}{P(X)}$$

where $P(Y \mid X)$ is the posterior probability of outcome Y given features X . In practice, causal inference remains limited by observational designs and predictors are frequently examined in isolation. Although formal Bayesian inference is not implemented in this study, this probabilistic framing motivates the use of well calibrated ML models evaluated via AUC and the Brier score, as described in Chapter 5.

2.3 Mental health in older adults

MH, including depression, anxiety, loneliness, and SOC isolation, strongly shapes quality of life. Evidence from TILDA shows strong links to both physical and SOC factors. [31] found that participation in physical, SOC, and cognitive activities summarised by the Act-Belong-Commit (ABC) indicator was associated

2. LITERATURE REVIEW

with lower depression and anxiety. This suggests SOC integration and lifestyle protect mental wellbeing. However, [32] reported that self reported measures may exaggerate such associations, raising concerns of bias. These two findings conflict: the effect of SOC engagement is strong when self reported and weaker when objectively assessed.

Objective data strengthen the case for activity. Accelerometer based measures show a dose response link between moderate to vigorous activity and lower depressive symptoms [13]. Yet reverse pathways are also evident: incident falls and functional decline predict later depression, mediated by FOF [29]. Together, these results reveal a bidirectional relationship, MH both influences and is influenced by physical decline. Most studies rely on broad self report scales, such as CES-D or Hospital Anxiety and Depression Scale (HADS), with little biomarker or clinical validation.

This literature suggests MH in ageing requires longitudinal, multidimensional approaches capable of capturing bidirectional pathways. Formally, the conditional probability

$$P(\text{Depression} \mid \text{Activity, Falls, SOC Engagement})$$

quantifies how these interacting features jointly influence MH outcomes, indicating which predictors carry the strongest signal and which may be redundant.

2.4 Nutrition and biological ageing

Nutrition interacts with both biological and psychosocial systems, shaping ageing trajectories and FR. Biomarkers like vitamin D, lutein, and zeaxanthin have been linked to physical and cognitive outcomes in TILDA. [12] showed that higher plasma lutein and zeaxanthin dietary carotenoids found in leafy vegetables were linked to slower FR progression. By contrast, [33] found vitamin D deficiency predicted DM, musculoskeletal decline, especially among adults with low sunlight exposure. These studies point to different nutritional mechanisms: antioxidant protection versus metabolic regulation. Identifying which biomarkers are most informative for feature selection in ML pipelines remains an open question.

2.4.1 Contextual and integrative considerations

Malnutrition also reflects SOC and functional risks. [24] found that hospitalisation, functional loss, and poor SOC support increased malnutrition risk, with notable sex differences. This highlights a limitation in much nutritional research: biological markers are studied without integrating SOC context.

The difference between biological and chronological age is a major point of debate. Biomarker based metrics that better capture these cumulative exposures, like FR indices or epigenetic clocks, frequently vary from chronological age. McCarthy and Azizi link metabolic syndrome and nutritional deficits to accelerated biological ageing [34, 35]. Although most of this evidence is cross sectional and cannot capture change over time, these indicators offer a more precise measure of vulnerability. Reliability is also reduced in biomarker studies with small sample sizes, limiting confidence in the estimated effect magnitudes.

Nutrition interacts with biological, metabolic, and SOC systems simultaneously, and isolating single nutrients risks oversimplification. Integrative modelling that combines biomarkers, clinical factors, and SOC determinants supported by machine learning pipelines offers a more promising route. Models that estimate the joint distribution of features and outcomes can better capture the complex dependencies relevant to biological ageing.

2.5 Machine Learning in ageing and chronic disease

ML is increasingly applied in ageing research because it can capture nonlinear and multidimensional relationships that traditional regression models, such as LR, often miss [19, 20]. Studies using ML in ageing research include many types of predictors: clinical measures, sociodemographic factors, lifestyle habits, cognitive tests, and psychosocial variables.

A recurring pattern is that models rely primarily on readily measured clinical data such as comorbidity counts, mobility scores, and vital signs, while nutrition, SOC, and lifestyle predictors remain underrepresented [6, 19]. This imbalance may limit the ability of models to capture the full complexity of chronic disease

2. LITERATURE REVIEW

risk with ageing, especially considering that MH and nutrition exert independent and interacting effects on later life outcomes. Models that rely solely on readily available clinical data risk reproducing the same biases seen in traditional regression approaches.

2.5.1 Methodological approaches

The methodological approaches used in ageing research span both traditional and advanced models. LR and Markov models remain common baselines due to their interpretability and simplicity, yet they are often unable to capture nonlinearities or higher order interactions. More recent work has shifted towards ensemble methods such as RF, GBM, as well as DNNs, which generally achieve higher predictive accuracy.

For instance, [36] evaluated mortality prediction using LR with demographic, clinical, and functional predictors, achieving an AUC of 0.78. In contrast, [19] reported an AUC of 0.854 using a stacked ensemble for DM prediction, illustrating that flexible nonlinear models can better capture complex interactions among ageing related predictors.

2.5.2 Performance and validation

Predictive performance across studies is generally moderate to strong, with AUC values between 0.70 and 0.90 for outcomes like DM, UGS, depression, and mortality. This indicates that models can distinguish reasonably well between individuals who will or will not experience an outcome.

However, there are important limitations. Many studies rely only on internal validation, testing models on the same data used for training. This can inflate performance estimates and reduce confidence in applying the model to new populations. Furthermore, most studies are cross sectional, so causal or temporal effects cannot be assessed. When combined with the underuse of nutrition and SOC predictors, these issues reduce the generalisability of existing models [19].

2.5.3 Explainability in machine learning for ageing

As ML models become more complex, interpretability emerges as a critical challenge. Explainability tools like SHAP can highlight feature importance, but their use is inconsistent across studies, particularly in deep learning models [4, 7, 19]. These methods improve transparency by revealing which features drive predictions, yet black-box concerns persist, particularly in deep learning, where feature interactions are difficult to track. For ageing research, where clinical adoption requires both accuracy and trust, explainability is not optional but essential. Current efforts show promise but remain fragmented, with no consensus on best practice. This gap links directly to the broader methodological limits discussed in the next section on gaps in the literature.

2.6 Gaps in the literature

First, most studies rely on TILDA or similar cohorts of Irish and predominantly older adults (aged 50 and over). This limits confidence in how well results transfer to other populations. This thesis focuses on TILDA in depth, using all five available longitudinal waves for model development and evaluation. Cross study replication using the RAND Harmonised TILDA dataset, which maps variables to international standards compatible with comparable cohorts such as Health and Retirement Study, (a longitudinal study of ageing in the United States) (HRS) and Survey of Health, Aging and Retirement in Europe (SHARE), is identified as a direction for future work.

Second, there is an over reliance on physical health predictors such as comorbidity counts and mobility measures, while nutrition, SOC, religious or spiritual, and environmental variables are often overlooked. As shown in [12], nutritional biomarkers like lutein and zeaxanthin are strong predictors of FR, yet these are rarely integrated into broader ML pipelines. By contrast, studies such as [24] highlight the role of SOC support and functional decline in malnutrition risk. Together, these examples show that excluding nutrition and SOC factors risks producing models that reinforce the same biomedical biases seen in regression

2. LITERATURE REVIEW

heavy work. Whether nutritional and psychosocial predictors provide independent signal beyond established health burden indicators in this cohort is empirically tested in Chapter 5.

Third, methodological choices remain conservative. Regression models remain dominant, likely due to their interpretability and ease of implementation. However, they often fail to capture nonlinear interactions and higher order dependencies present in ageing related data. Neural network architectures beyond standard regression are rarely explored in this literature. This study includes a feedforward MLP as a baseline neural network family alongside tree ensemble and linear methods. For instance, [36] achieved an AUC of 0.78 using LR for mortality prediction in TILDA, whereas [19] reported an AUC of 0.854 with ensemble methods for DM incidence. This contrast illustrates that more flexible ML models can provide superior predictive performance while maintaining interpretability when combined with explainability techniques. Where ensembles or brainPAD approaches have been attempted, validation is almost always internal, with little cross cohort testing. Weak validation and narrow feature sets limit the generalisability of these models and increase the risk of overfitting.

Fourth, many outcomes relevant to older adults such as pain, sleep quality, and subjective wellbeing remain underexplored. For example, [12] focused on plasma biomarkers for FR without assessing sleep or pain, and UGS models such as [7] similarly omit subjective quality of life. Omitting these outcomes limits the real world application of predictive models. Including subjective outcomes such as pain and wellbeing alongside clinical diagnoses would produce more actionable risk profiles for interventions targeting older adults.

Fifth, cross sectional bias and data handling weaken reliability. Much nutritional work, such as [12], relies on single time point biomarker data, which cannot capture longitudinal change. By contrast, studies applying multi wave TILDA data [23] demonstrate the added value of modelling temporal dynamics. Similarly, listwise deletion of missing data, as applied in [36], risks biasing results toward healthier participants. More robust imputation approaches remain underused.

Finally, interpretability challenges persist, even accurate models may face barriers to clinical acceptance. Taken together, these examples show that ageing

research continues to rely on narrow predictors, conservative models, and weak validation. Addressing these gaps requires integrative, diverse, and transparent approaches that link multidimensional predictors with explainable ML.

2.7 Chapter summary

The evidence reviewed in this chapter shows that FR, mental health, and nutrition do not operate in isolation. FR is partly reversible but remains strongly associated with mortality. MH both influences and is shaped by physical decline and nutrition interacts with biological, metabolic, and social systems in ways that single variable studies frequently underestimate.

While machine learning has improved prediction accuracy in ageing research, challenges remain in integrating diverse predictors, ensuring transparent feature attribution, and achieving robust longitudinal validation.

These gaps motivated the integrative, longitudinal approach developed in Chapters 3–5.

Chapter 3

Methodology

3.1 Study population and design

TILDA provides longitudinal data across five waves (Waves 1–5) for community dwelling adults in Ireland. The RAND harmonised TILDA dataset (Waves 1–2), aligned to cross study standards via the Gateway to Global Ageing Data (G2G) framework, was also cleaned using the same pipeline.

All participants who provided data in at least one TILDA wave were considered eligible. To maximise the available sample for machine learning, no exclusions were applied on the basis of age, medical conditions, mobility, cognitive status, or health centre attendance.

Participants were removed only in the rare case that, following manual variable filtering, no analytically usable variables remained for that individual. Filtering occurred primarily at the *variable level* during the manual screening stage, which excluded features with extreme missingness, lack of variation, or non informative structure. This approach preserves the largest possible sample while ensuring all retained inputs are analytically meaningful for downstream analysis and model development.

This approach prioritises data integrity and sample size, differing from exclusion heavy cohort definitions common in traditional epidemiological studies.

3.2 TILDA data collection and screening

TILDA data collection occurred over five longitudinal waves (Table 3.1).

Each wave included three primary components:

1. **Computer Assisted Personal Interview (CAPI):** Home based, computer assisted personal interviews covering health, socio demographics, and family.
2. **Self Completion Questionnaire (SCQ):** Paper based self completion questionnaires capturing sensitive information on MH, lifestyle, and well-being.
3. **Health Assessment:** Clinical and biomarker measurements conducted in dedicated centres or at home (wave 1 and wave 3).

All TILDA data were pseudonymised prior to release, meaning that personal identifiers such as names and addresses were removed or replaced with unique codes to protect participant confidentiality. Each participant received a unique identifier ('id'), along with household and cluster identifiers ('household', 'cluster'), allowing longitudinal linkage across waves without revealing individual identities.

Table 3.1: Dimensions of raw TILDA and harmonised datasets version 5.5 (prior to cleaning in Section 4.1).

Dataset	Collection Period	Participants (N)	Raw Variables (N)
Wave 1 [37]	2009–2011	8501	1619
Wave 2 [38]	2012–2013	7206	724
Wave 3 [39]	2014–2015	6397	1029
Wave 4 [40]	2016	5713	990
Wave 5 [41]	2018–2019	4978	983
Harmonised [42]	2016 (release)	8501	572

3. METHODOLOGY

3.3 Thematic domains

Variables were organised into seven thematic domains based on ageing literature and study objectives. Each variable’s prefix, as defined in the Pseudonymised Microdata File (PMF) metadata (Table 3.2), indicates its source or research domain. This systematic assignment ensures that each thematic group contains conceptually related features and provides a clear structure for downstream automated preprocessing and machine learning.

Each variable in TILDA was assigned a prefix indicating its data source or research domain. Home based CAPI variables use a two letter module code followed by a three digit question code (e.g., `ph121`). Variables with multiple responses or loops include an underscore and number to specify the response or iteration (e.g., `ph201_05`).

Variables from the self completion questionnaire are prefixed with SCQ, while derived variables constructed from either CAPI or SCQ data use uppercase codes corresponding to their research area (Table 3.2). These prefixes provide a consistent framework for categorising features and guiding the assignment into thematic domains for downstream analysis.

By categorising the raw variables into these seven thematic domains, a structured foundation was established for the technical dimensionality reduction and cleaning pipeline described in the following Section 3.4 and Chapter 4.

3.4 Manual variable screening

Prior to any data cleaning or modelling, a structured multi-stage workflow was implemented to screen and reduce the dimensionality of the raw TILDA datasets. As shown in Table 3.3 (for example, $1619 \rightarrow 809$ variables in wave 1), the raw PMF files were reduced to a subset of variables of interest. This procedure also separated automated diagnostic profiling from manual variable exclusion, ensuring transparency in all selection decisions.

The process consisted of the following steps:

1. **Raw data loading:** Raw TILDA PMF files were loaded without cleaning or recoding. Waves 1–5 were loaded from Statistical Package for the Social

Table 3.2: PMF v5.5 derived variable prefixes [3].

Variable Prefix	Research Area
1: Socio Demographic & Context	
INC	Income variables
SES	Social class
SOC	Social
2: Physical Health & Clinical Baseline	
BP	Blood pressure from sphygmomanometer
MD	Medication data
SCR	Screening tests
3: Functional Status & Frailty	
ADL	Activities of daily living
DIS	Disability, functional impairment, helpers
FR	Frailty, gait, exercise, falls and fractures
GRIP	Grip strength
IADL	Instrumental activities of daily living
4: Lifestyle & Behavioural	
BEH	Health behaviours
5: Nutrition & Metabolic Biomarkers	
BLOODS	Results of blood sample analysis
6: Psychological & Cognitive	
COG	Scales and questions on cognition
CRT	Choice reaction time (cognitive test)
MH	Scales and questions on mental health and wellbeing
Other / Administrative	
G2G	Gateway to Global Aging Data

3. METHODOLOGY

Sciences (SPSS) (`.sav`) files, while the harmonised dataset was loaded from a (Stata) (`.dta`) file due to technical compatibility issues.

2. **Automated variable profiling (Python):** For every variable, summary statistics were computed programmatically, including data type, proportion of missing values, number of unique values, most frequent value, and frequency of the most frequent value. These summaries were exported to spreadsheet format for inspection.
3. **Manual variable screening (spreadsheet based):** Using predefined rule based thresholds described below. Variables were manually reviewed and flagged for exclusion based on missingness, lack of variation, dominance of a single category, or administrative function.
4. **Creation of retained variable lists:** Variables not flagged for exclusion were programmatically concatenated in `.xlsx` and manually transferred into wave specific JavaScript Object Notation (JSON) files representing the retained *variables of interest*.
5. **Reloading filtered datasets:** The JSON files were then used to subset the original raw datasets, producing reduced datasets with identical rows but fewer variables. No cleaning, recoding, or imputation was applied at this stage.

Manual filtering was applied according to the following criteria:

- **Missingness:** Variables with $> 80\%$ missing values were dropped. This threshold retains sufficient feature coverage while avoiding the imputation uncertainty that arises when the majority of values are absent.
- **Unique values:** Drop variables with a single observed value, as they contain no discriminative information and cannot contribute to modelling or inference. Variables with low cardinality (2–4 unique values) were retained for review, as they frequently represent meaningful categorical responses (e.g., binary indicators or ordinal scales) relevant to ageing outcomes.

- **Dominant category (top value/frequency):** Variables where a single category (sample value) marked as the `topValue` occurs over $\approx > 90\%$ (`topFrequency`) of observations were flagged. Such dominance indicates limited variability, reducing analytical utility and predictive value. Variables exceeding this threshold were marked for review or exclusion.
- **Identifiers / administrative fields:** IDs, version tags, and sampling weights were identified using the PMF metadata. Variable names and descriptions were exported from each wave’s PMF file into Comma Separated Values (CSV) files (Appendix A) to systematically document and review features prior to filtering. These exports enabled structured manual inspection and traceability between raw PMF metadata and downstream feature selection decisions.

During manual screening and filtering, variables exceeding exclusion thresholds (e.g., high missingness, single value, dominant category, administrative identifiers) were visually flagged (e.g., marked in red). Non-flagged variables were programmatically concatenated with double quotes and commas to separate each variable using spreadsheet formulas (e.g., `=TEXTJOIN(", ", TRUE, CHAR(34) & J2:Jn & CHAR(34))`) ready for the manual transfer into wave specific JSON files for each wave. These files represent the *variables of interest* retained after manual screening and filtering and serve as inputs for the upcoming automated data preprocessing and cleaning in Section 4.1.

The retained variables defined in JSON files were subsequently used to subset the raw datasets. As shown in Table 3.3, this process yielded a significant reduced dataset for each wave. For instance, in wave 1, manual filtering reduced the feature space from 1,619 to 809 variables, a 50.03% reduction. When considering all five waves collectively, the total number of variables was reduced from 5,345 to 3,099 representing a count of 2,246 dropped features with an overall reduction average of 42.0%. This reduction ensures only analytically meaningful variables proceed to the automated cleaning engine.

Importantly, all variable exclusion decisions were completed at this stage, subsequent steps focus on numerical standardisation and model preparation.

3. METHODOLOGY




Figure 3.1: Flowchart of the manual five step workflow for variable screening and filtering. Placeholder (n) values represent the number of variables at each stage, illustrating the reduction from the raw dataset to the filtered dataset prior to automated preprocessing.

3.5 Dataset characteristics after filtering

To further understand the characteristics of these retained variables, the datasets were profiled using an exploratory visualiser (`.ipynb`) file implemented with `pandas`, `numpy`, `matplotlib`, and `seaborn`. This step examined data types, missingness patterns, unique value distributions, and representative sample values across all waves. The purpose of this profiling stage was not transformation but to expose structural inconsistencies and latent formatting issues that would undermine direct numerical conversion.

Table 3.3: Input shape for cleaning pipeline (post manual filtering workflow 3.1).

Dataset	Row (N participants)	Column (N features)	% Reduction
Wave 1	8501	809	50.0%
Wave 2	7206	482	33.4%
Wave 3	6397	639	37.9%
Wave 4	5713	592	40.2%
Wave 5	4978	577	41.3%
Harmonised	8501	453	20.8%

For example, in wave 1, the visualiser detected 650 categorical columns, 150 (`float64`) columns, and 9 object columns, while the harmonised dataset contained 304 categorical columns, 148 `float32` columns, and several integer columns. Age distributions confirmed that the study population was restricted to older adults across waves, however, ages were bottom coded for participants younger than 50 years and top coded for those aged 65–85 years and above. Missing value summaries indicated substantial variation (e.g., mean missing values ranging from 4.7% in wave 4 to 35% in the harmonised dataset, with some variables exceeding 77% missing).

These insights exposed structural inconsistencies. For instance, variables that appeared numeric but encoded labels such as “1.Rarely or none of the time” alongside sentinel codes (e.g., `−98`, `−99`) that directly informed the design of the deterministic cleaning pipeline described in Chapter 4.

3. METHODOLOGY

3.6 Retained variable distribution by domain

Using the PMF prefixes described in Table 3.2 as a guide, variables were assigned to seven thematic groups (Table 3.4), each capturing a conceptually coherent domain: physical, cognitive, social, and behavioural aspects of ageing. This structure supports reproducible preprocessing and helps machine learning models focus on meaningful, longitudinally robust features.

This grouping provides a clear framework for the automated cleaning rules described in Chapter 4 and ensures model inputs are conceptually aligned with study objectives.

The seven thematic groups integrate information from CAPI, SCQ, and derived variables, covering sociodemographic context, physical health, functional status, lifestyle behaviours, nutrition and metabolic biomarkers, psychological and cognitive measures, and administrative identifiers.

The heatmap at the base of Table 3.4 shows domain coverage across waves, darker shading indicates a higher variable count highlighting which domains contribute most features to the dataset.

3.6 Retained variable distribution by domain

Table 3.4: Thematic domain grouping of longitudinal features.

ID	Thematic Group	Description	Representative Variable Examples	Total Features
1	Socio-Demographic & Context	Baseline demographic and socioeconomic indicators	Age/Sex	844
			Education	
			Income	
			Marital status	
2	Physical Health & Clinical	Clinical and self reported health measures	Blood pressure	839
			BMI	
			Chronic disease status	
			Self rated health	
3	Functional Status & Frailty	Physical functioning and frailty markers	Activities of Daily Living (ADL)/Instrumental Activities of Daily Living (IADL)	174
			Grip strength	
			Gait speed	
4	Lifestyle & Behavioural	Health behaviours and activity patterns	Physical activity	120
			Smoking	
			Alcohol use	
5	Nutrition & Metabolic	Metabolic and biomarker indicators	C-Reactive Protein (CRP)	22
			Creatinine	
			Lipid markers	
6	Psychological & Cognitive	Cognitive performance and mental health	Mini-Mental State Examination (MMSE)	291
			Depressive symptoms	
			Stress scale	
7	Other / Administrative	Survey metadata and structural variables	Sampling weight	809
			Completion status	
			Contact names	

	SocioDemographic_Context	PhysicalHealth_Clinical	FunctionalStatus_Frailty	Lifestyle_Behavioural	Nutrition_Metabolic	Psychological_Cognitive	Other_Administrative	Total_Features
wave1	272	149	48	58	10	97	175	809
wave2	119	148	18	21	0	38	138	482
wave3	164	184	44	14	8	93	132	639
wave4	161	186	30	13	4	36	162	592
wave5	128	172	34	14	0	27	202	577
Total_per_Domain	844	839	174	120	22	291	809	3099

Thematic domain dominance across waves (higher n features per domain).

Chapter 4

Technical Implementation

4.1 Automated cleaning engine

The core challenge in converting heterogeneous variable types across the six datasets (Table 3.3) was achieving a single numerical standard suitable for downstream analysis. This required enforcing *numerical homogeneity*, defined here as representing all retained features using a single numerical representation (`float64`) with a unified missing or non response sentinel (`-1.0`).

Categorical variables were dominant (2,916 columns) while numeric types were fragmented, with `float64` (462 columns) adopted as the common standard to support decimal values from midpoints, ordinal scaling, and frequency normalisation. The solution was implemented as two stages: automated *variable scenario detection* (function `detect_column_scenario_mapping`, (Appendix C)) and a deterministic *six step numerical cleaning engine* (Appendix E). Nine scenario categories were defined initially and three served only as validation fallbacks and were eliminated as coverage improved, leaving six active transformation steps applied uniformly across all waves (Appendix B).

4.1.1 Stage 1: Variable scenario mapping and validation

All variables passed sequentially through the six step pipeline, most were resolved in Steps 1–5, with Step 6 (Appendix D) handling only residual variables that could not be resolved by earlier transformations.

To ensure robustness, the classification output was immediately processed by a validation routine that generated a comprehensive dictionary of feature states before and after cleaning, including all representative sample values for each variable. This allowed direct inspection of how the same variable was represented across waves prior to cleaning, particularly in cases where identical semantic categories appeared in different orders or formats. By comparing these grouped samples before and after each cleaning step, classification errors and inconsistent mappings were identified and corrected prior to execution of subsequent transformations.

The dictionary generated inside the `show_grouped_vars_for_scenarios` function (Appendix F) was formatted to create an automatic friendly “.md” file for rapid, surface level verification, which honed the final mapping dictionary (an example can be found in Appendix G) for all features across all waves. This process of using automated detection followed by visual, manual validation was essential for correcting errors in classification logic before the subsequent scenario transformations were executed in the pipeline.

4.1.2 Stage 2: Deterministic six step cleaning sequence

The nine input scenarios were processed sequentially by the *six step cleaning engine*, resolving simple and unambiguous cases first to maximise the proportion of clean numerical features before tackling more complex structures, particularly censored and multi class scenarios (Figure 4.1). With later steps progressively shifting from cleaning into semantic feature engineering, this deterministic sequence applied identical transformation and feature encoding logic to each wave, with later steps (particularly Steps 4–6) performing rule based feature engineering by deriving semantically meaningful numerical representations directly from observed category tokens at runtime. The rationale for this embedded feature engineering approach is detailed in Section 4.1.3, implementation is provided in Appendix D. This design reflects the empirical diversity of survey encodings, where a small subset of variables only reveal their semantic structure after simpler transformations have been applied.

4. TECHNICAL IMPLEMENTATION




Figure 4.1: Flowchart of the final six step cleaning pipeline applied to all TILDA waves. Detailed transformation tables are provided in Appendix B.7. The corresponding implementation “.ipynb” script is documented in Appendix E at each scenario step.

The final cleaning pipeline consisted of six deterministic steps applied uniformly across all TILDA waves, with increasingly complex transformations handled in later stages. Steps 4–6 required particular attention due to hybrid, ordinal, or multi class formats. A summary of each step and examples is provided below.

1. **Empty / Blank Values:** All missing entries, empty strings, and white-space were converted to the standard non-response sentinel (-1.0).
2. **Sentinel Values:** Wave specific non-response codes (e.g., -98, -99) and textual sentinels (e.g., “dk”, “not applicable”) were mapped to the unified (-1.0) placeholder.
3. **Numeric Transformation:** Numeric like columns containing embedded units, symbols, or hybrid strings (e.g., 50+, <10, 1-2.5) were parsed using regex and converted to `float64`. For ranges, midpoints &/or boundary values were used. For censored or annotated values, appropriate upper/lower bounds were applied.
4. **Censored / Ordinal Variables:** This step addressed variables representing ordinal scales, bracketed numeric ranges, or frequency expressions (e.g., “2–3 days a week”, “daily”). Transformations included:
 - Converting textual ordinal labels and Likert scale responses to numeric equivalents.
 - Mapping calendar based frequency descriptors to numeric weekly equivalents.
 - Manual verification was conducted for low count or unusual variables using the Markdown audit outputs to confirm semantic meaning was preserved.
5. **Binary Categorical Variables:** Two level features (e.g., Yes/No, Male/Female) were dynamically encoded using mappings derived from the observed value set of each variable:
 - Semantic rules were applied e.g., (“no”, “not”, “female” → 0.0) and (“yes”, “male” → 1.0).

4. TECHNICAL IMPLEMENTATION

- Count based detection verified that variables had exactly two non-missing unique values.
- Features with more than two sample values were also analysed for sentinel presence:
 - If a variable had three observed values and one was a sentinel, it was treated as binary.
 - If a variable had four observed values and two were sentinels, it was treated as binary.
- Sentinels were preserved as `-1.0`.
- This approach ensured order invariant encoding across waves, even when original labels or numeric prefixes differed.
- *Example (sentinel case)*: Feature `f1002_5` with pre transformed values `['NOT Getting in or out of bed', -1.0, 'Getting in or out of bed']` was encoded as `[0.0, -1.0, 1.0]`, demonstrating how a sentinel preserves binary semantics.

6. Multi-class / Mixed Variables (rule based feature engineering):

Variables with remaining multi class structure, mixed types, or unresolved string numeric hybrids after earlier transformations were processed in the final step.

Technical implementation details for this step are provided in Appendix D:

- Lexical parsing extracted numbers, ranges, units, percentages, and textual frequency descriptors into floats, yielding interpretable numerical feature representations.
- Sentinel handling ensured all known non-response codes mapped to `(-1.0)`.
- Original values were grouped and assigned numeric identifiers in first seen order, non numeric categorical labels were assigned integer codes above the highest observed numeric value to prevent collisions.
- Manual inspection using the Markdown audit file verified that semantic equivalence was maintained across waves.

- Step 6 was designed to be *order invariant*, dynamically interpreting category values within each wave rather than relying on predefined lookup tables shared across waves. This preserved consistent numeric representation regardless of variable ordering or wave specific encodings.
- *Example:* Step 5 handled simple binary variables such as `CHRany_pain` (any pain reported) with pre transformed values [`'pain'`, `'No pain'`] and numeric mapping [`1.0`, `0.0`]. In contrast, Step 6 dynamically processed multi class variables like `we114` (pre tax wage/salary) many of which contained over 20 distinct pre transformed categories (e.g., `-1.0`, `'200-299'`, `'Less than 100'`, ..., `'6,000-6,999'`) into consistent numeric representations (e.g., `-1.0`, `249.5`, `99`, ..., `6499.5`). This illustrates why Step 6 required wave specific, dynamic parsing to maintain semantic equivalence across diverse observed values.

4.1.3 Feature engineering within the cleaning pipeline

Although the six step pipeline is framed primarily as a numerical cleaning procedure, Steps 4–6 also perform explicit rule based feature engineering by interpreting heterogeneous categorical survey responses and converting them into semantically meaningful numerical representations. Rather than acting as a separate post processing stage, feature engineering is embedded directly within the cleaning logic, formalising ordinal structure, frequency, and magnitude encoded in text into directly modelable `float64` values suitable for downstream analysis.

Crucially, this process engineers the representation of each feature rather than expanding the feature space. For example, free text frequency responses such as “once or twice a week”, “a couple of times per month”, or “almost every day” are not treated as nominal categories. Instead, lexical cues (e.g., `once`, `twice`, `couple`) are resolved to numeric quantities and normalised onto a common temporal scale, yielding a continuous rate representation. Implicit semantic information such as ordering, intensity, and frequency is therefore preserved through deterministic parsing and normalisation without introducing additional variables.

4. TECHNICAL IMPLEMENTATION

This design maintains the original dimensionality of the dataset while ensuring numerical homogeneity and semantic integrity, producing a compact and model ready representation of complex real world survey data.

4.1.4 Cross wave semantic verification

Given the absence of guaranteed category ordering across waves, preserving *semantic equivalence* during numerical encoding and feature representation was essential to avoid introducing distortions into downstream ML modelling. Pre and post transformation values for each group were exported to a readable Markdown (.md) file. This representation confirmed that features of known importance for downstream predictive models were preserved and correctly encoded. For example, features such as `ph001` (self rated general health), `ph009` (comparative self rated health), and `bh006` (smoking frequency) correspond to items identified by [6] as among the most influential predictors in Frailty Index (FI) based mortality models. Retaining these features from the manual filtering thresholds applied in Section 3.4 and encoding them consistently across waves ensured that the cleaned dataset maintains coverage and semantic integrity, preventing distortions that could potentially compromise model performance.

A key challenge in cleaning the five TILDA waves was the lack of guaranteed ordering for categorical values of the same variable across different waves. Table 4.1 illustrates this for waves 4 and 5.

For example, gender (`sex`) variables appeared under different value encodings, with varied category orderings and numeric prefixes across waves. Values such as [`Male`, `Female`], [`Female`, `Male`], and prefixed forms like [`1.male`, `2.female`] were all mapped to a consistent numeric representation (1.0 for male, 0.0 for female). This ensured that semantic equivalence, rather than positional ordering or wave specific encoding, determined numerical assignment.

The Markdown audit confirmed that semantically identical categories were correctly grouped across waves regardless of variable name or encoding order, and that complex value spaces (e.g., income bands, frequency descriptors) were

4.2 Validation on the cleaning pipeline

being collapsed to stable numeric representations consistently across waves. Full audit examples are provided in Appendix G.

Table 4.1: Inconsistent category ordering for the same feature *ph009* (**self rated health compared to other people your age**) across waves and its impact on positional (order based) label encoding.

Pos	Wave 4		Wave 5	
	Category	Code	Category	Code
1	Good	3.0	Very Good	4.0
2	Fair	2.0	Fair	2.0
3	Poor	1.0	Excellent	5.0
4	Excellent	5.0	Good	3.0
5	DK	-1.0	Poor	1.0
6	Very Good	4.0	DK	-1.0
7	RF	-1.0	RF	-1.0

4.2 Validation on the cleaning pipeline

Validation assessed whether the pipeline preserved meaningful biological structure by checking whether known relationships reported in the literature could be recovered from the cleaned data.

Due to restricted access to certain outcome variables within TILDA, full end-to-end replication of all published models was not always feasible. In particular, access through the **Hotdesk Facility** for the official mortality outcomes is subject to additional governance requirements, including institutional GDPR training certification and approval by the TILDA data access committee [43].

As a result, validation focused on two complementary strategies:

- (i) Internal consistency checks against established biological and clinical relationships, and

4. TECHNICAL IMPLEMENTATION

- (ii) Constrained replication of published modelling frameworks using available predictors and the derived `8y_mortality_proxy` outcome.

Together, these validation steps demonstrate that the cleaning pipeline retains expected relational patterns and produces datasets appropriate for downstream modelling tasks.

4.2.1 Internal feature relationships

The first validation stage assessed whether cleaned predictors preserved biologically and clinically plausible relationships reported in prior TILDA studies. This analysis focused on predictors identified by [4] as accounting for approximately 95% of the explained variance in Gait Speed Reserve (GSR), defined as the difference between maximum and usual gait speed.

As GSR is not directly available in the public wave 3 dataset, validation was performed by examining the directional relationships between the 7 primary predictors themselves. This approach evaluates whether the numerical encoding process, including sentinel handling, missing value treatment, and ordinal mapping, retained the expected internal structure of the data rather than reproducing outcome specific performance.

Figure 4.2 presents the correlation matrix for the selected predictors following cleaning. Grip strength exhibited a negative association with both age and chair stand time, reflecting the inverse relationship between muscular strength and physical performance decline. Cognitive performance (Montreal Cognitive Assessment (MOCA)) demonstrated a moderate negative correlation with age and a positive association with educational level, consistent with known patterns of cognitive reserve in older adults. Education correlated positively with cognitive performance, and BMI showed the expected weak negative association with age, reflecting reduced physiological reserve in older cohorts.

Table 4.2 summarises the expected and observed directional relationships between key predictor pairs. Notably, grip strength showed moderate negative correlations with both age ($r = -0.265$) and chair stand time ($r = -0.170$), reflecting the expected inverse relationship between muscular strength and physical performance decline. Cognitive performance (MOCA) displayed a moderate

4.2 Validation on the cleaning pipeline

negative association with age ($r = -0.381$) and a positive association with education ($r = 0.367$), consistent with known patterns of cognitive reserve in older adults. BMI demonstrated the anticipated weak negative correlation with age ($r = -0.073$). These results confirm that the cleaning pipeline retained the expected numerical structure and relational patterns of the predictors, rather than introducing artificial associations.




Figure 4.2: Correlation heatmap for top 7 predictors (Wave 3).

4.2.2 Model based validation

To evaluate whether the cleaned dataset preserves predictive utility, a constrained replication of [6] was conducted using available wave 1 predictors. The study predicted 8-year mortality using 32 FI items. In the cleaned wave 1 dataset following the deterministic six step cleaning pipeline described in Section 4.1.2, only 16 of these 32 FI items remained following the manual variable filtering described in Section 3.4, which prioritised global numeric consistency across waves.

4. TECHNICAL IMPLEMENTATION

Table 4.2: Directional validation of the 7 features explaining 95% of Gait Speed Reserve (GSR) variance as identified by [4].

Predictor 1	Predictor 2	Expected Direction / Justification	Observed r
Grip Strength (GRIP)	Age	Negative (-): GRIP is a positive predictor of GSR, while age is a negative predictor.	-0.265
GRIP	Chair Stand Time	Negative (-): Higher strength (grip) is expected to correlate with faster (lower) performance time in physical tests.	-0.170
Montreal Cognitive Assessment (MOCA) Score	Age	Negative (-): Cognitive performance (MOCA) contributes positively to GSR, whereas increasing age is associated with reduced reserve.	-0.381
Education	MOCA Score	Positive (+): Third level education and cognitive scores are both cited as positive contributors to cognitive reserve and GSR.	0.367
Body Mass Index (BMI)	Age	Weak / Mixed: BMI and age both negatively impact GSR, though their internal correlation in older cohorts is typically weak.	-0.073

4.2 Validation on the cleaning pipeline

An ‘8y_mortality_proxy’ outcome was constructed to approximate the sex specific 8-year mortality rates reported in [6] (men: 14.9%, women: 11.1%), derived from linkage to Ireland’s Central Register Office records [44]. Due to access restrictions, the official mortality data were unavailable. Therefore, mortality status was first assigned by randomly selecting deceased participants from the wave 1 cohort aged 50 years or older to match the published sex specific mortality proportions observed at wave 5 follow up. An equal number of surviving participants were then randomly sampled within each sex to construct balanced datasets for model training. The resulting random proxy datasets included 1,114 men (557 deceased) and 982 women (491 deceased), reflecting the baseline wave 1 population aged ≥ 50 years ($n = 8,172$: 3,743 men and 4,429 women).

Two variants of this proxy were implemented:

- (i) the purely random assignment described above, used as a structural baseline, and
- (ii) biologically informed probabilistic assignment based on latent FR structure extracted via Principal Component Analysis (PCA). This dual construction allowed separation of statistical artefact from biologically meaningful signal.

The random proxy provides an initial diagnostic benchmark, mortality labels were assigned using purely random sampling within each sex to match the published 8-year mortality proportions. While this preserves overall class balance, it does not encode any biological or FR related information and therefore serves only as a structural validation baseline.

For the biologically informed proxy, the 16 available FI items were standardised to zero mean and unit variance using z-score transformation. PCA was then performed separately within each sex on complete case observations to extract the principal component representing the dominant latent FR structure. The First Principal Component (PC1) was retained as a latent FR score, and its direction was aligned such that higher PC1 scores correspond to higher FR by enforcing a positive correlation with the calculated FI. This latent FR score was subsequently combined with age to construct a probabilistic mortality assignment reflecting both biological vulnerability and time dependent risk.

Two model variants were tested for each sex:

4. TECHNICAL IMPLEMENTATION

1. **FI only model:** using the 16 available FI items, without age.
2. **FI + Age model:** including age as an additional predictor.

Model training and evaluation followed the procedure reported in [6] as closely as permitted by the available data. Features were min-max normalised prior to modelling. For each sex, data were split into training (80%) and testing (20%) sets. To mitigate overfitting and obtain robust estimates of model performance, 5-fold stratified cross-validation was applied on the training data. AUC was selected as the primary evaluation metric due to its widespread use in prior TILDA and ML based studies (Figure 2.2) and its robustness to class imbalance.

For six FI items (mh0014, ph001, ph102, ph108, ph114, bh201), the cleaned dataset transformations differed from the scoring rules published in [6]. To align precisely with the original 16/32-item FI methodology, these items were recoded following the published ordinal and dichotomous mappings. This step was necessary to ensure that the six remapped FI items reflects the same interpretation of health deficits used in the literature and is consistent with standard FI construction principles [45]. Models were then re-evaluated using this partial remapping FI to assess sensitivity to feature encoding.

The resulting AUC values are reported separately for (i) cleaned (Figure 4.3) vs 6/16 recoded FI items (Figure 4.4), (ii) random vs PCA informed mortality assignment, (iii) FI only vs FI + Age models, and (iv) men and women.

These results highlight several key points:

1. **Random proxy baseline (cleaned vs recoded FI):** Under purely random mortality assignment, discrimination remained at chance level for both versions of the FI. For the cleaned 16 FI items, the FI only model achieved $AUC = 0.507$ (men) and 0.512 (women), increasing marginally to 0.516 (men) and 0.531 (women) when age was included. When six of the sixteen available deficits were recoded to align with the published FI scoring rules [6], the AUC values increased to 0.567 (men) and 0.537 (women) for the FI only model, and to 0.572 (men) and 0.605 (women) for the FI + Age model. Despite this increase relative to the fully cleaned encoding, discrimination remained close to chance under random label assignment.




Figure 4.3: ROC curves for mortality prediction using the cleaned 16 frailty index items under the PCA informed mortality proxy. Separate models are shown for men and women, with and without age.




Figure 4.4: ROC curves for mortality prediction using the 6/16 recoded frailty index items aligned with [6]. Performance is shown separately for men and women, with and without age.

4. TECHNICAL IMPLEMENTATION

These results confirm that, without embedding biological FR structure into the outcome, predictive performance reflects statistical noise rather than meaningful signal, regardless of encoding refinement.

2. **PCA informed mortality proxy (cleaned vs recoded FI):** When mortality assignment incorporated the PCA derived FR representation PC1, discrimination improved relative to the random baseline for both FI constructions. For the 16 cleaned FI items, the FI only model achieved $AUC = 0.591$ (men) and 0.667 (women), increasing to 0.602 (men) and 0.660 (women) when age was included. When six of the sixteen deficits were recoded in accordance with the published scoring framework, the FI-only model achieved $AUC = 0.636$ (men) and 0.633 (women), while the FI + age model achieved 0.643 (men) and 0.652 (women).

This indicates that closer alignment with published ordinal deficit scoring improves discrimination relative to the simplified numeric encoding applied during initial cleaning.

3. **Comparison with published performance:** Absolute AUC values remain below those reported in [6] (approximately 0.70 for FI only and up to 0.80–0.90 when age is included), which is expected given the use of a constructed mortality proxy and only 16 of the original 32 FI items. However, the methodological sequence reported in the original study is preserved:

- (i) Random assignment yields chance level performance,
- (ii) Extracting latent FR structure via PCA improves discrimination,
- (iii) Inclusion of age generally improved mortality prediction.

Importantly, the cleaned dataset maintains realistic sex distributions (45.8% men, 54.2% women) and mortality proportions consistent with published estimates, confirming that preprocessing preserved demographic and structural integrity required for downstream modelling.

Chapter 5

Empirical Evaluation

5.1 Modelling and evaluation framework

The evaluation is based on participants aged between 50 – 84 years with a mean age of 66. To ensure that the prediction task reflects *incident* (new onset) disease, individuals with the target condition already present at the start of a transition were excluded, leaving only at risk observations for training and testing. This rule was applied consistently across all designs and for both Track A (Any disease outcome) and Track B (disease specific outcomes).

Final analysis samples differed by design and tracks due to data structure. The baseline design (D1) uses a single transition (Wave 1→Wave 5), with a follow-up period of approximately 8 years. The pooled multi-wave designs (D2 and D3) aggregate all eligible consecutive transitions (W1→W2, W2→W3, W3→W4, W4→W5), each spanning approximately 2 years, thereby capturing shorter term dynamics.

Sample sizes and incident rates for Track A are summarised in Table 5.1. Track B, cohort sizes and incident rates vary by condition. Appendix H provides these details for each disease specific model.

5.1.1 Outcome definitions (Track A and Track B)

Two complementary prediction tasks were defined.

5. EMPIRICAL EVALUATION

Track A: Predicting any chronic disease onset. Track A uses a binary outcome indicating the first occurrence of any chronic disease during follow-up.

- In D1, disease free status at wave one was established using a composite of self-reported conditions (e.g., eye conditions, cardiovascular conditions, diabetes related conditions, general chronic conditions, limiting long term illness, and self-reported chronic/health problems). Incident cases were then defined using any positive ICD10_XX codes from the WHO (*International Statistical Classification of Diseases and Related Health Problems 10th Revision*) at wave five (e.g., mental and behavioural disorders & musculoskeletal diseases).
 - No single ICD10_ANY variable exists in wave 1 to establish a clinical baseline. These clinical codes were recorded unevenly across the middle waves, with only three indicators available in wave 2, two in wave 3, and one in wave 4, before a comprehensive set of 16 variables appeared at wave 5, partially a consequence of the manual low heterogeneity filtering flow described in Section 3.4.
 - Physical & Cognitive Health (PH) variables reflect prior doctor diagnoses (“has a doctor ever told you”), whereas the “self-reported long term chronic/health problem” variable captures general perceived health burden without requiring clinical confirmation.
 - All feature scoring schemes and labels are provided in Appendix I.
- In D2 and D3, the “self-reported long term chronic/health problem” variable (where $y = 0$ denotes no chronic illness and $y = 1$ denotes presence of chronic illness) was used to both define the outcome and identify the at risk cohort (those with $y = 0$ at transition start) for inclusion in each wave. This variable is available across all waves, enabling consistent application across all four consecutive transitions.

$$\text{Coverage}_y = \frac{\sum_{i=1}^N \mathbb{1}(y_i \neq \text{missing}(-1))}{N} \times 100 = 99.91\%$$

5.1 Modelling and evaluation framework

- An analysis of wave 5 data compared long term chronic/health problem against clinical records. While raw agreement reached 59.5%, (*Cohen’s Kappa for agreement beyond chance*) ($\kappa = 0.167$) indicates poor agreement, showing that these variables capture different aspects of health status. Among participants with a confirmed clinical diagnosis, 45% reported themselves as healthy, whereas 38% of those without a clinical diagnosis reported a long term chronic/health problem. This low agreement suggests that “self-reported long term chronic/health problem” and clinically coded disease are distinct but complementary constructs, one capturing perceived illness burden and the other capturing objectively documented diagnoses.

Table 5.1: Cohort sample sizes by design for Track A

Design	Observations (n)	Incident cases (n)	Incidence rate (%)
D1: Baseline (W1→W5)	916	248	27.07
D2: Multi-wave pooled	14,296	3,212	22.5
D3: Top-20 (reduced)	14,296	3,212	22.5

Track B: Disease specific prediction. Track B targets individual chronic disease outcomes, e.g., circulatory disease, diabetes, and functional decline. For each prediction task, the outcome was defined as the first recorded diagnosis of the specific condition, and participants were excluded if the condition was present at the baseline of the corresponding transition. Scoring details for each disease specific outcome are also provided in the same Appendix I. Additionally, a predictor add-on analysis was conducted to evaluate whether individual candidate features from domains beyond the top-20 set contribute independent predictive value.

5.1.2 Modelling designs

Four supervised learning algorithms were evaluated across all main Track A designs (D1, D2, D3) to compare linear and nonlinear model families under the same evaluation framework.

5. EMPIRICAL EVALUATION

1. **LR** — A linear model providing interpretability through coefficients and odds ratios. In D1 and D2, a fixed configuration was used: `solver="liblinear"`, `C=0.001`, `class_weight="balanced"`, `max_iter=2000`. In D3, hyperparameters were tuned via `RandomizedSearchCV` over `C` (log-uniform $[10^{-4}, 10]$), `solver=["saga"]`, `l1_ratio` (uniform $[0, 1]$), and `max_iter` $\in \{1000, 2000, 5000\}$.
2. **XGB** — XGBoost is a gradient boosted tree ensemble capturing nonlinearities and feature interactions. In D1 and D2, fixed parameters were used: `n_estimators=1500`, `max_depth=3`, `learning_rate=0.03`, `min_child_weight=5`, `gamma=0.1`, `subsample=0.8`, `colsample_bytree=0.7`, with class imbalance handled via `scale_pos_weight` (negative to positive ratio). Early stopping (`early_stopping_rounds=50`) on an internal 20% validation split determined the optimal number of boosting rounds. The model was then refit on the full training set at that iteration. In D3, all tree and regularisation parameters were additionally tuned via `RandomizedSearchCV`.
3. **RF** — A bagged ensemble of decision trees providing robustness through random feature subsampling (`max_features="sqrt"`). Fixed parameters in D1/D2: `n_estimators=500`, `max_depth=5`, `min_samples_leaf=10`, with class imbalance handled via `class_weight={0:1, 1:neg/pos ratio}`. In D3, `n_estimators` (100 – 800), `max_depth` (3 – 10), `min_samples_leaf` (5 – 30), and `max_features` $\in \{"sqrt", "log2"\}$ were tuned via random search.
4. **MLP** — A feedforward neural network with two hidden layers capturing nonlinear hierarchical representations. Fixed parameters in D1/D2: `hidden_layer_sizes=(32,16)`, `activation="relu"`, `solver="adam"`, `alpha=0.01`, `learning_rate_init=0.001`, `max_iter=500`, with early stopping (`n_iter_no_change=20`, `validation_fraction=0.1`). Class imbalance was handled via `compute_sample_weight(class_weight="balanced")` passed at fit time, as MLP does not natively support `class_weight`. In D3, `hidden_layer_sizes` $\in \{(32,), (64,), (32,16), (64,32), (128,64)\}$, `activation`

5.1 Modelling and evaluation framework

$\in \{\text{‘relu’}, \text{‘tanh’}\}$, `alpha` (log-uniform $[10^{-4}, 1]$), and `learning_rate_init` (log-uniform $[10^{-4}, 10^{-1}]$) were tuned via random search.

The preprocessing backbone median imputation (`SimpleImputer`), variance filtering (threshold = 0.01), and missingness filter ($> 50\%$ on training only) was shared across all models, with scaling (`StandardScaler`) applied only to LR and MLP (sensitive to feature magnitude). Tree-based models were trained on the raw imputed features without scaling. All steps were fit exclusively on training data (prior to internal train/validation splitting) before being applied to validation and test sets, preventing information leakage.

Track B models used XGB exclusively, as it achieved the strongest and most consistent performance across D2 and D3 in Track A (see Section 5.2). The same model configuration and hyperparameter search space used in D3 was applied in Track B.

The three primary modelling designs were implemented to address and assess the effect of baseline prediction, longitudinal pooling, and feature reduction with optimisation, respectively.

- **D1 (Baseline):** A single W1→W5 transition. Only participants disease free at wave 1 (using self-reported and derived disease variables, plus explicit ICD10 source variables) were included, with incident disease defined by any positive ICD10_ANY code at wave 5 ($n = 916$, incidence 27.1%). Feature selection used `SelectKBest` ($k = 20$) and CV used `StratifiedKFold` (one observation per participant).
- **D2 (Multi-wave pooled):** All four eligible consecutive transitions (W1→W2, W2→W3, W3→W4, W4→W5) were stacked into a single pooled dataset. Disease free status and incident outcome were defined using (self-reported long term chronic/health problems) at each transition. A numeric wave transition indicator (`wave_transition_num`) was added as a feature to capture temporal context. The pooled cohort comprised $n = 14,296$ person wave observations (incidence 22.5%). Feature selection used `SelectKBest` ($k = 100$), and CV used `StratifiedGroupKFold` to ensure no participant appeared in more than one fold.

5. EMPIRICAL EVALUATION

- **D3 (Top-20 + Hyperparameter Optimization (HPO)):** Built directly on the D2 cohort and wave structure. The feature set was restricted to the 20 highest ranked predictors by XGB gain importance from D2, plus `wave_transition_num`. No additional feature selection step was applied. HPO was performed for all four model families using `RandomizedSearchCV` (200 iterations) within a `StratifiedGroupKFold` framework.

All three designs shared the same participant level train/test split (80%/20%, stratified by outcome), the same missingness filter and variance threshold applied on training data only, and the same five fold CV evaluation protocol. Track B models followed either the D2 or D3 structure depending on the outcome being predicted. Full details are provided in Subsection 5.2.4.

5.1 Modelling and evaluation framework




Figure 5.1: Pipeline overview: shared preprocessing applied to all data before branching into Track A (any chronic disease, D1/D2/D3) and Track B (disease specific, following D2/D3 structure). D3 is built directly on D2’s cohort and wave structure, adding feature reduction and hyperparameter optimisation.

5. EMPIRICAL EVALUATION

Figure 5.1 notes:

- (i) All grey pipeline steps (missingness filter, imputation, variance threshold, split) are shared across Track A and Track B. All fitting occurs on training data only.
- (ii) D1 uses a single W1→W5 transition with `StratifiedKFold`, D2 and D3 use all four pooled transitions with `StratifiedGroupKFold` to prevent participant level leakage across folds.
- (iii) D3 is built on D2: it uses the same cohort, waves, and wave indicator, but replaces `SelectKBest` with the top-20 features ranked by XGB gain from D2, and adds HPO for all model families.
- (iv) Feature counts after the missingness filter: D1 retains ≈ 570 features, further reduced to $k = 20$ by `SelectKBest` before model training. D2 retains ≈ 261 features, reduced to $k = 100$. D3 uses exactly 21 features (top-20 + wave indicator) with no further selection.
- (v) Track B uses XGB only, following the D2 or D3 design with a disease specific outcome and explicit exclusion of direct outcome proxies from the predictor set.

5.1.3 Participant level data splitting and leakage prevention

To prevent identity based leakage where models memorise participant specific health signatures rather than learning general risk patterns, all splitting was performed at the **participant level**. Individuals were assigned exclusively to either the training, validation, or test set, ensuring no participant contributed data to more than one split. The overall dataset was first split into 80% for model development and 20% as a held-out test set. The 80% development partition was then further divided 80%/20% internally, yielding a final three way allocation of 64% training, 16% validation, and 20% test. Splitting was performed using participant identifiers to ensure group wise separation, with stratification by outcome to

5.1 Modelling and evaluation framework

preserve class balance across splits. As demonstrated in longitudinal brain Magnetic Resonance Imaging (MRI) analysis [46], participant level splitting prevents identity confounding, where models learn individual health signatures rather than generalisable risk patterns.

D1 used `StratifiedKFold` ($k = 5$). D2 and D3 used `StratifiedGroupKFold` ($k = 5$), ensuring all observations from a given participant are assigned to a single fold and no participant appears in both training and validation sets simultaneously. Three additional leakage controls were applied across all designs:

- **Pipeline isolation:** Imputation medians, variance masks, and feature selection scores were computed on the training partition only. The resulting transformations were then applied unchanged to validation and test data.
- **Temporal ordering:** Predictors were drawn exclusively from the baseline wave of each transition (wave n) to predict outcomes at the subsequent (wave $n + 1$), eliminating any look ahead bias.
- **Exclusion of direct proxies:** Variables that directly encode the outcome being predicted (e.g., self-reported disease source indicators that feed into the ICD10 codes used as outcome, such as (“has a doctor ever told you that you have”) a Ministroke or TIA and Parkinson’s disease for nervous system diseases), were removed from the predictor set prior to modelling.

5.1.4 Evaluation protocol and decision metrics

Model performance was assessed using discrimination, calibration, and classification metrics. The primary metric was AUC. Models requiring HPO (D3) used `RandomizedSearchCV` within the same CV framework.

Calibration was evaluated using the Brier score, which measures the accuracy of predicted probabilities, while classification performance was summarised using the F1 score, capturing the balance between precision and recall in the presence of class imbalance (e.g., 22 – 27% incidence). Additional metrics, including sensitivity, specificity, and confusion matrices, were used to support interpretation.

5. EMPIRICAL EVALUATION

For Track B predictor add-on analysis, 95% Confidence Interval (CI)s for performance deltas were estimated via bootstrap resampling to ensure statistical significance.

5.2 Main results

Performance is evaluated first across the three Track A designs (D1, D2, and D3), followed by cross design and model comparisons. Results conclude with Track B disease specific outcomes.

5.2.1 Track A: Any disease onset

Results are presented across the three modelling designs, with tables summarising discrimination (AUC), calibration (Brier score), and classification performance (F1), alongside training, validation, and test metrics to assess generalisation.

5.2.1.1 Design 1 performance

Table 5.2 summarises the performance of the four models on the single transition (Wave 1 $\rightarrow$ Wave 5). Discrimination is weak with test AUC values ranging from 0.53–0.58, and the larger train-test gaps for tree based models indicate stronger overfitting in the baseline design.

Table 5.2: Predictive performance across model families for D1 (baseline design).

Model	CV AUC	Train AUC	Val AUC	Test AUC	Brier Score	F1 Optimal
Logistic Regression	0.589	0.677	0.582	0.571	0.245	0.411
XGBoost	0.569	0.825	0.563	0.544	0.240	0.398
Random Forest	0.579	0.871	0.565	0.534	0.231	0.440
MLP	0.536	0.664	0.552	0.582	0.241	0.419

5.2.1.2 Design 2 performance

Table 5.3 shows the results when using all consecutive transitions (pooled multi-wave design). All models improve substantially compared to D1 5.2.1.1, with test AUC values ranging from 0.69 to 0.72.

Table 5.3: Predictive performance across model families for D2 (multi-wave design).

Model	CV AUC	Train AUC	Val AUC	Test AUC	Brier Score	F1 Optimal
Logistic Regression	0.715	0.728	0.715	0.709	0.217	0.460
XGBoost	0.716	0.736	0.719	0.715	0.214	0.468
Random Forest	0.711	0.740	0.717	0.711	0.212	0.452
MLP	0.698	0.749	0.706	0.699	0.208	0.455

5.2.1.3 Design 3 performance

Table 5.4 presents performance using only the 20 most informative predictors (derived from XGB model trained on D2 5.2.1.2) with HPO applied across all models. Discrimination remains effectively unchanged compared to D2, with test AUC values tightly clustered around 0.71.

Table 5.4: Predictive performance across model families for D3 (tuned design).

Model	CV AUC	Train AUC	Val AUC	Test AUC	Brier Score	F1 Optimal
Logistic Regression	0.716	0.718	0.717	0.712	0.212	0.459
XGBoost	0.718	0.736	0.719	0.713	0.209	0.462
Random Forest	0.717	0.766	0.718	0.713	0.205	0.462
MLP	0.713	0.743	0.710	0.712	0.207	0.467

5.2.2 Cross design comparison

The best test AUC increased from 0.582 in D1 5.2.1.1 (achieved by MLP) to 0.715 in D2 5.2.1.2 by XGB, representing an improvement of 0.133, demonstrating the benefit of incorporating pooled longitudinal transitions.

Reducing the feature set to the top-20 predictors in D3 maintained this gain, with XGB achieving a test AUC of 0.713, only 0.002 lower than D2, confirming that most of the predictive signal is concentrated in a small subset of variables, and that performance is robust to feature reduction.

Across designs, CV performance also improves and stabilises:

- D1: 0.589 ± 0.072 (LR)

5. EMPIRICAL EVALUATION

- D2: 0.716 ± 0.007 (XGB)
- D3: 0.718 ± 0.006 (XGB)

The reduction in standard deviation from 0.072 (D1) to 0.007 (D2) is not only a statistical artifact of a larger sample. It reflects a shift in the nature of the learning problem. D1 asks the model to learn from a single snapshot of health at wave 1 and predict a clinically coded outcome eight years later, a task where signal is sparse and the outcome is heterogeneous, and chance variation dominates. D2 pools 14,296 person wave observations, each capturing a tighter 2-year transition window in which self-reported health burden is the direct and proximal outcome. This alignment between predictor and outcome horizon is the structural reason for the performance gain, not simply the larger n . The implication is that for short term incident prediction in survey cohorts, self-reported health state is a stronger signal source than objective biomarkers measured years earlier.

5.2.3 Model comparison

Once temporal structure is introduced (D2 and D3), model differences narrow: test AUC ranges shrink from 0.048 (D1) to 0.022 (D2) to 0.006 (D3), also clustering in the range (0.69–0.72), with no single model class dominating performance. XGB achieved the highest test AUC in both D2 (0.715) and D3 (0.713), though the margin over LR was narrow (≤ 0.006). The fact that the linear LR remained consistently competitive (0.709 in D2 5.2.1.2 and 0.712 in D3 5.2.1.3) suggests that risk signals in the ageing population are primarily linear. MLP slightly underperforms in D2 5.2.1.2 (0.699) but matched other models in D3 5.2.1.3 (0.712), indicating improved performance when the feature space is reduced to the most informative predictors. This indicates that individual burden indicators, particularly medication count and pain, dominate the risk score with largely linear effects, leaving limited room for nonlinear algorithms to outperform a well regularised linear baseline. The convergence of model families in D3, where the AUC range narrows to just 0.006, is a further sign that the available signal has been largely captured by the top-20 features. Improving performance from here would require richer data rather than more complex algorithms.

Figure 5.2 compares generalisation gaps (Train–Test) AUC across all three designs. The average train-test AUC gap (across all four models) drops from 0.202 in D1 to 0.030 in D2 and 0.028 in D3 – a reduction of over 85%. This demonstrates that the pooled multi-wave design effectively reduces overfitting. D1 exhibits the largest gaps, consistent with weaker signal and higher variance in estimates. In contrast, D2 and D3 show much smaller gaps, indicating improved stability. Tree based models (XGB and RF) exhibit the largest gaps in D1, consistent with the small sample size. In D2 and D3, XGB achieves the smallest gaps (0.021 and 0.023 respectively), while RF shows comparatively larger gaps (0.029 and 0.053). The strong performance of XGB in D3 is expected, as the top-20 feature set was selected using XGB gain importance from D2. Nevertheless, XGB also generalises well in D2, suggesting that its boosting mechanism is effective at learning stable patterns from pooled longitudinal data. In contrast, RF may be more prone to overfitting even with the pooled design, possibly due to its reliance on bagging and random feature selection, which may capture informative predictors less efficiently than boosting.




Figure 5.2: Train–Test generalisation gaps across models and designs. 0.05 marks a conventional heuristic threshold for acceptable error in AUC. Gaps below this level indicate that the model generalises well to unseen data.

5. EMPIRICAL EVALUATION

The figure also highlights that model level differences in generalisation gap are more pronounced in D1 5.2.1.1, whereas D2 5.2.1.2 and D3 5.2.1.3 exhibit convergence across model families, suggesting that data structure plays a larger role than algorithmic choice in controlling overfitting.

5.2.4 Track B: Disease specific

Track B targets individual chronic disease outcomes using the same pooled cohort structure and participant level splitting as D2 and D3, with XGB as the sole classifier given its consistently strong performance in Track A. Twenty four disease specific outcomes were evaluated using two feature strategies: all eligible predictors retained after the 50% missingness filter (for example, 261 features for functional decline and 351 for circulatory disease), and a restricted top-20 set derived from XGB gain importance.

Outcomes span key domains of ageing related health in TILDA: cardiovascular conditions, functional decline, mental health, and metabolic disease.

5.2.4.1 Outcome categories

Four outcome categories were evaluated:

- **Clinical (ICD10):** Circulatory, endocrine/metabolic, eye, and musculoskeletal diseases (comprehensive from wave 5 only, source predictors excluded to prevent leakage).
- **Functional:** Functional decline, falls (Inc. balance), pain, hearing loss, and urinary incontinence (self-reported, available across multiple waves e.g., $W2 \rightarrow W4$, $W3 \rightarrow W4 \rightarrow W5$ and $W2 \rightarrow W4$).
- **Family history:** Reports of family member diagnoses across eight conditions. These are not incident diagnoses of the participant and represent a distinct prediction target: estimating the likelihood of a participant newly reporting a family history item at follow-up. These variables were retained through the manual filtering process described in Section 3.4.

- **Medication/procedure proxies:** Antidepressant, antihypertensive, cholesterol medications, doctor confirmed hypertension, and cardiac procedure. These are downstream markers of clinical decision making used as prediction targets. They capture risk signals linked to eventual treatment rather than raw disease onset. As noted in Appendix H, incidence rates for medication proxies vary widely, 1.4% for cardiac procedure to 41.6% for doctor confirmed hypertension diagnosis (though this is based on a very small cohort of $n = 250$).

5.2.4.2 Overall performance

Figure 5.3 plots train AUC against test AUC for all disease specific models, coloured by outcome category. The diagonal represents perfect generalisation (train equals test), while dashed lines at 0.5 on both axes mark chance level performance. Points close to the diagonal indicate stable learned signal, whereas points far above it, with much higher train than test AUC, indicate overfitting. Overall, test AUC values range from approximately 0.45 to 0.72, reflecting substantial variation driven mainly by outcome type and incidence rate rather than model choice.

Functional and symptom outcomes were the most reliable across both feature strategies. Functional decline ($n = 14,296$, incidence 22.5%) achieved a test AUC of 0.713 with a small gap between train and test, consistent with the strong and persistent FR signal identified in the literature. FOF ($n = 18,114$, incidence 14.0%) achieved 0.721, the highest test AUC, closely followed by antihypertensive prescription, reflecting the well documented link between functional limitation and falls risk in TILDA. Hearing loss ($n = 10,780$, incidence 15.1%) reached 0.678, and urinary incontinence ($n = 16,208$, incidence 8.4%) achieved 0.682, both with gaps below 0.10. These outcomes benefit from consistent measurement across waves, sufficient event counts, and clear physiological pathways, which support more stable longitudinal prediction.

Medication proxies achieved competitive test AUC values. Antihypertensive prescription ($n = 19,845$, incidence 4.5%) reached 0.718, and antidepressant prescription ($n = 4,378$, incidence 3.2%) reached 0.702, despite low incidence. Both

5. EMPIRICAL EVALUATION

models showed train AUC above 0.99, indicating overfitting to training specific patterns rather than fully generalisable risk patterns. The test results show that the models can discriminate between cases and non cases, although part of this performance likely comes from established treatment profiles. For example, a participant already receiving antihypertensives at baseline has a clinical profile strongly associated with future prescription continuation. These models are therefore informative for risk stratification but should not be interpreted as predicting new disease onset.

Clinical ICD10 outcomes showed moderate performance. Circulatory disease ($n = 14,539$, incidence 12.2%) and eye diseases ($n = 4,396$, incidence 10.1%) were the strongest, reaching test AUC values of 0.626 and 0.653, respectively. This aligns with findings that cardiovascular outcomes in TILDA are supported by well established clinical predictors. Musculoskeletal diseases ($n = 4,269$, incidence 6.5%) and endocrine and metabolic diseases ($n = 4,117$, incidence 8.8%) performed near chance, with test AUC values of 0.507 and 0.515 under the all features strategy, alongside train AUC values of 1.000 and 0.967. This pattern indicates that the models memorised training labels without learning signal that transfers to new data. This issue is discussed further in Section 5.2.4.4.

Family history models produced the most variable and least reliable results. Using all features, test AUC ranged from 0.513 for cancer ($n = 3,971$, incidence 13.4%) to 0.665 for high cholesterol ($n = 4,312$, incidence 12.0%), while training AUC reached 1.000 for several outcomes such as Alzheimer’s disease and cancer, indicating severe memorisation. Switching to the top-20 feature set consistently degraded performance, with several models dropping below 0.50. The root cause is the indirect nature of the target: family history variables capture a participant’s reported knowledge of a relative’s diagnosis, rather than an outcome experienced by the participant. As a result, there is no direct causal pathway linking participant level predictors to these outcomes, limiting the model’s ability to learn generalisable patterns. What is learned from the training data therefore does not transfer well to unseen data.

5. EMPIRICAL EVALUATION

features models, none of which exceed test AUC of 0.54 despite high training performance.

Doctor confirmed hypertension is an outlier worth noting. Its incidence rate of 41.6% is the highest in Track B, and it achieved test AUC of 0.718. However, the cohort is very small at $n = 250$, making this estimate less reliable. This result should be interpreted with caution, as a cohort of this size can produce highly variable test scores depending on the specific participants allocated to the test split.

5.2.4.4 Overfitting and feature reduction

For outcomes where the all features strategy produced train AUC substantially above 0.90 alongside near chance test AUC, the top-20 strategy provides a more reliable estimate of generalisable performance, even when absolute performance remains modest. Musculoskeletal diseases moved from train 1.000 / test 0.507 to train 0.761 / test 0.548 under feature reduction. Endocrine and metabolic diseases similarly improved from 0.515 to 0.561. These are not large gains, but they indicate a more calibrated model that has learned from signal rather than noise. In contrast, for outcomes where both strategies produced similar test AUC with small gaps, such as functional decline, FOF, and hearing loss, the feature reduction confirms stable learning rather than addressing overfitting.

For family history targets, feature reduction worsened rather than helped. With only 20 features, the model is further constrained in its ability to identify even proxy signal for family reported diagnoses. This is consistent with the broader point that the target type, rather than the feature count, drives instability in these models.

The overall pattern across Track B is consistent with the preprocessing decisions made in Section 3.4. Variables were excluded during the manual filtering stage if they exceeded the missingness threshold, exhibited constant values, or had a single response category dominating more than approximately 90% of observations. This process improved overall signal quality, but it also reduced the number of available predictors for outcomes that are inherently sparse or indirectly measured. Outcomes with rich, well distributed predictor signals, such as

functional decline and FOF, benefited most. Outcomes dependent on rare or indirect signals, such as Alzheimer’s family history or cardiac procedure, remained constrained by both the target definition and the reduced predictor space. The results in Figure 5.3 should therefore be interpreted not only as a function of modelling choices, but as a reflection of data availability and the structural properties of each outcome in TILDA.

5.3 Model interpretability and feature importance

Feature importance analysis across all designs reveals three consistent findings. First, predictive signal is concentrated in a small, highly redundant set of health burden indicators, primarily spanning the Physical/Clinical and Functional thematic domains defined in Section 3.3, with other domains adding little additional discriminative information beyond the baseline feature set. Second, the most important predictors shift fundamentally between designs: objective clinical biomarkers dominate the 8 year prediction window in D1, while medication burden and self-rated health dominate the 2 year transitions in D2 and D3. Third, no single domain specific predictor adds statistically significant predictive value. This remained true within the constraints of the available features and model specification, as confirmed by the add-on analysis. Full feature importance bar plots for D1 and D2 across all four model families are provided in Appendix J. Figure 5.4 displays the add-on Δ visualisation.

5.3.1 Design 1: Clinical biomarkers dominate

In D1, the top-20 features selected by `SelectKBest` were dominated by cardiovascular and anthropometric measurements from the wave 1 health centre assessment (see Appendix J.1). Blood pressure variables, covering seated and standing systolic and diastolic readings and their means, appeared prominently across all four model families. Anthropometric FR markers, specifically hip circumference (0.084 for RF, 0.037 for MLP), waist circumference, and BMI, were consistently ranked alongside trail making test time as a marker of cognitive processing speed. Social engagement through attendance at classes or lectures, health insurance coverage,

5. EMPIRICAL EVALUATION

mother’s age at death as a familial longevity signal, socioeconomic group, and physical impairment count contributed additional signal across models.

This pattern aligns with what the literature review chapter identified as the primary drivers of chronic disease and mortality in this cohort. Blood pressure is a well established cardiovascular risk marker [36], anthropometric measures connect to the FR and obesity pathway in TILDA [28], and trail making test time reflects the cognitive reserve framework discussed in Chapter 2 [20]. The dominance of these objectively measured variables reflects the availability of a full wave 1 health centre assessment providing objective clinical measurements that were less consistently available in later waves.

Across model families, the ranking order varied modestly. Seated systolic blood pressure ranked first for both XGB (gain 0.072) and RF, which is notable given that these are both tree based models using different importance metrics, suggesting that the feature is consistently identified as important across tree based approaches. By contrast, LR showed a broader distribution placing attending classes or lectures at rank one (0.039), and MLP placed hip circumference first (0.037). Importance values are not directly comparable across model families as each uses a different scoring method, so the cross model consistency in which features appear, rather than their specific scores, is the more meaningful observation here.

5.3.2 Design 2: Medication burden and self-rated health emerge

Shifting from D1 to D2 produced a major change in the importance landscape (see Appendix J.2). Blood pressure variables, which dominated D1, did not appear in the top-20 for any model in D2. Medication burden and self-rated health became the primary drivers instead.

Medication count excluding supplements ranked first in XGB (0.068), RF (0.115), and MLP (0.012) in D2. Polypharmacy indicators, total medication counts including supplements, and extended medication burden measures collectively occupied much of the top 10 across all four model families. This shift reflects the change in prediction target from ICD10 coded hospitalisation over

5.3 Model interpretability and feature importance

8 years (D1) to self-reported chronic illness over 2 year transitions (D2). Over shorter windows, medication burden is a closer indicator of health deterioration: a participant already taking multiple medications at baseline is substantially more likely to report chronic illness at the next wave.

This reflects the difference in how far ahead each design is predicting. Over 8 years, clinical measurements such as blood pressure reflect long-term biological risk that takes time to appear as diagnosed disease. Over 2 years, medication burden and self-rated health are much more direct markers of near term change. The best predictors, in short, depend on the prediction window.

Self-rated general health ranked first for LR (0.150) and appeared in the top six for all model families. This predictor is one of the most consistently reported predictors of subsequent morbidity and mortality in older adult cohorts [6], and its prominence here validates the predictive framework. Comparative self-rated health, capturing how participants assess their health relative to peers of the same age, also appeared in the top-20 across LR, XGB and RF models.

Pain related variables contributed substantially in D2. Chronic pain limiting activities, pain severity, and any chronic pain indicator all ranked consistently across model families. Chapter 2.6 identified chronic pain as a marker of underlying functional decline and a strong predictor of subsequent disease burden [16]. Functional disability items, specifically difficulty getting up from a chair after sitting, chair rising steadiness, and aggregate physical limitation counts, rounded out the top predictors. Healthcare utilisation variables, general practitioner visit frequency and outpatient visit frequency, also appeared, reflecting that participants who engage heavily with the health system consistently showed elevated risk of incident chronic illness at the next wave.

5.3.3 Cross model consistency and the D3 feature set

A notable finding across D2 is the high degree of agreement between model families regarding which features matter. The top five features by XGB gain, RF Gini importance, LR absolute coefficient magnitude, and MLP permutation importance show substantial overlap in the highest ranked predictors, with only minor ordering differences. This agreement across four different model types

5. EMPIRICAL EVALUATION

strengthens confidence in the results. When a linear model, two tree ensembles, and a neural network independently converge on the same top features, it is unlikely to be a peculiarity of any single method. The health burden cluster is not just one way to interpret this data, it is the dominant signal in this cohort.

The D3 and Track B top-20 feature set was derived directly from XGB gain importance in D2 and applied unchanged across all four D3 model families and all Track B disease specific models. Table 5.5 lists this feature set with thematic domain assignments following the domains described in Section 3.4.

Table 5.5: Top-20 features from XGBoost gain in D2, applied in D3 and Track B.

Feature label	Description	Thematic domain
Reported medications (excl. supps)	Total reported medications excluding supplements	Physical/Clinical
Chronic pain (proxy)	Frequency of pain experienced	Functional/Symptom
Polypharmacy (excl. supps)	Taking five or more medications excluding supplements	Physical/Clinical
Regular medications	Number of regular medications including supplements	Physical/Clinical
Reported medications	Number of reported medications including supplements	Physical/Clinical
Self-rated health	General self-rated health (excellent to poor)	Physical/Clinical
Number of physical limitations	Count of activity limitations from mobility items	Functional
Health limits activities	Health problem limits kind or amount of activities	Functional
Pain limits activities	Chronic pain restricts daily activities	Functional/Symptom
GP visits (12 months)	Number of GP visits in past 12 months	Physical/Clinical
Large muscle ADL/IADL index	Composite of large muscle daily activity items	Functional
Pain severity	Level of pain reported	Functional/Symptom
Flu vaccination	Had a flu vaccination in past 12 months	Lifestyle
Walking/standing steadiness	Steadiness when walking or standing	Functional
Chronic pain	Any chronic pain present	Functional/Symptom
Chair rising steadiness	Steadiness when getting up from a chair	Functional
Hospital visits (12 months)	Number of outpatient visits in past 12 months	Physical/Clinical
Getting up from chair difficulty	Difficulty getting up from a chair after sitting	Functional
Functional difficulty	Difficulty stooping, kneeling, or crouching	Functional
Health vs peers	Self-rated health compared with others of same age	Physical/Clinical

^aChronic pain (proxy) is a derived variable from CAPI including proxy respondents. 'Chronic pain' is a separate binary indicator from the derived variable codebook.

The feature set spans two primary thematic domains: Physical/Clinical (medication counts, self-rated health, healthcare utilisation) and Functional (mobility difficulty, pain, physical limitation), with one Lifestyle item (flu vaccination). Nutritional and metabolic biomarkers, psychological and cognitive measures, and sociodemographic variables are absent from the top-20.

5.3.4 Predictor add-on analysis

The add-on analysis evaluated the incremental contribution of individual candidate features to the prediction of functional decline using a *BASE* versus *BASE+ADDON* framework. For each candidate, a model was trained on all available

5.3 Model interpretability and feature importance

predictors except that candidate (BASE), then retrained with it included. The baseline cohort and feature set are determined dynamically for each candidate. Only waves in which both the outcome target and the candidate feature were present were used, meaning cohort size and feature count varied across candidates. For example, when a history of blackout or fainting served as the candidate feature, the analysis included waves 1 to 3, yielding 929 held-out test participants and approximately 570 features entering the model after the missingness filter. When education level served as the candidate, waves 3 to 5 were used, yielding 660 test participants and approximately 464 features. The delta in AUC and (Average Precision (AP)) was estimated with bootstrapped 95% CIs ($B = 2,000$ resamples on the held-out test set). Full delta results are shown in Figure 5.4. The candidates span lifestyle, socioeconomic, cognitive, nutritional, and social domains, including features from thematic domains listed in Table 3.2 that are not represented in the top-20 feature set.

Given the large baseline feature sets entering each comparison, marginal gains from a single additional candidate feature are expected to be small. The purpose of the analysis is therefore to assess whether any domain contributes unique predictive information beyond this baseline rather than to achieve statistically significant improvements. No candidate produced a statistically significant improvement across any metric. Formally, for each candidate the null hypothesis $H_0: \Delta\text{AUC} = 0$ was tested via bootstrapped 95% confidence intervals ($B = 2,000$ resamples), rejection requires the interval to exclude zero. Every interval crossed zero, providing a consistent null result across all domains. Selected results, organised by domain cluster, are as follows.

- (i) **Functional predictors** (chair rising difficulty, physical limitations, chair rising steadiness, FOF). Among the functional candidates, the highest BASE AUC occurred when getting up from a chair difficulty served as the candidate feature (0.707). Adding it to the BASE produced a near zero marginal gain (CI: $[-0.012, 0.002]$). Physical limitation count (CI: $[-0.008, 0.007]$) and chair rising steadiness (CI: $[-0.006, 0.010]$) showed similarly null deltas. As reviewed in Table 2.3, gait speed, chair stand performance, and physical limitation are consistently identified as primary FR indicators in TILDA [7].

5. EMPIRICAL EVALUATION

The small incremental contributions are consistent with strong correlation across functional predictors: pain, steadiness, and mobility difficulty items share their predictive variance, and none appears to contribute substantial independent information beyond the others.

- (ii) **Socioeconomic predictors** (education level, household income). Education level produced the largest observed positive delta, with Test AUC moving from 0.711 to 0.719 (CI: $[-0.002, 0.018]$). The direction is consistent with the examined literature on social disadvantage [15], although the interval crosses zero and the effect cannot be confirmed statistically. Total household income produced a smaller positive trend ($[-0.004, 0.010]$). The smaller effect likely reflects alignment with healthcare utilisation and employment status predictors already in the BASE.
- (iii) **Psychosocial and mental health predictors** (University of California-Los Angeles (UCLA) loneliness, depressive symptoms, social connectedness). UCLA loneliness produced no detectable effect (CI: $[-0.009, 0.006]$). Depressive symptoms produced a small positive delta of $+0.001$ (CI: $[-0.008, 0.010]$). Social connectedness showed similarly minimal movement (CI: $[-0.008, 0.007]$). Chapter 2.3 documents bidirectional links between SOC (social isolation, depression, and functional health) in TILDA [29, 31]. The null deltas do not contradict these associations, they indicate that the relevant pathways are already captured within the functional and pain predictors present in the BASE.
- (iv) **Physical and behavioural predictors** (grip strength, BMI, cigarettes per day, CAGE alcohol scale, history of blackout or fainting). Grip strength produced a positive delta of $+0.004$ (CI: $[-0.004, 0.012]$). Chapter 2 identifies grip strength as a primary FR marker in TILDA [23]; the near zero increment confirms that the functional limitation variables in the BASE already capture this FR related signal. BMI produced $+0.002$ (CI: $[-0.007, 0.012]$). Cigarettes per day trended slightly negative ($[-0.012, 0.002]$), and the CAGE alcohol scale contributed minimally ($[-0.004, 0.008]$). A history of blackout or fainting produced the highest BASE AUC in the study (0.714, CV

5.3 Model interpretability and feature importance

0.726 ± 0.009), indicating a BASE model that is already performing strongly when this variable is withheld. Adding it back yielded no further gain (CI: $[-0.007, 0.007]$), suggesting its signal is captured through correlated cardiovascular and health burden predictors already present in the BASE.




Figure 5.4: Bootstrapped 95% confidence intervals for test AUC delta (BASE+ADDON minus BASE) across all candidate features ($B = 2,000$ resamples). Features are sorted in ascending order by the midpoint of the delta interval. All intervals cross zero, indicating no statistically significant incremental contribution from any candidate.

Across all designs and model families, predictive signal across these related health outcomes was concentrated within a highly correlated pattern of indicators associated with accumulated health burden. Medication load, self-rated health, pain frequency and severity, and mobility difficulty collectively capture most of the discriminative signal available in this dataset: social, cognitive, nutritional, and behavioural domains showed weak positive trends but no independent contribution within the context of the available feature set and model specification.

5. EMPIRICAL EVALUATION

This is supported by two convergent findings. Restricting D3 to 20 features produced no reduction in performance, and no add-on candidate improved discrimination significantly. Together, these results suggest that for 2-year transitions in this cohort, predictive signal structure reflects a compact and highly correlated set of health burden indicators rather than separable domain specific risk factors.

5.4 Health burden correlation structure

The results in this chapter reflect not only modelling choices but also the structure of the underlying data. This section examines pairwise correlations among the key health burden variables used in this study to explain three recurring patterns: why pooled designs outperformed the single wave baseline, why reducing the feature set caused negligible loss in performance, and why no add-on candidate produced statistically significant independent gain.

5.4.1 Shared health burden signal

When pairwise correlations among predictors approach $|r| = 1$, the effective rank of the feature matrix decreases and the marginal information gained from adding further correlated variables approaches zero, a property that directly explains why the feature reduction in D3 (Section 5.2.1.3) produced negligible performance loss, and why no add-on candidate in Subsection 5.3.4 improved discrimination significantly. Figure 5.5 presents pairwise Spearman correlations at wave 5 ($n = 4,978$) for six health burden variables used across Track A and Track B: self-reported long term health problem, long term illness, any clinically coded chronic disease (ICD10_ANY), chronic pain, self-rated health, and medication use.

The most striking feature of the matrix is the perfect correlation ($r = 1.00$) between self-reported long term health problem and long term illness. Both share identical prevalence (44.2%, $n = 2,201$ out of 4,977 valid responses) and are empirically indistinguishable within this wave of TILDA. They encode a single construct, and predictive performance for either target reflects the same signal rather than two independent outcomes.

5.4 Health burden correlation structure




Figure 5.5: Pairwise Spearman correlations among six health burden variables at wave 5 ($n = 4,978$). Self-reported long term illness and chronic health problem form an identical construct ($r = 1.00$), while ICD10_ANY shows consistently weak associations with all self-reported measures.

A more consequential pattern concerns the alignment between ICD10_ANY and the self-reported measures. Correlations range from $r = 0.094$ with chronic pain to $r = 0.245$ with medication use, with long term illness at $r = 0.168$ and self-rated health at $r = -0.174$. These weak associations are not driven by imbalance: ICD10_ANY prevalence was 37.6%, comparable to the self-reported outcomes. They reflect a genuine measurement gap, and as confirmed by the Cohen’s Kappa analysis in Section 5.1.1 ($\kappa = 0.167$), the agreement between them is poor.

All top-20 variables identified in D2 and D3, including medication burden, self-rated health, chronic pain, mobility limitation, and healthcare utilisation, are survey derived and naturally aligned with the self-reported layer rather than with

5. EMPIRICAL EVALUATION

clinically coded records. The issue is not that these predictors are uninformative, but that they are aligned more closely with subjective and functional health states than with clinically coded disease definitions. This explains why D1, which used ICD10_ANY as its outcome, produced substantially weaker and less stable discrimination than D2 and D3.

A third pattern concerns the internal structure of the self-reported measures. Medication use, self-rated health, chronic pain, and long term illness are moderately correlated with pairwise values ranging from $|r| = 0.25$ to $|r| = 0.43$. Self-rated health is inversely associated with all other burden indicators: medication use ($r = -0.423$), chronic pain ($r = -0.335$), and long term illness ($r = -0.418$). These moderate correlations indicate a shared burden signal, while still leaving each measure with some independent predictive value.

This internal structure directly explains why the add-on analysis in Section 5.3 produced no statistically significant results. Add-on candidates from outside this set, including education level, grip strength, UCLA loneliness, and cognitive function (MMSE, the survey based cognitive screener available across all waves), were each tested against a BASE model already containing the core burden indicators. None produced a measurable increment, because the principal signal had already been absorbed by these variables.

Prediction of chronic disease risk in this cohort is therefore governed by a compact and internally correlated set of perceived and functional health measures. Further gains from adding variables of the same type are unlikely. The present analysis used the publicly accessible TILDA release (Waves 1 – 5), which contains self-reported health, functional, cognitive, nutritional, and behavioural variables, together with ICD10 coded disease indicators from wave 2 onwards. Richer data that could distinguish perceived health burden from objective physiological decline, including linked mortality records, primary care records, and repeated biomarker panels, are held under elevated access and were not available for this study. The inclusion of family history indicators in Track B partly reflects this constraint: participant level onset data for specific conditions were often sparse or absent in the public release, and family reported diagnoses served as an indirect proxy where direct measures were unavailable.

5.4 Health burden correlation structure

Taken together, the empirical results suggest that in a general community dwelling older adult cohort with publicly available survey data, chronic disease onset prediction is largely a function of how burdened a person already feels captured by their medications, pain, and self-rated health rather than of specific biomarker or lifestyle profiles. Extending this signal would require access to richer linked data, a direction outlined in Chapter 6.

Chapter 6

Conclusion

6.1 Summary

Models x, y, z

6.2 Conclusions

6.2.1 Data availability Statement

The data analysed in this study is subject to the following licenses/restrictions: The datasets generated during and/or analysed during the current study are not publicly available due to data protection regulations but are accessible at TILDA on reasonable request. Requests to access these datasets should be directed to <https://tilda.tcd.ie/data/accessing-data/>.

6.2.2 Ethics Statement

The studies involving human participants were reviewed and approved by the Faculty of Health Sciences Research Ethics Committee at Trinity College Dublin, Ireland. The patients/participants provided their written informed consent to participate in this study.

6.3 Contributions

6.4 Future Work

To use wave6 published on 15/12/2025, IDS and covid-19 datasets. How well our models generalise well compared to international data. The utilisation of the harmonised dataset.

Appendix A

Python code for exporting PMF metadata to CSV

```
1 import pandas as pd
2 import pyreadstat
3 from pathlib import Path
4 import json
5
6 data_files = {
7     "wave1.json": "data/0053-01_TILDA_Wave1_2009-2011/0053-01
8         _TILDA_Wave1_Data/SPSS/0053-01_TILDA_Wave1_PMF_v1.12.sav",
9     "wave2.json": "data/0053-01_TILDA_Wave2_2012-2013/Data
10         /0053-02_TILDA_Wave2_PMF_v2.7.sav",
11     "wave3.json": "data/0053-01_TILDA_Wave3_2014-2015/Data
12         /0053-04_TILDA_Wave3_PMF_v3.6.sav",
13     "wave4.json": "data/0053-01_TILDA_Wave4_2016/Data/0053-05
14         _TILDA_Wave4_PMF_v4.4.sav",
15     "wave5.json": "data/0053-01_TILDA_Wave5_2018/Data/0053-06
16         _TILDA_Wave5_PMF_v5.5.sav",
17     "harmonized.json": "data/0053-06_TILDA_Harmonized_2016/Data
18         /0053-03_TILDA_Harmonized_v1.2.dta",
19 }
20
21 def load_df_with_var_of_interest(
22     var_dir="var_of_interest", data_files=data_files, verbose=
23     False
```

```

18 ):
19     dfs = {}
20     var_dir = Path(var_dir)
21
22     for json_name, data_path in data_files.items():
23         file = var_dir / json_name
24         with open(file, "r") as f:
25             vars_list = json.load(f).get("variables_of_interest")
26             if verbose:
27                 print(f"Variables_of_interest_from_{file.name}:_{vars_list[:10]}_...")
28
29             if data_path.endswith(".sav"):
30                 df_full, meta = pyreadstat.read_sav(
31                     data_path, encoding="latin1", apply_value_formats
32                     =True
33                 )
34                 df, _ = pyreadstat.read_sav(
35                     data_path,
36                     usecols=vars_list,
37                     encoding="latin1",
38                     apply_value_formats=True,
39                 )
40             else:
41                 df_full = pd.read_stata(data_path,
42                                         convert_categoricals=True)
43                 df = pd.read_stata(data_path, convert_categoricals=
44                                     True)[vars_list]
45
46             if verbose:
47                 print(
48                     f>Data_shape_(Original):_{df_full.shape[0]}_rows_
49                     x_{df_full.shape[1]}_columns"
50                 )
51                 print(f>Data_shape_(Cleaned):_{df.shape[0]}_rows_x_{
52                     df.shape[1]}_columns")
53                 print("
54                     -----")
55
56     dfs[file.stem] = df

```

Appendix

```
52     return dfs
53
54
55 if __name__ == "__main__":
56     for json_name, path_str in data_files.items():
57         path = Path(path_str)
58         wave_name = json_name.replace(".json", "")
59         if path_str.endswith(".sav"):
60             # SPSS
61             df, meta = pyreadstat.read_sav(
62                 path, encoding="latin1", apply_value_formats=True
63             )
64
65         else: # Stata .dta file
66             df, meta = pyreadstat.read_dta(path, encoding="latin1")
67
68         pd.DataFrame(
69             {"variable": meta.column_names, "label": meta.
70              column_labels}
71         ).to_csv(Path("output") / f"{wave_name}
72                  _variable_descriptions.csv", index=False)
73
74         print(f"-----wave_{path}-----")
75         print(df.shape)
76         print(df.columns[:20])
77         print(
78             "Variable/Feature_descriptions, csv file saved
79             successfully->dir=output/"
80         )
81         df.to_csv((Path("output") / f"{wave_name}.csv"), index=
82                   False)
83
84     dfs = load_df_with_var_of_interest(verbose=True)
```

Appendix B

Scenario: Cleaning Pipeline Tables

Table B.1: Initial Raw Feature Counts Categorised by Nine Scenarios (Pre Cleaning)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	9	0	7	0	9	0
Numeric with sentinel	187	59	143	60	100	141
Clean numeric	14	27	18	22	20	8
Censored / bracketed numeric	84	71	91	85	85	73
Binary categorical	248	159	177	220	207	187
Multi class categorical / mixed	267	166	203	205	156	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total Columns	809	482	639	592	577	453

Appendix

Table B.2: Scenario Count Progression: Post Step 1 (Empty / Blank Handling)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	81	31	42	32	75	15
Clean numeric	124	55	123	50	54	134
Censored / bracketed numeric	84	71	91	85	85	73
Binary categorical	251	159	179	220	207	187
Multi class categorical / mixed	269	166	204	205	156	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Table B.3: Scenario Count Progression: Post Step 2 (Sentinel Standardisation)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	0	0	0	0	0	0
Clean numeric	205	86	165	82	129	149
Censored / bracketed numeric	84	71	91	85	85	73
Binary categorical	251	159	179	220	207	187
Multi class categorical / mixed	269	166	204	205	156	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Table B.4: Scenario Count Progression: Post Step 3 (Numeric Cleaning)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	0	0	0	0	0	0
Clean numeric	263	117	215	124	172	149
Censored / bracketed numeric	16	23	17	16	17	73
Binary categorical	251	160	180	221	207	187
Multi class categorical / mixed	279	182	227	231	181	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Table B.5: Scenario Count Progression: Post Step 4 (Censored / Ordinal Mapping)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	0	0	0	0	0	0
Clean numeric	279	140	233	140	189	222
Censored / bracketed numeric	0	0	0	0	0	0
Binary categorical	251	160	180	221	207	187
Multi class categorical / mixed	279	182	226	231	181	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Table B.6: Scenario Count Progression: Post Step 5 (Binary Classification)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	0	0	0	0	0	0
Clean numeric	530	300	413	361	396	409
Censored / bracketed numeric	0	0	0	0	0	0
Binary categorical	0	0	0	0	0	0
Multi class categorical / mixed	279	182	226	231	181	44
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Table B.7: Final Dfs Cleaned: Post Step 6 (Multi-Class / Mixed Parsing)

Scenario	Wave 1	Wave 2	Wave 3	Wave 4	Wave 5	Harmonised
Empty / blank values	0	0	0	0	0	0
Numeric with sentinel	0	0	0	0	0	0
Clean numeric	809	482	639	592	577	453
Censored / bracketed numeric	0	0	0	0	0	0
Binary categorical	0	0	0	0	0	0
Multi class categorical / mixed	0	0	0	0	0	0
Single value categorical	0	0	0	0	0	0
Special symbol / mixed	0	0	0	0	0	0
Unknown / complex mixed	0	0	0	0	0	0
Total	809	482	639	592	577	453

Appendix C

First Stage: Scenario Variable Mapping

```
1 # Sentinel values (numeric and string)
2 # -1 and -1.0 is sentinel but will be used in the clean pipeline
3 standardised_sentinels = {'-1', '-1.0', -1, -1.0} # set ->
    duplicates removed -> counts correct -> single value detection
    is zero
4 numeric_sentinels = [-1, -1.0, -98, -98.0, -99, -99.0,
5                      95, 95.0, 96, 96.0, 98, 98.0, 99, 99.0]
6 string_sentinels = [str(x) for x in numeric_sentinels] + [f"_{x}"
7                  for x in numeric_sentinels] + \
    ['na', 'n/a', 'refused', 'missing', 'dk', 'rf', 'refused', "
    refuse", 'none', 'no_response', 'nan', 'not_answered', 'no
    _answer',
8    'not_applicable', 'no_consent', 'dont_know', "don't_know", "didn
    _t_answer", 'prefer_not_to_say', 'task_not_done', '
    insufficient_sample', 'unable_to_record',
9    '__', '*']
10 blanks = ['', ' ', '\t', '\n']
11
12 SCENARIOS = [
13     "Empty_/blank_values",
14     "Numeric_with_sentinel",
15     "Clean_numeric",
16     "Censored_/bracketed_numeric",
17     "Binary_categorical",
```

```

18     "Multi_class_categorical/_mixed",
19     "Single_value_categorical",
20     "Special_symbol/_mixed",
21     "Unknown/_complex_mixed"
22 ]
23
24
25 # flatten all dtypes across the waves to float and category
26 def flatten_column_types(df):
27     df_flat = df.copy()
28
29     for col in df_flat.columns:
30         if pd.api.types.is_numeric_dtype(df_flat[col]): # Numeric
31             # columns
32             df_flat[col] = df_flat[col].astype(float) # Convert
33             # to float
34         else:
35             df_flat[col] = ( # Convert to string, strip
36                 whitespace, lowercase, then category
37                 df_flat[col]
38                 .astype(str)
39                 .str.strip()
40                 .str.lower()
41                 .astype('category')
42             )
43
44     return df_flat
45
46 def detect_column_scenario_mapping(df, sample_size=10):
47     summary = []
48
49     # Regex patterns
50     special_symbols_pattern = r'[^A-Za-z0-9\s\.\,\-\+&/()]' #
51         # special symbols excluding common numeric formatting
52     bracketed_numeric_pattern = r"\d{1,3}(?:,\d{3})*[-/]\d{1,3}(?:,\d{3})*|\d+\s*[\<>+-]" # patterns like "10-20",
53         "30/40", ">=50"
54
55     sentinel_set = set(x.lower() for x in string_sentinels) #
56         Lowercase string sentinels for comparison
57
58     for col in df.columns:

```

C. FIRST STAGE: SCENARIO VARIABLE MAPPING

```
52     col_data = df[col].copy()
53     dtype = str(col_data.dtype) # get data type as string
54
55     # Convert to string for sentinel / blank detection
56     str_vals = col_data.astype(str).str.lower().str.strip() #
        lowercase and strip whitespace
57     clean_vals = col_data[~str_vals.isin(sentinel_set) & ~(
        str_vals.isin(blanks))] # remove sentinels and blanks
58
59     # Remove sentinels and blanks for scenario detection only
60     vals_no_sentinel = clean_vals[~clean_vals.astype(str).str
        .lower().isin(sentinel_set)
61                                     & ~clean_vals.astype(str).
        str.lower().isin(blanks)
        ].unique()
62     num_unique_no_sentinel = len(vals_no_sentinel)
63
64     # Check if any sentinel values are present
65     sentinel_present = str_vals.isin(sentinel_set).any()
66
67     # Detection flags
68     empty_detected = str_vals.isin(blanks).any() or len(
        col_data) == 0
69
70     # Numeric detection: coerce to numeric, NaNs for non-
        numeric
71     numeric_vals = pd.to_numeric(clean_vals, errors='coerce')
        # coerce non-numeric to NaN
72     numeric_like = numeric_vals.notna().all() and len(
        clean_vals) > 0 # all values are numeric-like after
        cleaning
73
74     sentinel_detected = str_vals[~str_vals.isin(
        standardised_sentinels)].isin(sentinel_set).any() # or
        col_data.eq(-1.0).any() # check for sentinel presence
75     censored_detected = clean_vals.astype(str).str.contains(
        bracketed_numeric_pattern).any() # check for bracketed
        numeric patterns
76
77     # Binary categorical detection (exactly 2 unique values
        after cleaning)
```

```

78     binary_categorical_detected = False
79     if dtype == 'category':
80         if num_unique_no_sentinel == 2:
81             binary_categorical_detected = True
82         elif num_unique_no_sentinel == 1 and sentinel_present
83             :
84                 binary_categorical_detected = True
85
86     # Multi-class categorical (3+ unique values, object/
87     # category)
88     multi_class_categorical_detected = num_unique_no_sentinel
89     > 2 and dtype == 'category'
90
91     # Single value categorical
92     single_value_detected = num_unique_no_sentinel == 1 and
93     not binary_categorical_detected
94
95     # Special symbols detection (ignore numeric formatting)
96     symbol_detected = clean_vals.astype(str).str.contains(
97         special_symbols_pattern).any()
98
99     # Mixed types detection
100     mixed_detected = len(set(type(v) for v in col_data)) > 1
101     # more than one data type present
102
103     # Determine scenario in order of pipeline
104     if empty_detected:
105         scenario = SCENARIOS[0]
106         handling = "Replace_numeric/categorical_empty/blank_
107         with_-1.0"
108     elif numeric_like and sentinel_detected:
109         scenario = SCENARIOS[1]
110         handling = "Replace_numeric_sentinel_values_with_-1.0
111         "
112     elif numeric_like and not sentinel_detected:
113         scenario = SCENARIOS[2]
114         handling = "Keep_as_numeric"
115     elif censored_detected:
116         scenario = SCENARIOS[3]
117         handling = "Convert_numeric_ranges_to_midpoints_or_
118         keep_as_categorical"

```

Appendix

```
110     elif binary_categorical_detected:
111         scenario = SCENARIOS[4]
112         handling = "Encode as 0/1 or keep as category"
113     elif multi_class_categorical_detected:
114         scenario = SCENARIOS[5]
115         handling = "One-hot encode, label encode, or keep as
116                     category"
117     elif single_value_detected:
118         scenario = SCENARIOS[6]
119         handling = "Keep as category / constant column"
120     elif symbol_detected:
121         scenario = SCENARIOS[7]
122         handling = "Inspect and preprocess based on context"
123     else:
124         scenario = SCENARIOS[8]
125         handling = "Inspect manually / complex mixed types"
126
127     sample_values = list(col_data.unique()[:sample_size]) #
128                     sample unique values
129
130     summary.append({
131         'Variable': col,
132         'DataType': dtype,
133         'UniqueValues': num_unique_no_sentinel,
134         'Scenario': scenario,
135         'SuggestedHandling': handling,
136         'SampleValues': sample_values
137     })
138
139     return pd.DataFrame(summary)
```

Appendix D

Step 6: Scenario ‘Multi class categorical’ Cleaning Function

```
1 def categorical_transform_S6(df): # Step6; Scenario -> Multi
    class categorical
2     df_cleaned = df.copy()
3     sent_set = set([str(x).lower() for x in string_sentinels]) |
        set([str(x).lower() for x in standardised_sentinels])
4     numeric_sentinel_set = set(float(x) for x in
        numeric_sentinels)
5
6     # Helper normaliser
7     def _norm(tok):
8         if tok is None:
9             return None
10        s = str(tok).strip().lower()
11        if s in blanks:
12            return ''
13        return s
14
15    # Words -> number map
16    word_num_map = {
17        'zero':0.0, 'one':1.0, 'two':2.0, 'three':3.0, 'four':4.0, '
18        five':5.0, 'six':6.0, 'seven':7.0, 'eight':8.0, 'nine'
        :9.0,
        'ten':10.0, 'eleven':11.0, 'twelve':12.0, 'thirteen':13.0, '
        fourteen':14.0, 'fifteen':15.0, 'twenty':20.0,
```

D. STEP 6: SCENARIO ‘MULTI CLASS CATEGORICAL’ CLEANING FUNCTION

```
19         'thirty':30.0, 'forty':40.0, 'fifty':50.0, 'sixty':60.0, '
20             seventy':70.0, 'eighty':80.0, 'ninety':90.0,
21         'a_few':2.0, 'a_couple':2.0, 'few':2.0, 'once':1.0, 'twice'
22             :2.0, 'several':3.0, 'couple':2.0
23     }
24
25     def words_to_num(token):
26         if token is None:
27             return None
28         token = token.strip().lower()
29         if token in word_num_map:
30             return word_num_map[token]
31         try:
32             return float(token)
33         except Exception:
34             return None
35
36     # Regexes for parsing
37     RE_TIME = re.compile(r'^\s*(\d{1,2}):(\d{2})\s*$')
38     RE_PERCENT = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*%\s*$')
39     RE_DIRECT_NUM = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*$')
40     RE_RANGE = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*[\--/]\s*(-?\d+(?:\.\d+)?)\s*$')
41     RE_RANGE_TO = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*(?:to|TO)\s*(-?\d+(?:\.\d+)?)\s*$')
42     RE_PLUS = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*\+\s*$')
43     RE_GT = re.compile(r'^\s*(?:>=|>)\s*(-?\d+(?:\.\d+)?)\s*$')
44     RE_LT_ANCHOR = re.compile(r'^\s*(?:<|<=)\s*(-?\d+(?:\.\d+)?)\s*$')
45     RE_NUM_FIND = re.compile(r'^\s*(-?\d+(?:\.\d+)?)\s*$')
46     RE_WORD_TOK = re.compile(r"[a-z']+(?:\s[a-z']+)?")
47     # RE_SURVEY_TIME = re.compile(r'^\s*(?:[a-z]+\s+)?(\d+(?:\.\d+
48         +)?)\s*(?:month|week|year)s?\.?$', re.IGNORECASE)
49
50     def norm_return(v):
51         try:
52             vf = float(v)
53         except Exception:
54             return None
55         if vf in numeric_sentinel_set:
56             return 'SENTINEL'
57         return vf
```

```

55     def try_parse_token(x):
56         """Return float, 'SENTINEL', or None for unknown token x
57         """
58         if x is None:
59             return None
60
61         # preserve numeric pre transformed values
62         if isinstance(x, (int, float)):
63             if float(x) in numeric_sentinel_set:
64                 return 'SENTINEL'
65             return float(x)
66
67         s = _norm(x)
68         # Extending sentinel detection for categorical parsing
69         # scenario
70         if s == '':
71             return 'SENTINEL'
72         if 'not_applicable' in s or 'does_not_have' in s or "don't
73         receive" in s or "don\x92t receive" in s or 'unknown
74         ' in s:
75             return 'SENTINEL'
76         if s in sent_set or re.fullmatch(r'[~0-9a-z]+', s):
77             return 'SENTINEL'
78         if s in ('other', 'other_specify') or s.startswith('other
79         ') or s.endswith('(specify)':
80             return 'SENTINEL'
81
82         s0 = s.replace(',', '').replace('$', '').replace(EUR, '')
83             .replace('#', '')
84
85         s0 = re.sub(r'(\d+)-', r'\1-', s0)
86         s0 = re.sub(r'-(\d+)', r'-\1', s0)
87
88         RE_PREFIX_NUM = re.compile(r'^s*(-?\d+(?:\.\d+)?)\.\s*.$')
89
90         m = RE_PREFIX_NUM.match(s0)
91         if m:
92             # If the format is 'NUM. anything', return the number
93             # as the category value
94             return norm_return(float(m.group(1)))

```

D. STEP 6: SCENARIO ‘MULTI CLASS CATEGORICAL’ CLEANING FUNCTION

```
88
89     # time
90     m = RE_TIME.match(s0)
91     if m:
92         h, mi = float(m.group(1)), float(m.group(2))
93         return norm_return(h * 60.0 + mi)
94
95     # percent
96     m = RE_PERCENT.match(s0)
97     if m:
98         return norm_return(float(m.group(1)))
99
100    # direct numeric
101    if RE_DIRECT_NUM.match(s0):
102        return norm_return(s0)
103
104    # ranges
105    m = RE_RANGE.match(s0)
106    if m:
107        try:
108            a, b = float(m.group(1)), float(m.group(2))
109            return norm_return((a + b) / 2.0)
110        except Exception:
111            pass
112    m = RE_RANGE_T0.match(s0)
113    if m:
114        try:
115            a, b = float(m.group(1)), float(m.group(2))
116            return norm_return((a + b) / 2.0)
117        except Exception:
118            pass
119
120    # plus / greater than
121    m = RE_PLUS.match(s0) or RE_GT.match(s0)
122    if m:
123        nums = RE_NUM_FIND.findall(s0)
124        if nums:
125            return norm_return(nums[0])
126
127    # less than
128    if RE_LT_ANCHOR.search(s0) or 'less_than' in s0:
```

```

129         nums = RE_NUM_FIND.findall(s0)
130         if nums:
131             return norm_return(nums[0])
132
133     # or less / more
134     m = re.search(r'(-?\d+(?:\.\d+)?)\s*or\s*less', s0)
135     if m:
136         return norm_return(m.group(1))
137     m = re.search(r'(-?\d+(?:\.\d+)?)\s*or\s*more', s0)
138     if m:
139         return norm_return(m.group(1))
140
141     # "more than X but less than Y", "over X but less than Y"
142     m = re.search(r'(?:(more|than|over)\s*e?(-?\d+(?:\.\d+)?)\s*
143         s*(?:but\s*)?(?:less|than|under)\s*e?(-?\d+(?:\.\d+)?
144         ', s0)
145     if m:
146         try:
147             a, b = float(m.group(1)), float(m.group(2))
148             return norm_return((a + b) / 2.0)
149         except Exception:
150             pass
151
152     # "between X and Y" / "between X - Y"
153     m = re.search(r'between\s*e?(-?\d+(?:\.\d+)?)\s*(?:and|[-
154         --/])\s*e?(-?\d+(?:\.\d+)?)', s0)
155     if m:
156         try:
157             a, b = float(m.group(1)), float(m.group(2))
158             return norm_return((a + b) / 2.0)
159         except Exception:
160             pass
161
162     # survey time based
163     time_map_weeks = {
164         'one|week': 1.0,
165         'two|weeks': 2.0,
166         'a|month|(4|weeks)': 4.0,
167         'a|month/4|weeks': 4.0,
168         'three|months|(13|weeks)': 13.0,
169         'three|months/13|weeks': 13.0,

```

D. STEP 6: SCENARIO ‘MULTI CLASS CATEGORICAL’ CLEANING FUNCTION

```
167         'six_months_(26_weeks)': 26.0,
168         'six_months/26_weeks': 26.0,
169         'one_year_(12_months/52_weeks)': 52.0,
170         'one_year/12_months/52_weeks': 52.0
171     }
172     if s0 in time_map_weeks:
173         return norm_return(time_map_weeks[s0])
174
175     # If a category is '3 months or more', try to extract the
176     # number and use upper bound
177     if 'months_or_more' in s0 and RE_NUM_FIND.search(s0):
178         nums = RE_NUM_FIND.findall(s0)
179         if nums:
180             months = float(nums[0])
181             return norm_return(months * 4.33) # Convert
182             # months to weeks (4.33 weeks per month)
183
184     # Frequency calendar based
185     if any(tok in s0 for tok in ('day', 'week', 'month', 'year',
186     'daily', 'never', 'almost_every_day', 'once', 'twice', '
187     thrice', 'three', 'several', 'couple')):
188         nums = RE_NUM_FIND.findall(s0)
189         if nums:
190             val = (float(nums[0]) + float(nums[1])) / 2.0 if
191             len(nums) >= 2 else float(nums[0])
192         else:
193             if 'once_or_twice' in s0:
194                 val = 1.5
195             else:
196                 val = None
197                 for w in RE_WORD_TOK.findall(s0):
198                     wn = words_to_num(w)
199                     if wn is not None:
200                         val = wn
201                         break
202     if val is not None:
203         if 'day' in s0:
204             if 'week' in s0:
205                 return norm_return(val * 4.33)
206             if 'month' in s0:
207                 return norm_return(val)
```

```

203         if 'daily' in s0 or 'every_day' in s0 or '
           almost_every_day' in s0:
204             return norm_return(val * 30.0)
205         return norm_return(val * 4.33)
206     if 'week' in s0:
207         return norm_return(val * 4.33)
208     if 'month' in s0:
209         return norm_return(val)
210     if 'year' in s0:
211         return norm_return(val / 12.0)
212     return norm_return(val)
213
214
215     likert_map = {
216         # Likert / ordinals (expanded with quintile/lowest/
           highest detection)
217         'strongly_disagree': 0.0, 'disagree': 1.0, 'neither_
           agree_nor_disagree': 2.0, 'neither': 2.0,
218         'agree': 3.0, 'strongly_agree': 4.0,
219         'very_poor': 0.0, 'poor': 1.0, 'fair': 2.0, 'good':
           3.0, 'very_good': 4.0, 'excellent': 5.0,
220         'none': 0.0, 'not_at_all': 0.0, 'hardly_ever': 0.0,
221         'a_little': 1.0, 'some': 2.0, 'a_lot': 3.0, 'alot':
           3.0, 'often': 3.0,
222         'yes': 1.0, 'no': 0.0, 'sometimes': 2.0, 'rarely':
           1.0, 'most_or_all_of_the_time': 4.0,
223         'pass': 2.0, 'fail': 1.0, '100': 100.0,
224         # Problem severity mappings
225         'no_problem': 1.0, 'minor_problem': 2.0, 'moderate_
           problem': 3.0, 'major_problem': 4.0,
226         # Concern level mappings
227         'not_at_all_concerned': 1.0, 'somewhat_concerned':
           2.0, 'fairly_concerned': 3.0, 'very_concerned': 4.0,
228         # Survey frequency mappings
229         'daily_/almost_daily': 7.0, 'once_a_week_or_more':
           6.0, 'twice_a_month_or_more': 5.0, 'about_once_a_
           month': 4.0,
230         'every_few_months': 3.0, 'about_once_or_twice_a_year'
           : 2.0, 'less_than_once_a_year': 1.0, 'never': 0.0,
231         'daily': 7.0, 'every_day': 7.0, 'almost_every_day':
           7.0, 'most_or_all_of_the_time': 7.0,

```

D. STEP 6: SCENARIO ‘MULTI CLASS CATEGORICAL’ CLEANING FUNCTION

```
232         'every_week': 6.0, 'once_a_week': 6.0, 'several_times_
233             per_week': 6.0,
234         'twice_a_month': 5.0, 'two_a_month': 5.0, 'several_
235             times_per_month': 5.0, 'once_or_twice_a_month':
236             5.0,
237         'once_a_month': 4.0, 'once_or_twice_a_year': 2.0, '
238             less_than_once_a_month': 1.0,
239     }
240
241     if s0 in likert_map:
242         return float(likert_map[s0])
243
244     # Quintile / ordinal like tokens: 'lowest', '2nd quintile
245     ', 'highest'
246     if 'quintile' in s0 or 'lowest' in s0 or 'highest' in s0
247     or 'middle' in s0 or 'median' in s0:
248         if 'lowest' in s0:
249             return norm_return(1.0)
250         if 'highest' in s0:
251             return norm_return(5.0)
252         if 'middle' in s0 or 'median' in s0:
253             return norm_return(3.0)
254         mq = re.search(r'(\d+)(?:st|nd|rd|th)?\s+quintile
255             ', s0)
256         if mq:
257             return norm_return(float(mq.group(1)))
258         nums = RE_NUM_FIND.findall(s0)
259         if nums:
260             return norm_return(nums[0])
261
262     if 'adjacent' in s0: # Adjacent boxes: keep semantic
263         average if present
264         nums = RE_NUM_FIND.findall(s0)
265         if len(nums) >= 2:
266             return norm_return((float(nums[0]) + float(nums
267                 [1])) / 2.0)
268         elif nums:
269             return norm_return(nums[0])
270         return None
271
272     # Fallback: first number
```

```

264     nums = RE_NUM_FIND.findall(s0)
265     if nums:
266         return norm_return(nums[0])
267
268     return None
269
270 def category_sort_key(u):
271     us = _norm(u) or ''
272     parsed = try_parse_token(us)
273     if isinstance(parsed, (int, float)):
274         return (0, float(parsed), us)
275     if us == 'no' or us.startswith('no_') or us.startswith('
not_'):
276         return (1, 0.0, us)
277     if 'yes' in us:
278         if 'both' in us or 'two' in us:
279             return (1, 2.0, us)
280         if 'one' in us:
281             return (1, 1.0, us)
282         return (1, 1.0, us)
283     amount_keywords = ['none', 'not_at_all', 'hardly_ever', '
a_little', 'some', 'a_lot', 'alot', 'often', '
sometimes', 'rarely']
284     for i, key in enumerate(amount_keywords):
285         if key in us:
286             return (2, float(i), us)
287     if 'adjacent_boxes' in us or 'adjacent_numbers' in us:
288         nums = RE_NUM_FIND.findall(us)
289         if len(nums) >= 2:
290             a, b = float(nums[0]), float(nums[1])
291             return (10, (a + b) / 2.0, us)
292         elif nums:
293             return (10, float(nums[0]), us)
294         return (10, 0, us)
295     return (99, 0, us)
296
297 # Operate only on categorical columns
298 cat_cols = df_cleaned.select_dtypes(include='category').
columns.tolist()
299 for col in cat_cols:

```

D. STEP 6: SCENARIO ‘MULTI CLASS CATEGORICAL’ CLEANING FUNCTION

```
300     uniques = list(dict.fromkeys(df_cleaned[col].tolist())) #
        Preserve original tokens with types (do NOT cast to
        str here)
301     normalised_pairs = [(u, _norm(u)) for u in uniques] #
        Build normalised pairs keeping original token too
302     # Keep tokens that are non sentinel and parseable (
        strings or numbers)
303     non_sentinel = [u for u, nu in normalised_pairs if (nu
        and nu not in sent_set and nu not in blanks and
        try_parse_token(nu) != 'SENTINEL')]
304
305     if not non_sentinel:
306         continue
307
308     # Computing parse results keyed by normalized string (but
        keep list of originals too)
309     parse_results = { _norm(u): try_parse_token(_norm(u)) for
        u in non_sentinel }
310
311     numeric_count = sum(1 for v in parse_results.values() if
        isinstance(v, (int, float)))
312     sentinel_parsed_count = sum(1 for v in parse_results.
        values() if v == 'SENTINEL')
313     all_parse_numeric = (numeric_count +
        sentinel_parsed_count == len(parse_results))
314
315     if all_parse_numeric:
316         # Map token string -> numeric (SENTINEL -> -1.0)
317         code_map = { k: (float(v) if isinstance(v, (int,
            float)) else -1.0) for k, v in parse_results.items
            () }
318
319     def map_to_numeric(x):
320         # Preserve the already numeric cells (except
            numeric sentinels)
321         if isinstance(x, (int, float)) and not pd.isna(x)
            :
322             if float(x) in numeric_sentinel_set:
323                 return -1.0
324             return float(x)
325         if pd.isna(x):
```

```

326         return -1.0
327     xs = _norm(x)
328     if not xs or xs in sent_set or xs in blanks or re
329         .fullmatch(r'[^0-9a-z]+', xs):
330         return -1.0
331     return float(code_map.get(xs, -1.0))
332
333 df_cleaned[col] = df_cleaned[col].apply(
334     map_to_numeric).astype(float)
335
336 else:
337     first_seen_norm = []
338     seen = set()
339     for u in non_sentinel:
340         nu = _norm(u)
341         if nu not in seen:
342             first_seen_norm.append(nu)
343             seen.add(nu)
344
345     parse_results = {nu: try_parse_token(nu) for nu in
346         first_seen_norm}
347     max_reserved_val = -1.0
348     for nu, val in parse_results.items():
349         if isinstance(val, (int, float)):
350             max_reserved_val = max(max_reserved_val, val)
351             # Assuming any parsed float is a reserved
352             # ID if it came from the map
353     start_i = int(max_reserved_val) + 1
354     if start_i == 0: # Ensure we never start at 0 if 0 is
355         a reserved category i.e for ('no')
356         start_i = 1
357     string_tokens = [nu for nu in first_seen_norm if not
358         isinstance(parse_results.get(nu), (int, float))]
359     sorted_strings = sorted(string_tokens, key=
360         category_sort_key)
361
362     code_map_strings = { norm_tok: i for i, norm_tok in
363         enumerate(sorted_strings, start=start_i) }
364
365     def map_mixed(x):

```

Appendix

```
357         if isinstance(x, (int, float)) and not pd.isna(x)
358             :# Preserve real numeric cell values
359             if float(x) in numeric_sentinel_set:
360                 return -1.0
361             return float(x)
362         if pd.isna(x):
363             return -1.0
364         xs = _norm(x)
365         if xs == '' or xs in sent_set or xs in blanks or
366             re.fullmatch(r'[^0-9a-z]+', xs):
367             return -1.0
368
369         parsed_val = try_parse_token(xs)
370         if parsed_val == 'SENTINEL':
371             return -1.0
372         if isinstance(parsed_val, (int, float)):#
373             Captures 'no' (0.0), 'yes' (1.0), and other
374             hardcoded likert values.
375             return float(parsed_val)
376         if xs in code_map_strings:
377             return float(code_map_strings[xs])
378         return -1.0
379
380     df_cleaned[col] = df_cleaned[col].apply(map_mixed).
381         astype(float)
382
383     # Final sweep on numeric columns
384     for c in df_cleaned.select_dtypes(include='float').columns:
385         df_cleaned[c] = df_cleaned[c].fillna(-1.0)
386         df_cleaned[c] = df_cleaned[c].replace(list(
387             numeric_sentinel_set), -1.0)
388
389     return df_cleaned
```


Appendix E

Second Stage: Deterministic *six step* Cleaning Pipeline

```
1 # Cleaning pipeline to all waves
2 dfs_cleaned = {}
3
4 # flattened dtype df
5 dfs_flat = {wave: flatten_column_types(df) for wave, df in dfs.
6             items()} # flatten dtypes
7
8 # Original df
9 display(scenario_count_table(dfs_flat).style.set_caption("
10     Original Table - pre cleaning")) # display original scenario
11     count table
12
13 # Step 1: Clean empty/missing values
14 dfs_step1 = {wave: clean_empty_missing(df) for wave, df in
15             dfs_flat.items()} # apply step 1 cleaning
16 display(scenario_count_table(dfs_step1).style.hide(axis="index").
17         set_caption("Step 1: Empty / Blank post cleaning"))
18
19 # Step 2: Clean sentinel values
20 dfs_step2 = {wave: clean_sentinel(df) for wave, df in dfs_step1.
21             items()} # apply step 2 cleaning
22 display(scenario_count_table(dfs_step2).style.hide(axis="index").
23         set_caption("Step 2: Sentinel post cleaning"))
24
```

Appendix

```
18 # Step 3: Numerical Transformation
19 dfs_step3 = {wave: numerical_transform(df) for wave, df in
    dfs_step2.items()} # apply step 3 cleaning
20 display(scenario_count_table(dfs_step3).style.hide(axis="index").
    set_caption("Step3: Numeric Transformation-post cleaning"))
21
22 # Step 4: Categorical Transformation for censored scenario
23 dfs_step4 = {wave: categorical_transform_S4(df) for wave, df in
    dfs_step3.items()} # apply step 4 cleaning
24 display(scenario_count_table(dfs_step4).style.hide(axis="index").
    set_caption("Step4: Category Transformation_S4-post
    cleaning"))
25
26 # Step 5: Categorical Transformation for binary values
27 dfs_step5 = {wave: categorical_transform_S5(df) for wave, df in
    dfs_step4.items()} # apply step 5 cleaning
28 display(scenario_count_table(dfs_step5).style.hide(axis="index").
    set_caption("Step5: Category Transformation_S5-post
    cleaning"))
29
30 # Step 6: Categorical Transformation for multi class/mixed values
31 dfs_step6 = {wave: categorical_transform_S6(df) for wave, df in
    dfs_step5.items()} # apply step 6 cleaning
32 display(scenario_count_table(dfs_step6).style.hide(axis="index").
    set_caption("Step6: Category Transformation_S6-post
    cleaning"))
33
34 dfs_cleaned = dfs_step6
```

Appendix F

MD Dictionary: Scenario Grouping and Transformation Function

```
1 def show_grouped_vars_for_scenarios(dfs_original, dfs_transformed
  , scenarios_to_show): # Function to show grouped variables per
  scenario across waves -> markdown format
2     """
3     Used to inspect the scenario variables/features that need
  handling for transformation/cleaning.
4     A pre and post cleaning helper function to identify variables
  that need specific handling and to
5     Inspect actual changes for a scenario from previous cleaning
  step to current step.
6     """
7
8     print("# Category Transformation Mapping")
9     # print(f"\n## Scenarios: {scenarios_to_show}") # Markdown
  mapping dictionary header
10    for wave in dfs_original.keys():
11        print(f"\n### ===== {wave.upper()} =====")
12
13        mapping_df = detect_column_scenario_mapping(
            dfs_transformed[wave]) # Get scenario mapping from
            transformed/cleaned to see overall changes for all
            variables
```

F. MD DICTIONARY: SCENARIO GROUPING AND TRANSFORMATION FUNCTION

```
14     # mapping_df = detect_column_scenario_mapping(  
15         dfs_original[wave]) # Get scenario mapping from  
16         original to see untransformed values  
17  
18     for scenario in scenarios_to_show:  
19         vars_in_scenario = mapping_df[mapping_df['Scenario']  
20             == scenario]['Variable'].tolist() # Variables in  
21             scenario  
22  
23         print(f"\n---Scenario_{scenario}:_{len(  
24             vars_in_scenario)}_---") # Scenario header for  
25             pipeline git commit  
26         if not vars_in_scenario:  
27             print("\nNo_variables_found.")  
28             continue  
29  
30         # Dictionary: frozen set(values) -> list of variables  
31         groups = {}  
32  
33         for var in vars_in_scenario:  
34             unique_vals = list(dict.fromkeys(dfs_original[  
35                 wave][var].dropna())) # Preserve first seen  
36                 order from ORIGINAL  
37             key = tuple(unique_vals) # Use ordered tuple as  
38                 key  
39  
40             if key not in groups: # Initialise list if key  
41                 not present  
42                 groups[key] = []  
43             groups[key].append(var) # Append variable to the  
44                 group  
45  
46         # Print grouped variables in markdown format friendly  
47         for Notion -> mapping dictionary  
48         for value_set, var_list in groups.items():  
49             print("\n*Variables:*", "`" + ", ".join(var_list)  
50                 + "`_") # \n  
51             print(f"*Pre_transformed_values:_{list(value_set  
52                 )}_")  
53  
54         # Pull transformed values from dfs_cleaned /  
55         specific step using preserved order
```

```

40         try:
41             df_before = dfs_original[wave][var_list[0]]
42             df_after = dfs_transformed[wave][var_list[0]]
43
44             # Build transformed list in same order as
45             # original values
46             transformed_vals = []
47             for orig_val in value_set: # Iterate through
48                 # original values in order
49                 mask = df_before == orig_val
50                 if mask.any():
51                     trans_vals = df_after[mask].
52                     unique().tolist() # Get unique
53                     transformed values
54                     if trans_vals:
55                         transformed_vals.append(
56                             trans_vals[0]) # Append
57                             first transformed value
58
59         except Exception:
60             transformed_vals = []
61         print(f"*Transformed_numeric:*_{transformed_vals}
62             ")
63
64     scenarios_to_show = SCENARIOS
65     # scenarios_to_show = ["Clean numeric"]
66     # scenarios_to_show = ["Censored / bracketed numeric"]
67     # scenarios_to_show = ["Binary categorical"]
68     # scenarios_to_show = ["Multi class categorical / mixed"]
69
70     show_grouped_vars_for_scenarios(dfs, dfs_cleaned,
71                                     scenarios_to_show) # prev step == comparison to current step
72     else current step transformed/cleaned for ready .md dictionary

```

Appendix G

MD Dictionary: Scenario Grouping and Transformation Audit Outputs

The grouped Markdown representation reveals three critical points:

1. Semantically identical categories are correctly grouped even under different variable names (ph001 vs ph009), enabling direct comparison of representations that would otherwise appear fragmented across waves.
2. Numerical encoding is invariant to category ordering, preserving ordinal meaning across waves. Without this approach, positional encoding would assign inconsistent values, potentially distorting performance for downstream models.
3. For variables with a large and heterogeneous set of observed values (e.g., income bands, frequency ranges, or mixed numeric text responses), the grouped view provided essential visibility into how complex category spaces were being collapsed into stable numeric representations, supporting both validation and error detection at scale.

```

%-----]
↪ -----%
%-----MARKDOWN_MAPPING_DICTIONARY-----]
↪ -----%
%-----]
↪ -----%

# Category Transformation Mapping

### ===== WAVE1 =====

--- Scenario Empty / blank values: 0 ---

No variables found.

--- Scenario Numeric with sentinel: 0 ---

No variables found.

--- Scenario Clean numeric: 809 ---

*Variables:* 'sex, gd002'
*Pre transformed values:* ['Male', 'Female']
*Transformed numeric:* '[1.0, 0.0]'

*Variables:* 'ph001'
*Pre transformed values:* ['Fair', 'Good', 'Very good', 'Excellent',
↪ 'Poor', "Don't know"]
*Transformed numeric:* '[2.0, 3.0, 4.0, 5.0, 1.0, -1.0]'

*Variables:* 'bh006'
*Pre transformed values:* ['20-39', 10.0, -1.0, 15.0, 5.0, '60+',
↪ "Don't Know", 2.0, 8.0, 3.0, '40-59', 4.0, 7.0, 1.0, 6.0, 14.0,
↪ 12.0, 16.0, 18.0, 13.0, 9.0, 0.0, 19.0, 11.0, 17.0]

```

G. MD DICTIONARY: SCENARIO GROUPING AND TRANSFORMATION AUDIT OUTPUTS

```
*Transformed numeric:* '[29.5, 10.0, -1.0, 15.0, 5.0, 60.0, -1.0,  
↳ 2.0, 8.0, 3.0, 49.5, 4.0, 7.0, 1.0, 6.0, 14.0, 12.0, 16.0, 18.0,  
↳ 13.0, 9.0, 0.0, 19.0, 11.0, 17.0]'
```

```
--- Scenario Censored / bracketed numeric: 0 ---
```

```
No variables found.
```

```
--- Scenario Binary categorical: 0 ---
```

```
No variables found.
```

```
--- Scenario Multi class categorical / mixed: 0 ---
```

```
No variables found.
```

```
--- Scenario Single value categorical: 0 ---
```

```
No variables found.
```

```
--- Scenario Special symbol / mixed: 0 ---
```

```
No variables found.
```

```
--- Scenario Unknown / complex mixed: 0 ---
```

```
No variables found.
```

```
### ===== WAVE2 =====
```

```
...
```

```
--- Scenario Clean numeric: 482 ---
```

```
*Variables:* 'gd002, sex'
```

```
*Pre transformed values:* ['Female', 'Male']
```

```

*Transformed numeric:* '[0.0, 1.0]'

*Variables:* 'bh006'
*Pre transformed values:* [-1.0, '10 - 19', '20 - 29', 'Less than
↪ 10', '30+', "Don't know"]
*Transformed numeric:* '[-1.0, 14.5, 24.5, 10.0, 30.0, -1.0]'

*Variables:* 'ph001'
*Pre transformed values:* ['Very good', 'Good', 'Fair', 'Excellent',
↪ 'Poor']
*Transformed numeric:* '[4.0, 3.0, 2.0, 5.0, 1.0]'

...

### ===== WAVE3 =====

...

--- Scenario Clean numeric: 639 ---

*Variables:* 'sex, gd002'
*Pre transformed values:* ['Female', 'Male']
*Transformed numeric:* '[0.0, 1.0]'

*Variables:* 'ph001, ph009'
*Pre transformed values:* ['Very Good', 'Good', 'Excellent', 'Fair',
↪ 'Poor', 'DK']
*Transformed numeric:* '[4.0, 3.0, 5.0, 2.0, 1.0, -1.0]'

*Variables:* 'bh006'
*Pre transformed values:* [-1.0, '10 - 19', 'Less than 10', '20 -
↪ 29', '30+', -98.0, -99.0]
*Transformed numeric:* '[-1.0, 14.5, 10.0, 24.5, 30.0, -1.0, -1.0]'

...

```

G. MD DICTIONARY: SCENARIO GROUPING AND TRANSFORMATION AUDIT OUTPUTS

```
### ===== WAVE4 =====

...

--- Scenario Clean numeric: 592 ---

*Variables:* 'bh006'
*Pre transformed values:* [-1.0, 'Less than 10', '20 - 29', '10 -
↳ 19', '30+', "Don't know"]
*Transformed numeric:* '[-1.0, 10.0, 24.5, 14.5, 30.0, -1.0]'

*Variables:* 'gd002, sex'
*Pre transformed values:* ['Female', 'Male']
*Transformed numeric:* '[0.0, 1.0]'

*Variables:* 'ph001'
*Pre transformed values:* ['Good', 'Fair', 'Poor', 'Excellent', 'Very
↳ Good', 'RF', 'DK']
*Transformed numeric:* '[3.0, 2.0, 1.0, 5.0, 4.0, -1.0, -1.0]'

...

### ===== WAVE5 =====

...

--- Scenario Clean numeric: 577 ---

*Variables:* 'bh006'
*Pre transformed values:* [-1.0, 'Less than 10', '20 - 29', '10 -
↳ 19', '30+', "Don't know"]
*Transformed numeric:* '[-1.0, 10.0, 24.5, 14.5, 30.0, -1.0]'

*Variables:* 'gd002, sex'
*Pre transformed values:* ['Female', 'Male']
*Transformed numeric:* '[0.0, 1.0]'
```

```
*Variables:* 'ph001'
*Pre transformed values:* ['Very Good', 'Fair', 'Excellent', 'Good',
↪ 'Poor']
*Transformed numeric:* '[4.0, 2.0, 5.0, 3.0, 1.0]'

...
```

Appendix H

Cohort sample sizes by design for Track B

Table H.1: 24-incident rates by disease specific for Track B, 10-year prediction window

Disease	Type	Obs. n	Inc. n	Inc. rate %
Circulatory disease	Clinical	14539	1774	12.2
Endocrine/metabolic diseases	Clinical	4117	362	8.8
Eye diseases	Clinical	4396	444	10.1
Musculoskeletal diseases	Clinical	4269	277	6.5
Functional decline	Functional	14296	3217	22.5
Fear of falling	Functional	18114	2536	14.0
Diabetes	Family history	4307	276	6.4
High cholesterol	Family history	4312	517	12.0
Hypertension	Family history	3590	679	18.9
Heart disease	Family history	2770	598	21.6
Osteoporosis	Family history	4779	330	6.9
Alzheimer's/dementia	Family history	4827	309	6.4
Cancer	Family history	3971	532	13.4
Depression	Family history	4760	343	7.2
Pain analgesia	Medication	2152	775	36.0
High cholesterol	Medication	733	181	24.7
Antidepressant	Medication	4378	140	3.2
Antihypertensive	Medication	19845	893	4.5
Chronic pain (proxy)	Self-reported	15571	2709	17.4
	disease			
Hearing loss	Self-reported	10780	1628	15.1
	disease			
Urinary incontinence	Self-reported	16208	1361	8.4
	disease			
Chronic pain	Self-reported	10914	1888	17.3
	disease			
Angioplasty/stent	Procedure	9233	129	1.4
Hypertension	Doctor diagnosis	250	104	41.6

Appendix I

Track A and Track B: Item index and scoring of individual features

Table I.1: 40-items: and scoring of individual features

Item	Variable	Scoring
Doctor diagnosed eye disease	ph105_5	0 = None; 1 = Yes
Doctor diagnosed hypertension	ph201_01	1 = Yes; 0 = No
Doctor diagnosed high cholesterol	ph201_08	0 = No; 1 = Yes
No conditions	ph201_14	1 = None; 0 = Other-wise
Doctor diagnosed arthritis	ph301_03	1 = Yes; 0 = No
No listed conditions	ph301_17	1 = None; 0 = Other-wise
Self-reported long-term chronic/health problem	ph003	1 = Yes; 0 = No; -1 = DK/RF
Long term illness/health problem	DISlongterm	0 = No illness; 1 = Illness; 1 = Limiting illness
Neoplasms	ICD10_02	0 = No; 1 = Yes
Diseases of the blood	ICD10_03	0 = No; 1 = Yes
Endocrine/metabolic disease	ICD10_04	0 = No; 1 = Yes
Mental and behavioural disorders	ICD10_05	0 = No; 1 = Yes
Diseases of the nervous system	ICD10_06	0 = No; 1 = Yes

Continued on next page

Item	Variable	Scoring
Eye disease	ICD10_07	0 = No; 1 = Yes
Circulatory disease	ICD10_09	0 = No; 1 = Yes
Respiratory disease	ICD10_10	0 = No; 1 = Yes
Digestive system disease	ICD10_11	0 = No; 1 = Yes
Musculoskeletal disease	ICD10_13	0 = No; 1 = Yes
Genitourinary disease	ICD10_14	0 = No; 1 = Yes
Family history of diabetes	ph726_01	0 = No; 1 = Yes
Family history of high cholesterol	ph726_02	0 = No; 1 = Yes
Family history of hypertension	ph726_03	0 = No; 1 = Yes
Family history of heart disease	ph726_04	0 = No; 1 = Yes
Family history of osteoporosis	ph726_06	0 = No; 1 = Yes
Family history of alzheimer's / dementia	ph726_07	0 = No; 1 = Yes
Family history of cancer	ph726_08_to_11	1 = Yes; 0 = No
Family history of depression	ph726_12	0 = No; 1 = Yes
Family history of other condition	ph726_95	0 = No; 1 = Yes
No family history of any disease	ph726_96	0 = No; 1 = Yes
Pain medication use	ph505	1 = Yes; 0 = No; -1 = DK/RF
Cholesterol medication	ph225	1 = Yes; 0 = No; -1 = DK/RF
Antidepressant use	MDantidepressant	0 = No; 1 = Yes
Antihypertensive use	MDantihypertensive	0 = No; 1 = Yes
Self-rated chronic pain	ph501 (proxy)	1 = Yes; 0 = No; -1 = DK
Self-rated chronic pain	CHRany_pain	0 = No; 1 = Yes
Self-rated hearing loss	ph145	0 = No; 1 = Yes; -1 = DK
Self-rated urinary incontinence	ph601	0 = No; 1 = Yes; -1 = DK/RF
Angioplasty/stent	ph208	0 = No; 1 = Yes; -1 = DK
Fear of falling	ph408	0 = No; 1 = Yes; -1 = DK
Antihypertensive medication use	ph202a	1 = Yes; 0 = No; -1 = DK

Appendix J

D1 and D2: Top 20 features




Figure J.1: Top 20 features by importance for D1.

Appendix




Figure J.2: Top 20 features by importance for D2.

References

- [1] Kai Petersen, Sairam Vakkalanka, and Ludwik Kuzniarz. Guidelines for conducting systematic mapping studies in software engineering: An update. *Information and Software Technology*, 64:1–18, August 2015. ISSN 0950-5849. doi: 10.1016/j.infsof.2015.03.007. viii, 5, 7
- [2] Barbara Kitchenham, O. Pearl Brereton, David Budgen, Mark Turner, John Bailey, and Stephen Linkman. Systematic literature reviews in software engineering – A systematic literature review. *Information and Software Technology*, 51(1):7–15, January 2009. ISSN 09505849. doi: 10.1016/j.infsof.2008.09.009. viii, 5, 8, 9
- [3] The Irish Longitudinal Study on Ageing. Tilda pseudonymised microdata file release guide v5.5. <https://tilda.tcd.ie/data/documentation/>, 2023. Accessed: 2025-10-09. viii, 21
- [4] James Davis, Silvin P. Knight, Rossella Rizzo, Orna A. Donoghue, Rose Anne Kenny, and Roman Romero-Ortuno. A linear regression-based machine learning pipeline for the discovery of clinically relevant correlates of gait speed reserve from multiple physiological systems. In *2021 29th European Signal Processing Conference (EUSIPCO)*, pages 1266–1270, August 2021. doi: 10.23919/EUSIPCO54536.2021.9616187. viii, 15, 36, 38
- [5] Neal Haddaway, Matthew J Page, Chris C Pritchard, and Luke A McGuinness. PRISMA2020: An R package and Shiny app for producing PRISMA 2020-compliant flow diagrams, with interactivity for optimised digital transparency and Open Synthesis, 2022. x, 8
- [6] Sebastian Moguilner, Silvin P. Knight, James R. C. Davis, Aisling M. O’Halloran, Rose Anne Kenny, and Roman Romero-Ortuno. The Importance of Age in the Prediction of Mortality by a Frailty Index: A Machine Learning Approach in the Irish Longitudinal Study on Ageing. *Geriatrics (Basel)*, 6(3):84, August 2021.

REFERENCES

- ISSN 2308-3417. doi: 10.3390/geriatrics6030084. x, 2, 9, 13, 34, 37, 39, 40, 41, 42, 63
- [7] James R. C. Davis, Silvin P. Knight, Orna A. Donoghue, Belinda Hernández, Rossella Rizzo, Rose Anne Kenny, and Roman Romero-Ortuno. Comparison of Gait Speed Reserve, Usual Gait Speed, and Maximum Gait Speed of Adults Aged 50+ in Ireland Using Explainable Machine Learning. *Front Netw Physiol*, 1:754477, 2021. ISSN 2674-0109. doi: 10.3389/fnetp.2021.754477. 1, 9, 10, 15, 16, 65
- [8] Patrick V. Moore, Kathleen Bennett, and Charles Normand. Counting the time lived, the time left or illness? Age, proximity to death, morbidity and prescribing expenditures. *Social Science & Medicine*, 184:1–14, 2017. ISSN 0277-9536. doi: 10.1016/j.socscimed.2017.04.038.
- [9] Ying Huang, Yuhao Su, Ying Jiang, and Meilan Zhu. Sex differences in the associations between blood pressure and anxiety and depression scores in a middle-aged and elderly population: The Irish Longitudinal Study on Ageing (TILDA). *Journal of Affective Disorders*, 274:118–125, September 2020. ISSN 0165-0327. doi: 10.1016/j.jad.2020.05.133. 1
- [10] World Health Organization Europe. New data: Noncommunicable diseases cause 1.8 million avoidable deaths and cost US\$ 514 billion every year, reveals new WHO/Europe report. <https://www.who.int/europe/news/item/27-06-2025-new-data-noncommunicable-diseases-cause-1-8-million-avoidable-deaths-and-cost-us-514-billion-USD-every-year-reveals-new-who-europe-report>, 2025. 1
- [11] Niamh Rice and Charles Normand. The cost associated with disease-related malnutrition in Ireland. *Public Health Nutr*, 15(10):1966–1972, October 2012. ISSN 1475-2727. doi: 10.1017/S1368980011003624. 1
- [12] Caoileann H. Murphy, Eoin Duggan, James Davis, Aisling M. O’Halloran, Silvin P. Knight, Rose Anne Kenny, Sinead N. McCarthy, and Roman Romero-Ortuno. Plasma lutein and zeaxanthin concentrations associated with musculoskeletal health and incident frailty in The Irish Longitudinal Study on Ageing (TILDA). *Experimental Gerontology*, 171:112013, 2023. ISSN 0531-5565. doi: 10.1016/j.exger.2022.112013. 1, 2, 10, 12, 15, 16
- [13] Eamon Laird, Charlotte Lund Rasmussen, Rose Anne Kenny, and Matthew P. Herring. Physical Activity Dose and Depression in a Cohort of Older Adults in

REFERENCES

- The Irish Longitudinal Study on Ageing. *JAMA Netw Open*, 6(7):e2322489, July 2023. ISSN 2574-3805. doi: 10.1001/jamanetworkopen.2023.22489. 1, 12
- [14] C. P. McDowell, R. K. Dishman, M. Hallgren, C. MacDonncha, and M. P. Herring. Associations of physical activity and depression: Results from the Irish Longitudinal Study on Ageing. *Experimental Gerontology*, 112:68–75, 2018. ISSN 0531-5565. doi: 10.1016/j.exger.2018.09.004. 1
- [15] Cathal McCrory, Ciaran Finucane, Celia O’Hare, John Frewen, Hugh Nolan, Richard Layte, Patricia M. Kearney, and Rose Anne Kenny. Social Disadvantage and Social Isolation Are Associated With a Higher Resting Heart Rate: Evidence From The Irish Longitudinal Study on Ageing. *J Gerontol B Psychol Sci Soc Sci*, 71(3):463–473, May 2016. ISSN 1079-5014. doi: 10.1093/geronb/gbu163. 1, 66
- [16] Eamon Laird, Matthew P. Herring, Brian P. Carson, Catherine B. Woods, Cathal Walsh, Rose Anne Kenny, and Charlotte Lund Rasmussen. Physical activity for depression among the chronically ill: Results from older diabetics in the Irish longitudinal study on ageing. *Psychiatry Research*, 326:115274, August 2023. ISSN 0165-1781. doi: 10.1016/j.psychres.2023.115274. 2, 10, 63
- [17] Orna A Donoghue, Belinda Hernandez, Matthew D L O’Connell, and Rose Anne Kenny. Using Conditional Inference Forests to Examine Predictive Ability for Future Falls and Syncope in Older Adults: Results from The Irish Longitudinal Study on Ageing. *J Gerontol A Biol Sci Med Sci*, 78(4):673–682, April 2023. ISSN 1758-535X. doi: 10.1093/gerona/glac156. 3, 9, 10
- [18] Richard J. Torraco. Writing Integrative Literature Reviews: Guidelines and Examples. *Human Resource Development Review*, 4(3):356–367, September 2005. ISSN 1534-4843, 1552-6712. doi: 10.1177/1534484305278283. 5
- [19] Xuezhong Xu, Xue Mingyang, Jie Yang, Hailong Zheng, and Zhifei Che. Tailored machine learning for evaluating the long-term diabetes risk in older individuals: Findings from the Irish Longitudinal Study on Ageing (TILDA). *BMJ Open*, 13(5):e072991, May 2023. ISSN 2044-6055. doi: 10.1136/bmjopen-2023-072991. 9, 10, 13, 14, 15, 16
- [20] Rory Boyle, Lee Jollans, Laura M. Rueda-Delgado, Rossella Rizzo, Görsev G. Yener, Jason P. McMorrow, Silvin P. Knight, Daniel Carey, Ian H. Robertson, Derya D. Emek-Savaş, Yaakov Stern, Rose Anne Kenny, and Robert Whelan.

REFERENCES

- Brain-predicted age difference score is related to specific cognitive functions: A multi-site replication analysis. *Brain Imaging Behav*, 15(1):327–345, February 2021. ISSN 1931-7565. doi: 10.1007/s11682-020-00260-3. 9, 10, 13, 62
- [21] Roy Tzemah-Shahar, Hagit Hochner, Khalil Iktilat, and Maayan Agmon. What can we learn from physical capacity about biological age? A systematic review. *Ageing Research Reviews*, 77:101609, May 2022. ISSN 1568-1637. doi: 10.1016/j.arr.2022.101609. 9
- [22] Morgana A. Shirsath, John D. O’Connor, Rory Boyle, Louise Newman, Silvin P. Knight, Belinda Hernandez, Robert Whelan, James F. Meaney, and Rose Anne Kenny. Slower speed of blood pressure recovery after standing is associated with accelerated brain ageing: Evidence from The Irish Longitudinal Study on Ageing (TILDA). *Cerebral Circulation - Cognition and Behavior*, 6:100212, January 2024. ISSN 2666-2450. doi: 10.1016/j.cccb.2024.100212. 9
- [23] Roman Romero-Ortuno, Peter Hartley, James Davis, Silvin P. Knight, Rossella Rizzo, Belinda Hernández, Rose Anne Kenny, and Aisling M. O’Halloran. Transitions in frailty phenotype states and components over 8 years: Evidence from The Irish Longitudinal Study on Ageing. *Archives of Gerontology and Geriatrics*, 95:104401, 2021. ISSN 0167-4943. doi: 10.1016/j.archger.2021.104401. 9, 10, 11, 16, 66
- [24] Laura A Bardon, Melanie Streicher, Clare A Corish, Michelle Clarke, Lauren C Power, Rose Anne Kenny, Deirdre M O’Connor, Eamon Laird, Eibhlís M O’Connor, Marjolein Visser, Dorothee Volkert, Eileen R Gibney, and MaNuEL Consortium. Predictors of Incident Malnutrition in Older Irish Adults from the Irish Longitudinal Study on Ageing Cohort—A MaNuEL study. *J Gerontol A Biol Sci Med Sci*, 75(2):249–256, January 2020. ISSN 1079-5006. doi: 10.1093/gerona/gly225. 9, 10, 13, 15
- [25] Zuo Zhang, Lauren Robinson, Robert Whelan, Lee Jollans, Zijian Wang, Frauke Nees, Congying Chu, Marina Bobou, Dongping Du, Ilinca Cristea, Tobias Banaschewski, Gareth J. Barker, Arun L. W. Bokde, Antoine Grigis, Hugh Garavan, Andreas Heinz, Rüdiger Brühl, Jean-Luc Martinot, Marie-Laure Paillère Martinot, Eric Artiges, Dimitri Papadopoulos Orfanos, Luise Poustka, Sarah Hohmann, Sabina Millenet, Juliane H. Fröhner, Michael N. Smolka, Nilakshi Vaidya, Henrik Walter, Jeanne Winterer, M. John Broulidakis, Betteke Maria van Noort, Argyris

REFERENCES

- Stringaris, Jani Penttilä, Yvonne Grimmer, Corinna Insensee, Andreas Becker, Yuning Zhang, Sinead King, Julia Sinclair, Gunter Schumann, Ulrike Schmidt, and Sylvane Desrivieres. Machine learning models for diagnosis and risk prediction in eating disorders, depression, and alcohol use disorder. *Journal of Affective Disorders*, 379:889–899, June 2025. ISSN 0165-0327. doi: 10.1016/j.jad.2024.12.053. 9, 10
- [26] Dr Angelina R. Sutin, Martina Luchetti, Damaris Aschwanden, Yannick Stephan, Amanda A. Sesker, and Antonio Terracciano. Sense of meaning and purpose in life and risk of incident dementia: New data and meta-analysis. *Archives of Gerontology and Geriatrics*, 105:104847, 2023. ISSN 0167-4943. doi: 10.1016/j.archger.2022.104847. 9
- [27] A. A. Zarudsky and K. I. Prashchayeu. P277: One-legged balance test and falls in old patients with cardiovascular diseases. *European Geriatric Medicine*, 5:S171–S172, 2014. ISSN 1878-7649. doi: 10.1016/S1878-7649(14)70448-6. 10
- [28] Chuanying Huang, Shuqin Sun, Xiaocao Tian, Tong Wang, Tianyu Wang, Haiping Duan, and Yili Wu. Age modify the associations of obesity, physical activity, vision and grip strength with functional mobility in Irish aged 50 and older. *Archives of Gerontology and Geriatrics*, 84:103895, 2019. ISSN 0167-4943. doi: 10.1016/j.archger.2019.05.020. 10, 11, 62
- [29] Louis Jacob, Karel Kostev, Jae Il Shin, Lee Smith, Hans Oh, Adel S. Abduljabbar, Josep Maria Haro, and Ai Koyanagi. Falls increase the risk for incident anxiety and depressive symptoms among adults aged ≥ 50 years: An analysis of the Irish longitudinal study on ageing. *Archives of Gerontology and Geriatrics*, 114:105098, 2023. ISSN 0167-4943. doi: 10.1016/j.archger.2023.105098. 10, 12, 66
- [30] Kevin McCarthy, Eamon Laird, Aisling M. O’Halloran, Padraic Fallon, Román Romero Ortuño, and Rose Anne Kenny. Association between metabolic syndrome and risk of both prevalent and incident frailty in older adults: Findings from The Irish Longitudinal Study on Ageing (TILDA). *Experimental Gerontology*, 172:112056, 2023. ISSN 0531-5565. doi: 10.1016/j.exger.2022.112056. 11
- [31] Ziggi Ivan Santini, Ai Koyanagi, Stefanos Tyrovolas, Josep Maria Haro, Robert J. Donovan, Line Nielsen, and Vibeke Koushede. The protective properties of Act-Belong-Commit indicators against incident depression, anxiety, and cognitive impairment among older Irish adults: Findings from a prospective community-

REFERENCES

- based study. *Experimental Gerontology*, 91:79–87, 2017. ISSN 0531-5565. doi: 10.1016/j.exger.2017.02.074. 11, 66
- [32] A. L. Juola, M. P. Bjorkman, H. Kautiainen, S. Pylkkanen, U. H. Finne-Soveri, H. Soini, K. H. Pitkälä, and J. S. Bell. O1.17: Nursing staff education to reduce potentially harmful medication use among older people in assisted living facilities: Effects of randomized controlled trial on cognition and falls. *European Geriatric Medicine*, 5:S50–S51, 2014. ISSN 1878-7649. doi: 10.1016/S1878-7649(14)70100-7. 12
- [33] Kevin McCarthy, Eamon Laird, Aisling M. O’Halloran, Cathal Walsh, Martin Healy, Annette L. Fitzpatrick, James B. Walsh, Belinda Hernández, Padraic Fallon, Anne M. Molloy, and Rose Anne Kenny. Association between vitamin D deficiency and the risk of prevalent type 2 diabetes and incident prediabetes: A prospective cohort study using data from The Irish Longitudinal Study on Ageing (TILDA). *EClinicalMedicine*, 53:101654, November 2022. ISSN 2589-5370. doi: 10.1016/j.eclinm.2022.101654. 12
- [34] Kevin McCarthy, Aisling M. O’Halloran, Padraic Fallon, Rose Anne Kenny, and Cathal McCrory. Metabolic syndrome accelerates epigenetic ageing in older adults: Findings from The Irish Longitudinal Study on Ageing (TILDA). *Experimental Gerontology*, 183:112314, 2023. ISSN 0531-5565. doi: 10.1016/j.exger.2023.112314. 13
- [35] Zahra Azizi, Rebecca J. Hirst, Alan O’ Dowd, Cathal McCrory, Rose Anne Kenny, Fiona N. Newell, and Annalisa Setti. Evidence for an association between allostatic load and multisensory integration in middle-aged and older adults. *Archives of Gerontology and Geriatrics*, 116:105155, 2024. ISSN 0167-4943. doi: 10.1016/j.archger.2023.105155. 13
- [36] Soraya Matthews, Mark Ward, Anne Nolan, Charles Normand, Rose Anne Kenny, and Peter May. Predicting mortality in The Irish Longitudinal Study on Ageing (TILDA): Development of a four-year index and comparison with international measures. *BMC Geriatr*, 22:510, June 2022. ISSN 1471-2318. doi: 10.1186/s12877-022-03196-z. 14, 16, 62
- [37] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Wave 1, 2009-2011, 2025. URL <https://doi.org/10.7929/ISSDA/AWCUY3>. 19

REFERENCES

- [38] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Wave 2, 2012-2013, 2025. URL <https://doi.org/10.7929/ISSDA/HSBNCU>. 19
- [39] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Wave 3, 2014-2015, 2025. URL <https://doi.org/10.7929/ISSDA/9Z4MFF>. 19
- [40] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Wave 4, 2016, 2025. URL <https://doi.org/10.7929/ISSDA/R4BZYX>. 19
- [41] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Wave 5, 2018-2019, 2025. URL <https://doi.org/10.7929/ISSDA/JCM06P>. 19
- [42] TILDA. The Irish Longitudinal Study on Ageing (TILDA) Harmonized TILDA, 2016, 2025. URL <https://doi.org/10.7929/ISSDA/FHM5I8>. 19
- [43] Hot Desks - The Irish Longitudinal Study on Ageing (TILDA) - Trinity College Dublin. <https://tilda.tcd.ie/data/accessing-data/hotdesk/>, 2026. 35
- [44] Mark Ward, Peter May, Robert Briggs, Triona McNicholas, Charles Normand, Rose Anne Kenny, and Anne Nolan. Linking death registration and survey data: Procedures and cohort profile for The Irish Longitudinal Study on Ageing (TILDA). *HRB open research*, 3:43, 2020. ISSN 2515-4826. doi: 10.12688/hrbopenres.13083.2. 39
- [45] Samuel D. Searle, Arnold Mitnitski, Evelyne A. Gahbauer, Thomas M. Gill, and Kenneth Rockwood. A standard procedure for creating a frailty index. *BMC Geriatrics*, 8(1):24, September 2008. ISSN 1471-2318. doi: 10.1186/1471-2318-8-24. 40
- [46] Dewinda Julianensi Rumala. How You Split Matters: Data Leakage and Subject Characteristics Studies in Longitudinal Brain MRI Analysis. volume 14242, pages 235–245. 2023. doi: 10.1007/978-3-031-45249-9_23. 51