



Date: 15.06.2022

Smart Contract Security Audit

USDT PROTOCOL TOKEN



Harry Kedelman
General Manager



Audit Result

USDT PROTOCOL TOKEN has PASSED the smart contract audit with below listed privileges

(Other unknown security vulnerabilities are not included in the audit responsibility scope)

Audit Result: Passed

Ownership: Not renounced yet

KYC Verification: NA at report edition date

Audit Date: June 15, 2022

Audit Team: CONTRACTCHECKER

Findings

Privileges of Ownership

⚠ Owner can change the fees up to 100%

Owner can exclude accounts from rewards

Auto liquidity is going to an externally owned account

Owner can exclude an account from paying fees

Owner can withdraw any token from the contract

A Blacklist available to owner. Owner can use it to block any contract from trading

Important Notice for Investors

As Contract Checker team we are mainly auditing the contract code to find out how it will be functioning, and risks which are hidden in the code if any.

There are many factors must be taken into consideration before investing to a project, like: ownership status, project team approach, marketing, general market condition, liquidity, token holdings etc.

Investors must always do their own research and manage their risk considering different factors which can affect the success of a project.



Table of Contents

Audit Result	1
Findings	1
Privileges of Ownership	1
SUMMARY	3
Project Summary	3
OVERVIEW	
Auditing Approach and Applied Methodologies	4
Security	4
Sound Architecture	4
Code Correctness and Quality	4
Risk Classification	5
High level vulnerability	5
Medium level vulnerability	5
Low level vulnerability <mark></mark>	5
Vulnerability Checklist	5
Manual Audit:	
Smart Contract SWC Attack Test	
> SWC-103: A floating pragma is set	7
> SWC-108: State variable visibility is not set	7
> SWC-120: Potential use of "block.number" as source of randonmness	9
Automated Audit	
Remix Compiler Warnings	9
Disclaimer	10





SUMMARY

CONTRACTCHECKER received an application for smart contract security audit of USDT PROTOCOL TOKEN on June 10, 2022, from the project team to discover if any vulnerability in the source codes of the USDT PROTOCOL TOKEN as well as any contract dependencies. Detailed test has been performed using Static Analysis and Manual Review techniques.

The auditing process focuses to the following considerations with collaboration of an expert team

- Functionality test of the Smart Contract to determine if proper logic has been followed throughout the whole process.
- Manually detailed examination of the code line by line by experts.
- Live test by multiple clients using Testnet.
- Analysing failure preparations to check how the Smart Contract performs in case of any bugs and vulnerabilities.
- Checking whether all the libraries used in the code are on the latest version.
- Analysing the security of the on-chain data.

Project Summary

Token Name USDT PROTOCOL TOKEN

Web Site https://usdtprotocol.com/

Twitter https://twitter.com/USDTProtocol

Telegram https://t.me/USDTProtocol

Platform Binance Smart Chain

Token Type BEP20

Language Solidity

Platforms & Tools Remix IDE, Truffle, Truffle Team, Ganache, Solhint, VScode, Mythril, Contract Library

Contract Address 0xb49182102f9e6F5b52b298ba2176beE0A26F7Be5

Contract Link https://bscscan.com/token/0xb49182102f9e6F5b52b298ba2176beE0A26F7Be5





OVERVIEW

This Audit Report mainly focuses on overall security of USDT PROTOCOL TOKEN smart contract. Contract Checker team scanned the contract and assessed overall system architecture and the smart contract codebase against vulnerabilities, exploitations, hacks, and back-doors to ensure its reliability and correctness.

Auditing Approach and Applied Methodologies

Contract Checker team has performed rigorous test procedures of the project

- Code design patterns analysis in which smart contract architecture is reviewed to ensure it is structured according to industry standards and safe use of third-party smart contracts and libraries.
- Line-by-line inspection of the Smart Contract to find any potential vulnerability like race conditions, transaction-ordering dependence, timestamp dependence, and denial of service attacks.
- Unit testing Phase, we coded/conducted custom unit tests written for each function in the contract to verify that each function works as expected.
- Automated Test performed with our in-house developed tools to identify vulnerabilities and security flaws of the Smart Contract.

The focus of the audit was to verify that the Smart Contract System is secure, resilient, and working according to the specifications. The audit activities can be grouped in the following three categories:

Security

Identifying security related issues within each contract and the system of contract.

Sound Architecture

Evaluation of the architecture of this system through the lens of established smart contract best practices and general software best practices.

Code Correctness and Quality

A full review of the contract source code. The primary areas of focus include:

- Accuracy
- Readability
- Sections of code with high complexity
- Quantity and quality of test coverage



Risk Classification

Vulnerabilities are classified in 3 main levels as below based on possible effect to the contract.

High level vulnerability

Vulnerabilities on this level must be fixed immediately as they might lead to fund and data loss and open to manipulation. Any High-level finding will be highlighted with **RED** text

Medium level vulnerability

Vulnerabilities on this level also important to fix as they have potential risk of future exploit and manipulation. Any Medium-level finding will be highlighted with **ORANGE** text

Low level vulnerability

Vulnerabilities on this level are minor and may not affect the smart contract execution. Any Low-level finding will be highlighted with **BLUE** text

Vulnerability Checklist

Νō	Description.	Result
1	Compiler warnings.	Passed
2	Race conditions and Re-entrancy. Cross-function race conditions.	Passed
3	Possible delays in data delivery.	Passed
4	Oracle calls.	Passed
5	Front running.	Passed
6	Timestamp dependence.	Passed
7	Integer Overflow and Underflow.	Passed
8	DoS with Revert.	Passed
9	DoS with block gas limit.	Passed
10	Methods execution permissions.	Passed
11	Economy model.	Passed
12	The impact of the exchange rate on the logic.	Passed
13	Private user data leaks.	Passed
14	Malicious Event log.	Passed
15	Scoping and Declarations.	Passed
16	Uninitialized storage pointers.	Passed
17	Arithmetic accuracy.	Passed
18	Design Logic.	Passed
19	Cross-function race conditions.	Passed
20	Safe Zeppelin module.	Passed
21	Fallback function security.	Passed



Manual Audit:

For this section the code was tested/read line by line by our developers. Additionally, Remix IDE's JavaScript VM and Kovan networks used to test the contract functionality.

Smart Contract SWC Attack Test

SWC ID	Description	Test Result
SWC-100	Function Visibility	Passed
SWC-101	Integer Overflow and Underflow	Passed
SWC-102	Outdated Compiler Version	Passed
SWC-103	Floating Pragma	LOW
SWC-104	Unchecked Call Return Value	Passed
SWC-105	Unprotected Ether Withdrawal	Passed
SWC-106	Unprotected SELFDESTRUCT Instruction	Passed
SWC-107	Re-entrancy	Passed
SWC-108	State Variable Default Visibility	LOW
SWC-109	Uninitialized Storage Pointer	Passed
SWC-110	Assert Violation	Passed
SWC-111	Use of Depr <mark>eca</mark> ted Solidity Functions	Passed
SWC-112	Delegate Call to Untrusted Callee	Passed
SWC-113	DoS with Failed Call	Passed
SWC-114	Transaction Order Dependence	Passed
SWC-115	Authorization through tx.origin	Passed
SWC-116	Block values as a proxy for time	Passed
SWC-117	Signature Malleability	Passed
SWC-118	Incorrect Constructor Name	Passed
SWC-119	Shadowing State Variables	Passed
SWC-120	Weak Sources of Randomness from Chain Attributes	LOW
SWC-121	Missing Protection against Signature Replay Attacks	Passed
SWC-122	Lack of Proper Signature Verification	Passed
SWC-123	Requirement Violation	Passed
SWC-124	Write to Arbitrary Storage Location	Passed
SWC-125	Incorrect Inheritance Order	Passed
SWC-126	Insufficient Gas Griefing	Passed
SWC-127	Arbitrary Jump with Function Type Variable	Passed
SWC-128	DoS With Block Gas Limit	Passed
SWC-129	Typographical Error	Passed
SWC-130	Right-To-Left-Override control character (U+202E)	Passed
SWC-131	Presence of unused variables	Passed
SWC-132	Unexpected Ether balance	Passed
SWC-133	Hash Collisions with Multiple Variable Length Arguments	Passed
SWC-134	Message call with hardcoded gas amount	Passed
SWC-135	Code With No Effects (Irrelevant/Dead Code)	Passed
SWC-136	Unencrypted Private Data On-Chain	Passed



> SWC-103: A floating pragma is set

The current pragma Solidity directive is ""\0.7.4"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This isespecially important if you rely on bytecode-level verification of the code.

```
5 // SPDX-License-Identifier: MIT
6
7 pragma_solidity_^0.7.4.
```

SWC-108: State variable visibility is not set

It is best practice to set the visibility of state variables explicitly. The default visibility for "_token" is internal. Other possible visibility settings are public and private.

```
using SafeMath for uint256;

address _token;
```

The default visibility for "USDT" is internal. Other possible visibility settings are public and private.

The default visibility for "router" is internal. Other possible visibility settings are public and private.

```
350 // IERC20 USDT = IERC20(0x7ef95a0FEE0Dd31b22626fA2e10Ee6A223F8a684);
351
352 IPancakeSwapRouter router;
```

The default visibility for "shareholders" is internal. Other possible visibility settings are public and private.

```
354 address[] shareholders;
355 mapping (address => uint256) shareholderIndexes;
356 mapping (address => uint256) shareholderClaims;
```

The default visibility for "shareholderIndexes" is internal. Other possible visibility settings are public and private.

```
address[] shareholders;
mapping (address => uint256) shareholderIndexes;
mapping (address => uint256) shareholderClaims;
```

The default visibility for "shareholderClaims" is internal. Other possible visibility settings are public and private.

```
address[] shareholders;

mapping (address => uint256) shareholderIndexes;

mapping (address => uint256) shareholderClaims;
```

The default visibility for "initialized" is internal. Other possible visibility settings are public and private.

```
570 | bool initialized;
371 | modifier initialization() {
372 | require(!initialized);
```



The default visibility for "inSwap" is internal. Other possible visibility settings are public and private.

```
583 bool public swapEnabled = true;
584 bool inSwap = false;
585 bool _autoAddLiquidity = true;
```

The default visibility for "_autoAddLiquidity" is internal. Other possible visibility settings are public and private.

```
bool public swapEnabled = true;
bool inSwap = false;
bool _autoAddLiquidity = true;
```

The default visibility for "DEAD" is internal. Other possible visibility settings are public and private.

The default visibility for "ZERO" is internal. Other possible visibility settings are public and private.

The default visibility for "_isFee Exempt" is internal. Other possible visibility settings are public and private.

```
597 mapping(address => bool) _isFeeExempt;
598 mapping(address => bool) public blacklist;
599 mapping(address => bool) public isDividendExempt;
```

The default visibility for "_buyRewardUsdtFee" is internal. Other possible visibility settings are public and private.

```
603  uint256 _buyRewardUsdtFee = 150;
604  uint256 _buyNiquidityFee = 20;
605  uint256 _buymarketingFee = 20;
```

The default visibility for "_buyliquidityFee" is internal. Other possible visibility settings are public and private.

```
uint256 _buyRewardUsdtFee = 150;

uint256 _buyliquidityFee = 20;

uint256 _buymarketingFee = 20;
```

The default visibility for "_buymarketingFee" is internal. Other possible visibility settings are public and private.

```
683  uint256 _buyRewardUsdtFee = 150;
684  uint256 _buyliquidityFee = 20;
685  uint256 _buymarketingFee = 20;
```

The default visibility for "_buybuybackFee" is internal. Other possible visibility settings are public and private.

```
604 uint256 _buyliquidityFee = 20;
605 uint256 _buymarketingFee = 20;
606 uint256 _buymarketingFee = 10;
```



The default visibility for "_sellRewardUsdtFee" is internal. Other possible visibility settings are public and private.

```
uint256 _sellRewardUsdtfee = 150;

uint256 _sellliquidityFee = 20;

uint256 _sellmarketingFee = 20;
```

The default visibility for "_sellliquidityFee" is internal. Other possible visibility settings are public and private.

```
uint256 _sellRewardUsdtFee = 150;
uint256 _sellliquidityFee = 20;
uint256 _sellmarketingFee = 20;
```

The default visibility for "_sellmarketingFee" is internal. Other possible visibility settings are public and private.

```
689 uint256 _sellliquidityfee = 20;
610 uint256 _sellmarketingFee = 20;
611 uint256 _sellbuybackFee = 10;
```

The default visibility for "_sellbuybackFee" is internal. Other possible visibility settings are public and private.

```
600  uint256 _sellliquidityFee = 20;
610  uint256 _sellmarketingFee = 20;
611  uint256 _sellbuybackFee = 10;
```

The default visibility for "distributor" is internal. Other possible visibility settings are public and private.

```
637 DividendDistributor distributor;
638 address public USDTPDividendReceiver;
639
```

The default visibility for "distributorGas" is internal. Other possible visibility settings are public and private.

```
address public USOTPDividendReceiver;

639

640 uint256 distributorGas = 500000;
```

SWC-120: Potential use of "block.number" as source of randonmness

The environment variable "block.number" looks like it might be used as a source of randomness. Note that the values of variables like coinbase, gaslimit, block number and timestampare predictable and can be manipulated by a malicious miner. Also keep in mind that attackers know hashes of earlier blocks. Don't use any of those environment variables as sources of randomness and be aware that use of these variables introduces a certain level of trust into miners.

```
972 | address holder = holders();
973 | require(holder != address(0), "no zero");
974 | require(block.timestamp != block number);
```

Automated Audit

Remix Compiler Warnings

It throws warnings by Solidity's compiler. No issues found.



Disclaimer

This is a limited report on our findings based on our analysis, in accordance with good industry practice as at the date of this report, in relation to cybersecurity vulnerabilities and issues in the framework and algorithms based on smart contracts, the details of which are set out in this report. To get a full view of our analysis, it is crucial for you to read the full report. While we have done our best in conducting our analysis and producing this report, it is important to note that you should not rely on this report and cannot claim against us based on what it says or doesn't say, or how we produced it, and it is important for you to conduct your own independent investigations before making any decisions. We go into more detail on this in the below disclaimer below – please make sure to read it in full.

DISCLAIMER: By reading this report or any part of it, you agree to the terms of this disclaimer. If you do not agree to the terms, then please immediately cease reading this report, and delete and destroy all copies of this report downloaded and/or printed by you. This report is provided for information purposes only and on a non-reliance basis and does not constitute investment advice. No one shall have any right to rely on the report or its contents, and ContractChecker and its affiliates (including holding companies, shareholders, subsidiaries, employees, directors, officers and other representatives) (ContractChecker) owe no duty of care towards you or any other person, nor does ContractChecker make any warranty or representation to any person on the accuracy or completeness of the report. The report is provided "as is", without any conditions, warranties or other terms of any kind except as set out in this disclaimer, and ContractChecker hereby excludes all representations, warranties, conditions and other terms (including, without limitation, the warranties implied by law of satisfactory quality, fitness for purpose and the use of reasonable care and skill) which, but for this clause, might have effect in relation to the report. Except and only to the extent that it is prohibited by law, ContractChecker hereby excludes all liability and responsibility, and neither you nor any other person shall have any claim against ContractChecker, for any amount or kind of loss or damage that may result to you or any other person (including without limitation, any direct, indirect, special, punitive, consequential or pure economic loss or damages, or any loss of income, profits, goodwill, data, contracts, use of money, or business interruption, and whether in delict, tort (including without limitation negligence), contract, breach of statutory duty, misrepresentation (whether innocent or negligent) or otherwise under any claim of any nature whatsoever in any jurisdiction) in any way arising from or connected with this report and the use, inability to use or the results of use of this report, and any reliance on this report.

The analysis of the security is purely based on the smart contracts alone. No applications or operations were reviewed for security. No product code has been reviewed. If you have any doubt about the Genuity for this document, please check QR code:

