



### LCM INTERFACE

PIN	1	2	3	4	5	6	7	8	9	10
SIGNAL	/CSA/CSB	VSS	VDD	V0	D/I	R/W	E	DB0	DB1	
PIN	11	12	13	14	15	16	17	18	19	20
SIGNAL	DB2	DB3	DB4	DB5	DB6	DB7	/RST	VEE	A	K

### PERFORMANCE FEATURES

LC FLUID	<input type="checkbox"/> STN	<input type="checkbox"/> HTN	<input type="checkbox"/> TN
POLARIZER	<input type="checkbox"/> TRANSPARENT	<input type="checkbox"/> REFLECTIVE	<input type="checkbox"/> TRANSMISSIVE
COLOR	<input type="checkbox"/> YELLOW	<input type="checkbox"/> BLUE	<input type="checkbox"/> GRAY
BACKLIGHT	<input type="checkbox"/> LED	<input type="checkbox"/> SIDE	<input type="checkbox"/> EL
VIEWING ANGLE	<input type="checkbox"/> 6:00	<input type="checkbox"/> 12:00	
TEMPERATURE RANGE	<input type="checkbox"/> STANDARD	<input type="checkbox"/> WIDE	

### TOUCH PANEL

PIN #	Assignment
1	Y-
2	X-
3	Y+
4	X+

## XIAMEN OCULAR OPTICS CO.,LTD

REVISION RECORD					Drawn:	Model Name:
Ver	Date	Modify	Contents	Name	Confirm	
1						GDM12864B-T
2						
3						
4						
5						
					Approved:	UNIT: mm
						Page: 1/1