

# 3GPP TS 38.101-1 V15.29.0 (2025-09)

*Technical Specification*

## **3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone (Release 15)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented.

This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification.

Specifications and Reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

## **3GPP**

Postal address

3GPP support office address  
650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet  
<http://www.3gpp.org>

### ***Copyright Notification***

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© 2025, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).  
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members  
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners  
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners  
GSM® and the GSM logo are registered and owned by the GSM Association

# Contents

|                                                                                  |    |
|----------------------------------------------------------------------------------|----|
| Foreword                                                                         | 11 |
| 1 Scope                                                                          | 12 |
| 2 References                                                                     | 12 |
| 3 Definitions, symbols and abbreviations                                         | 12 |
| 3.1 Definitions                                                                  | 12 |
| 3.2 Symbols                                                                      | 13 |
| 3.3 Abbreviations                                                                | 15 |
| 4 General                                                                        | 16 |
| 4.1 Relationship between minimum requirements and test requirements              | 16 |
| 4.2 Applicability of minimum requirements                                        | 16 |
| 4.3 Specification suffix information                                             | 16 |
| 5 Operating bands and channel arrangement                                        | 17 |
| 5.1 General                                                                      | 17 |
| 5.2 Operating bands                                                              | 17 |
| 5.2A Operating bands for CA                                                      | 18 |
| 5.2A.1 Intra-band CA                                                             | 18 |
| 5.2A.2 Inter-band CA                                                             | 19 |
| 5.2A.2.1 Inter-band CA (two bands)                                               | 19 |
| 5.2B Void                                                                        | 19 |
| 5.2C Operating band combination for SUL                                          | 19 |
| 5.3 UE channel bandwidth                                                         | 20 |
| 5.3.1 General                                                                    | 20 |
| 5.3.2 Maximum transmission bandwidth configuration                               | 21 |
| 5.3.3 Minimum guardband and transmission bandwidth configuration                 | 21 |
| 5.3.4 RB alignment                                                               | 22 |
| 5.3.5 UE channel bandwidth per operating band                                    | 22 |
| 5.3.6 Asymmetric channel bandwidths                                              | 24 |
| 5.3A UE channel bandwidth for CA                                                 | 25 |
| 5.3A.1 General                                                                   | 25 |
| 5.3A.2 Maximum transmission bandwidth configuration for CA                       | 25 |
| 5.3A.3 Minimum guardband and transmission bandwidth configuration for CA         | 25 |
| 5.3A.4 Void                                                                      | 27 |
| 5.3A.5 UE channel bandwidth per operating band for CA                            | 27 |
| 5.4 Channel arrangement                                                          | 28 |
| 5.4.1 Channel spacing                                                            | 28 |
| 5.4.1.1 Channel spacing for adjacent NR carriers                                 | 28 |
| 5.4.2 Channel raster                                                             | 28 |
| 5.4.2.1 NR-ARFCN and channel raster                                              | 28 |
| 5.4.2.2 Channel raster to resource element mapping                               | 29 |
| 5.4.2.3 Channel raster entries for each operating band                           | 29 |
| 5.4.3 Synchronization raster                                                     | 30 |
| 5.4.3.1 Synchronization raster and numbering                                     | 30 |
| 5.4.3.2 Synchronization raster to synchronization block resource element mapping | 31 |
| 5.4.3.3 Synchronization raster entries for each operating band                   | 31 |
| 5.4.4 TX–RX frequency separation                                                 | 32 |
| 5.4A Channel arrangement for CA                                                  | 33 |
| 5.4A.1 Channel spacing for CA                                                    | 33 |
| 5.4A.2 Channel raster for CA                                                     | 33 |
| 5.4A.3 Synchronization raster for CA                                             | 34 |

|            |                                                                |    |
|------------|----------------------------------------------------------------|----|
| 5.4A.4     | Tx-Rx frequency separation for CA                              | 34 |
| 5.5        | Void                                                           | 34 |
| 5.5A       | Configurations for CA                                          | 34 |
| 5.5A.1     | Configurations for intra-band contiguous CA                    | 34 |
| 5.5A.2     | Void                                                           | 35 |
| 5.5A.3     | Configurations for inter-band CA                               | 35 |
| 5.5A.3.1   | Configurations for inter-band CA (two bands)                   | 35 |
| 5.5B       | Void                                                           | 38 |
| 5.5C       | Configurations for SUL                                         | 38 |
| 6          | Transmitter characteristics                                    | 40 |
| 6.1        | General                                                        | 40 |
| 6.2        | Transmitter power                                              | 40 |
| 6.2.1      | UE maximum output power                                        | 40 |
| 6.2.2      | UE maximum output power reduction                              | 41 |
| 6.2.3      | UE additional maximum output power reduction                   | 42 |
| 6.2.3.1    | General                                                        | 42 |
| 6.2.3.2    | A-MPR for NS_04                                                | 46 |
| 6.2.3.3    | A-MPR for NS_10                                                | 47 |
| 6.2.3.4    | A-MPR for NS_05 and NS_05U                                     | 48 |
| 6.2.3.5    | A-MPR for NS_40                                                | 50 |
| 6.2.3.6    | A-MPR for NS_43 and NS_43U                                     | 50 |
| 6.2.3.7    | A-MPR for NS_03 and NS_03U                                     | 51 |
| 6.2.3.8    | A-MPR for NS_37                                                | 51 |
| 6.2.3.9    | A-MPR for NS_38                                                | 52 |
| 6.2.3.10   | A-MPR for NS_39                                                | 52 |
| 6.2.3.11   | A-MPR for NS_41                                                | 53 |
| 6.2.3.12   | A-MPR for NS_42                                                | 53 |
| 6.2.3.13   | A-MPR for NS_18                                                | 54 |
| 6.2.4      | Configured transmitted power                                   | 55 |
| 6.2A       | Transmitter power for CA                                       | 57 |
| 6.2A.1     | UE maximum output power for CA                                 | 57 |
| 6.2A.1.1   | Void                                                           | 57 |
| 6.2A.1.2   | Void                                                           | 57 |
| 6.2A.1.3   | UE maximum output power for Inter-band CA                      | 57 |
| 6.2A.2     | UE maximum output power reduction for CA                       | 57 |
| 6.2A.2.1   | Void                                                           | 57 |
| 6.2A.2.2   | Void                                                           | 57 |
| 6.2A.2.3   | UE maximum output power reduction for Inter-band CA            | 57 |
| 6.2A.3     | UE additional maximum output power reduction for CA            | 57 |
| 6.2A.3.1.1 | Void                                                           | 57 |
| 6.2A.3.1.2 | Void                                                           | 57 |
| 6.2A.3.1.3 | UE additional maximum output power reduction for Inter-band CA | 57 |
| 6.2A.4     | Configured output power for CA                                 | 58 |
| 6.2A.4.1   | Configured transmitted power level                             | 58 |
| 6.2A.4.1.1 | Void                                                           | 58 |
| 6.2A.4.1.2 | Void                                                           | 58 |
| 6.2A.4.1.3 | Configured transmitted power for Inter-band CA                 | 58 |
| 6.2A.4.2   | $\Delta T_{IB,c}$ for CA                                       | 60 |
| 6.2A.4.2.1 | Void                                                           | 61 |
| 6.2A.4.2.2 | Void                                                           | 61 |
| 6.2A.4.2.3 | $\Delta T_{IB,c}$ for Inter-band CA (two bands)                | 61 |
| 6.2B       | Void                                                           | 61 |
| 6.2C       | Transmitter power for SUL                                      | 61 |

|          |                                                                                                                      |    |
|----------|----------------------------------------------------------------------------------------------------------------------|----|
| 6.2C.1   | Configured transmitted power for SUL                                                                                 | 61 |
| 6.2C.2   | $\Delta T_{IB,c}$                                                                                                    | 61 |
| 6.2D     | Transmitter power for UL MIMO                                                                                        | 62 |
| 6.2D.1   | UE maximum output power for UL MIMO                                                                                  | 62 |
| 6.2D.2   | UE maximum output power reduction for UL MIMO                                                                        | 62 |
| 6.2D.3   | UE additional maximum output power reduction for UL MIMO                                                             | 63 |
| 6.2D.4   | Configured transmitted power for UL MIMO                                                                             | 63 |
| 6.3      | Output power dynamics                                                                                                | 64 |
| 6.3.1    | Minimum output power                                                                                                 | 64 |
| 6.3.2    | Transmit OFF power                                                                                                   | 64 |
| 6.3.3    | Transmit ON/OFF time mask                                                                                            | 64 |
| 6.3.3.1  | General                                                                                                              | 64 |
| 6.3.3.2  | General ON/OFF time mask                                                                                             | 65 |
| 6.3.3.3  | Transmit power time mask for slot and short or long subslot boundaries                                               | 65 |
| 6.3.3.4  | PRACH time mask                                                                                                      | 65 |
| 6.3.3.5  | Void                                                                                                                 | 66 |
| 6.3.3.6  | SRS time mask                                                                                                        | 66 |
| 6.3.3.7  | PUSCH-PUCCH and PUSCH-SRS time masks                                                                                 | 68 |
| 6.3.3.8  | Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries | 69 |
| 6.3.3.9  | Transmit power time mask for consecutive short subslot transmissions boundaries                                      | 69 |
| 6.3.4    | Power control                                                                                                        | 70 |
| 6.3.4.1  | General                                                                                                              | 70 |
| 6.3.4.2  | Absolute power tolerance                                                                                             | 70 |
| 6.3.4.3  | Relative power tolerance                                                                                             | 70 |
| 6.3.4.4  | Aggregate power tolerance                                                                                            | 71 |
| 6.3A     | Output power dynamics for CA                                                                                         | 71 |
| 6.3A.1   | Minimum output power for CA                                                                                          | 71 |
| 6.3A.1.1 | Void                                                                                                                 | 71 |
| 6.3A.1.2 | Void                                                                                                                 | 71 |
| 6.3A.1.3 | Minimum output power for inter-band CA                                                                               | 71 |
| 6.3A.2   | Transmit OFF power for CA                                                                                            | 72 |
| 6.3A.2.1 | Void                                                                                                                 | 72 |
| 6.3A.2.2 | Void                                                                                                                 | 72 |
| 6.3A.2.3 | Transmit OFF power for inter-band CA                                                                                 | 72 |
| 6.3A.3   | Transmit ON/OFF time mask for CA                                                                                     | 72 |
| 6.3A.3.1 | Void                                                                                                                 | 72 |
| 6.3A.3.2 | Void                                                                                                                 | 72 |
| 6.3A.3.3 | Transmit ON/OFF time mask for inter-band CA                                                                          | 72 |
| 6.3A.4   | Power control for CA                                                                                                 | 72 |
| 6.3A.4.1 | Void                                                                                                                 | 72 |
| 6.3A.4.2 | Void                                                                                                                 | 72 |
| 6.3A.4.3 | Power control for inter-band CA                                                                                      | 72 |
| 6.3D     | Output power dynamics for UL MIMO                                                                                    | 72 |
| 6.3D.1   | Minimum output power for UL MIMO                                                                                     | 72 |
| 6.3D.2   | Transmit OFF power for UL MIMO                                                                                       | 72 |
| 6.3D.3   | Transmit ON/OFF time mask for UL MIMO                                                                                | 73 |
| 6.3D.4   | Power control for UL MIMO                                                                                            | 73 |
| 6.4      | Transmit signal quality                                                                                              | 73 |
| 6.4.1    | Frequency error                                                                                                      | 73 |
| 6.4.2    | Transmit modulation quality                                                                                          | 73 |
| 6.4.2.0  | General                                                                                                              | 73 |
| 6.4.2.1  | Error Vector Magnitude                                                                                               | 73 |

|           |                                                                 |    |  |
|-----------|-----------------------------------------------------------------|----|--|
| 6.4.2.2   | Carrier leakage                                                 | 74 |  |
| 6.4.2.3   | In-band emissions                                               | 74 |  |
| 6.4.2.4   | EVM equalizer spectrum flatness                                 | 75 |  |
| 6.4.2.4.1 | Requirements for Pi/2 BPSK modulation                           | 76 |  |
| 6.4A      | Transmit signal quality for CA                                  | 77 |  |
| 6.4A.1    | Frequency error for CA                                          | 77 |  |
| 6.4A.1.1  | Void                                                            | 77 |  |
| 6.4A.1.2  | Void                                                            | 77 |  |
| 6.4A.1.3  | Frequency error for inter-band CA                               | 77 |  |
| 6.4A.2    | Transmit modulation quality for CA                              | 77 |  |
| 6.4A.2.1  | Void                                                            | 77 |  |
| 6.4A.2.2  | Void                                                            | 77 |  |
| 6.4A.2.3  | Transmit modulation quality for inter-band CA                   | 77 |  |
| 6.4D      | Transmit signal quality for UL MIMO                             | 78 |  |
| 6.4D.0    | General                                                         | 78 |  |
| 6.4D.1    | Frequency error for UL MIMO                                     | 78 |  |
| 6.4D.2    | Transmit modulation quality for UL MIMO                         | 78 |  |
| 6.4D.2.0  | General                                                         | 78 |  |
| 6.4D.2.1  | Error Vector Magnitude                                          | 78 |  |
| 6.4D.2.2  | Carrier leakage                                                 | 78 |  |
| 6.4D.2.3  | In-band emissions                                               | 79 |  |
| 6.4D.2.4  | EVM equalizer spectrum flatness for UL MIMO                     | 79 |  |
| 6.4D.3    | Time alignment error for UL MIMO                                | 79 |  |
| 6.4D.4    | Requirements for coherent UL MIMO                               | 79 |  |
| 6.5       | Output RF spectrum emissions                                    | 79 |  |
| 6.5.1     | Occupied bandwidth                                              | 79 |  |
| 6.5.2     | Out of band emission                                            | 80 |  |
| 6.5.2.1   | General                                                         | 80 |  |
| 6.5.2.2   | Spectrum emission mask                                          | 80 |  |
| 6.5.2.3   | Additional spectrum emission mask                               | 81 |  |
| 6.5.2.3.1 | Requirements for network signalling value "NS_35"               | 81 |  |
| 6.5.2.3.2 | Requirements for network signalling value "NS_04"               | 82 |  |
| 6.5.2.3.3 | Requirements for network signalling values "NS_03" and "NS_03U" | 82 |  |
| 6.5.2.3.4 | Requirements for network signalling value "NS_06"               | 83 |  |
| 6.5.2.3.5 | Void                                                            | 83 |  |
| 6.5.2.3.6 | Void                                                            | 83 |  |
| 6.5.2.3.7 | Void                                                            | 83 |  |
| 6.5.2.4   | Adjacent channel leakage ratio                                  | 83 |  |
| 6.5.2.4.1 | NR ACLR                                                         | 84 |  |
| 6.5.2.4.2 | UTRA ACLR                                                       | 84 |  |
| 6.5.3     | Spurious emissions                                              | 85 |  |
| 6.5.3.0   | General                                                         | 85 |  |
| 6.5.3.1   | General spurious emissions                                      | 85 |  |
| 6.5.3.2   | Spurious emissions for UE co-existence                          | 85 |  |
| 6.5.3.3   | Additional spurious emissions                                   | 90 |  |
| 6.5.3.3.1 | Requirement for network signalling value "NS_04"                | 90 |  |
| 6.5.3.3.2 | Requirement for network signalling value "NS_17"                | 91 |  |
| 6.5.3.3.3 | Requirement for network singalling value "NS_18"                | 91 |  |
| 6.5.3.3.4 | Requirement for network signalling values "NS_05" and "NS_05U"  | 91 |  |
| 6.5.3.3.5 | Requirement for network signalling values "NS_43" and "NS_43U"  | 91 |  |
| 6.5.3.3.6 | Requirement for network signalling value "NS_37"                | 92 |  |
| 6.5.3.3.7 | Requirement for network signalling value "NS_38"                | 92 |  |
| 6.5.3.3.8 | Requirement for network signalling value "NS_39"                | 92 |  |

|              |                                                          |    |
|--------------|----------------------------------------------------------|----|
| 6.5.3.3.9    | Requirement for network signalling value "NS_40"         | 92 |
| 6.5.3.3.10   | Requirement for network signalling value "NS_41"         | 93 |
| 6.5.3.3.11   | Requirement for network signalling value "NS_42"         | 93 |
| 6.5.3.3.12   | Void                                                     | 93 |
| 6.5.3.3.13   | Void                                                     | 93 |
| 6.5.3.3.14   | Void                                                     | 93 |
| 6.5.3.3.15   | Void                                                     | 93 |
| 6.5.3.3.16   | Requirement for network signalling value "NS_50"         | 93 |
| 6.5.4        | Transmit intermodulation                                 | 94 |
| 6.5A         | Output RF spectrum emissions for CA                      | 94 |
| 6.5A.0       | General                                                  | 94 |
| 6.5A.1       | Occupied bandwidth for CA                                | 94 |
| 6.5A.1.1     | Void                                                     | 94 |
| 6.5A.1.2     | Void                                                     | 94 |
| 6.5A.1.3     | Occupied bandwidth for Inter-band CA                     | 94 |
| 6.5A.2       | Out of band emission for CA                              | 95 |
| 6.5A.2.1     | General                                                  | 95 |
| 6.5A.2.2     | Spectrum emission mask                                   | 95 |
| 6.5A.2.2.1   | Void                                                     | 95 |
| 6.5A.2.2.2   | Void                                                     | 95 |
| 6.5A.2.2.3   | Spectrum emission mask for Inter-band CA                 | 95 |
| 6.5A.2.3     | Additional spectrum emission mask                        | 95 |
| 6.5A.2.3.1   | Void                                                     | 95 |
| 6.5A.2.3.2   | Void                                                     | 95 |
| 6.5A.2.3.3   | Additional spectrum emission mask for Inter-band CA      | 95 |
| 6.5A.2.4     | Adjacent channel leakage ratio                           | 95 |
| 6.5A.2.4.1   | NR ACLR                                                  | 95 |
| 6.5A.2.4.1.1 | Void                                                     | 95 |
| 6.5A.2.4.1.2 | Void                                                     | 95 |
| 6.5A.2.4.1.3 | NR ACLR for Inter-band CA                                | 95 |
| 6.5A.2.4.2   | UTRA ACLR                                                | 95 |
| 6.5A.2.4.2.1 | Void                                                     | 95 |
| 6.5A.2.4.2.2 | Void                                                     | 95 |
| 6.5A.2.4.2.3 | UTRA ACLR for Inter-band CA                              | 95 |
| 6.5A.3       | Spurious emission for CA                                 | 95 |
| 6.5A.3.1     | General spurious emissions                               | 95 |
| 6.5A.3.2     | Spurious emissions for UE co-existence                   | 96 |
| 6.5A.3.2.1   | Void                                                     | 96 |
| 6.5A.3.2.2   | Void                                                     | 96 |
| 6.5A.3.2.3   | Spurious emissions for UE co-existence for Inter-band CA | 96 |
| 6.5A.4       | Transmit intermodulation for CA                          | 96 |
| 6.5A.4.1     | Void                                                     | 96 |
| 6.5A.4.2     | Void                                                     | 96 |
| 6.5A.4.3     | Transmit intermodulation for Inter-band CA               | 96 |
| 6.5D         | Output RF spectrum emissions for UL MIMO                 | 97 |
| 6.5D.1       | Occupied bandwidth for UL MIMO                           | 97 |
| 6.5D.2       | Out of band emission for UL MIMO                         | 97 |
| 6.5D.3       | Spurious emission for UL MIMO                            | 97 |
| 6.5D.4       | Transmit intermodulation for UL MIMO                     | 97 |
| 7            | Receiver characteristics                                 | 98 |
| 7.1          | General                                                  | 98 |
| 7.2          | Diversity characteristics                                | 98 |
| 7.3          | Reference sensitivity                                    | 98 |

|            |                                                                                    |     |  |
|------------|------------------------------------------------------------------------------------|-----|--|
| 7.3.1      | General                                                                            | 98  |  |
| 7.3.2      | Reference sensitivity power level                                                  | 98  |  |
| 7.3.3      | $\Delta R_{IB,c}$                                                                  | 104 |  |
| 7.3A       | Reference sensitivity for CA                                                       | 104 |  |
| 7.3A.1     | General                                                                            | 104 |  |
| 7.3A.2     | Reference sensitivity power level for CA                                           | 104 |  |
| 7.3A.2.1   | Reference sensitivity power level for Intra-band contiguous CA                     | 104 |  |
| 7.3A.2.2   | Void                                                                               | 104 |  |
| 7.3A.2.3   | Reference sensitivity power level for Inter-band CA                                | 104 |  |
| 7.3A.2.4   | Void                                                                               | 105 |  |
| 7.3A.3     | $\Delta R_{IB,c}$ for CA                                                           | 106 |  |
| 7.3A.3.1   | General                                                                            | 106 |  |
| 7.3A.3.2   | $\Delta R_{IB,c}$ for Inter-band CA                                                | 106 |  |
| 7.3A.3.2.1 | $\Delta R_{IB,c}$ for two bands                                                    | 106 |  |
| 7.3A.3.2.2 | Void                                                                               | 106 |  |
| 7.3A.4     | Reference sensitivity exceptions due to UL harmonic interference for CA            | 106 |  |
| 7.3A.5     | Reference sensitivity exceptions due to intermodulation interference due to 2UL CA | 109 |  |
| 7.3A.6     | Reference sensitivity exceptions due to cross band isolation for CA                | 109 |  |
| 7.3B       | Void                                                                               | 110 |  |
| 7.3C       | Reference sensitivity for SUL                                                      | 110 |  |
| 7.3C.1     | General                                                                            | 110 |  |
| 7.3C.2     | Reference sensitivity power level for SUL                                          | 110 |  |
| 7.3C.3     | $\Delta R_{IB,c}$ for SUL                                                          | 113 |  |
| 7.3C.3.1   | General                                                                            | 113 |  |
| 7.3C.3.2   | SUL band combination                                                               | 113 |  |
| 7.3C.3.2.1 | $\Delta R_{IB,c}$ for two bands                                                    | 113 |  |
| 7.3D       | Reference sensitivity for UL MIMO                                                  | 113 |  |
| 7.4        | Maximum input level                                                                | 113 |  |
| 7.4A       | Maximum input level for CA                                                         | 114 |  |
| 7.4A.1     | Maximum input level for Intra-band contiguous CA                                   | 114 |  |
| 7.4A.2     | Void                                                                               | 114 |  |
| 7.4A.3     | Maximum input level for Inter-band CA                                              | 114 |  |
| 7.4D       | Maximum input level for UL MIMO                                                    | 114 |  |
| 7.5        | Adjacent channel selectivity                                                       | 115 |  |
| 7.5A       | Adjacent channel selectivity for CA                                                | 119 |  |
| 7.5A.1     | Adjacent channel selectivity for Intra-band contiguous CA                          | 119 |  |
| 7.5A.2     | Void                                                                               | 121 |  |
| 7.5A.3     | Adjacent channel selectivity Inter-band CA                                         | 121 |  |
| 7.5D       | Adjacent channel selectivity for UL MIMO                                           | 121 |  |
| 7.6        | Blocking characteristics                                                           | 121 |  |
| 7.6.1      | General                                                                            | 121 |  |
| 7.6.2      | In-band blocking                                                                   | 121 |  |
| 7.6.3      | Out-of-band blocking                                                               | 123 |  |
| 7.6.4      | Narrow band blocking                                                               | 126 |  |
| 7.6A       | Blocking characteristics for CA                                                    | 127 |  |
| 7.6A.1     | General                                                                            | 127 |  |
| 7.6A.2     | In-band blocking for CA                                                            | 127 |  |
| 7.6A.2.1   | In-band blocking for Intra-band contiguous CA                                      | 127 |  |
| 7.6A.2.2   | Void                                                                               | 128 |  |
| 7.6A.2.3   | In-band blocking for Inter-band CA                                                 | 128 |  |
| 7.6A.3     | Out-of-band blocking for CA                                                        | 128 |  |
| 7.6A.3.1   | Out-of-band blocking for Intra-band contiguous CA                                  | 128 |  |
| 7.6A.3.2   | Void                                                                               | 129 |  |



|          |                                                        |     |
|----------|--------------------------------------------------------|-----|
| 7.6A.3.3 | Out-of-band blocking for Inter-band CA                 | 129 |
| 7.6A.4   | Narrow band blocking for CA                            | 130 |
| 7.6A.4.1 | Narrow band blocking for Intra-band contiguous CA      | 130 |
| 7.6A.4.2 | Void                                                   | 131 |
| 7.6A.4.3 | Narrow band blocking for Inter-band CA                 | 131 |
| 7.6C     | Blocking characteristics for SUL                       | 131 |
| 7.6C.1   | General                                                | 131 |
| 7.6C.2   | In-band blocking for SUL                               | 131 |
| 7.6C.3   | Out-of-band blocking for SUL                           | 131 |
| 7.6C.4   | Narrow band blocking for SUL                           | 132 |
| 7.6D     | Blocking characteristics for UL MIMO                   | 132 |
| 7.7      | Spurious response                                      | 132 |
| 7.7A     | Spurious response for CA                               | 134 |
| 7.7A.1   | Spurious response for Intra-band contiguous CA         | 134 |
| 7.7A.2   | Void                                                   | 134 |
| 7.7A.3   | Spurious response for Inter-band CA                    | 134 |
| 7.7D     | Spurious response for UL MIMO                          | 134 |
| 7.8      | Intermodulation characteristics                        | 134 |
| 7.8.1    | General                                                | 134 |
| 7.8.2    | Wide band Intermodulation                              | 134 |
| 7.8A     | Intermodulation characteristics for CA                 | 137 |
| 7.8A.1   | General                                                | 137 |
| 7.8A.2   | Wide band intermodulation for CA                       | 137 |
| 7.8A.2.1 | Wide band intermodulation for Intra-band contiguous CA | 137 |
| 7.8A.2.2 | Void                                                   | 138 |
| 7.8A.2.3 | Wide band intermodulation for Inter-band CA            | 138 |
| 7.8D     | Intermodulation characteristics for UL MIMO            | 138 |
| 7.9      | Spurious emissions                                     | 138 |
| 7.9A     | Spurious emissions for CA                              | 139 |
| 7.9A.1   | Void                                                   | 139 |
| 7.9A.2   | Void                                                   | 139 |
| 7.9A.3   | Spurious emissions for Inter-band CA                   | 139 |

## **Annex A (normative): Measurement channels 140**

|         |                                        |     |
|---------|----------------------------------------|-----|
| A.1     | General                                | 140 |
| A.2     | UL reference measurement channels      | 140 |
| A.2.1   | General                                | 140 |
| A.2.2   | Reference measurement channels         | 141 |
| A.2.2.1 | DFT-s-OFDM Pi/2-BPSK                   | 141 |
| A.2.2.2 | DFT-s-OFDM QPSK                        | 142 |
| A.2.2.3 | DFT-s-OFDM 16QAM                       | 143 |
| A.2.2.4 | DFT-s-OFDM 64QAM                       | 144 |
| A.2.2.5 | DFT-s-OFDM 256QAM                      | 145 |
| A.2.2.6 | CP-OFDM QPSK                           | 146 |
| A.2.2.7 | CP-OFDM 16QAM                          | 148 |
| A.2.2.8 | CP-OFDM 64QAM                          | 151 |
| A.2.2.9 | CP-OFDM 256QAM                         | 153 |
| A.2.3   | Reference measurement channels for TDD | 155 |
| A.2.3.1 | DFT-s-OFDM Pi/2-BPSK                   | 155 |
| A.2.3.2 | DFT-s-OFDM QPSK                        | 155 |
| A.2.3.3 | DFT-s-OFDM 16QAM                       | 155 |
| A.2.3.4 | DFT-s-OFDM 64QAM                       | 155 |
| A.2.3.5 | DFT-s-OFDM 256QAM                      | 155 |

|         |                                                                 |     |
|---------|-----------------------------------------------------------------|-----|
| A.2.3.6 | CP-OFDM QPSK                                                    | 155 |
| A.2.3.7 | CP-OFDM 16QAM                                                   | 156 |
| A.2.3.8 | CP-OFDM 64QAM                                                   | 156 |
| A.2.3.9 | CP-OFDM 256QAM                                                  | 156 |
| A.3     | DL reference measurement channels                               | 157 |
| A.3.1   | General                                                         | 157 |
| A.3.2   | DL reference measurement channels for FDD                       | 159 |
| A.3.2.1 | General                                                         | 159 |
| A.3.2.2 | FRC for receiver requirements for QPSK                          | 160 |
| A.3.2.3 | FRC for maximum input level for 64QAM                           | 163 |
| A.3.2.4 | FRC for maximum input level for 256 QAM                         | 166 |
| A.3.3   | DL reference measurement channels for TDD                       | 169 |
| A.3.3.1 | General                                                         | 169 |
| A.3.3.2 | FRC for receiver requirements for QPSK                          | 170 |
| A.3.3.3 | FRC for maximum input level for 64QAM                           | 173 |
| A.3.3.4 | FRC for maximum input level for 256 QAM                         | 176 |
| A.4     | CSI reference measurement channels                              | 179 |
| A.5     | OFDMA Channel Noise Generator (OCNG)                            | 179 |
| A.5.1   | OCNG Patterns for FDD                                           | 179 |
| A.5.1.1 | OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs | 179 |
| A.5.2   | OCNG Patterns for TDD                                           | 179 |
| A.5.2.1 | OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs | 179 |
| A.6     | Void                                                            | 179 |

## **Annex B (informative): Void 180**

## **Annex C (informative): Downlink physical channels 181**

|       |                                         |     |
|-------|-----------------------------------------|-----|
| C.1   | General                                 | 181 |
| C.2   | Setup                                   | 181 |
| C.3   | Connection                              | 181 |
| C.3.1 | Measurement of Receiver Characteristics | 181 |

## **Annex D (normative): Characteristics of the interfering signal 182**

|     |         |     |
|-----|---------|-----|
| D.1 | General | 182 |
| D.2 | Void    | 182 |

## **Annex E (normative): Environmental conditions 182**

|       |               |     |
|-------|---------------|-----|
| E.1   | General       | 182 |
| E.2   | Environmental | 182 |
| E.2.1 | Temperature   | 182 |
| E.2.2 | Voltage       | 183 |
| E.2.3 | Vibration     | 183 |

## **Annex F (normative): Transmit modulation 184**

|     |                                          |     |
|-----|------------------------------------------|-----|
| F.0 | General                                  | 184 |
| F.1 | Measurement Point                        | 184 |
| F.2 | Basic Error Vector Magnitude measurement | 184 |

|                                                  |                                           |            |
|--------------------------------------------------|-------------------------------------------|------------|
| F.3                                              | Basic in-band emissions measurement       | 185        |
| F.4                                              | Modified signal under test                | 185        |
| F.5                                              | Window length                             | 187        |
| F.5.1                                            | Timing offset                             | 187        |
| F.5.2                                            | Window length                             | 187        |
| F.5.3                                            | Window length for normal CP               | 187        |
| F.5.4                                            | Window length for Extended CP             | 189        |
| F.5.5                                            | Window length for PRACH                   | 189        |
| F.6                                              | Averaged EVM                              | 190        |
| F.7                                              | Spectrum Flatness                         | 191        |
| F.8                                              |                                           | 191        |
| F.9                                              |                                           | 191        |
| F.10                                             | EVM for UL MIMO                           | 192        |
| F10.1                                            | General                                   | 192        |
| F10.2                                            | MIMO Equalization                         | 193        |
| F10.3                                            | Layer processing                          | 193        |
| <b>Annex G (normative):</b>                      |                                           | <b>195</b> |
| G.0                                              | General                                   | 195        |
| G.1                                              | Measurement Point                         | 195        |
| G.2                                              | Relative Phase Error Measurement          | 196        |
| G.2.1                                            | Symbols and subcarriers used              | 196        |
| G.2.2                                            | CFO (carrier frequency offset) correction | 196        |
| G.2.3                                            | Steps of the measurement method           | 196        |
| <b>Annex H (normative): ModifiedMPR-Behavior</b> |                                           | <b>197</b> |
| H.1                                              | Indication of modified MPR behavior       | 197        |
| <b>Annex I (informative): Void</b>               |                                           | <b>197</b> |
| <b>Annex J (informative): Void</b>               |                                           | <b>197</b> |
| <b>Annex K (informative): Void</b>               |                                           | <b>197</b> |
| <b>Annex L (informative): Change history</b>     |                                           | <b>198</b> |