

3GPP TS 38.101-1 V16.24.0 (2025-09)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Radio Access Network;
NR;
User Equipment (UE) radio transmission and reception;
Part 1: Range 1 Standalone
(Release 16)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and Reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

3GPP

Postal address

3GPP support office address
650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet
<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2025, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners

LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners

GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword	16
1	Scope 18
2	References 18
3	Definitions, symbols and abbreviations 18
3.1	Definitions 18
3.2	Symbols 20
3.3	Abbreviations 22
4	General 23
4.1	Relationship between minimum requirements and test requirements 23
4.2	Applicability of minimum requirements 23
4.3	Specification suffix information 23
5	Operating bands and channel arrangement 24
5.1	General 24
5.2	Operating bands 25
5.2A	Operating bands for CA 26
5.2A.0	General 26
5.2A.1	Intra-band CA 26
5.2A.2	Inter-band CA 27
5.2A.2.1	Inter-band CA (two bands) 27
5.2A.2.2	Inter-band CA (three bands) 31
5.2A.2.3	Inter-band CA (four bands) 32
5.2B	Operating bands for DC 32
5.2C	Operating band combination for SUL 32
5.2D	Operating bands for UL MIMO 33
5.2E	Operating band for V2X 33
5.2E.1	V2X operating bands 33
5.2E.2	V2X operating bands for concurrent operation 34
5.3	UE channel bandwidth 34
5.3.1	General 34
5.3.2	Maximum transmission bandwidth configuration 35
5.3.3	Minimum guardband and transmission bandwidth configuration 35
5.3.4	RB alignment 37
5.3.5	UE channel bandwidth per operating band 37
5.3.6	Asymmetric channel bandwidths 40
5.3A	UE channel bandwidth for CA 41
5.3A.1	General 41
5.3A.2	Maximum transmission bandwidth configuration for CA 41
5.3A.3	Minimum guardband and transmission bandwidth configuration for CA 42
5.3A.4	Void 43
5.3A.5	UE channel bandwidth per operating band for CA 43
5.3E	Channel bandwidth for V2X 44
5.3E.1	General 44
5.3E.2	Channel bandwidth for V2X concurrent operation 45
5.4	Channel arrangement 45
5.4.1	Channel spacing 45
5.4.1.1	Channel spacing for adjacent NR carriers 45
5.4.2	Channel raster 45
5.4.2.1	NR-ARFCN and channel raster 45
5.4.2.2	Channel raster to resource element mapping 46

5.4.2.3	Channel raster entries for each operating band	46
5.4.3	Synchronization raster	49
5.4.3.1	Synchronization raster and numbering	49
5.4.3.3	Synchronization raster entries for each operating band	50
5.4.4	TX–RX frequency separation	53
5.4A	Channel arrangement for CA	53
5.4A.1	Channel spacing for CA	53
5.4A.2	Channel raster for CA	54
5.4A.3	Synchronization raster for CA	54
5.4A.4	Tx-Rx frequency separation for CA	54
5.4B	Reserved	55
5.4C	Reserved	55
5.4D	Reserved	55
5.4E	Channel arrangement for V2X	55
5.4E.1	Channel spacing	55
5.4E.2	Channel raster	55
5.4E.2.1	NR-ARFCN and channel raster	55
5.4E.2.2	Channel raster to resource element mapping	55
5.4E.2.3	Channel raster entries for each operating band	55
5.4E.3	Synchronization raster for V2X	55
5.5	Void	56
5.5A	Configurations for CA	56
5.5A.0	General	56
5.5A.1	Configurations for intra-band contiguous CA	57
5.5A.2	Configurations for intra-band non-contiguous CA	60
5.5A.3	Configurations for inter-band CA	60
5.5A.3.1	Configurations for inter-band CA (two bands)	60
5.5A.3.2	Configurations for inter-band CA (three bands)	72
5.5A.3.3	Configurations for inter-band CA (four bands)	81
5.5B	Configurations for DC	84
5.5C	Configurations for SUL	85
6	Transmitter characteristics	87
6.1	General	87
6.1A	General	87
6.1F	General	87
6.2	Transmitter power	87
6.2.1	UE maximum output power	87
6.2.2	UE maximum output power reduction	89
6.2.3	UE additional maximum output power reduction	92
6.2.3.1	General	92
6.2.3.2	A-MPR for NS_04	97
6.2.3.3	A-MPR for NS_10	98
6.2.3.4	A-MPR for NS_05 and NS_05U	98
6.2.3.5	A-MPR for NS_40	101
6.2.3.6	A-MPR for NS_43 and NS_43U	101
6.2.3.7	A-MPR for NS_03 and NS_03U	102
6.2.3.8	A-MPR for NS_37	103
6.2.3.9	A-MPR for NS_38	104
6.2.3.10	A-MPR for NS_39	104
6.2.3.11	A-MPR for NS_41	104
6.2.3.12	A-MPR for NS_42	105
6.2.3.13	A-MPR for NS_18	105
6.2.3.14	A-MPR for NS_21	106

6.2.3.15	A-MPR for NS_24	106
6.2.3.16	A-MPR for NS_27	107
6.2.3.17	A-MPR for NS_46	108
6.2.3.18	A-MPR for NS_47	109
6.2.3.19	A-MPR for NS_50	110
6.2.3.20	A-MPR for NS_44	111
6.2.3.21	A-MPR for NS_12	111
6.2.3.22	A-MPR for NS_13	112
6.2.3.23	A-MPR for NS_14	112
6.2.3.24	A-MPR for NS_15	113
6.2.3.25	A-MPR for NS_45	114
6.2.3.26	A-MPR for NS_48	114
6.2.3.27	A-MPR for NS_49	115
6.2.3.28	A-MPR for NS_51	116
6.2.4	Configured transmitted power	116
6.2A	Transmitter power for CA	118
6.2A.1	UE maximum output power for CA	118
6.2A.1.1	UE maximum output power for Intra-band contiguous CA	118
6.2A.1.2	UE maximum output power for Intra-band non-contiguous CA	119
6.2A.1.3	UE maximum output power for Inter-band CA	119
6.2A.1.4	Void	122
6.2A.1.5	Void	122
6.2A.2	UE maximum output power reduction for CA	122
6.2A.2.1	UE maximum output power reduction for Intra-band contiguous CA	122
6.2A.2.2	UE maximum output power reduction for Intra-band non-contiguous CA	124
6.2A.2.2.0	General	124
6.2A.2.2.1	MPR to meet -30dBm/MHz	124
6.2A.2.2.2	MPR to meet -13dBm/MHz	125
6.2A.2.3	UE maximum output power reduction for Inter-band CA	125
6.2A.2.4	Void	125
6.2A.3	UE additional maximum output power reduction for CA	125
6.2A.3.1.1	UE additional maximum output power reduction for Intra-band contiguous CA	125
6.2A.3.1.1.1	A-MPR for CA_NS_04	126
6.2A.3.1.2	UE additional maximum output power reduction for Intra-band non-contiguous CA	132
6.2A.3.1.3	UE additional maximum output power reduction for Inter-band CA	134
6.2A.4	Configured output power for CA	136
6.2A.4.1	Configured transmitted power level	136
6.2A.4.1.1	Configured transmitted power for Intra-band contiguous CA	136
6.2A.4.1.2	Configured transmitted power for Intra-band non-contiguous CA	138
6.2A.4.1.3	Configured transmitted power for Inter-band CA	140
6.2A.4.1.4	Void	142
6.2A.4.2	$\Delta T_{IB,c}$ for CA	142
6.2A.4.2.1	Void	142
6.2A.4.2.2	Void	142
6.2A.4.2.3	$\Delta T_{IB,c}$ for Inter-band CA (two bands)	142
6.2A.4.2.4	$\Delta T_{IB,c}$ for Inter-band CA (three bands)	147
6.2A.4.2.5	$\Delta T_{IB,c}$ for Inter-band CA (four bands)	150
6.2B	Transmitter power for NR-DC	150
6.2B.0	General	150
6.2B.1	UE maximum output power for NR-DC	150
6.2B.2	UE maximum output power reduction for NR-DC	151
6.2B.3	UE additional maximum output power reduction for NR-DC	151
6.2B.4	Configured output power for NR-DC	151

6.2B.4.1	Configured transmitted power level for NR-DC	151
6.2B.4.2	$\Delta T_{IB,c}$ for NR-DC	154
6.2C	Transmitter power for SUL	154
6.2C.1	Configured transmitted power for SUL	154
6.2C.2	$\Delta T_{IB,c}$	154
6.2D	Transmitter power for UL MIMO	155
6.2D.1	UE maximum output power for UL MIMO	155
6.2D.2	UE maximum output power reduction for UL MIMO	156
6.2D.3	UE additional maximum output power reduction for UL MIMO	157
6.2D.4	Configured transmitted power for UL MIMO	157
6.2E	Transmitter power for V2X	158
6.2E.1	UE maximum output power for V2X	158
6.2E.1.1	General	158
6.2E.1.2	UE maximum output power for V2X con-current operation	159
6.2E.2	UE maximum output power reduction for V2X	159
6.2E.2.1	General	159
6.2E.2.2	MPR for Power class 3 V2X UE	159
6.2E.2.3	MPR for Power class 3 V2X concurrent operation	160
6.2E.3	UE additional maximum output power reduction for V2X	160
6.2E.3.1	General	160
6.2E.3.2	A-MPR for Power class 3 V2X UE by NS_33	161
6.2E.3.3	A-MPR for Power class 3 V2X UE by NS_52	163
6.2E.3.4	A-MPR for power class 3 V2X concurrent operation	164
6.2E.4	Configured transmitted power for V2X	165
6.2E.4.1	General	165
6.2E.4.2	Configured transmitted power for V2X concurrent operation	166
6.2F	Transmitter power for shared spectrum channel access	167
6.2F.1	UE maximum output power	167
6.2F.1A	UE maximum output power for CA	168
6.2F.1A.1	UE maximum output power for inter-band CA	168
6.2F.2	UE maximum output power reduction	168
6.2F.2A	UE maximum output power reduction for CA	169
6.2F.2A.1	UE maximum output power reduction for inter-band CA	169
6.2F.3	UE additional maximum output power reduction	169
6.2F.3.1	General	169
6.2F.3.2	A-MPR for NS_28	170
6.2F.3.3	A-MPR for NS_29	170
6.2F.3.4	A-MPR for NS_30	171
6.2F.3.5	A-MPR for NS_31	171
6.2F.3.6	A-MPR for NS_53	172
6.2F.3.7	A-MPR for NS_54	172
6.2F.3A	UE additional maximum output power reduction for CA	173
6.2F.3A.1	UE additional maximum output power reduction for inter-band CA	173
6.2F.4	Configured transmitted power	173
6.3	Output power dynamics	173
6.3.1	Minimum output power	173
6.3.2	Transmit OFF power	174
6.3.3	Transmit ON/OFF time mask	174
6.3.3.1	General	174
6.3.3.2	General ON/OFF time mask	175
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries	175
6.3.3.4	PRACH time mask	175
6.3.3.5	Void	177

6.3.3.6	SRS time mask	177
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	178
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	179
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	180
6.3.4	Power control	181
6.3.4.1	General	181
6.3.4.2	Absolute power tolerance	181
6.3.4.3	Relative power tolerance	181
6.3.4.4	Aggregate power tolerance	181
6.3A	Output power dynamics for CA	182
6.3A.1	Minimum output power for CA	182
6.3A.1.1	Minimum output power for intra-band contiguous CA	182
6.3A.1.2	Minimum output power for intra-band non-contiguous CA	182
6.3A.1.3	Minimum output power for inter-band CA	182
6.3A.1.4	Void	182
6.3A.2	Transmit OFF power for CA	182
6.3A.2.1	Transmit OFF power for intra-band contiguous CA	182
6.3A.2.2	Transmit OFF power for intra-band non-contiguous CA	182
6.3A.2.3	Transmit OFF power for inter-band CA	182
6.3A.2.4	Void	183
6.3A.3	Transmit ON/OFF time mask for CA	183
6.3A.3.1	Transmit ON/OFF time mask for intra-band contiguous CA	183
6.3A.3.2	Transmit ON/OFF time mask for intra-band non-contiguous CA	183
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA	183
6.3A.3.3.1	General	183
6.3A.3.3.2	Time mask for switching between two uplink carriers	183
6.3A.3.4	Void	185
6.3A.4	Power control for CA	185
6.3A.4.1	Power control for intra-band contiguous CA	185
6.3A.4.1.1	Absolute power tolerance	185
6.3A.4.1.2	Relative power tolerance	185
6.3A.4.1.3	Aggregate power control tolerance	185
6.3A.4.2	Power control for intra-band non-contiguous CA	185
6.3A.4.2.1	Absolute power tolerance	185
6.3A.4.2.1.1	Minimum requirements	186
6.3A.4.2.2	Relative power tolerance	186
6.3A.4.2.2.1	Minimum requirements	186
6.3A.4.2.3	Aggregate power control tolerance	186
6.3A.4.3	Power control for inter-band CA	186
6.3A.4.4	Void	186
6.3B	Output power dynamics for NR-DC	186
6.3C	Output power dynamics for SUL	186
6.3C.1	Void	186
6.3C.2	Void	186
6.3C.3	Transmit ON/OFF time mask for SUL	186
6.3C.3.1	Time mask for switching between two uplink carriers	186
6.3D	Output power dynamics for UL MIMO	188
6.3D.1	Minimum output power for UL MIMO	188
6.3D.2	Transmit OFF power for UL MIMO	188
6.3D.3	Transmit ON/OFF time mask for UL MIMO	188
6.3D.4	Power control for UL MIMO	188
6.3E	Output power dynamics for V2X	188

6.3E.1	Minimum output power for V2X	188
6.3E.1.1	General	188
6.3E.1.2	Minimum output power for V2X concurrent operation	189
6.3E.2	Transmit OFF power for V2X	189
6.3E.2.1	General	189
6.3E.2.2	Transmit OFF power for V2X concurrent operation	189
6.3E.3	Transmit ON/OFF time mask for V2X	189
6.3E.3.1	General	189
6.3E.3.2	General time mask	190
6.3E.3.3	S-SSB time mask	190
6.3E.3.4	Transmit ON/OFF time mask for V2X concurrent operation	191
6.3E.4	Power control for V2X	191
6.3E.4.1	General	191
6.3E.4.2	Absolute power tolerance	191
6.3E.4.3	Power control for V2X concurrent operation	191
6.3F	Output power dynamics for shared spectrum channel access	191
6.3F.1	Minimum output power	191
6.3F.2	Transmit OFF power	191
6.3F.3	Transmit ON/OFF time mask	191
6.3F.3.1	General	191
6.3F.3.2	General ON/OFF time mask	191
6.3F.3A	General ON/OFF mask for CA	192
6.3F.3A.1	General ON/OFF mask for inter-band CA	192
6.3F.4	Power control	192
6.3F.4.1	General	192
6.3F.4.2	Absolute power tolerance	192
6.3F.4.3	Relative power tolerance	192
6.3F.4.4	Aggregate power tolerance	192
6.4	Transmit signal quality	193
6.4.1	Frequency error	193
6.4.2	Transmit modulation quality	193
6.4.2.0	General	193
6.4.2.1	Error Vector Magnitude	193
6.4.2.1a	Error Vector Magnitude including symbols with transient period	194
6.4.2.2	Carrier leakage	195
6.4.2.3	In-band emissions	195
6.4.2.4	EVM equalizer spectrum flatness	196
6.4.2.4.1	Requirements for Pi/2 BPSK modulation	197
6.4A	Transmit signal quality for CA	198
6.4A.1	Frequency error for CA	198
6.4A.1.1	Frequency error for intra-band contiguous CA	198
6.4A.1.2	Frequency error for intra-band non-contiguous CA	198
6.4A.1.3	Frequency error for inter-band CA	198
6.4A.1.4	Void	199
6.4A.2	Transmit modulation quality for CA	199
6.4A.2.1	Transmit modulation quality for intra-band contiguous CA	199
6.4A.2.1.0	General	199
6.4A.2.1.1	Error Vector Magnitude	199
6.4A.2.1.2	In-band emissions	199
6.4A.2.1.3	Carrier leakage	202
6.4A.2.2	Transmit modulation quality for intra-band non-contiguous CA	202
6.4A.2.2.0	General	202
6.4A.2.2.1	Error Vector Magnitude	202

6.4A.2.2.2	In-band emissions	203	
6.4A.2.2.3	Carrier leakage	203	
6.4A.2.3	Transmit modulation quality for inter-band CA		203
6.4A.2.4	Void	203	
6.4B	Transmit signal quality for NR-DC	203	
6.4D	Transmit signal quality for UL MIMO	203	
6.4D.0	General	203	
6.4D.1	Frequency error for UL MIMO	204	
6.4D.2	Transmit modulation quality for UL MIMO		204
6.4D.2.0	General	204	
6.4D.2.1	Error Vector Magnitude	204	
6.4D.2.2	Carrier leakage	204	
6.4D.2.3	In-band emissions	204	
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO		204
6.4D.3	Time alignment error for UL MIMO	205	
6.4D.4	Requirements for coherent UL MIMO	205	
6.4E	Transmit signal quality for V2X	205	
6.4E.1	Frequency error for V2X	205	
6.4E.1.1	General	205	
6.4E.1.2	Frequency error for V2X concurrent operation		206
6.4E.2	Transmit modulation quality for V2X	206	
6.4E.2.1	General	206	
6.4E.2.2	Error Vector Magnitude for V2X	206	
6.4E.2.3	Carrier leakage for V2X	206	
6.4E.2.4	In-band emissions for V2X	206	
6.4E.2.5	EVM equalizer spectrum flatness for V2X	206	
6.4E.2.6	Transmit modulation quality for V2X concurrent operation		206
6.4F	Transmit signal quality for shared spectrum channel access	207	
6.4F.1	Frequency error	207	
6.4F.2	Transmit modulation quality	207	
6.4F.2.0	General	207	
6.4F.2.1	Error Vector Magnitude	207	
6.4F.2.2	Carrier leakage	207	
6.4F.2.3	In-band emissions	207	
6.4F.2.4	EVM equalizer spectrum flatness	208	
6.4F.2A	Transmit modulation quality for CA	208	
6.4F.2A.1	Transmit modulation quality for inter-band CA		208
6.5	Output RF spectrum emissions	209	
6.5.1	Occupied bandwidth	209	
6.5.2	Out of band emission	209	
6.5.2.1	General	209	
6.5.2.2	Spectrum emission mask	209	
6.5.2.3	Additional spectrum emission mask	210	
6.5.2.3.1	Requirements for network signalling value "NS_35"		210
6.5.2.3.2	Requirements for network signalling value "NS_04"		211
6.5.2.3.3	Requirements for network signalling values "NS_03", "NS_03U", and "NS_21"		211
6.5.2.3.4	Requirements for network signalling value "NS_06"		212
6.5.2.3.5	Void	213	
6.5.2.3.6	Void	213	
6.5.2.3.7	Void	213	
6.5.2.3.8	Requirements for network signalling value "NS_27"		213
6.5.2.4	Adjacent channel leakage ratio	213	
6.5.2.4.1	NR ACLR	213	

6.5.2.4.2	UTRA ACLR	214	
6.5.3	Spurious emissions	214	
6.5.3.0	General	214	
6.5.3.1	General spurious emissions	215	
6.5.3.2	Spurious emissions for UE co-existence	215	
6.5.3.3	Additional spurious emissions	223	
6.5.3.3.1	Requirement for network signalling value "NS_04"	223	
6.5.3.3.2	Requirement for network signalling value "NS_17"	224	
6.5.3.3.3	Requirement for network signalling value "NS_18"	224	
6.5.3.3.4	Requirement for network signalling values "NS_05" and "NS_05U"	224	
6.5.3.3.5	Requirement for network signalling values "NS_43" and "NS_43U"	224	
6.5.3.3.6	Requirement for network signalling value "NS_37"	225	
6.5.3.3.7	Requirement for network signalling value "NS_38"	225	
6.5.3.3.8	Requirement for network signalling value "NS_39"	225	
6.5.3.3.9	Requirement for network signalling value "NS_40"	225	
6.5.3.3.10	Requirement for network signalling value "NS_41"	226	
6.5.3.3.11	Requirement for network signalling value "NS_42"	226	
6.5.3.3.12	Requirement for network signalling value "NS_21"	226	
6.5.3.3.13	Requirement for network signalling value "NS_24"	227	
6.5.3.3.14	Requirement for network signalling value "NS_27"	227	
6.5.3.3.15	Requirement for network signalling value "NS_47"	227	
6.5.3.3.16	Requirement for network signalling value "NS_50"	228	
6.5.3.3.17	Requirement for network signalling value "NS_12"	228	
6.5.3.3.18	Requirement for network signalling value "NS_13"	228	
6.5.3.3.19	Requirement for network signalling value "NS_14"	229	
6.5.3.3.20	Requirement for network signalling value "NS_15"	229	
6.5.3.3.21	Requirement for network signalling value "NS_45"	229	
6.5.3.3.22	Requirement for network signalling values "NS_48" and "NS_51"	230	
6.5.3.3.23	Requirement for network signalling value "NS_49"	230	
6.5.3.3.24	Requirement for network signalling value "NS_44"	230	
6.5.3.3.25	Requirement for network signalling value "NS_46"	231	
6.5.4	Transmit intermodulation	231	
6.5A	Output RF spectrum emissions for CA	232	
6.5A.0	General	232	
6.5A.1	Occupied bandwidth for CA	232	
6.5A.1.1	Void	232	
6.5A.1.1a	Occupied bandwidth for Intra-band contiguous CA	232	
6.5A.1.2	Occupied bandwidth for Intra-band non-contiguous CA	232	
6.5A.1.3	Occupied bandwidth for Inter-band CA	232	
6.5A.2	Out of band emission for CA	232	
6.5A.2.1	General	232	
6.5A.2.2	Spectrum emission mask	232	
6.5A.2.2.1	Spectrum emission mask for intra-band contiguous CA	232	
6.5A.2.2.2	Spectrum emission mask for intra-band non-contiguous CA	233	
6.5A.2.2.3	Spectrum emission mask for Inter-band CA	233	
6.5A.2.2.4	Void	233	
6.5A.2.3	Additional spectrum emission mask for CA	233	
6.5A.2.3.1	Additional spectrum emission mask for intra-band contiguous CA	233	
6.5A.2.3.1	Void	234	
6.5A.2.3.2	Additional spectrum emission mask for Intra-band non-contiguous CA	234	
6.5A.2.3.2.1	Minimum requirement (network signalling value "CA_NC_NS_04")	234	
6.5A.2.3.3	Additional spectrum emission mask for Inter-band CA	234	

6.5A.2.4	Adjacent channel leakage ratio	234
6.5A.2.4.1	NR ACLR	234
6.5A.2.4.2	UTRA ACLR	235
6.5A.3	Spurious emission for CA	235
6.5A.3.1	General spurious emissions	235
6.5A.3.2	Spurious emissions for UE co-existence	236
6.5A.3.2.1	Spurious emissions for UE co-existence for intra-band contiguous CA	236
6.5A.3.2.2	Spurious emissions for UE co-existence for intra-band non-contiguous CA	237
6.5A.3.2.3	Spurious emissions for UE co-existence for Inter-band CA	238
6.5A.3.2.4	Void	241
6.5A.3.2.5	Void	241
6.5A.3.2.6	Void	241
6.5A.3.3	Additional spurious emissions for CA	241
6.5A.3.3.1	Additional spurious emissions for intra-band contiguous CA	241
6.5A.3.3.2	Additional spurious emissions for intra-band non-contiguous CA	242
6.5A.4	Transmit intermodulation for CA	242
6.5A.4.2.1	Transmit intermodulation for intra-band contiguous CA	242
6.5A.4.2.2	Void	243
6.5B	Output RF spectrum emissions for NR-DC	243
6.5D	Output RF spectrum emissions for UL MIMO	243
6.5D.1	Occupied bandwidth for UL MIMO	243
6.5D.2	Out of band emission for UL MIMO	243
6.5D.3	Spurious emission for UL MIMO	244
6.5D.4	Transmit intermodulation for UL MIMO	244
6.5E	Output RF spectrum emissions for V2X	244
6.5E.1	Occupied bandwidth for V2X	244
6.5E.1.1	General	244
6.5E.1.2	Occupied bandwidth for V2X concurrent operation	244
6.5E.2	Out of band emission for V2X	245
6.5E.2.1	General	245
6.5E.2.2	Spectrum emission mask	245
6.5E.2.2.1	General	245
6.5E.2.2.2	Spectrum emission mask for V2X concurrent operation	245
6.5E.2.3	Additional Spectrum emission mask	245
6.5E.2.3.1	Requirements for network signalling value "NS_33"	245
6.5E.2.3.2	Requirements for network signalling value "NS_52"	246
6.5E.2.4	Adjacent channel leakage ratio	246
6.5E.2.4.1	General	246
6.5E.2.4.2	ACLR for V2X concurrent operation	246
6.5E.3	Spurious emissions for V2X	246
6.5E.3.1	General spurious emissions	246
6.5E.3.2	Spurious emissions for UE co-existence	247
6.5E.3.3	Spurious emissions for UE co-existence for V2X concurrent operation	247
6.5E.3.4	Additional spurious emissions requirements for V2X	247
6.5E.3.4.1	General	247
6.5E.3.4.2	Requirements for network signalling value "NS_33"	248
6.5E.3.4.3	Void	248
6.5E.4	Transmit intermodulation	248
6.5E.4.1	General	248
6.5E.4.2	Transmit intermodulation for V2X concurrent operation	248
6.5F	Output RF spectrum emissions	248
6.5F.1	Occupied bandwidth	248
6.5F.2	Out of band emission	248

6.5F.2.1	General	248	
6.5F.2.2	Spectrum emission mask for operation with shared spectrum channel access		249
6.5F.2.2.0	General	249	
6.5F.2.2.1	Spectrum emission mask for non-transmitted channels		249
6.5F.2.3	Additional spectrum emission mask	250	
6.5F.2.4	Adjacent channel leakage ratio	250	
6.5F.2.4.0	General	250	
6.5F.2.4.1	Shared spectrum channel access ACLR	250	
6.5F.2.4.2	Additional requirement for network signaled value "NS_29"		250
6.5F.3	Spurious emissions	250	
6.5F.3.0	General	250	
6.5F.3.1	General spurious emissions	251	
6.5F.3.2	Spurious emissions for UE co-existence	251	
6.5F.3.3	Additional spurious emissions	251	
6.5F.3.3.0	General	251	
6.5F.3.3.1	Requirement for network signalling value "NS_28"		251
6.5F.3.3.2	Requirement for network signalling value "NS_29"		251
6.5F.3.3.3	Requirement for network signalling value "NS_30"		253
6.5F.3.3.4	Requirement for network signalling value "NS_31"		254
6.5F.3.3.5	Requirements for network signalling value "NS_53" or "NS_54"		255
6.5F.4	Transmit intermodulation	255	
6.6	Void	255	
6.6E	Time alignment error	255	
7	Receiver characteristics	256	
7.1	General	256	
7.1A	General	256	
7.1F	General	257	
7.2	Diversity characteristics	257	
7.3	Reference sensitivity	257	
7.3.1	General	257	
7.3.2	Reference sensitivity power level	257	
7.3.3	$\Delta R_{IB,c}$	265	
7.3A	Reference sensitivity for CA	265	
7.3A.1	General	265	
7.3A.2	Reference sensitivity power level for CA	266	
7.3A.2.1	Reference sensitivity power level for Intra-band contiguous CA		266
7.3A.2.2	Reference sensitivity power level for Intra-band non-contiguous CA		266
7.3A.2.3	Reference sensitivity power level for Inter-band CA	267	
7.3A.2.4	Void	267	
7.3A.3	$\Delta R_{IB,c}$ for CA	267	
7.3A.3.1	General	267	
7.3A.3.2	$\Delta R_{IB,c}$ for Inter-band CA	267	
7.3A.3.2.1	$\Delta R_{IB,c}$ for two bands	269	
7.3A.3.2.2	Void	272	
7.3A.3.2.3	$\Delta R_{IB,c}$ for three bands	272	
7.3A.3.2.4	$\Delta R_{IB,c}$ for four bands	274	
7.3A.4	Reference sensitivity exceptions due to UL harmonic interference for CA	274	
7.3A.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA	279	
7.3A.6	Reference sensitivity exceptions due to cross band isolation for CA	285	
7.3B	Reference sensitivity for NR-DC	286	
7.3C	Reference sensitivity for SUL	286	
7.3C.1	General	286	
7.3C.2	Reference sensitivity power level for SUL	286	

7.3C.3	$\Delta R_{IB,c}$ for SUL	289	
7.3C.3.1	General	289	
7.3C.3.2	SUL band combination	289	
7.3C.3.2.1	$\Delta R_{IB,c}$ for two bands	290	
7.3D	Reference sensitivity for UL MIMO	290	
7.3E	Reference sensitivity for V2X	290	
7.3E.1	General	290	
7.3E.2	Minimum requirements	290	
7.3E.3	Reference sensitivity power level for V2X concurrent operation	291	
7.3F	Reference sensitivity for shared spectrum channel access	292	
7.3F.1	General	292	
7.3F.2	Reference sensitivity power level	292	
7.3F.3	$\Delta R_{IB,c}$	293	
7.3F.4	Intra-band contiguous shared spectrum channel access CA	293	
7.3F.5	Inter-band CA with shared spectrum channel access	293	
7.3F.5.1	Reference sensitivity exceptions due to UL harmonic interference	293	
7.3F.5.2	Reference sensitivity exceptions due to receiver harmonic mixing	294	
7.3F.5.3	Reference sensitivity exceptions due to cross band isolation	294	
7.4	Maximum input level	295	
7.4A	Maximum input level for CA	295	
7.4A.1	Maximum input level for Intra-band contiguous CA	295	
7.4A.2	Maximum input level for Intra-band non-contiguous CA	296	
7.4A.3	Maximum input level for Inter-band CA	296	
7.4B	Maximum input level for NR-DC	296	
7.4D	Maximum input level for UL MIMO	296	
7.4E	Maximum input level for V2X	296	
7.4E.1	General	296	
7.4E.2	Maximum input level for V2X concurrent operation	297	
7.5	Adjacent channel selectivity	297	
7.5A	Adjacent channel selectivity for CA	301	
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA	301	
7.5A.2	Adjacent channel selectivity Intra-band non-contiguous CA	303	
7.5A.3	Adjacent channel selectivity Inter-band CA	304	
7.5B	Adjacent channel selectivity for NR-DC	304	
7.5D	Adjacent channel selectivity for UL MIMO	304	
7.5E	Adjacent channel selectivity for V2X	304	
7.5E.1	General	304	
7.5E.2	Adjacent channel selectivity for V2X concurrent operation	305	
7.5F	Adjacent channel selectivity	305	
7.5F.1	General	305	
7.5F.2	Intra-band contiguous shared spectrum channel access CA	306	
7.6	Blocking characteristics	307	
7.6.1	General	307	
7.6.2	In-band blocking	307	
7.6.3	Out-of-band blocking	311	
7.6.4	Narrow band blocking	314	
7.6A	Blocking characteristics for CA	315	
7.6A.1	General	315	
7.6A.2	In-band blocking for CA	315	
7.6A.2.1	In-band blocking for Intra-band contiguous CA	315	
7.6A.2.2	In-band blocking for Intra-band non-contiguous CA	317	
7.6A.2.3	In-band blocking for Inter-band CA	317	
7.6A.3	Out-of-band blocking for CA	318	

7.6A.3.1	Out-of-band blocking for Intra-band contiguous CA	318
7.6A.3.2	Out-of-band blocking for Intra-band non-contiguous CA	319
7.6A.3.3	Out-of-band blocking for Inter-band CA	319
7.6A.4	Narrow band blocking for CA	320
7.6A.4.1	Narrow band blocking for Intra-band contiguous CA	320
7.6A.4.2	Narrow band blocking for Intra-band non-contiguous CA	321
7.6A.4.3	Narrow band blocking for Inter-band CA	321
7.6B	Blocking characteristics for NR-DC	321
7.6C	Blocking characteristics for SUL	322
7.6C.1	General	322
7.6C.2	In-band blocking for SUL	322
7.6C.3	Out-of-band blocking for SUL	322
7.6C.4	Narrow band blocking for SUL	322
7.6D	Blocking characteristics for UL MIMO	322
7.6E	Blocking characteristics for V2X	323
7.6E.1	General	323
7.6E.2	In-band blocking	323
7.6E.2.1	General	323
7.6E.2.2	In-band blocking for V2X concurrent operation	323
7.6E.3	Out-of-band blocking	324
7.6E.3.1	General	324
7.6E.3.2	Out-of-band blocking for V2X concurrent operation	324
7.6F	Blocking characteristics	324
7.6F.1	General	324
7.6F.2	In-band blocking	325
7.6F.2.1	General	325
7.6F.2.2	Intra-band contiguous shared spectrum channel access CA	325
7.6F.3	Out-of-band blocking	326
7.6F.3.1	General	326
7.6F.3.2	Intra-band contiguous shared spectrum channel access CA	327
7.7	Spurious response	328
7.7A	Spurious response for CA	329
7.7A.1	Spurious response for Intra-band contiguous CA	329
7.7A.2	Spurious response for Intra-band non-contiguous CA	330
7.7A.3	Spurious response for Inter-band CA	330
7.7B	Spurious response for NR-DC	330
7.7D	Spurious response for UL MIMO	330
7.7E	Spurious response for V2X	330
7.7E.1	General	330
7.7E.2	Spurious response for V2X concurrent operation	331
7.7F	Spurious response for shared spectrum channel access	331
7.7F.1	General	331
7.7F.2	Intra-band contiguous shared spectrum channel access CA	331
7.8	Intermodulation characteristics	332
7.8.1	General	332
7.8.2	Wide band Intermodulation	332
7.8A	Intermodulation characteristics for CA	334
7.8A.1	General	334
7.8A.2	Wide band intermodulation for CA	334
7.8A.2.1	Wide band intermodulation for Intra-band contiguous CA	334
7.8A.2.2	Wide band intermodulation for Intra-band non-contiguous CA	335
7.8A.2.3	Wide band intermodulation for Inter-band CA	335
7.8B	Intermodulation characteristics for NR-DC	335

7.8D	Intermodulation characteristics for UL MIMO	336
7.8E	Intermodulation characteristics for V2X	336
7.8E.1	General	336
7.8E.2	Wide band Intermodulation	336
7.8E.2.1	General	336
7.8E.2.2	Wide band Intermodulation for V2X concurrent operation	336
7.8F	Intermodulation characteristics for shared spectrum channel access	336
7.8F.1	General	336
7.8F.2	Wide band Intermodulation	337
7.9	Spurious emissions	337
7.9A	Spurious emissions for CA	338
7.9A.1	Void	338
7.9A.2	Void	338
7.9A.3	Spurious emissions for Inter-band CA	338
7.9B	Spurious emissions for NR-DC	338

Annex A (normative): Measurement channels 340

A.1	General	340
A.2	UL reference measurement channels	340
A.2.1	General	340
A.2.2	Reference measurement channels	342
A.2.2.1	DFT-s-OFDM Pi/2-BPSK	342
A.2.2.2	DFT-s-OFDM QPSK	343
A.2.2.3	DFT-s-OFDM 16QAM	344
A.2.2.4	DFT-s-OFDM 64QAM	345
A.2.2.5	DFT-s-OFDM 256QAM	346
A.2.2.6	CP-OFDM QPSK	347
A.2.2.7	CP-OFDM 16QAM	349
A.2.2.8	CP-OFDM 64QAM	351
A.2.2.9	CP-OFDM 256QAM	353
A.2.3	Reference measurement channels for TDD	355
A.2.3.1	DFT-s-OFDM Pi/2-BPSK	355
A.2.3.2	DFT-s-OFDM QPSK	355
A.2.3.3	DFT-s-OFDM 16QAM	355
A.2.3.4	DFT-s-OFDM 64QAM	355
A.2.3.5	DFT-s-OFDM 256QAM	355
A.2.3.6	CP-OFDM QPSK	356
A.2.3.7	CP-OFDM 16QAM	356
A.2.3.8	CP-OFDM 64QAM	356
A.2.3.9	CP-OFDM 256QAM	356
A.3	DL reference measurement channels	357
A.3.1	General	357
A.3.2	DL reference measurement channels for FDD	359
A.3.2.1	General	359
A.3.2.2	FRC for receiver requirements for QPSK	360
A.3.2.3	FRC for maximum input level for 64QAM	362
A.3.2.4	FRC for maximum input level for 256 QAM	365
A.3.3	DL reference measurement channels for TDD	368
A.3.3.1	General	368
A.3.3.2	FRC for receiver requirements for QPSK	369
A.3.3.3	FRC for maximum input level for 64QAM	372
A.3.3.4	FRC for maximum input level for 256 QAM	375

A.4	CSI reference measurement channels	378
A.5	OFDMA Channel Noise Generator (OCNG)	378
A.5.1	OCNG Patterns for FDD	378
A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs	378
A.5.2	OCNG Patterns for TDD	378
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	378
A.6	Void	379
A.7	V2X reference measurement channels	379
A.7.1	General	379
A.7.2	FRC for V2X receiver requirements for QPSK	379
A.7.3	FRC for maximum input level for 64QAM	381
A.7.4	FRC for maximum input level for 256QAM	382

Annex B (informative): Void 384

Annex C (informative): Downlink physical channels 385

C.1	General	385
C.2	Setup	385
C.3	Connection	385
C.3.1	Measurement of Receiver Characteristics	385

Annex D (normative): Characteristics of the interfering signal 386

D.1	General	386
D.2	Void	386

Annex E (normative): Environmental conditions 386

E.1	General	386
E.2	Environmental	386
E.2.1	Temperature	386
E.2.2	Voltage	387
E.2.3	Vibration	387

Annex F (normative): Transmit modulation 388

F.0	General	388
F.1	Measurement Point	388
F.2	Basic Error Vector Magnitude measurement	388
F.3	Basic in-band emissions measurement	389
F.4	Modified signal under test	390
F.5	Window length	392
F.5.1	Timing offset	392
F.5.2	Window length	392
F.5.3	Window length for normal CP	392
F.5.4	Window length for Extended CP	393
F.5.5	Window length for PRACH	394
F.6	Averaged EVM	395
F.7	Spectrum Flatness	396

F.8 396

F.9 396

F.10 EVM for UL MIMO 396

F10.1 General 396

F10.2 MIMO Equalization 397

F10.3 Layer processing 397

Annex G (normative): 399

G.0 General 399

G.1 Measurement Point 399

G.2 Relative Phase Error Measurement 400

G.2.1 Symbols and subcarriers used 400

G.2.2 CFO (carrier frequency offset) correction 400

G.2.3 Steps of the measurement method 400

Annex H (informative): Void 401

Annex I (informative): Void 401

Annex J (informative): Void 401

Annex K (informative): Void 401

Annex L (normative): ModifiedMPR-Behavior 401

L.1 Indication of modified MPR behavior 401

Annex M (informative): Change history 403