

3GPP TS 38.101-1 V17.19.0 (2025-09)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Radio Access Network;
NR;
User Equipment (UE) radio transmission and reception;
Part 1: Range 1 Standalone
(Release 17)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and Reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

3GPP

Postal address

3GPP support office address
650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet
<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2025, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
GSM® and the GSM logo are registered and owned by the GSM Association

3GPP

Contents

Foreword	19	
1	Scope	21
2	References	21
3	Definitions, symbols and abbreviations	22
3.1	Definitions	22
3.2	Symbols	23
3.3	Abbreviations	25
4	General	26
4.1	Relationship between minimum requirements and test requirements	26
4.2	Applicability of minimum requirements	26
4.3	Specification suffix information	27
5	Operating bands and channel arrangement	28
5.1	General	28
5.2	Operating bands	28
5.2A	Operating bands for CA	30
5.2A.0	General	30
5.2A.1	Intra-band CA	30
5.2A.2	Inter-band CA	31
5.2A.2.1	Inter-band CA (two bands)	32
5.2A.2.2	Inter-band CA (three bands)	38
5.2A.2.3	Inter-band CA (four bands)	43
5.2A.2.4	Inter-band CA (five bands)	45
5.2B	Operating bands for DC	45
5.2C	Operating band combination for SUL	45
5.2D	Operating bands for UL MIMO	47
5.2E	Operating band for V2X	48
5.2E.1	V2X operating bands	48
5.2E.2	V2X operating bands for concurrent operation	48
5.3	UE channel bandwidth	49
5.3.1	General	49
5.3.2	Maximum transmission bandwidth configuration	51
5.3.3	Minimum guardband and transmission bandwidth configuration	51
5.3.4	RB alignment	53
5.3.5	UE channel bandwidth per operating band	53
5.3.6	Asymmetric channel bandwidths	57
5.3A	UE channel bandwidth for CA	58
5.3A.1	General	58
5.3A.2	Maximum transmission bandwidth configuration for CA	59
5.3A.3	Minimum guardband and transmission bandwidth configuration for CA	59
5.3A.4	Void	61
5.3A.5	UE channel bandwidth per operating band for CA	61
5.3E	Channel bandwidth for V2X	62
5.3E.1	General	62
5.3E.2	Channel bandwidth for V2X concurrent operation	63
5.3I	Channel bandwidth for RedCap	64
5.4	Channel arrangement	64
5.4.1	Channel spacing	64
5.4.1.1	Channel spacing for adjacent NR carriers	64
5.4.2	Channel raster	64

5.4.2.1	NR-ARFCN and channel raster	64
5.4.2.2	Channel raster to resource element mapping	65
5.4.2.3	Channel raster entries for each operating band	65
5.4.3	Synchronization raster	69
5.4.3.1	Synchronization raster and numbering	69
5.4.3.2	Synchronization raster to synchronization block resource element mapping	70
5.4.3.3	Synchronization raster entries for each operating band	70
5.4.4	TX–RX frequency separation	73
5.4A	Channel arrangement for CA	74
5.4A.1	Channel spacing for CA	74
5.4A.2	Channel raster for CA	75
5.4A.3	Synchronization raster for CA	75
5.4A.4	Tx-Rx frequency separation for CA	75
5.4B	Reserved	75
5.4C	Reserved	75
5.4D	Reserved	75
5.4E	Channel arrangement for V2X	75
5.4E.1	Channel spacing	75
5.4E.2	Channel raster	76
5.4E.2.1	NR-ARFCN and channel raster	76
5.4E.2.2	Channel raster to resource element mapping	76
5.4E.2.3	Channel raster entries for each operating band	76
5.4E.3	Synchronization raster for V2X	76
5.4I	Channel arrangement for RedCap	76
5.4I.1	Channel spacing for RedCap	76
5.4I.2	Channel raster for RedCap	76
5.4I.2.1	NR-ARFCN and channel raster	76
5.4I.2.2	Channel raster to resource element mapping	76
5.4I.2.3	Channel raster entries for each operating band	76
5.4I.3	Synchronization raster for RedCap	77
5.4I.4	Tx-Rx frequency separation for RedCap	77
5.5	Void	77
5.5A	Configurations for CA	77
5.5A.0	General	77
5.5A.1	Configurations for intra-band contiguous CA	78
5.5A.2	Configurations for intra-band non-contiguous CA	83
5.5A.3	Configurations for inter-band CA	88
5.5A.3.1	Configurations for inter-band CA (two bands)	88
5.5A.3.2	Configurations for inter-band CA (three bands)	126
5.5A.3.3	Configurations for inter-band CA (four bands)	193
5.5A.3.4	Configurations for inter-band CA (five bands)	228
5.5B	Configurations for DC	231
5.5C	Configurations for SUL	237
6	Transmitter characteristics	245
6.1	General	245
6.1A	General	245
6.1F	General	245
6.2	Transmitter power	245
6.2.1	UE maximum output power	245
6.2.1I	Void	247
6.2.2	UE maximum output power reduction	247
6.2.3	UE additional maximum output power reduction	250
6.2.3.1	General	250

6.2.3.2	A-MPR for NS_04	255	
6.2.3.3	A-MPR for NS_10	256	
6.2.3.4	A-MPR for NS_05 and NS_05U	256	
6.2.3.5	A-MPR for NS_40	260	
6.2.3.6	A-MPR for NS_43 and NS_43U	261	
6.2.3.7	A-MPR for NS_03 and NS_03U	262	
6.2.3.8	A-MPR for NS_37	262	
6.2.3.9	A-MPR for NS_38	263	
6.2.3.10	A-MPR for NS_39	263	
6.2.3.11	A-MPR for NS_41	264	
6.2.3.12	A-MPR for NS_42	264	
6.2.3.13	A-MPR for NS_18	265	
6.2.3.14	A-MPR for NS_21	266	
6.2.3.15	A-MPR for NS_24	267	
6.2.3.16	A-MPR for NS_27	268	
6.2.3.17	A-MPR for NS_46	269	
6.2.3.18	A-MPR for NS_47	270	
6.2.3.19	A-MPR for NS_50	271	
6.2.3.20	A-MPR for NS_44	273	
6.2.3.21	A-MPR for NS_12	274	
6.2.3.22	A-MPR for NS_13	274	
6.2.3.23	A-MPR for NS_14	274	
6.2.3.24	A-MPR for NS_15	275	
6.2.3.25	A-MPR for NS_45	276	
6.2.3.26	A-MPR for NS_48	276	
6.2.3.27	A-MPR for NS_49	278	
6.2.3.28	A-MPR for NS_51	280	
6.2.3.29	A-MPR for NS_07	281	
6.2.3.30	A-MPR for NS_56	281	
6.2.4	Configured transmitted power	282	
6.2A	Transmitter power for CA	284	
6.2A.0	General	284	
6.2A.1	UE maximum output power for CA	285	
6.2A.1.1	UE maximum output power for Intra-band contiguous CA	285	
6.2A.1.2	UE maximum output power for Intra-band non-contiguous CA	285	
6.2A.1.3	UE maximum output power for Inter-band CA	286	
6.2A.1.4	Void	291	
6.2A.1.5	Void	291	
6.2A.2	UE maximum output power reduction for CA	291	
6.2A.2.1	UE maximum output power reduction for Intra-band contiguous CA	291	
6.2A.2.2	UE maximum output power reduction for Intra-band non-contiguous CA	294	
6.2A.2.2.0	General	294	
6.2A.2.2.1	MPR to meet -30dBm/MHz	295	
6.2A.2.2.1.1	PC3 with indicating dualPA-Architecture supported	295	
6.2A.2.2.1.2	PC2 with indicating dualPA-Architecture supported	296	
6.2A.2.2.1.3	PC3 without indicating dualPA-Architecture supported	296	
6.2A.2.2.1.4	PC2 without indicating dualPA-Architecture supported	296	
6.2A.2.2.2	MPR to meet -13dBm/MHz	297	
6.2A.2.2.2.1	PC3 with indicating dualPA-Architecture supported	297	
6.2A.2.2.2.2	PC2 with indicating dualPA-Architecture supported	297	
6.2A.2.2.2.3	PC3 without indicating dualPA-Architecture supported	297	
6.2A.2.2.2.4	PC2 without indicating dualPA-Architecture supported	298	
6.2A.2.3	UE maximum output power reduction for Inter-band CA	298	

6.2A.2.4	Void	298
6.2A.3	UE additional maximum output power reduction for CA	298
6.2A.3.1	UE additional maximum output power reduction for Intra-band CA	298
6.2A.3.1.1	UE additional maximum output power reduction for Intra-band contiguous CA	298
6.2A.3.1.1.1	A-MPR for CA_NS_04	299
6.2A.3.1.1.1.2	Non-contiguous allocations	300
6.2A.3.1.2	UE additional maximum output power reduction for Intra-band non-contiguous CA	305
6.2A.3.1.3	UE additional maximum output power reduction for Inter-band CA	308
6.2A.4	Configured output power for CA	311
6.2A.4.1	Configured transmitted power level	311
6.2A.4.1.1	Configured transmitted power for Intra-band contiguous CA	311
6.2A.4.1.2	Configured transmitted power for Intra-band non-contiguous CA	313
6.2A.4.1.3	Configured transmitted power for Inter-band CA	315
6.2A.4.1.4	Void	319
6.2A.4.2	$\Delta T_{IB,c}$ for CA	319
6.2A.4.2.1	Void	319
6.2A.4.2.2	Void	319
6.2A.4.2.3	$\Delta T_{IB,c}$ for Inter-band CA (two bands)	319
6.2A.4.2.4	$\Delta T_{IB,c}$ for Inter-band CA (three bands)	327
6.2A.4.2.5	$\Delta T_{IB,c}$ for Inter-band CA (four bands)	337
6.2A.4.2.6	$\Delta T_{IB,c}$ for Inter-band CA (five bands)	343
6.2B	Transmitter power for NR-DC	343
6.2B.0	General	343
6.2B.1	UE maximum output power for NR-DC	343
6.2B.2	UE maximum output power reduction for NR-DC	344
6.2B.3	UE additional maximum output power reduction for NR-DC	344
6.2B.4.1	Configured transmitted power level for NR-DC	345
6.2B.4.2	$\Delta T_{IB,c}$ for NR-DC	349
6.2C	Transmitter power for SUL	349
6.2C.1	Configured transmitted power for SUL	349
6.2C.2	$\Delta T_{IB,c}$	349
6.2D	Transmitter power for UL MIMO	352
6.2D.1	UE maximum output power for UL MIMO	352
6.2D.2	UE maximum output power reduction for UL MIMO	353
6.2D.3	UE additional maximum output power reduction for UL MIMO	354
6.2D.4	Configured transmitted power for UL MIMO	355
6.2E	Transmitter power for V2X	356
6.2E.1	UE maximum output power for V2X	356
6.2E.1.1	General	356
6.2E.1.2	UE maximum output power for V2X concurrent operation	356
6.2E.2	UE maximum output power reduction for V2X	357
6.2E.2.1	General	357
6.2E.2.2	MPR for Power class 2 and Power class 3 V2X UE	357
6.2E.2.3	MPR for Power class 2 and Power class 3 V2X concurrent operation	359
6.2E.2.4	MPR for Power class 1 UE in Band n14	362
6.2E.3	UE additional maximum output power reduction for V2X	362
6.2E.3.1	General	362
6.2E.3.2	A-MPR for V2X UE by NS_33	363
6.2E.3.3	A-MPR for Power class 3 V2X UE by NS_52	367
6.2E.3.4	A-MPR for V2X concurrent operation	368
6.2E.4	Configured transmitted power for V2X	369
6.2E.4.1	General	369
6.2E.4.2	Configured transmitted power for inter-band V2X concurrent operation	370

6.2E.4.3	Configured transmitted power for intra-band V2X concurrent operation	371
6.2F	Transmitter power for shared spectrum channel access	373
6.2F.1	UE maximum output power	373
6.2F.1A	UE maximum output power for CA	374
6.2F.1A.1	UE maximum output power for inter-band CA	374
6.2F.1A.2	UE maximum output power for intra-band contiguous CA	374
6.2F.1B	UE maximum output power for NR-DC	375
6.2F.1D	UE maximum output power for UL MIMO	375
6.2F.2	UE maximum output power reduction	375
6.2F.2A	UE maximum output power reduction for CA	376
6.2F.2A.1	UE maximum output power reduction for inter-band CA	376
6.2F.2A.2	UE maximum output power reduction for intra-band contiguous CA	377
6.2F.2D	UE maximum output power reduction for UL MIMO	378
6.2F.3	UE additional maximum output power reduction	379
6.2F.3.1	General	379
6.2F.3.2	A-MPR for NS_28	380
6.2F.3.3	A-MPR for NS_29	380
6.2F.3.4	A-MPR for NS_30	381
6.2F.3.5	A-MPR for NS_31	381
6.2F.3.6	A-MPR for NS_53	382
6.2F.3.7	A-MPR for NS_54	382
6.2F.3.8	A-MPR for NS_58	383
6.2F.3.9	A-MPR for NS_59	384
6.2F.3.10	A-MPR for NS_60	385
6.2F.3.11	A-MPR for NS_61	385
6.2F.3A	UE additional maximum output power reduction for CA	386
6.2F.3A.1	UE additional maximum output power reduction for inter-band CA	386
6.2F.3D	UE additional maximum output power reduction for UL MIMO	386
6.2F.4	Configured transmitted power	386
6.2F.4D	Configured transmitted power UL MIMO	386
6.2G	Transmitter power for Tx Diversity	387
6.2G.1	UE maximum output power for Tx Diversity	387
6.2G.2	UE maximum output power reduction for Tx Diversity	387
6.2G.3	UE additional maximum output power reduction for Tx Diversity	387
6.2G.4	Configured transmitted power for Tx Diversity	387
6.2H	Transmitter power for CA with UL MIMO	388
6.2H.1	Transmitter power for intra-band UL contiguous CA with UL MIMO	388
6.2H.1.1	UE maximum output power for intra-band UL contiguous CA with UL MIMO	388
6.2H.1.2	UE maximum output power reduction for intra-band UL contiguous CA with UL MIMO	388
6.2H.1.3	UE additional maximum output power reduction for intra-band UL contiguous CA with UL MIMO	389
6.2H.1.4	Configured transmitted power for intra-band UL contiguous CA with UL MIMO	389
6.2I	Transmitter power for RedCap	389
6.2I.1	Maximum output power for RedCap	389
6.3	Output power dynamics	390
6.3.1	Minimum output power	390
6.3.2	Transmit OFF power	390
6.3.3	Transmit ON/OFF time mask	390
6.3.3.1	General	390

6.3.3.2	General ON/OFF time mask	391
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries	391
6.3.3.4	PRACH time mask	391
6.3.3.5	Void	393
6.3.3.6	SRS time mask	393
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	394
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	395
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	396
6.3.4	Power control	397
6.3.4.1	General	397
6.3.4.2	Absolute power tolerance	397
6.3.4.3	Relative power tolerance	397
6.3.4.4	Aggregate power tolerance	398
6.3A	Output power dynamics for CA	398
6.3A.1	Minimum output power for CA	398
6.3A.1.1	Minimum output power for intra-band contiguous CA	398
6.3A.1.2	Minimum output power for intra-band non-contiguous CA	398
6.3A.1.3	Minimum output power for inter-band CA	398
6.3A.1.4	Void	399
6.3A.2	Transmit OFF power for CA	399
6.3A.2.1	Transmit OFF power for intra-band contiguous CA	399
6.3A.2.2	Transmit OFF power for intra-band non-contiguous CA	399
6.3A.2.3	Transmit OFF power for inter-band CA	399
6.3A.2.4	Void	399
6.3A.3	Transmit ON/OFF time mask for CA	399
6.3A.3.1	Transmit ON/OFF time mask for intra-band contiguous CA	399
6.3A.3.2	Transmit ON/OFF time mask for intra-band non-contiguous CA	400
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA	400
6.3A.3.3.1	General	400
6.3A.3.3.2	Time mask for switching between two uplink carriers	400
6.3A.3.3.3	Time mask for switching between two uplink carriers with two transmit antenna connectors	402
6.3A.3.3.4	Time mask for switching between one uplink band with one transmit antenna connector and one uplink band with two transmit antenna connectors	403
6.3A.3.3.5	Time mask for switching between two uplink bands with two transmit antenna connectors	404
6.3A.3.4	Void	406
6.3A.4	Power control for CA	406
6.3A.4.1	Power control for intra-band contiguous CA	406
6.3A.4.1.1	Absolute power tolerance	406
6.3A.4.1.2	Relative power tolerance	406
6.3A.4.1.3	Aggregate power control tolerance	406
6.3A.4.2	Power control for intra-band non-contiguous CA	406
6.3A.4.2.1	Absolute power tolerance	406
6.3A.4.2.1.1	Minimum requirements	406
6.3A.4.2.2	Relative power tolerance	407
6.3A.4.2.2.1	Minimum requirements	407
6.3A.4.2.3	Aggregate power control tolerance	407
6.3A.4.3	Power control for inter-band CA	407
6.3A.4.4	Void	407
6.3B	Output power dynamics for NR-DC	407

6.3C	Output power dynamics for SUL	407
6.3C.1	Void	407
6.3C.2	Void	407
6.3C.3	Transmit ON/OFF time mask for SUL	407
6.3C.3.1	Time mask for switching between two uplink carriers	407
6.3C.3.2	Time mask for switching between two uplink carriers with two transmit antenna connectors	409
6.3C.3.3	Time mask for switching between one uplink band with one transmit antenna connector and one uplink band with two transmit antenna connectors	410
6.3C.3.4	Time mask for switching between two uplink bands with two transmit antenna connectors	411
6.3D	Output power dynamics for UL MIMO	412
6.3D.1	Minimum output power for UL MIMO	412
6.3D.2	Transmit OFF power for UL MIMO	412
6.3D.3	Transmit ON/OFF time mask for UL MIMO	412
6.3D.4	Power control for UL MIMO	413
6.3E	Output power dynamics for V2X	413
6.3E.1	Minimum output power for V2X	413
6.3E.1.1	General	413
6.3E.1.2	Minimum output power for V2X concurrent operation	413
6.3E.2	Transmit OFF power for V2X	414
6.3E.2.1	General	414
6.3E.2.2	Transmit OFF power for V2X concurrent operation	414
6.3E.3	Transmit ON/OFF time mask for V2X	414
6.3E.3.1	General	414
6.3E.3.2	General time mask	414
6.3E.3.3	S-SSB time mask	415
6.3E.3.4	Transmit ON/OFF time mask for V2X concurrent operation	415
6.3E.4	Power control for V2X	416
6.3E.4.1	General	416
6.3E.4.2	Absolute power tolerance	416
6.3E.4.3	Power control for V2X concurrent operation	417
6.3F	Output power dynamics for shared spectrum channel access	417
6.3F.1	Minimum output power	417
6.3F.2	Transmit OFF power	417
6.3F.3	Transmit ON/OFF time mask	417
6.3F.3.1	General	417
6.3F.3.2	General ON/OFF time mask	417
6.3F.3A	General ON/OFF mask for CA	418
6.3F.3A.1	General ON/OFF mask for inter-band CA	418
6.3F.4	Power control	418
6.3F.4.1	General	418
6.3F.4.2	Absolute power tolerance	418
6.3F.4.3	Relative power tolerance	418
6.3F.4.4	Aggregate power tolerance	418
6.3F.4A	Power control for inter-band CA	418
6.3G	Output power dynamics for Tx Diversity	418
6.3G.1	Minimum output power for Tx Diversity	418
6.3G.2	Transmit OFF power for Tx Diversity	418
6.3G.3	Transmit ON/OFF time mask for Tx Diversity	418
6.3G.4	Power control for Tx Diversity	419
6.3H	Output power dynamics for CA with UL MIMO	419

6.3H.1	Output power dynamics for intra-band UL contiguous CA with UL MIMO	419
6.3H.1.1	Minimum output power for intra-band UL contiguous CA with UL MIMO	419
6.3H.1.2	Transmit OFF power for intra-band UL contiguous CA with UL MIMO	419
6.3H.1.3	Transmit ON/OFF time mask for intra-band UL contiguous CA with UL MIMO	419
6.3H.1.4	Power control for intra-band UL contiguous CA with UL MIMO	419
6.4	Transmit signal quality	420
6.4.1	Frequency error	420
6.4.2	Transmit modulation quality	420
6.4.2.0	General	420
6.4.2.1	Error Vector Magnitude	420
6.4.2.1a	Error Vector Magnitude including symbols with transient period	421
6.4.2.2	Carrier leakage	422
6.4.2.3	In-band emissions	422
6.4.2.4	EVM equalizer spectrum flatness	423
6.4.2.4.1	Requirements for Pi/2 BPSK modulation	424
6.4.2.5	Phase continuity requirements for DMRS bundling	425
6.4A	Transmit signal quality for CA	426
6.4A.1	Frequency error for CA	426
6.4A.1.1	Frequency error for intra-band contiguous CA	426
6.4A.1.2	Frequency error for intra-band non-contiguous CA	427
6.4A.1.3	Frequency error for inter-band CA	427
6.4A.1.4	Void	427
6.4A.2	Transmit modulation quality for CA	427
6.4A.2.1	Transmit modulation quality for intra-band contiguous CA	427
6.4A.2.1.0	General	427
6.4A.2.1.1	Error Vector Magnitude	427
6.4A.2.1.2	In-band emissions	428
6.4A.2.1.3	Carrier leakage	431
6.4A.2.2	Transmit modulation quality for intra-band non-contiguous CA	431
6.4A.2.2.0	General	431
6.4A.2.2.1	Error Vector Magnitude	431
6.4A.2.2.2	In-band emissions	432
6.4A.2.2.3	Carrier leakage	432
6.4A.2.3	Transmit modulation quality for inter-band CA	432
6.4A.2.4	Void	433
6.4B	Transmit signal quality for NR-DC	433
6.4C	Transmit signal quality for SUL	433
6.4D	Transmit signal quality for UL MIMO	433
6.4D.0	General	433
6.4D.1	Frequency error for UL MIMO	434
6.4D.2	Transmit modulation quality for UL MIMO	434
6.4D.2.0	General	434
6.4D.2.1	Error Vector Magnitude	434
6.4D.2.2	Carrier leakage	434
6.4D.2.3	In-band emissions	434
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	434
6.4D.3	Time alignment error for UL MIMO	435
6.4D.4	Requirements for coherent UL MIMO	435
6.4E	Transmit signal quality for V2X	435
6.4E.1	Frequency error for V2X	435
6.4E.1.1	General	435
6.4E.1.2	Frequency error for V2X concurrent operation	436
6.4E.2	Transmit modulation quality for V2X	436

6.4E.2.1	General	436	
6.4E.2.2	Error Vector Magnitude for V2X	436	
6.4E.2.3	Carrier leakage for V2X	436	
6.4E.2.4	In-band emissions for V2X	436	
6.4E.2.5	EVM equalizer spectrum flatness for V2X	436	
6.4E.2.6	Transmit modulation quality for V2X concurrent operation	436	
6.4F	Transmit signal quality for shared spectrum channel access	437	
6.4F.1	Frequency error	437	
6.4F.2	Transmit modulation quality	437	
6.4F.2.0	General	437	
6.4F.2.1	Error Vector Magnitude	437	
6.4F.2.2	Carrier leakage	437	
6.4F.2.3	In-band emissions	437	
6.4F.2.4	EVM equalizer spectrum flatness	438	
6.4F.2A	Transmit modulation quality for CA	438	
6.4F.2A.1	Transmit modulation quality for inter-band CA	438	
6.4G	Transmit signal quality for Tx Diversity	439	
6.4G.1	Frequency error for Tx Diversity	439	
6.4G.2	Transmit modulation quality for Tx Diversity	439	
6.4G.2.0	General	439	
6.4H	Transmit signal quality for CA with UL MIMO	440	
6.4H.1	Transmit signal quality for intra-band UL contiguous CA with UL MIMO	440	
6.4H.1.1	Frequency error for intra-band UL contiguous CA with UL MIMO	440	
6.4H.1.2	Transmit modulation quality for intra-band UL contiguous CA with UL MIMO	440	
6.4H.1.2.0	General	440	
6.4H.1.2.1	Error Vector Magnitude	440	
6.4H.1.2.2	Carrier leakage	440	
6.4H.1.2.3	In-band emissions	441	
6.4H.1.3	Time alignment error for intra-band UL contiguous CA with UL MIMO	441	
6.4H.1.4	Coherent UL MIMO requirement for intra-band UL contiguous CA with UL MIMO	441	
6.5	Output RF spectrum emissions	441	
6.5.1	Occupied bandwidth	441	
6.5.2	Out of band emission	441	
6.5.2.1	General	441	
6.5.2.2	Spectrum emission mask	441	
6.5.2.3	Additional spectrum emission mask	442	
6.5.2.3.1	Requirements for network signalling value "NS_35"	442	
6.5.2.3.2	Requirements for network signalling value "NS_04"	442	
6.5.2.3.3	Requirements for network signalling values "NS_03" and "NS_03U"	443	
6.5.2.3.4	Requirements for network signalling value "NS_06" or "NS_07"	444	
6.5.2.3.5	Void	444	
6.5.2.3.6	Void	444	
6.5.2.3.7	Void	444	
6.5.2.3.8	Requirements for network signalling value "NS_27"	444	
6.5.2.3.9	Requirements for network signalling value "NS_21"	445	
6.5.2.4	Adjacent channel leakage ratio	445	
6.5.2.4.1	NR ACLR	446	
6.5.2.4.2	UTRA ACLR	446	
6.5.3	Spurious emissions	447	
6.5.3.0	General	447	
6.5.3.1	General spurious emissions	447	
6.5.3.2	Spurious emissions for UE co-existence	447	

6.5.3.3	Additional spurious emissions	456	
6.5.3.3.1	Requirement for network signalling value "NS_04"	456	
6.5.3.3.2	Requirement for network signalling value "NS_17"	457	
6.5.3.3.3	Requirement for network signalling value "NS_18"	457	
6.5.3.3.4	Requirement for network signalling values "NS_05" and "NS_05U"	457	
6.5.3.3.5	Requirement for network signalling values "NS_43" and "NS_43U"	457	
6.5.3.3.6	Requirement for network signalling value "NS_37"	458	
6.5.3.3.7	Requirement for network signalling value "NS_38"	458	
6.5.3.3.8	Requirement for network signalling value "NS_39"	458	
6.5.3.3.9	Requirement for network signalling value "NS_40"	458	
6.5.3.3.10	Requirement for network signalling value "NS_41"	459	
6.5.3.3.11	Requirement for network signalling value "NS_42"	459	
6.5.3.3.12	Requirement for network signalling value "NS_21"	459	
6.5.3.3.13	Requirement for network signalling value "NS_24"	460	
6.5.3.3.14	Requirement for network signalling value "NS_27"	460	
6.5.3.3.15	Requirement for network signalling value "NS_47"	460	
6.5.3.3.16	Requirement for network signalling value "NS_50"	461	
6.5.3.3.17	Requirement for network signalling value "NS_12"	461	
6.5.3.3.18	Requirement for network signalling value "NS_13"	461	
6.5.3.3.19	Requirement for network signalling value "NS_14"	462	
6.5.3.3.20	Requirement for network signalling value "NS_15"	462	
6.5.3.3.21	Requirement for network signalling value "NS_45"	462	
6.5.3.3.22	Requirement for network signalling values "NS_48" and "NS_51"	463	
6.5.3.3.23	Requirement for network signalling value "NS_49"	463	
6.5.3.3.24	Requirement for network signalling value "NS_44"	463	
6.5.3.3.25	Requirement for network signalling value "NS_46"	464	
6.5.3.3.26	Requirement for network signalling value "NS_07"	464	
6.5.3.3.27	Requirement for network signalling value "NS_56"	464	
6.5.4	Transmit intermodulation	465	
6.5A	Output RF spectrum emissions for CA	465	
6.5A.0	General	465	
6.5A.1	Occupied bandwidth for CA	466	
6.5A.1.1	Void	466	
6.5A.1.1a	Occupied bandwidth for Intra-band contiguous CA	466	
6.5A.1.2	Occupied bandwidth for Intra-band non-contiguous CA	466	
6.5A.1.3	Occupied bandwidth for Inter-band CA	466	
6.5A.2	Out of band emission for CA	466	
6.5A.2.1	General	466	
6.5A.2.2	Spectrum emission mask	466	
6.5A.2.2.1	Spectrum emission mask for intra-band contiguous CA	466	
6.5A.2.2.2	Spectrum emission mask for intra-band non-contiguous CA	467	
6.5A.2.2.3	Spectrum emission mask for Inter-band CA	467	
6.5A.2.2.4	Void	467	
6.5A.2.3	Additional spectrum emission mask for CA	467	
6.5A.2.3.1	Additional spectrum emission mask for intra-band contiguous CA	467	
6.5A.2.3.2	Additional spectrum emission mask for Intra-band non-contiguous CA	468	
6.5A.2.3.3	Additional spectrum emission mask for Inter-band CA	468	
6.5A.2.4	Adjacent channel leakage ratio	468	
6.5A.2.4.1	NR ACLR	468	
6.5A.2.4.2	UTRA ACLR	470	
6.5A.3	Spurious emission for CA	470	
6.5A.3.1	General spurious emissions	470	
6.5A.3.2	Spurious emissions for UE co-existence	471	

6.5A.3.2.1	Spurious emissions for UE co-existence for intra-band contiguous CA	471
6.5A.3.2.2	Spurious emissions for UE co-existence for intra-band non-contiguous CA	475
6.5A.3.2.3	Spurious emissions for UE co-existence for Inter-band CA	476
6.5A.3.2.4	Void	483
6.5A.3.2.5	Void	483
6.5A.3.2.6	Void	483
6.5A.3.3	Additional spurious emissions for CA	483
6.5A.3.3.1	Additional spurious emissions for intra-band contiguous CA	483
6.5A.3.3.2	Additional spurious emissions for intra-band non-contiguous CA	484
6.5A.4	Transmit intermodulation for CA	484
6.5A.4.2.1	Transmit intermodulation for intra-band contiguous CA	484
6.5A.4.2.2	Void	484
6.5B	Output RF spectrum emissions for NR-DC	485
6.5D	Output RF spectrum emissions for UL MIMO	485
6.5D.1	Occupied bandwidth for UL MIMO	485
6.5D.2	Out of band emission for UL MIMO	485
6.5D.3	Spurious emission for UL MIMO	485
6.5D.4	Transmit intermodulation for UL MIMO	486
6.5E	Output RF spectrum emissions for V2X	486
6.5E.1	Occupied bandwidth for V2X	486
6.5E.1.1	General	486
6.5E.1.2	Occupied bandwidth for V2X concurrent operation	486
6.5E.2	Out of band emission for V2X	486
6.5E.2.1	General	486
6.5E.2.2	Spectrum emission mask	486
6.5E.2.2.1	General	486
6.5E.2.2.2	Spectrum emission mask for V2X concurrent operation	487
6.5E.2.3	Additional Spectrum emission mask	487
6.5E.2.3.1	Requirements for network signalling value "NS_33"	487
6.5E.2.3.2	Requirements for network signalling value "NS_52"	487
6.5E.2.3.3	Requirements for network signalling value "NS_06"	488
6.5E.2.4	Adjacent channel leakage ratio	488
6.5E.2.4.1	General	488
6.5E.2.4.2	ACLR for V2X concurrent operation	488
6.5E.3	Spurious emissions for V2X	488
6.5E.3.1	General spurious emissions	488
6.5E.3.2	Spurious emissions for UE co-existence	489
6.5E.3.3	Spurious emissions for UE co-existence for V2X concurrent operation	489
6.5E.3.4	Additional spurious emissions requirements for V2X	490
6.5E.3.4.1	General	490
6.5E.3.4.2	Requirements for network signalling value "NS_33"	490
6.5E.3.4.3	Void	490
6.5E.4	Transmit intermodulation	490
6.5E.4.1	General	490
6.5E.4.2	Transmit intermodulation for V2X concurrent operation	490
6.5F	Output RF spectrum emissions for shared spectrum channel access	491
6.5F.1	Occupied bandwidth	491
6.5F.2	Out of band emission	491
6.5F.2.1	General	491
6.5F.2.2	Spectrum emission mask for operation with shared spectrum channel access	491
6.5F.2.2.0	General	491
6.5F.2.2.1	Spectrum emission mask for non-transmitted channels	492
6.5F.2.3	Additional spectrum emission mask	492

6.5F.2.4	Adjacent channel leakage ratio	492
6.5F.2.4.0	General	492
6.5F.2.4.1	Shared spectrum channel access ACLR	492
6.5F.2.4.2	Additional requirement for network signalled value "NS_29"	492
6.5F.2A	Out of band emission for CA	493
6.5F.2A.1	Spectrum emission mask for CA	493
6.5F.2A.1.1	Spectrum emission mask for Inter-band CA	493
6.5F.2A.1.2	Spectrum emission mask for Intra-band contiguous CA	493
6.5F.2A.1.2.1	General	493
6.5F.2A.1.2.2	Intra-band contiguous CA spectrum emission mask for non-transmitted channels	493
6.5F.2A.2	Adjacent channel leakage ratio for CA	494
6.5F.2A.2.1	Adjacent channel leakage ratio for inter-band CA	494
6.5F.2A.2.2	Adjacent channel leakage ratio for intra-band contiguous CA	494
6.5F.3	Spurious emissions	494
6.5F.3.0	General	494
6.5F.3.1	General spurious emissions	495
6.5F.3.2	Spurious emissions for UE co-existence	495
6.5F.3.3	Additional spurious emissions	495
6.5F.3.3.0	General	495
6.5F.3.3.1	Requirement for network signalling value "NS_28"	495
6.5F.3.3.2	Requirement for network signalling value "NS_29"	495
6.5F.3.3.3	Requirement for network signalling value "NS_30"	497
6.5F.3.3.4	Requirement for network signalling value "NS_31"	498
6.5F.3.3.5	Requirements for network signalling value "NS_53" or "NS_54" or "NS_60"	499
6.5F.3.3.6	Requirements for network signalling value "NS_58"	499
6.5F.3.3.7	Requirements for network signalling value "NS_61"	499
6.5F.4	Transmit intermodulation	499
6.5G	Output RF spectrum emissions for Tx Diversity	500
6.5G.1	Occupied bandwidth for Tx Diversity	500
6.5G.2	Out of band emission for Tx Diversity	500
6.5G.3	Spurious emission for Tx Diversity	500
6.5G.4	Transmit intermodulation for Tx Diversity	500
6.5H	Output RF spectrum emissions for CA with UL MIMO	500
6.5H.1	Output RF spectrum emissions for intra-band UL contiguous CA with UL MIMO	500
6.5H.1.1	Occupied bandwidth for intra-band UL contiguous CA with UL MIMO	500
6.5H.1.2	Out of band emission for intra-band UL contiguous CA with UL MIMO	500
6.5H.1.3	Spurious emission for intra-band UL contiguous CA with UL MIMO	501
6.5H.1.4	Transmit intermodulation for intra-band UL contiguous CA with UL MIMO	501
6.6	Void	501
6.6E	Time alignment error	501
7	Receiver characteristics	502
7.1	General	502
7.1A	General	502
7.1F	General	503
7.1I	General	503
7.2	Diversity characteristics	503
7.3	Reference sensitivity	503
7.3.1	General	503
7.3.2	Reference sensitivity power level	503
7.3.3	$\Delta R_{IB,c}$	514
7.3A	Reference sensitivity for CA	514
7.3A.1	General	514

7.3A.2	Reference sensitivity power level for CA	515
7.3A.2.1	Reference sensitivity power level for Intra-band contiguous CA	515
7.3A.2.2	Reference sensitivity power level for Intra-band non-contiguous CA	515
7.3A.2.3	Reference sensitivity power level for Inter-band CA	516
7.3A.2.4	Void	516
7.3A.3	$\Delta R_{IB,c}$ for CA	517
7.3A.3.1	General	517
7.3A.3.2	$\Delta R_{IB,c}$ for Inter-band CA	517
7.3A.3.2.1	$\Delta R_{IB,c}$ for two bands	518
7.3A.3.2.2	Void	522
7.3A.3.2.3	$\Delta R_{IB,c}$ for three bands	522
7.3A.3.2.4	$\Delta R_{IB,c}$ for four bands	530
7.3A.3.2.5	$\Delta R_{IB,c}$ for five bands	536
7.3A.3.3	$\Delta R_{IB,c}$ for Intra-band CA	536
7.3A.4	Reference sensitivity exceptions due to UL harmonic interference for CA	536
7.3A.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA	546
7.3A.6	Reference sensitivity exceptions due to cross band isolation for CA	575
7.3B	Reference sensitivity for NR-DC	580
7.3C	Reference sensitivity for SUL	580
7.3C.1	General	580
7.3C.2	Reference sensitivity power level for SUL	580
7.3C.3	$\Delta R_{IB,c}$ for SUL	584
7.3C.3.1	General	584
7.3C.3.2	SUL band combination	584
7.3C.3.2.1	$\Delta R_{IB,c}$ for two bands	584
7.3C.3.2.2	$\Delta R_{IB,c}$ for three bands	585
7.3C.3.2.3	$\Delta R_{IB,c}$ for four bands	585
7.3D	Reference sensitivity for UL MIMO	585
7.3E	Reference sensitivity for V2X	585
7.3E.1	General	585
7.3E.2	Minimum requirements	586
7.3E.3	Reference sensitivity power level for V2X concurrent operation	586
7.3F	Reference sensitivity for shared spectrum channel access	588
7.3F.1	General	588
7.3F.2	Reference sensitivity power level	589
7.3F.3	Void	590
7.3F.4	Void	590
7.3F.4A	Shared spectrum channel access CA	590
7.3F.4A.1	Intra-band contiguous shared spectrum channel access CA	590
7.3F.5	Void	590
7.3F.5.1	Void	590
7.3F.5.2	Void	590
7.3F.5.3	Void	590
7.3G	Reference sensitivity for Tx Diversity	590
7.3G.5	Void	590
7.3G.5.0	Void	590
7.3I	Reference sensitivity for RedCap	590
7.3I.1	General	590
7.3I.2	Reference sensitivity power level	590
7.4	Maximum input level	597
7.4A	Maximum input level for CA	597
7.4A.1	Maximum input level for Intra-band contiguous CA	597
7.4A.2	Maximum input level for Intra-band non-contiguous CA	598

7.4A.3	Maximum input level for Inter-band CA	598	
7.4B	Maximum input level for NR-DC	598	
7.4D	Maximum input level for UL MIMO	598	
7.4E	Maximum input level for V2X	598	
7.4E.1	General	598	
7.4E.2	Maximum input level for V2X concurrent operation	599	
7.5	Adjacent channel selectivity	599	
7.5A	Adjacent channel selectivity for CA	601	
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA	601	
7.5A.2	Adjacent channel selectivity Intra-band non-contiguous CA	603	
7.5A.3	Adjacent channel selectivity Inter-band CA	604	
7.5B	Adjacent channel selectivity for NR-DC	604	
7.5D	Adjacent channel selectivity for UL MIMO	604	
7.5E	Adjacent channel selectivity for V2X	604	
7.5E.1	General	604	
7.5E.2	Adjacent channel selectivity for V2X concurrent operation	606	
7.5F	Adjacent channel selectivity for shared spectrum channel access	606	
7.5F.1	General	606	
7.5F.1A	Adjacent channel selectivity for shared spectrum channel access CA	607	
7.5F.1A.1	Intra-band contiguous shared spectrum channel access CA	607	
7.5F.2	Void	608	
7.6	Blocking characteristics	608	
7.6.1	General	608	
7.6.2	In-band blocking	608	
7.6.3	Out-of-band blocking	610	
7.6.4	Narrow band blocking	614	
7.6A	Blocking characteristics for CA	614	
7.6A.1	General	614	
7.6A.2	In-band blocking for CA	614	
7.6A.2.1	In-band blocking for Intra-band contiguous CA	614	
7.6A.2.2	In-band blocking for Intra-band non-contiguous CA	616	
7.6A.2.3	In-band blocking for Inter-band CA	616	
7.6A.3	Out-of-band blocking for CA	617	
7.6A.3.1	Out-of-band blocking for Intra-band contiguous CA	617	
7.6A.3.2	Out-of-band blocking for Intra-band non-contiguous CA	618	
7.6A.3.3	Out-of-band blocking for Inter-band CA	618	
7.6A.4	Narrow band blocking for CA	620	
7.6A.4.1	Narrow band blocking for Intra-band contiguous CA	620	
7.6A.4.2	Narrow band blocking for Intra-band non-contiguous CA	620	
7.6A.4.3	Narrow band blocking for Inter-band CA	620	
7.6B	Blocking characteristics for NR-DC	621	
7.6C	Blocking characteristics for SUL	621	
7.6C.1	General	621	
7.6C.2	In-band blocking for SUL	621	
7.6C.3	Out-of-band blocking for SUL	621	
7.6C.4	Narrow band blocking for SUL	622	
7.6D	Blocking characteristics for UL MIMO	622	
7.6E	Blocking characteristics for V2X	622	
7.6E.1	General	622	
7.6E.2	In-band blocking	622	
7.6E.2.1	General	622	
7.6E.2.2	In-band blocking for V2X concurrent operation	623	
7.6E.3	Out-of-band blocking	623	

7.6E.3.1	General	623	
7.6E.3.2	Out-of-band blocking for V2X concurrent operation	624	
7.6F	Blocking characteristics for shared spectrum channel access	624	
7.6F.1	General	624	
7.6F.2	In-band blocking	624	
7.6F.2.1	General	624	
7.6F.2.2	Void	625	
7.6F.2A	In-band blocking for shared spectrum CA	625	
7.6F.2A.1	Intra-band contiguous shared spectrum channel access CA	625	
7.6F.3	Out-of-band blocking	626	
7.6F.3.1	General	626	
7.6F.3.2	Void	627	
7.6F.3A	Out-of-band blocking for shared spectrum CA	627	
7.6F.3A.1	Intra-band contiguous shared spectrum channel access CA	627	
7.6I	Blocking characteristics for RedCap	628	
7.7	Spurious response	628	
7.7A	Spurious response for CA	629	
7.7A.1	Spurious response for Intra-band contiguous CA	629	
7.7A.2	Spurious response for Intra-band non-contiguous CA	629	
7.7A.3	Spurious response for Inter-band CA	629	
7.7B	Spurious response for NR-DC	630	
7.7D	Spurious response for UL MIMO	630	
7.7E	Spurious response for V2X	630	
7.7E.1	General	630	
7.7E.2	Spurious response for V2X concurrent operation	630	
7.7F	Spurious response for shared spectrum channel access	631	
7.7F.1	General	631	
7.7F.1A	Spurious response for shared spectrum channel access CA	631	
7.7F.1A.1	Intra-band contiguous shared spectrum channel access CA	631	
7.7F.2	Void	631	
7.8	Intermodulation characteristics	632	
7.8.1	General	632	
7.8.2	Wide band Intermodulation	632	
7.8A	Intermodulation characteristics for CA	634	
7.8A.1	General	634	
7.8A.2	Wide band intermodulation for CA	634	
7.8A.2.1	Wide band intermodulation for Intra-band contiguous CA	634	
7.8A.2.2	Wide band intermodulation for Intra-band non-contiguous CA	635	
7.8A.2.3	Wide band intermodulation for Inter-band CA	635	
7.8B	Intermodulation characteristics for NR-DC	635	
7.8D	Intermodulation characteristics for UL MIMO	636	
7.8E	Intermodulation characteristics for V2X	636	
7.8E.1	General	636	
7.8E.2	Wide band Intermodulation	636	
7.8E.2.1	General	636	
7.8E.2.2	Wide band Intermodulation for V2X concurrent operation	637	
7.8F	Intermodulation characteristics for shared spectrum channel access	637	
7.8F.1	General	637	
7.8F.2	Wide band Intermodulation	637	
7.9	Spurious emissions	638	
7.9A	Spurious emissions for CA	638	
7.9A.1	Void	638	
7.9A.2	Void	638	

7.9A.3	Spurious emissions for Inter-band CA	638
7.9B	Spurious emissions for NR-DC	639

Annex A (normative): Measurement channels 640

A.1	General	640
A.2	UL reference measurement channels	640
A.2.1	General	640
A.2.2	Reference measurement channels	642
A.2.2.1	DFT-s-OFDM Pi/2-BPSK	642
A.2.2.2	DFT-s-OFDM QPSK	643
A.2.2.3	DFT-s-OFDM 16QAM	643
A.2.2.4	DFT-s-OFDM 64QAM	645
A.2.2.5	DFT-s-OFDM 256QAM	647
A.2.2.6	CP-OFDM QPSK	649
A.2.2.7	CP-OFDM 16QAM	651
A.2.2.8	CP-OFDM 64QAM	653
A.2.2.9	CP-OFDM 256QAM	655
A.2.3	Reference measurement channels for TDD	657
A.2.3.1	DFT-s-OFDM Pi/2-BPSK	657
A.2.3.2	DFT-s-OFDM QPSK	657
A.2.3.3	DFT-s-OFDM 16QAM	657
A.2.3.4	DFT-s-OFDM 64QAM	657
A.2.3.5	DFT-s-OFDM 256QAM	657
A.2.3.6	CP-OFDM QPSK	658
A.2.3.7	CP-OFDM 16QAM	658
A.2.3.8	CP-OFDM 64QAM	658
A.2.3.9	CP-OFDM 256QAM	658
A.3	DL reference measurement channels	659
A.3.1	General	659
A.3.2	DL reference measurement channels for FDD	661
A.3.2.1	General	661
A.3.2.2	FRC for receiver requirements for QPSK	662
A.3.2.3	FRC for maximum input level for 64QAM	665
A.3.2.4	FRC for maximum input level for 256 QAM	668
A.3.2.5	FRC for maximum input level for 1024 QAM	671
A.3.3	DL reference measurement channels for TDD	674
A.3.3.1	General	674
A.3.3.2	FRC for receiver requirements for QPSK	675
A.3.3.3	FRC for maximum input level for 64QAM	678
A.3.3.4	FRC for maximum input level for 256 QAM	681
A.3.3.5	FRC for maximum input level for 1024 QAM	684
A.4	CSI reference measurement channels	687
A.5	OFDMA Channel Noise Generator (OCNG)	687
A.5.1	OCNG Patterns for FDD	687
A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs	687
A.5.2	OCNG Patterns for TDD	687
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	687
A.6	Void	688
A.7	V2X reference measurement channels	688
A.7.1	General	688

A.7.2	FRC for V2X receiver requirements for QPSK	688
A.7.3	FRC for maximum input level for 64QAM	690
A.7.4	FRC for maximum input level for 256QAM	691

Annex B (informative): Void 693

Annex C (informative): Downlink physical channels 694

C.1	General	694
C.2	Setup	694
C.3	Connection	694
C.3.1	Measurement of Receiver Characteristics	694

Annex D (normative): Characteristics of the interfering signal 695

D.1	General	695
D.2	Void	695

Annex E (normative): Environmental conditions 695

E.1	General	695
E.2	Environmental	695
E.2.1	Temperature	695
E.2.2	Voltage	696
E.2.3	Vibration	696

Annex F (normative): Transmit modulation 697

F.0	General	697
F.1	Measurement Point	697
F.2	Basic Error Vector Magnitude measurement	697
F.3	Basic in-band emissions measurement	698
F.4	Modified signal under test	699
F.5	Window length	701
F.5.1	Timing offset	701
F.5.2	Window length	701
F.5.3	Window length for normal CP	701
F.5.4	Window length for Extended CP	702
F.5.5	Window length for PRACH	703
F.6	Averaged EVM	704
F.7	Spectrum Flatness	705
F.8	EVM measurement for 2Tx	705
F.9	Phase offset measurement for DMRS bundling	705
F.9.1	Measurement point	705
F.9.2	Symbols used	705
F.9.3	Modified test signal	705
F.9.4	Phase offset measurement	706
F.10	EVM for UL MIMO	706
F10.1	General	706

F10.2	MIMO Equalization	707
F10.3	Layer processing	707

Annex G (normative): Difference of relative phase and power errors 709

G.0	General	709
G.1	Measurement Point	709
G.2	Relative Phase Error Measurement	709
G.2.1	Symbols and subcarriers used	709
G.2.2	CFO (carrier frequency offset) correction	710
G.2.3	Steps of the measurement method	710

Annex H (informative): Void 711

Annex I (informative): Void 711

Annex J (informative): Void 711

Annex K (informative): Void 711

Annex L (normative): ModifiedMPR-Behavior 711

L.1	Indication of modified MPR behavior	711
-----	-------------------------------------	-----

Annex M (normative): Declared Supported Post Antenna Gain for UE 715

M.1	FRMCS operating bands	715
-----	-----------------------	-----

Annex N (informative): Change history 716

