

3GPP TS 38.101-3 V15.29.0 (2025-06)

Technical Specification

3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; User Equipment (UE) radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios (Release 15)



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP..

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented.

This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification.

Specifications and Reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

3GPP

Postal address

3GPP support office address
650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet
<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2025, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword		11
1	Scope	12
2	References	12
3	Definitions, symbols and abbreviations	13
3.1	Definitions	13
3.2	Symbols	13
3.3	Abbreviations	13
4	General	14
4.1	Relationship between minimum requirements and test requirements	14
4.2	Applicability of minimum requirements	14
4.3	Specification suffix information	15
5	Operating bands and channel arrangement	16
5.1	General	16
5.2	Operating bands	16
5.2A	Operating bands for CA	16
5.2A.1	Inter-band CA between FR1 and FR2	16
5.2B	Operating bands for DC	17
5.2B.1	General	17
5.2B.2	Void	17
5.2B.3	Void	17
5.2B.4	Void	17
5.2B.5	Void	17
5.2B.6	Void	17
5.2B.7	Void	17
5.3	UE Channel bandwidth	17
5.3A	UE Channel bandwidth for CA	17
5.3A.1	Inter-band CA between FR1 and FR2	17
5.3B	UE Channel bandwidth for DC	17
5.3B.0	General	17
5.3B.1	Intra-band EN-DC in FR1	18
5.3B.1.1	General	18
5.3B.1.2	BCS for Intra-band contiguous EN-DC	18
5.3B.1.3	BCS for Intra-band non-contiguous EN-DC	19
5.4	Void	20
5.4A	Channel arrangement for CA	20
5.4B	Channel arrangement for DC	20
5.4B.1	Channel spacing for intra-band EN-DC carriers	20
5.5	Configuration	21
5.5A	Configuration for CA	21
5.5A.1	Inter-band CA configurations between FR1 and FR2	21
5.5B	Configuration for DC	24
5.5B.1	General	24
5.5B.2	Intra-band contiguous EN-DC	25
5.5B.3	Intra-band non-contiguous EN-DC	25
5.5B.4	Inter-band EN-DC within FR1	25
5.5B.4.1	Inter-band EN-DC configurations within FR1 (two bands)	25
5.5B.4.2	Inter-band EN-DC configurations within FR1 (three bands)	28
5.5B.4.3	Inter-band EN-DC configurations within FR1 (four bands)	33
5.5B.4.4	Inter-band EN-DC configurations within FR1 (five bands)	37

5.5B.4.5	Inter-band EN-DC configurations within FR1 (six bands)	39
5.5B.4a	Inter-band NE-DC within FR1	39
5.5B.4a.1	Inter-band NE-DC configurations within FR1 (two bands)	39
5.5B.5	Inter-band EN-DC including FR2	40
5.5B.5.1	Inter-band EN-DC configurations including FR2 (two bands)	40
5.5B.5.2	Inter-band EN-DC configurations including FR2 (three bands)	44
5.5B.5.3	Inter-band EN-DC configurations including FR2 (four bands)	47
5.5B.5.4	Inter-band EN-DC configurations including FR2 (five bands)	48
5.5B.5.5	Void	49
5.5B.6	Inter-band EN-DC including FR1 and FR2	49
5.5B.6.1	Void	49
5.5B.6.2	Inter-band EN-DC configurations including FR1 and FR2 (three bands)	49
5.5B.6.3	Inter-band EN-DC configurations including FR1 and FR2 (four bands)	52
5.5B.6.4	Inter-band EN-DC configurations including FR1 and FR2 (five bands)	53
5.5B.6.5	Inter-band EN-DC configurations including FR1 and FR2 (six bands)	54
5.5B.7	Inter-band NR-DC between FR1 and FR2	54
5.5B.7.0	General	54
5.5B.7.1	Inter-band NR-DC configurations between FR1 and FR2 (two bands)	54
6	Transmitter characteristics	56
6.1	General	56
6.2	Void	56
6.2A	Transmitter power for CA	56
6.2A.1	UE maximum output power for CA	56
6.2A.1.1	Inter-band CA between FR1 and FR2	56
6.2A.2	UE maximum output power reduction for CA	56
6.2A.2.1	Inter-band CA between FR1 and FR2	56
6.2A.3	UE additional maximum output power reduction for CA	56
6.2A.4	Configured output power for CA	56
6.2A.4.1	Configured output power level	56
6.2A.4.2	$\Delta T_{IB,c}$ for CA	57
6.2A.4.2.1	$\Delta T_{IB,c}$ for Inter-band CA between FR1 and FR2	57
6.2B	Transmitter power for DC	57
6.2B.1	UE maximum output power for DC	57
6.2B.1.1	Intra-band contiguous EN-DC	57
6.2B.1.2	Intra-band non-contiguous EN-DC	58
6.2B.1.3	Inter-band EN-DC within FR1	58
6.2B.1.3a	Inter-band NE-DC within FR1	60
6.2B.1.4	Inter-band EN-DC including FR2	61
6.2B.1.5	Inter-band EN-DC including both FR1 and FR2	61
6.2B.2	UE maximum output power reduction for DC	61
6.2B.2.0	General	61
6.2B.2.1	Intra-band contiguous EN-DC	61
6.2B.2.1.1	General	61
6.2B.2.1.2	MPR for power class 3 and power class 2	62
6.2B.2.2	Intra-band non-contiguous EN-DC	62
6.2B.2.2.1	General	62
6.2B.2.2.2	MPR for power class 3 and power class 2	63
6.2B.2.3	Inter-band EN-DC within FR1	64
6.2B.2.3a	Inter-band NE-DC within FR1	64
6.2B.2.4	Inter-band EN-DC including FR2	64
6.2B.2.5	Inter-band EN-DC including both FR1 and FR2	64
6.2B.3	UE additional maximum output power reduction for EN-DC	64
6.2B.3.1	Intra-band contiguous EN-DC	64

6.2B.3.1.0	General	64	
6.2B.3.1.1	A-MPR for DC_(n)71AA	64	
6.2B.3.1.2	A-MPR for NS_04	66	
6.2B.3.2	Intra-band non-contiguous EN-DC	68	
6.2B.3.2.0	General	68	
6.2B.3.2.1	A-MPR for NS_04	68	
6.2B.3.3	Inter-band EN-DC within FR1	70	
6.2B.3.3A	Inter-band NE-DC within FR1	71	
6.2B.3.4	Inter-band EN-DC including FR2	72	
6.2B.3.5	Inter-band EN-DC including both FR1 and FR2	72	
6.2B.4	Configured output power for DC	72	
6.2B.4.1	Configured output power level	72	
6.2B.4.1.1	Intra-band contiguous EN-DC	72	
6.2B.4.1.2	Intra-band non-contiguous EN-DC	76	
6.2B.4.1.3	Inter-band EN-DC within FR1	77	
6.2B.4.1.3a	Inter-band NE-DC within FR1	80	
6.2B.4.1.4	Inter-band EN-DC including FR2	83	
6.2B.4.1.5	Inter-band EN-DC including both FR1 and FR2	83	
6.2B.4.2	$\Delta T_{IB,c}$ for DC	84	
6.2B.4.2.0	General	84	
6.2B.4.2.1	Intra-band contiguous EN-DC	84	
6.2B.4.2.2	Intra-band non-contiguous EN-DC	84	
6.2B.4.2.3	Inter-band EN-DC within FR1	84	
6.2B.4.2.3.1	$\Delta T_{IB,c}$ for EN-DC two bands	84	
6.2B.4.2.3.5	$\Delta T_{IB,c}$ for EN-DC six bands	97	
6.2B.4.2.3a	Inter-band NE-DC within FR1	97	
6.2B.4.2.4	Inter-band EN-DC including FR2	97	
6.2B.4.2.4.1	$\Delta T_{IB,c}$ for EN-DC two bands	97	
6.2B.4.2.4.2	$\Delta T_{IB,c}$ for EN-DC three bands	97	
6.2B.4.2.4.3	$\Delta T_{IB,c}$ for EN-DC four bands	97	
6.2B.4.2.4.4	$\Delta T_{IB,c}$ for EN-DC five bands	97	
6.2B.4.2.4.5	Void	98	
6.2B.4.2.5	Inter-band EN-DC including both FR1 and FR2	98	
6.2B.4.2.5.1	$\Delta T_{IB,c}$ for EN-DC three bands	98	
6.2B.4.2.5.2	$\Delta T_{IB,c}$ for EN-DC four bands	98	
6.2B.4.2.5.3	$\Delta T_{IB,c}$ for EN-DC five bands	98	
6.2B.4.2.5.4	$\Delta T_{IB,c}$ for EN-DC six bands	98	
6.2B.5	Configured output power for NR-DC	98	
6.2B.5.1	Configured output power level	98	
6.2B.5.1.1	Inter-band NR-DC between FR1 and FR2	98	
6.3	Output power dynamics	98	
6.3A	Output power dynamics for CA	99	
6.3B	Output power dynamics for DC	99	
6.3B.0	General	99	
6.3B.1	Output power dynamics for EN-DC with UL sharing from UE perspective	99	
6.3B.1.1	E-UTRA and NR switching time mask for TDM based UL sharing from UE perspective	99	
6.3B.1a	Output power dynamics for NE-DC with UL sharing from UE perspective	100	
6.3B.2	Output power dynamics for intra-band EN-DC without dual PA capability	100	
6.3B.3	Output power dynamics for intra-band EN-DC with dual PA capability	101	
6.4	Void	102	
6.4A	Transmit signal quality for CA	102	
6.4A.1	Frequency error for CA	102	
6.4A.2	Transmit modulation quality for CA	102	

6.4B	Transmit signal quality for DC	102
6.4B.2	Transmit modulation quality for DC	103
6.4B.2.1	Transmit modulation quality for Intra-band contiguous EN-DC	103
6.4B.2.1.1	Error Vector Magnitude	103
6.4B.2.1.2	Carrier leakage	103
6.4B.2.1.3	In-band emissions	103
6.4B.2.2	Transmit modulation quality for Intra-band non-contiguous EN-DC	103
6.4B.2.2.1	Error Vector Magnitude	103
6.4B.2.2.2	Carrier leakage	103
6.4B.2.2.3	In-band emissions	104
6.4B.2.3a	Transmit modulation quality for Inter-band NE-DC within FR1	104
6.4B.2.4	Transmit modulation quality for Inter-band EN-DC including FR2	104
6.4B.2.5	Transmit modulation quality for inter-band EN-DC including both FR1 and FR2	104
6.5	Void	104
6.5A	Output RF spectrum emissions for CA	104
6.5A.1	Occupied bandwidth for CA	104
6.5A.2	Out-of-band emissions for CA	104
6.5A.3	Spurious emissions for CA	105
6.5A.3.1	Inter-band CA between FR1 and FR2	105
6.5A.4	Transmit intermodulation for CA	105
6.5B	Output RF spectrum emissions for DC	105
6.5B.1	Occupied bandwidth for EN-DC	105
6.5B.1.4	Inter-band EN-DC including FR2	105
6.5B.1.5	Inter-band EN-DC including both FR1 and FR2	105
6.5B.2	Out-of-band emissions for DC	105
6.5B.2.1	Intra-band contiguous EN-DC	105
6.5B.2.1.1	Spectrum emissions mask	106
6.5B.2.1.2	Additional spectrum emissions mask	106
6.5B.2.1.2.1	Requirements for network signalled value "NS_35"	106
6.5B.2.1.2.2	Requirements for network signalled value "NS_04"	106
6.5B.2.1.3	Adjacent channel leakage ratio	107
6.5B.2.2	Intra-band non-contiguous EN-DC	107
6.5B.2.2.1	Spectrum emissions mask	107
6.5B.2.2.2	Additional spectrum emissions mask	107
6.5B.2.2.3	Adjacent channel leakage ratio	107
6.5B.2.3	Inter-band EN-DC within FR1	108
6.5B.2.3a	Inter-band NE-DC within FR1	108
6.5B.2.4	Inter-band EN-DC including FR2	108
6.5B.2.5	Inter-band EN-DC including both FR1 and FR2	108
6.5B.3	Spurious emissions for DC	108
6.5B.3.1	Intra-band contiguous EN-DC	108
6.5B.3.1.1	General spurious emissions	108
6.5B.3.1.2	Spurious emission band UE co-existence	108
6.5B.3.2	Intra-band non-contiguous EN-DC	109
6.5B.3.2.1	General spurious emissions	109
6.5B.3.2.2	Spurious emission band UE co-existence	109
6.5B.3.3	Inter-band EN-DC within FR1	110
6.5B.3.3.2	Spurious emission band UE co-existence	110
6.5B.3.3a	Inter-band NE-DC within FR1	115
6.5B.3.3a.1	General spurious emissions	115
6.5B.3.3a.2	Spurious emission band UE co-existence	115
6.5B.3.4	Inter-band EN-DC including FR2	116
6.5B.3.4.1	Spurious emission band UE co-existence	116

6.5B.3.5	Inter-band EN-DC including both FR1 and FR2	116
6.5B.3.5.1	Spurious emission band UE co-existence	116
6.5B.4	Additional spurious emissions	116
6.5B.4.1	General	116
6.5B.4.1.1	Void	117
6.5B.4.2	Intra-band contiguous EN-DC	117
6.5B.4.2.1	Minimum requirement (network signalled value "NS_04")	117
6.5B.4.3	Intra-band non-contiguous EN-DC	117
6.5B.4.3.1	Minimum requirement (network signalled value "NS_04")	117
6.5B.4.4	Inter-band EN-DC within FR1	117
6.5B.4.4a	Inter-band NE-DC within FR1	117
6.5B.4.5	Inter-band EN-DC including FR2	117
6.5B.4.6	Inter-band EN-DC including both FR1 and FR2	118
6.5B.5	Transmit intermodulation for DC	118
6.5B.5.1	Intra-band contiguous EN-DC	118
6.5B.5.2	Intra-band non-contiguous EN-DC	118
6.5B.5.3	Inter-band EN-DC within FR1	118
6.5B.5.3a	Inter-band NE-DC within FR1	118
6.5B.5.4	Inter-band EN-DC including FR2	118
6.5B.5.5	Inter-band EN-DC including both FR1 and FR2	118
6.6B	Beam correspondence for DC	118
6.6B.1	Void	118
6.6B.2	Void	118
6.6B.3	Void	118
6.6B.4	Inter-band EN-DC including FR2	118
6.6B.5	Inter-band EN-DC including both FR1 and FR2	118
7	Receiver characteristics	119
7.1	General	119
7.2	Void	120
7.3	Void	120
7.3A	Reference sensitivity for CA	120
7.3A.1	General	120
7.3A.2	Reference sensitivity power level for CA	120
7.3A.3	$\Delta R_{IB,c}$ for CA	120
7.3A.3.1	$\Delta R_{IB,c}$ for Inter-band CA between FR1 and FR2	120
7.3A.4	Void	120
7.3B	Reference sensitivity level for DC	120
7.3B.1	General	120
7.3B.2	Reference sensitivity for DC	121
7.3B.2.1	Intra-band contiguous EN-DC	121
7.3B.2.2	Intra-band non-contiguous EN-DC	121
7.3B.2.3	Inter-band EN-DC within FR1	122
7.3B.2.3.1	Reference sensitivity exceptions due to UL harmonic interference for EN-DC in NR FR1	122
7.3B.2.3.2	Reference sensitivity exceptions due to receiver harmonic mixing for EN-DC in NR FR1	126
7.3B.2.3.3	Void	128
7.3B.2.3.4	Reference sensitivity exceptions due to cross band isolation for EN-DC in NR FR1	128
7.3B.2.3.5	MSD for intermodulation interference due to dual uplink operation for EN-DC in NR FR1	130
7.3B.2.3.5.1	MSD test points for intermodulation interference due to dual uplink operation for EN-DC in NR FR1 involving two bands	131

7.3B.2.3.5.2	MSD test points for intermodulation interference due to dual uplink operation for EN-DC in NR FR1 involving three bands	133
7.3B.2.3.5.3	Void	139
7.3B.2.3.6	Reference sensitivity exceptions due to Tx non-linearity interference in 1 st or 2 nd adjacent channel of UL band for EN-DC in NR FR1	139
7.3B.2.3a	Inter-band NE-DC within FR1	140
7.3B.2.3a.1	Reference sensitivity exceptions due to UL harmonic interference for NE-DC in NR FR1	140
7.3B.2.4	Inter-band EN-DC including FR2	140
7.3B.2.4.1	Void	140
7.3B.2.5	Inter-band EN-DC including both FR1 and FR2	140
7.3B.2.5.1	Reference sensitivity exceptions due to UL harmonic interference for EN-DC including both FR1 and FR2	140
7.3B.3	$\Delta R_{IB,c}$, ΔR_{IBNC} for DC	140
7.3B.3.0	General	140
7.3B.3.1	Intra-band contiguous EN-DC	142
7.3B.3.2	Intra-band non-contiguous EN-DC	142
7.3B.3.3	Inter-band EN-DC within FR1	143
7.3B.3.3.1	$\Delta R_{IB,c}$ for EN-DC in two bands	143
7.3B.3.3.2	$\Delta R_{IB,c}$ for EN-DC three bands	145
7.3B.3.3.4	$\Delta R_{IB,c}$ for EN-DC five bands	152
7.3B.3.3.5	$\Delta R_{IB,c}$ for EN-DC six bands	154
7.3B.3.3a	Inter-band NE-DC within FR1	154
7.3B.3.4	Inter-band EN-DC including FR2	154
7.3B.3.4.1	$\Delta R_{IB,c}$ for EN-DC in two bands	154
7.3B.3.4.2	$\Delta R_{IB,c}$ for EN-DC three bands	154
7.3B.3.4.3	$\Delta R_{IB,c}$ for EN-DC four bands	155
7.3B.3.4.4	$\Delta R_{IB,c}$ for EN-DC five bands	155
7.3B.3.4.5	Void	155
7.3B.3.5	Inter-band EN-DC including both FR1 and FR2	155
7.3B.3.5.2	$\Delta R_{IB,c}$ for EN-DC three bands	155
7.3B.3.5.3	$\Delta R_{IB,c}$ for EN-DC four bands	155
7.3B.3.5.4	$\Delta R_{IB,c}$ for EN-DC five bands	155
7.3B.3.5.5	$\Delta R_{IB,c}$ for EN-DC six bands	155
7.4	Void	155
7.4A	Maximum input level for CA	155
7.4B	Maximum input level for DC in FR1	156
7.4B.1	Intra-band contiguous EN-DC in FR1	156
7.4B.2	Intra-band non-contiguous EN-DC in FR1	156
7.4B.3	Inter-band EN-DC within FR1	156
7.5	Void	156
7.5A	Adjacent channel selectivity for CA	156
7.5B	Adjacent channel selectivity for DC in FR1	157
7.5B.1	Intra-band contiguous EN-DC in FR1	157
7.5B.2	Intra-band non-contiguous EN-DC in FR1	157
7.5B.3	Inter-band EN-DC within FR1	157
7.6	Void	159
7.6A	Blocking characteristics for CA	159
7.6B	Blocking characteristics for DC in FR1	159
7.6B.1	General	159
7.6B.2	Inband blocking for DC in FR1	159
7.6B.2.1	Intra-band contiguous EN-DC in FR1	159

7.6B.2.2	Intra-band non-contiguous EN-DC in FR1	159
7.6B.2.3	Inter-band EN-DC within FR1	159
7.6B.3	Out-of-band blocking for DC in FR1	160
7.6B.3.1	Intra-band contiguous EN-DC in FR1	160
7.6B.3.2	Intra-band non-contiguous EN-DC in FR1	160
7.6B.3.3	Inter-band EN-DC within FR1	160
7.6B.3.3a	Inter-band NE-DC within FR1	161
7.6B.3.4	Inter-band EN-DC including FR2	162
7.6B.3.5	Inter-band EN-DC including both FR1 and FR2	162
7.6B.4	Narrow band blocking for DC in FR1	162
7.6B.4.1	Intra-band contiguous EN-DC in FR1	162
7.6B.4.2	Intra-band non-contiguous EN-DC in FR1	162
7.6B.4.3	Inter-band EN-DC within FR1	162
7.7	Void	163
7.7A	Spurious response for CA	163
7.7B	Spurious response for DC in FR1	163
7.7B.1	Intra-band contiguous EN-DC in FR1	163
7.7B.2	Intra-band non-contiguous EN-DC in FR1	163
7.7B.3	Inter-band EN-DC within FR1	163
7.8	Void	164
7.8A	Intermodulation characteristics for CA	164
7.8B	Intermodulation characteristics for DC in FR1	164
7.8B.1	General	164
7.8B.2	Wide band Intermodulation	164
7.8B.2.1	Intra-band contiguous EN-DC in FR1	164
7.8B.2.2	Intra-band non-contiguous EN-DC in FR1	164
7.8B.2.3	Inter-band EN-DC within FR1	165
7.8B.2.3a	Inter-band NE-DC within FR1	165
7.8B.2.4	Inter-band EN-DC including FR2	165
7.8B.2.5	Inter-band EN-DC including both FR1 and FR2	165
7.9	Void	165
7.9A	Spurious emissions for CA	165
7.9B	Spurious emissions for DC in FR1	165
7.9B.1	Intra-band contiguous EN-DC in FR1	165
7.9B.2	Intra-band non-contiguous EN-DC in FR1	165
7.9B.3	Inter-band EN-DC within FR1	165
7.9B.4	Inter-band EN-DC including FR2	166
7.9B.5	Inter-band EN-DC including both FR1 and FR2	166

Annex A (normative): Measurement channels 170

A.1	General	170
A.2	UL reference measurement channels for E-UTRA TDD Config 2	170
A.2.1	General	170
A.2.2	Reference measurement channels for E-UTRA	171
A.2.2.1	Full RB allocation	171
A.2.2.1.1	QPSK	171
A.2.2.1.2	16-QAM	172
A.2.2.1.3	64-QAM	173
A.2.2.1.4	256 QAM	174
A.2.2.2	Partial RB allocation	175
A.2.2.2.1	QPSK	175
A.2.2.2.2	16-QAM	176

A.2.2.2.3	64-QAM	177
A.2.2.2.4	256 QAM	178
A.3	DL reference measurement channels for E-UTRA	178
A.3.1	General	178
A.3.1.1	QPSK	179
A.3.1.2	64-QAM	180
A.3.1.3	256-QAM	181
Annex B:	Void	181
Annex C:	Void	181
Annex D:	Void	181
Annex E:	Void	182
Annex F:	Void	182
Annex G:	Void	182
Annex H (normative): Modified MPR behavior		182
Annex I (normative): Dual uplink interferer		182
Annex J:	Void	183
Annex K:	Void	183
Annex L (informative): Change history		184

