

3GPP TS 38.101-3 V16.24.0 (2025-06)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Radio Access Network;
NR;
User Equipment (UE) radio transmission and reception;
Part 3: Range 1 and Range 2 Interworking operation with other
radios
(Release 16)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented.

This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification.

Specifications and Reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2025, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners

LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners

GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword	12
1	Scope 14
2	References 14
3	Definitions, symbols and abbreviations 15
3.1	Definitions 15
3.2	Symbols 15
3.3	Abbreviations 15
4	General 16
4.1	Relationship between minimum requirements and test requirements 16
4.2	Applicability of minimum requirements 17
4.3	Specification suffix information 18
5	Operating bands and channel arrangement 18
5.1	General 18
5.2	Operating bands 18
5.2A	Operating bands for CA 19
5.2A.1	Inter-band CA between FR1 and FR2 19
5.2B	Operating bands for DC 20
5.2B.1	General 20
5.2B.2	Void 20
5.2B.3	Void 20
5.2B.4	Void 20
5.2B.5	Void 20
5.2B.6	Void 20
5.2B.7	Void 20
5.2E	Operating bands for V2X 20
5.2E.1	Intra-band V2X bands 20
5.2E.2	Inter-band V2X bands 20
5.3	UE Channel bandwidth 21
5.3A	UE Channel bandwidth for CA 21
5.3A.1	Inter-band CA between FR1 and FR2 21
5.3B	UE Channel bandwidth for DC 21
5.3B.0	General 21
5.3B.1	Intra-band EN-DC in FR1 22
5.3B.1.1	General 22
5.3B.1.2	BCS for Intra-band contiguous EN-DC 22
5.3B.1.3	BCS for Intra-band non-contiguous EN-DC 26
5.3C	Void 30
5.3D	Void 30
5.3E	UE Channel bandwidth for V2X 30
5.3E.0	General 30
5.3E.1	Intra-band contiguous V2X in FR1 30
5.3E.2	Intra-band non-contiguous V2X in FR1 30
5.3E.3	Inter-band V2X in FR1 30
5.4	Void 31
5.4A	Channel arrangement for CA 31
5.4B	Channel arrangement for DC 31
5.4B.0	General 31
5.4B.1	Channel spacing for intra-band EN-DC carriers 31
5.5	Configuration 32

5.5A	Configuration for CA	32
5.5A.1	Inter-band CA configurations between FR1 and FR2	32
5.5B	Configuration for DC	71
5.5B.1	General	71
5.5B.2	Intra-band contiguous EN-DC	72
5.5B.3	Intra-band non-contiguous EN-DC	72
5.5B.4	Inter-band EN-DC within FR1	74
5.5B.4.1	Inter-band EN-DC configurations within FR1 (two bands)	74
5.5B.4.2	Inter-band EN-DC configurations within FR1 (three bands)	82
5.5B.4.3	Inter-band EN-DC configurations within FR1 (four bands)	103
5.5B.4.4	Inter-band EN-DC configurations within FR1 (five bands)	123
5.5B.4.5	Inter-band EN-DC configurations within FR1 (six bands)	131
5.5B.4a	Inter-band NE-DC within FR1	132
5.5B.4a.1	Inter-band NE-DC configurations within FR1 (two bands)	132
5.5B.5	Inter-band EN-DC including FR2	133
5.5B.5.1	Inter-band EN-DC configurations including FR2 (two bands)	133
5.5B.5.2	Inter-band EN-DC configurations including FR2 (three bands)	153
5.5B.5.3	Inter-band EN-DC configurations including FR2 (four bands)	176
5.5B.5.4	Inter-band EN-DC configurations including FR2 (five bands)	194
5.5B.5.5	Void	201
5.5B.6	Inter-band EN-DC including FR1 and FR2	201
5.5B.6.1	Void	201
5.5B.6.2	Inter-band EN-DC configurations including FR1 and FR2 (three bands)	201
5.5B.6.3	Inter-band EN-DC configurations including FR1 and FR2 (four bands)	210
5.5B.6.4	Inter-band EN-DC configurations including FR1 and FR2 (five bands)	228
5.5B.6.5	Inter-band EN-DC configurations including FR1 and FR2 (six bands)	242
5.5B.7	Inter-band NR-DC between FR1 and FR2	245
5.5B.7.0	General	245
5.5B.7.1	Inter-band NR-DC configurations between FR1 and FR2 (two bands)	247
5.5B.7.2	Inter-band NR-DC configurations between FR1 and FR2 (three bands)	250
5.5C	Void	251
5.5D	Void	251
5.5E	Configuration for V2X operation	251
5.5E.1	General	251
5.5E.2	Intra-band contiguous V2X operation in FR1	251
5.5E.3	Intra-band non-contiguous V2X operation in FR1	251
5.5E.4	Inter-band V2X operation in FR1	251
5.5E.4.1	Inter-band V2X configurations within FR1 (two bands)	251
6	Transmitter characteristics	252
6.1	General	252
6.2	Void	252
6.2A	Transmitter power for CA	252
6.2A.1	UE maximum output power for CA	252
6.2A.1.1	Inter-band CA between FR1 and FR2	252
6.2A.2	UE maximum output power reduction for CA	252
6.2A.2.1	Inter-band CA between FR1 and FR2	252
6.2A.3	UE additional maximum output power reduction for CA	252
6.2A.4	Configured output power for CA	252
6.2A.4.1	Configured output power level	252
6.2A.4.2	$\Delta T_{IB,c}$ for CA	253
6.2A.4.2.1	$\Delta T_{IB,c}$ for Inter-band CA between FR1 and FR2	253
6.2B	Transmitter power for DC	253
6.2B.1	UE maximum output power for DC	253

6.2B.1.1	Intra-band contiguous EN-DC	253	
6.2B.1.2	Intra-band non-contiguous EN-DC	255	
6.2B.1.3	Inter-band EN-DC within FR1	256	
6.2B.1.3a	Inter-band NE-DC within FR1	262	
6.2B.1.4	Inter-band EN-DC including FR2	262	
6.2B.1.5	Inter-band EN-DC including both FR1 and FR2	263	
6.2B.2	UE maximum output power reduction for DC	263	
6.2B.2.0	General	263	
6.2B.2.1	Intra-band contiguous EN-DC	263	
6.2B.2.1.1	General	263	
6.2B.2.1.2	MPR for power class 3 and power class 2	264	
6.2B.2.2	Intra-band non-contiguous EN-DC	264	
6.2B.2.2.1	General	264	
6.2B.2.2.2	MPR for power class 3 and power class 2	265	
6.2B.2.3	Inter-band EN-DC within FR1	266	
6.2B.2.3a	Inter-band NE-DC within FR1	266	
6.2B.2.4	Inter-band EN-DC including FR2	266	
6.2B.2.5	Inter-band EN-DC including both FR1 and FR2	266	
6.2B.3	UE additional maximum output power reduction for EN-DC	266	
6.2B.3.1	Intra-band contiguous EN-DC	266	
6.2B.3.1.0	General	266	
6.2B.3.1.1	A-MPR for DC _(n) 71AA	266	
6.2B.3.1.2	A-MPR for NS_04	268	
6.2B.3.2	Intra-band non-contiguous EN-DC	270	
6.2B.3.2.0	General	270	
6.2B.3.2.1	A-MPR for NS_04	271	
6.2B.3.3	Inter-band EN-DC within FR1	272	
6.2B.3.3A	Inter-band NE-DC within FR1	275	
6.2B.3.4	Inter-band EN-DC including FR2	276	
6.2B.3.5	Inter-band EN-DC including both FR1 and FR2	276	
6.2B.4	Configured output power for DC	276	
6.2B.4.1	Configured output power level	276	
6.2B.4.1.1	Intra-band contiguous EN-DC	276	
6.2B.4.1.2	Intra-band non-contiguous EN-DC	280	
6.2B.4.1.3a	Inter-band NE-DC within FR1	285	
6.2B.4.1.4	Inter-band EN-DC including FR2	288	
6.2B.4.1.5	Inter-band EN-DC including both FR1 and FR2	289	
6.2B.4.2	$\Delta T_{IB,c}$ for DC	289	
6.2B.4.2.0	General	289	
6.2B.4.2.1	Intra-band contiguous EN-DC	289	
6.2B.4.2.2	Intra-band non-contiguous EN-DC	289	
6.2B.4.2.3	Inter-band EN-DC within FR1	290	
6.2B.4.2.3.1	$\Delta T_{IB,c}$ for EN-DC two bands	290	
6.2B.4.2.3.2	$\Delta T_{IB,c}$ for EN-DC three bands	297	
6.2B.4.2.3.3	$\Delta T_{IB,c}$ for EN-DC four bands	316	
6.2B.4.2.3.4	$\Delta T_{IB,c}$ for EN-DC five bands	334	
6.2B.4.2.3.5	$\Delta T_{IB,c}$ for EN-DC six bands	340	
6.2B.4.2.3a	Inter-band NE-DC within FR1	341	
6.2B.4.2.4	Inter-band EN-DC including FR2	341	
6.2B.4.2.4.1	$\Delta T_{IB,c}$ for EN-DC two bands	341	
6.2B.4.2.4.2	$\Delta T_{IB,c}$ for EN-DC three bands	341	
6.2B.4.2.4.3	$\Delta T_{IB,c}$ for EN-DC four bands	341	
6.2B.4.2.4.4	$\Delta T_{IB,c}$ for EN-DC five bands	341	

6.2B.4.2.4.5	Void	341	
6.2B.4.2.5	Inter-band EN-DC including both FR1 and FR2	341	
6.2B.4.2.5.1	$\Delta T_{IB,c}$ for EN-DC three bands	341	
6.2B.4.2.5.2	$\Delta T_{IB,c}$ for EN-DC four bands	341	
6.2B.4.2.5.3	$\Delta T_{IB,c}$ for EN-DC five bands	342	
6.2B.4.2.5.4	$\Delta T_{IB,c}$ for EN-DC six bands	342	
6.2B.5	Configured output power for NR-DC	342	
6.2B.5.1	Configured output power level	342	
6.2B.5.1.1	Inter-band NR-DC between FR1 and FR2	342	
6.2E	Transmitter power for V2X in FR1	342	
6.2E.1	UE maximum output power for V2X	342	
6.2E.1.1	UE maximum output power for Intra-band contiguous V2X	342	
6.2E.1.2	UE maximum output power for Intra-band non-contiguous V2X	342	
6.2E.1.3	UE maximum output power for Inter-band V2X	343	
6.2E.2	UE maximum output power reduction for V2X	343	
6.2E.2.1	UE maximum output power reduction for Intra-band V2X	343	
6.2E.2.2	UE maximum output power reduction for Inter-band V2X	343	
6.2E.3	UE additional maximum output power reduction for V2X	343	
6.2E.3.1	UE additional maximum output power reduction for Intra-band V2X	343	
6.2E.3.2	UE additional maximum output power reduction for Inter-band V2X	343	
6.2E.4	Configured output power for V2X	343	
6.2E.4.1	UE configured output power for Intra-band V2X	343	
6.2E.4.2	UE configured output power for Inter-band V2X	344	
6.3	Output power dynamics	344	
6.3A	Output power dynamics for CA	345	
6.3B	Output power dynamics for DC	345	
6.3B.0	General	345	
6.3B.1	Output power dynamics for EN-DC with UL sharing from UE perspective	345	
6.3B.1.1	E-UTRA and NR switching time mask for TDM based UL sharing from UE perspective	345	
6.3B.1a	(Void)	346	
6.3B.2	Output power dynamics for intra-band EN-DC without dual PA capability	346	
6.3B.3	Output power dynamics for intra-band EN-DC with dual PA capability	347	
6.3B.4	Output power dynamics for switching between two uplink carriers	348	
6.3B.4.1	E-UTRA and NR switching time mask between two uplink carriers	348	
6.3B.5	Output power dynamics for inter-band EN-DC	349	
6.3E	Output power dynamics for V2X	349	
6.3E.1	General	349	
6.3E.2	Output power dynamics for intra-band V2X operation	350	
6.3E.3	Output power dynamics for inter-band V2X con-current operation	350	
6.4	Void	350	
6.4A	Transmit signal quality for CA	350	
6.4A.1	Frequency error for CA	350	
6.4A.2	Transmit modulation quality for CA	350	
6.4B	Transmit signal quality for DC	350	
6.4B.2	Transmit modulation quality for DC	351	
6.4B.2.1	Transmit modulation quality for Intra-band contiguous EN-DC	351	
6.4B.2.1.1	Error Vector Magnitude	351	
6.4B.2.1.2	Carrier leakage	351	
6.4B.2.1.3	In-band emissions	351	
6.4B.2.2	Transmit modulation quality for Intra-band non-contiguous EN-DC	352	
6.4B.2.2.1	Error Vector Magnitude	352	
6.4B.2.2.2	Carrier leakage	352	
6.4B.2.2.3	In-band emissions	352	

6.4B.2.3a	Transmit modulation quality for Inter-band NE-DC within FR1	352
6.4B.2.4	Transmit modulation quality for Inter-band EN-DC including FR2	352
6.4B.2.5	Transmit modulation quality for inter-band EN-DC including both FR1 and FR2	352
6.4E	Transmit signal quality for V2X operation in FR1	353
6.4E.1	Frequency error for V2X	353
6.4E.2	Transmit modulation quality for V2X	353
6.4E.2.1	Transmit modulation quality for Intra-band V2X	353
6.4E.2.2.1	Error Vector Magnitude	353
6.4E.2.2.2	Carrier leakage	353
6.4E.2.2.3	In-band emissions	353
6.4E.2.2	Transmit modulation quality for Inter-band V2X	353
6.5	Void	353
6.5A	Output RF spectrum emissions for CA	353
6.5A.1	Occupied bandwidth for CA	353
6.5A.2	Out-of-band emissions for CA	354
6.5A.3	Spurious emissions for CA	354
6.5A.3.1	Inter-band CA between FR1 and FR2	354
6.5A.4	Transmit intermodulation for CA	354
6.5B	Output RF spectrum emissions for DC	354
6.5B.1	Occupied bandwidth for EN-DC	354
6.5B.1.4	Inter-band EN-DC including FR2	354
6.5B.1.5	Inter-band EN-DC including both FR1 and FR2	354
6.5B.2	Out-of-band emissions for DC	355
6.5B.2.1	Intra-band contiguous EN-DC	355
6.5B.2.1.1	Spectrum emissions mask	355
6.5B.2.1.2	Additional spectrum emissions mask	355
6.5B.2.1.2.1	Requirements for network signalled value "NS_35"	355
6.5B.2.1.2.2	Requirements for network signalled value "NS_04"	355
6.5B.2.1.3	Adjacent channel leakage ratio	356
6.5B.2.2	Intra-band non-contiguous EN-DC	356
6.5B.2.2.1	Spectrum emissions mask	356
6.5B.2.2.2	Additional spectrum emissions mask	357
6.5B.2.2.3	Adjacent channel leakage ratio	357
6.5B.2.3	Inter-band EN-DC within FR1	357
6.5B.2.3a	(Void)	357
6.5B.2.4	Inter-band EN-DC including FR2	357
6.5B.2.5	Inter-band EN-DC including both FR1 and FR2	357
6.5B.3	Spurious emissions for DC	357
6.5B.3.1	Intra-band contiguous EN-DC	357
6.5B.3.1.1	General spurious emissions	357
6.5B.3.1.2	Spurious emission band UE co-existence	357
6.5B.3.2	Intra-band non-contiguous EN-DC	358
6.5B.3.2.1	General spurious emissions	358
6.5B.3.2.2	Spurious emission band UE co-existence	358
6.5B.3.3	Inter-band EN-DC within FR1	359
6.5B.3.3.2	Spurious emission band UE co-existence	360
6.5B.3.3a	Inter-band NE-DC within FR1	367
6.5B.3.3a.1	(Void)	367
6.5B.3.3a.2	Spurious emission band UE co-existence	367
6.5B.3.4	Inter-band EN-DC including FR2	367
6.5B.3.4.0	General spurious emission	367
6.5B.3.4.1	Spurious emission band UE co-existence	367
6.5B.3.5	Inter-band EN-DC including both FR1 and FR2	367

6.5B.3.5.0	General spurious emission	367
6.5B.3.5.1	Spurious emission band UE co-existence	367
6.5B.4	Additional spurious emissions	368
6.5B.4.1	General	368
6.5B.4.1.1	Void	368
6.5B.4.2	Intra-band contiguous EN-DC	368
6.5B.4.2.1	Minimum requirement (network signalled value "NS_04")	368
6.5B.4.3	Intra-band non-contiguous EN-DC	368
6.5B.4.3.1	Minimum requirement (network signalled value "NS_04")	368
6.5B.4.4	Inter-band EN-DC within FR1	369
6.5B.4.4a	Inter-band NE-DC within FR1	369
6.5B.4.5	Inter-band EN-DC including FR2	369
6.5B.4.6	Inter-band EN-DC including both FR1 and FR2	369
6.5B.5	Transmit intermodulation for DC	369
6.5B.5.1	Intra-band contiguous EN-DC	369
6.5B.5.2	Intra-band non-contiguous EN-DC	369
6.5B.5.3	Inter-band EN-DC within FR1	369
6.5B.5.3a	(Void)	369
6.5B.5.4	Inter-band EN-DC including FR2	369
6.5B.5.5	Inter-band EN-DC including both FR1 and FR2	369
6.5E	Output RF spectrum emissions for V2X operation in FR1	370
6.5E.1	Occupied bandwidth	370
6.5E.1.1	Intra-band V2X	370
6.5E.1.2	inter-band V2X con-current operation	370
6.5E.2	Out-of-band emissions	370
6.5E.2.1	Intra-band V2X	370
6.5E.2.2	Inter-band V2X con-current operation	370
6.5E.3	Spurious emissions	370
6.5E.3.1	Intra-band V2X	370
6.5E.3.1.1	General spurious emissions	370
6.5E.3.1.2	Spurious emission band UE co-existence	370
6.5E.3.2	Inter-band V2X con-current operation	370
6.5E.3.2.1	General spurious emissions	370
6.5E.3.2.2	Spurious emission band UE co-existence	371
6.5E.4	Transmit intermodulation	371
6.5E.4.1	Intra-band V2X	371
6.5E.4.2	Inter-band V2X con-current operation	372
6.6B	Beam correspondence for DC	372
6.6B.1	Void	372
6.6B.2	Void	372
6.6B.3	Void	372
6.6B.4	Inter-band EN-DC including FR2	372
6.6B.5	Inter-band EN-DC including both FR1 and FR2	372
7	Receiver characteristics	372
7.1	General	372
7.2	Void	373
7.3	Void	373
7.3A	Reference sensitivity for CA	373
7.3A.1	General	373
7.3A.2	Reference sensitivity power level for CA	374
7.3A.3	$\Delta R_{IB,c}$ for CA	374
7.3A.3.1	$\Delta R_{IB,c}$ for Inter-band CA between FR1 and FR2	374
7.3A.4	Void	374

7.3B	Reference sensitivity level for DC	374
7.3B.1	General	374
7.3B.2	Reference sensitivity for DC	375
7.3B.2.1	Intra-band contiguous EN-DC	375
7.3B.2.2	Intra-band non-contiguous EN-DC	376
7.3B.2.3	Inter-band EN-DC within FR1	377
7.3B.2.3.0	General	377
7.3B.2.3.1	Reference sensitivity exceptions due to UL harmonic interference for EN-DC in NR FR1	377
7.3B.2.3.2	Reference sensitivity exceptions due to receiver harmonic mixing for EN-DC in NR FR1	385
7.3B.2.3.3	Void	387
7.3B.2.3.4	Reference sensitivity exceptions due to cross band isolation for EN-DC in NR FR1	387
7.3B.2.3.5	MSD for intermodulation interference due to dual uplink operation for EN-DC in NR FR1	395
7.3B.2.3.5.1	MSD test points for intermodulation interference due to dual uplink operation for PC3 EN-DC in NR FR1 involving two bands	396
7.3B.2.3.5.2	MSD test points for intermodulation interference due to dual uplink operation for EN-DC in NR FR1 involving three bands	401
7.3B.2.3.5.3	Void	426
7.3B.2.3.5.4	MSD test points for intermodulation interference due to dual uplink operation for EN-DC in NR FR1 involving four bands	426
7.3B.2.3.6	Reference sensitivity exceptions due to Tx non-linearity interference in 1 st or 2 nd adjacent channel of UL band for EN-DC in NR FR1	426
7.3B.2.3a	Inter-band NE-DC within FR1	427
7.3B.2.3a.0	General	427
7.3B.2.3a.1	Reference sensitivity exceptions due to UL harmonic interference for NE-DC in NR FR1	427
7.3B.2.4	Inter-band EN-DC including FR2	427
7.3B.2.4.1	Void	427
7.3B.2.5	Inter-band EN-DC including both FR1 and FR2	427
7.3B.2.5.1	Reference sensitivity exceptions due to UL harmonic interference for EN-DC including both FR1 and FR2	427
7.3B.3	$\Delta R_{IB,c}$, ΔR_{IBNC} for DC	427
7.3B.3.0	General	427
7.3B.3.1	Intra-band contiguous EN-DC	429
7.3B.3.2	Intra-band non-contiguous EN-DC	429
7.3B.3.3	Inter-band EN-DC within FR1	434
7.3B.3.3.1	$\Delta R_{IB,c}$ for EN-DC in two bands	434
7.3B.3.3.2	$\Delta R_{IB,c}$ for EN-DC three bands	438
7.3B.3.3.3	$\Delta R_{IB,c}$ for EN-DC four bands	449
7.3B.3.3.4	$\Delta R_{IB,c}$ for EN-DC five bands	462
7.3B.3.3.5	$\Delta R_{IB,c}$ for EN-DC six bands	467
7.3B.3.3a	(Void)	467
7.3B.3.4	Inter-band EN-DC including FR2	467
7.3B.3.4.1	$\Delta R_{IB,c}$ for EN-DC in two bands	467
7.3B.3.4.2	$\Delta R_{IB,c}$ for EN-DC three bands	468
7.3B.3.4.3	$\Delta R_{IB,c}$ for EN-DC four bands	468
7.3B.3.4.4	$\Delta R_{IB,c}$ for EN-DC five bands	468
7.3B.3.4.5	Void	468
7.3B.3.5	Inter-band EN-DC including both FR1 and FR2	468
7.3B.3.5.2	$\Delta R_{IB,c}$ for EN-DC three bands	468
7.3B.3.5.3	$\Delta R_{IB,c}$ for EN-DC four bands	468

7.3B.3.5.4	$\Delta R_{IB,c}$ for EN-DC five bands	468
7.3B.3.5.5	$\Delta R_{IB,c}$ for EN-DC six bands	468
7.3E	Reference sensitivity for V2X operation in FR1	469
7.3E.1	General	469
7.3E.2	Reference sensitivity for V2X	469
7.3E.2.1	Intra-band contiguous V2X	469
7.3E.2.2	Intra-band non-contiguous V2X	469
7.3E.2.3	Inter-band V2X con-current operation	469
7.3E.2.3.0	General	469
7.3E.2.3.1	Reference sensitivity exception due to UL harmonic problem	470
7.4	Void	471
7.4A	Maximum input level for CA	471
7.4B	Maximum input level for DC in FR1	471
7.4B.1	Intra-band contiguous EN-DC in FR1	471
7.4B.2	Intra-band non-contiguous EN-DC in FR1	471
7.4B.3	Inter-band EN-DC within FR1	471
7.4B.3a	(Void)	471
7.4E	Maximum input level for V2X operation in FR1	472
7.5	Void	472
7.5A	Adjacent channel selectivity for CA	472
7.5B	Adjacent channel selectivity for DC in FR1	472
7.5B.1	Intra-band contiguous EN-DC in FR1	472
7.5B.2	Intra-band non-contiguous EN-DC in FR1	473
7.5B.3	Inter-band EN-DC within FR1	473
7.5B.3a	(Void)	473
7.5E	Adjacent channel selectivity for V2X operation in FR1	474
7.6	Void	474
7.6A	Blocking characteristics for CA	474
7.6B	Blocking characteristics for DC in FR1	474
7.6B.1	General	474
7.6B.2	In-band blocking for DC in FR1	474
7.6B.2.1	Intra-band contiguous EN-DC in FR1	474
7.6B.2.2	Intra-band non-contiguous EN-DC in FR1	474
7.6B.2.3	Inter-band EN-DC within FR1	475
7.6B.2.3a	(Void)	475
7.6B.2.4	Inter-band EN-DC including FR2	475
7.6B.2.5	Inter-band EN-DC including both FR1 and FR2	475
7.6B.2.6	Void	475
7.6B.3	Out-of-band blocking for DC in FR1	475
7.6B.3.1	Intra-band contiguous EN-DC in FR1	475
7.6B.3.2	Intra-band non-contiguous EN-DC in FR1	475
7.6B.3.3	Inter-band EN-DC within FR1	476
7.6B.3.3a	(Void)	477
7.6B.4	Narrow band blocking for DC in FR1	477
7.6B.4.1	Intra-band contiguous EN-DC in FR1	477
7.6B.4.2	Intra-band non-contiguous EN-DC in FR1	477
7.6B.4.3	Inter-band EN-DC within FR1	477
7.6B.4.3a	(Void)	478
7.6E	Blocking characteristics for V2X in FR1	478
7.7	Void	478
7.7A	Spurious response for CA	478
7.7B	Spurious response for DC in FR1	478
7.7B.1	Intra-band contiguous EN-DC in FR1	478

7.7B.2	Intra-band non-contiguous EN-DC in FR1	478
7.7B.3	Inter-band EN-DC within FR1	479
7.7E	Spurious response for V2X in FR1	479
7.8	Void	479
7.8A	Intermodulation characteristics for CA	479
7.8B	Intermodulation characteristics for DC in FR1	480
7.8B.1	General	480
7.8B.2	Wide band Intermodulation	480
7.8B.2.1	Intra-band contiguous EN-DC in FR1	480
7.8B.2.2	Intra-band non-contiguous EN-DC in FR1	480
7.8B.2.3	Inter-band EN-DC within FR1	480
7.8B.2.3a	(Void)	480
7.8E	Intermodulation characteristics for V2X operation in FR1	481
7.9	Void	481
7.9A	Spurious emissions for CA	481
7.9B	Spurious emissions for DC in FR1	481
7.9B.1	Intra-band contiguous EN-DC in FR1	481
7.9B.2	Intra-band non-contiguous EN-DC in FR1	481
7.9B.3	Inter-band EN-DC within FR1	481
7.9B.3a	(Void)	481
7.10	Void	482
7.10A	Void	482
7.10B	power imbalance for DC	482
7.10B.1	Void	482
7.10B.2	Void	482
7.10B.3	Inter-band EN-DC within FR1	482

Annex A (normative): Measurement channels 482

A.1	General	482
A.2	UL reference measurement channels for E-UTRA TDD Config 2	482
A.2.1	General	482
A.2.2	Reference measurement channels for E-UTRA	483
A.2.2.1	Full RB allocation	483
A.2.2.1.1	QPSK	483
A.2.2.1.2	16-QAM	484
A.2.2.1.3	64-QAM	485
A.2.2.1.4	256 QAM	486
A.2.2.2	Partial RB allocation	487
A.2.2.2.1	QPSK	487
A.2.2.2.2	16-QAM	490
A.2.2.2.3	64-QAM	493
A.2.2.2.4	256 QAM	496
A.3	DL reference measurement channels for E-UTRA	499
A.3.1	General	499
A.3.1.1	QPSK	500
A.3.1.2	64-QAM	501
A.3.1.3	256-QAM	502

Annex B: Void 502

Annex C: Void 502

Annex D:	Void	502
Annex E:	Void	503
Annex F:	Void	503
Annex G:	Void	503
Annex H (normative): Modified MPR behavior		503
Annex I (normative): Dual uplink interferer		504
Annex J:	Void	504
Annex K:	Void	504
Annex L (informative): Change history		505

