## ш3schools.com





HTML CSS

MORE ▼



Q

# Python MySQL Create Table

Previous

Next >

## Creating a Table

To create a table in MySQL, use the "CREATE TABLE" statement.

Make sure you define the name of the database when you create the connection

## Example

Create a table named "customers":

```
import mysql.connector
mydb = mysql.connector.connect(
  host="localhost",
  user="yourusername",
  passwd="yourpassword",
  database="mydatabase"
)
mycursor = mydb.cursor()
mycursor.execute("CREATE TABLE customers (name VARCHAR(255), address
VARCHAR(255))")
```

Run example »

If the above code was executed with no errors, you have now successfully created a table.

## Check if Table Exists

You can check if a table exist by listing all tables in your database with the "SHOW TABLES" statement:

## Example

Return a list of your system's databases:

```
import mysql.connector

mydb = mysql.connector.connect(
   host="localhost",
   user="yourusername",
   passwd="yourpassword",
   database="mydatabase"
)

mycursor = mydb.cursor()

mycursor.execute("SHOW TABLES")

for x in mycursor:
   print(x)
```

Run example »

## **Primary Key**

When creating a table, you should also create a column with a unique key for each record.

This can be done by defining a PRIMARY KEY.

We use the statement "INT AUTO\_INCREMENT PRIMARY KEY" which will insert a unique number for each record. Starting at 1, and increased by one for each record.

## Example

Create primary key when creating the table:

```
import mysql.connector

mydb = mysql.connector.connect(
   host="localhost",
   user="yourusername",
   passwd="yourpassword",
   database="mydatabase"
)

mycursor = mydb.cursor()

mycursor.execute("CREATE TABLE customers (id INT AUTO_INCREMENT PRIMARY KEY, name VARCHAR(255), address VARCHAR(255))")
Run example »
```

If the table already exists, use the ALTER TABLE keyword:

## Example

Create primary key on an existing table:

```
import mysql.connector

mydb = mysql.connector.connect(
   host="localhost",
   user="yourusername",
   passwd="yourpassword",
   database="mydatabase"
)

mycursor = mydb.cursor()

mycursor.execute("ALTER TABLE customers ADD COLUMN id INT AUTO_INCREMENT PRIMARY KEY")
```

Run example »

Previous

Next >

#### **COLOR PICKER**



#### HOW TO

**Tabs** Dropdowns Accordions Side Navigation Top Navigation **Modal Boxes Progress Bars Parallax** Login Form **HTML Includes** Google Maps Range Sliders **Tooltips** Slideshow Filter List Sort List

#### **SHARE**







#### **CERTIFICATES**

HTML CSS JavaScript SQL Python PHP jQuery Bootstrap XML

Read More »

#### REPORT ERROR

PRINT PAGE

**FORUM** 

**ABOUT** 

### **Top Tutorials**

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
jQuery Tutorial
Java Tutorial
C++ Tutorial

## **Top References**

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
jQuery Reference
Java Reference
Angular Reference

### **Top Examples**

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
jQuery Examples
Java Examples
XML Examples

#### Web Certificates

HTML Certificate
CSS Certificate
JavaScript Certificate
SQL Certificate
Python Certificate
jQuery Certificate
PHP Certificate
Bootstrap Certificate
XML Certificate

Get Certified »

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

