



Python JSON

[< Previous](#)[Next >](#)

JSON is a syntax for storing and exchanging data.

JSON is text, written with JavaScript object notation.

JSON in Python

Python has a built-in package called `json`, which can be used to work with JSON data.

Example

Import the json module:

```
import json
```

Parse JSON - Convert from JSON to Python

If you have a JSON string, you can parse it by using the `json.loads()` method.

The result will be a Python dictionary.

Example

Convert from JSON to Python:

```
import json

# some JSON:
x = '{ "name":"John", "age":30, "city":"New York"}'

# parse x:
y = json.loads(x)

# the result is a Python dictionary:
print(y["age"])
```

Try it Yourself »

Convert from Python to JSON

If you have a Python object, you can convert it into a JSON string by using the `json.dumps()` method.

Example

Convert from Python to JSON:

```
import json

# a Python object (dict):
x = {
    "name": "John",
    "age": 30,
    "city": "New York"
}

# convert into JSON:
y = json.dumps(x)

# the result is a JSON string:
print(y)
```

[Try it Yourself »](#)

You can convert Python objects of the following types, into JSON strings:

- dict
- list
- tuple
- string
- int
- float
- True
- False
- None

Example

Convert Python objects into JSON strings, and print the values:

```
import json

print(json.dumps({"name": "John", "age": 30}))
print(json.dumps(["apple", "bananas"]))
print(json.dumps(("apple", "bananas")))
print(json.dumps("hello"))
print(json.dumps(42))
print(json.dumps(31.76))
print(json.dumps(True))
print(json.dumps(False))
print(json.dumps(None))
```

[Try it Yourself »](#)

When you convert from Python to JSON, Python objects are converted into the JSON (JavaScript) equivalent:

Python	JSON
dict	Object

list	Array
tuple	Array
str	String
int	Number
float	Number
True	true
False	false
None	null

Example

Convert a Python object containing all the legal data types:

```
import json

x = {
    "name": "John",
    "age": 30,
    "married": True,
    "divorced": False,
    "children": ("Ann","Billy"),
    "pets": None,
    "cars": [
        {"model": "BMW 230", "mpg": 27.5},
        {"model": "Ford Edge", "mpg": 24.1}
    ]
}

print(json.dumps(x))
```

Try it Yourself »

Format the Result

The example above prints a JSON string, but it is not very easy to read, with no indentations and line breaks.

The `json.dumps()` method has parameters to make it easier to read the result:

Example

Use the `indent` parameter to define the numbers of indents:

```
json.dumps(x, indent=4)
```

[Try it Yourself »](#)

You can also define the separators, default value is `(", ", ": ")`, which means using a comma and a space to separate each object, and a colon and a space to separate keys from values:

Example

Use the `separators` parameter to change the default separator:

```
json.dumps(x, indent=4, separators=(". ", " = "))
```

[Try it Yourself »](#)

Order the Result

The `json.dumps()` method has parameters to order the keys in the result:


Example

Use the `sort_keys` parameter to specify if the result should be sorted or not:

```
json.dumps(x, indent=4, sort_keys=True)
```

[Try it Yourself »](#)[◀ Previous](#)[Next ▶](#)

COLOR PICKER



HOW TO

Tabs
Dropdowns
Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE



CERTIFICATES

HTML
CSS
JavaScript
SQL
Python
PHP
jQuery
Bootstrap
XML

[Read More »](#)

[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
jQuery Tutorial
Java Tutorial
C++ Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference

[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)
[Java Reference](#)
[Angular Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[jQuery Examples](#)
[Java Examples](#)
[XML Examples](#)

Web Certificates

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[jQuery Certificate](#)
[PHP Certificate](#)
[Bootstrap Certificate](#)
[XML Certificate](#)

[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

