



HTML

CSS

MORE ▼



# Python Sets

[< Previous](#)[Next >](#)

## Set

A set is a collection which is unordered and unindexed. In Python sets are written with curly brackets.

## Example

Create a Set:

```
thisset = {"apple", "banana", "cherry"}  
print(thisset)
```

[Try it Yourself »](#)

**Note:** Sets are unordered, so you cannot be sure in which order the items will appear.

## Access Items

You cannot access items in a set by referring to an index, since sets are unordered the items has no index.

But you can loop through the set items using a **for** loop, or ask if a specified value is present in a set, by using the **in** keyword.

## Example

Loop through the set, and print the values:

```
thisset = {"apple", "banana", "cherry"}

for x in thisset:
    print(x)
```

Try it Yourself »

## Example

Check if "banana" is present in the set:

```
thisset = {"apple", "banana", "cherry"}

print("banana" in thisset)
```

Try it Yourself »

---

## Change Items

Once a set is created, you cannot change its items, but you can add new items.

---

## Add Items

To add one item to a set use the **add()** method.

To add more than one item to a set use the **update()** method.

## Example

Add an item to a set, using the `add()` method:

```
thisset = {"apple", "banana", "cherry"}  
  
thisset.add("orange")  
  
print(thisset)
```

Try it Yourself »

## Example

Add multiple items to a set, using the `update()` method:

```
thisset = {"apple", "banana", "cherry"}  
  
thisset.update(["orange", "mango", "grapes"])  
  
print(thisset)
```

Try it Yourself »

---

## Get the Length of a Set

To determine how many items a set has, use the `len()` method.

## Example

Get the number of items in a set:

```
thisset = {"apple", "banana", "cherry"}  
  
print(len(thisset))
```

[Try it Yourself »](#)

## Remove Item

To remove an item in a set, use the `remove()`, or the `discard()` method.

### Example

Remove "banana" by using the `remove()` method:

```
thisset = {"apple", "banana", "cherry"}  
  
thisset.remove("banana")  
  
print(thisset)
```

[Try it Yourself »](#)

**Note:** If the item to remove does not exist, `remove()` will raise an error.

### Example

Remove "banana" by using the `discard()` method:

```
thisset = {"apple", "banana", "cherry"}  
  
thisset.discard("banana")  
  
print(thisset)
```

[Try it Yourself »](#)

**Note:** If the item to remove does not exist, `discard()` will **NOT** raise an error.

You can also use the `pop()` method to remove an item, but this method will remove the *last* item. Remember that sets are unordered, so you will not know what item that gets removed.

The return value of the `pop()` method is the removed item.

## Example

Remove the last item by using the `pop()` method:

```
thisset = {"apple", "banana", "cherry"}  
  
x = thisset.pop()  
  
print(x)  
  
print(thisset)
```

Try it Yourself »

**Note:** Sets are *unordered*, so when using the `pop()` method, you will not know which item that gets removed.

## Example

The `clear()` method empties the set:

```
thisset = {"apple", "banana", "cherry"}  
  
thisset.clear()  
  
print(thisset)
```

Try it Yourself »

## Example

The `del` keyword will delete the set completely:

```
thisset = {"apple", "banana", "cherry"}  
  
del thisset  
  
print(thisset)
```

Try it Yourself »

---

## Join Two Sets

There are several ways to join two or more sets in Python.

You can use the `union()` method that returns a new set containing all items from both sets, or the `update()` method that inserts all the items from one set into another:

## Example

The `union()` method returns a new set with all items from both sets:

```
set1 = {"a", "b" , "c"}  
set2 = {1, 2, 3}  
  
set3 = set1.union(set2)  
print(set3)
```

Try it Yourself »

## Example

The `update()` method inserts the items in set2 into set1:

```
set1 = {"a", "b" , "c"}  
set2 = {1, 2, 3}  
  
set1.update(set2)  
print(set1)
```

Try it Yourself »

**Note:** Both `union()` and `update()` will exclude any duplicate items.

There are other methods that joins two sets and keeps ONLY the duplicates, or NEVER the duplicates, check the full list of set methods in the bottom of this page.

## The set() Constructor

It is also possible to use the `set()` constructor to make a set.

### Example

Using the `set()` constructor to make a set:

```
thisset = set(("apple", "banana", "cherry")) # note the double round-  
brackets  
print(thisset)
```

Try it Yourself »

## Set Methods

Python has a set of built-in methods that you can use on sets.

Method	Description
<u><a href="#">add()</a></u>	Adds an element to the set

<u>clear()</u>	Removes all the elements from the set
<u>copy()</u>	Returns a copy of the set
<u>difference()</u>	Returns a set containing the difference between two or more sets
<u>difference_update()</u>	Removes the items in this set that are also included in another, specified set
<u>discard()</u>	Remove the specified item
<u>intersection()</u>	Returns a set, that is the intersection of two other sets
<u>intersection_update()</u>	Removes the items in this set that are not present in other, specified set(s)
<u>isdisjoint()</u>	Returns whether two sets have a intersection or not
<u>issubset()</u>	Returns whether another set contains this set or not
<u>issuperset()</u>	Returns whether this set contains another set or not
<u>pop()</u>	Removes an element from the set
<u>remove()</u>	Removes the specified element
<u>symmetric_difference()</u>	Returns a set with the symmetric differences of two sets
<u>symmetric_difference_update()</u>	inserts the symmetric differences from this set and another
<u>union()</u>	Return a set containing the union of sets
<u>update()</u>	Update the set with the union of this set and others

## Test Yourself With Exercises



## Exercise:

Check if "apple" is present in the `fruits` set.

```
fruits = {"apple", "banana", "cherry"}  
if "apple" in fruits:  
    print("Yes, apple is a fruit!")
```

[Submit Answer »](#)

[Start the Exercise](#)

[◀ Previous](#)

[Next ▶](#)

## COLOR PICKER



## HOW TO

Tabs  
Dropdowns  
Accordions  
Side Navigation  
Top Navigation  
Modal Boxes

Progress Bars  
Parallax  
Login Form  
HTML Includes  
Google Maps  
Range Sliders  
Tooltips  
Slideshow  
Filter List  
Sort List

SHARE



CERTIFICATES

HTML  
CSS  
JavaScript  
SQL  
Python  
PHP  
jQuery  
Bootstrap  
XML

[Read More »](#)

---

[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

---

## Top Tutorials

HTML Tutorial  
CSS Tutorial  
JavaScript Tutorial  
How To Tutorial  
SQL Tutorial  
Python Tutorial  
W3.CSS Tutorial  
Bootstrap Tutorial  
PHP Tutorial  
jQuery Tutorial  
Java Tutorial  
C++ Tutorial

## Top References

HTML Reference  
CSS Reference  
JavaScript Reference  
SQL Reference  
Python Reference  
W3.CSS Reference  
Bootstrap Reference  
PHP Reference  
HTML Colors  
jQuery Reference  
Java Reference  
Angular Reference

## Top Examples

HTML Examples  
CSS Examples  
JavaScript Examples  
How To Examples  
SQL Examples  
Python Examples  
W3.CSS Examples  
Bootstrap Examples  
PHP Examples  
jQuery Examples  
Java Examples  
XML Examples

## Web Certificates

HTML Certificate  
CSS Certificate  
JavaScript Certificate  
SQL Certificate  
Python Certificate  
jQuery Certificate  
PHP Certificate  
Bootstrap Certificate

## XML Certificate

[Get Certified »](#)

---

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.  
Powered by W3.CSS.

