



NumPy Splitting Array

[< Previous](#)[Next >](#)

Splitting NumPy Arrays

Splitting is reverse operation of Joining.

Joining merges multiple arrays into one and Splitting breaks one array into multiple.

We use `array_split()` for splitting arrays, we pass it the array we want to split and the number of splits.

Example

Split the array in 3 parts:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 6])

newarr = np.array_split(arr, 3)

print(newarr)
```

[Try it Yourself »](#)

Note: The return value is an array containing three arrays.

If the array has less elements than required, it will adjust from the end accordingly.

Example

Split the array in 4 parts:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 6])

newarr = np.array_split(arr, 4)

print(newarr)
```

Try it Yourself »

Note: We also have the method `split()` available but it will not adjust the elements when elements are less in source array for splitting like in example above, `array_split()` worked properly but `split()` would fail.

Split Into Arrays

The return value of the `array_split()` method is an array containing each of the split as an array.

If you split an array into 3 arrays, you can access them from the result just like any array element:

Example

Access the splitted arrays:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 6])

newarr = np.array_split(arr, 3)
```

```
print(newarr[0])  
print(newarr[1])  
print(newarr[2])
```

Try it Yourself »

Splitting 2-D Arrays

Use the same syntax when splitting 2-D arrays.

Use the `array_split()` method, pass in the array you want to split and the number of splits you want to do.

Example

Split the 2-D array into three 2-D arrays.

```
import numpy as np  
  
arr = np.array([[1, 2], [3, 4], [5, 6], [7, 8], [9, 10], [11, 12]])  
  
newarr = np.array_split(arr, 3)  
  
print(newarr)
```

Try it Yourself »

The example above returns three 2-D arrays.

Let's look at another example, this time each element in the 2-D arrays contains 3 elements.

Example

Split the 2-D array into three 2-D arrays.

```
import numpy as np
```

```
arr = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9], [10, 11, 12], [13, 14, 15], [16, 17, 18]])

newarr = np.array_split(arr, 3)

print(newarr)
```

Try it Yourself »

The example above returns three 2-D arrays.

In addition, you can specify which axis you want to do the split around.

The example below also returns three 2-D arrays, but they are split along the row (axis=1).

Example

Split the 2-D array into three 2-D arrays along rows.

```
import numpy as np

arr = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9], [10, 11, 12], [13, 14, 15], [16, 17, 18]])

newarr = np.array_split(arr, 3, axis=1)

print(newarr)
```

Try it Yourself »

An alternate solution is using `hsplit()` opposite of `hstack()`

Example

Use the `hsplit()` method to split the 2-D array into three 2-D arrays along rows.

```
import numpy as np

arr = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9], [10, 11, 12], [13, 14, 15], [16, 17, 18]])
```

```
newarr = np.hsplit(arr, 3)

print(newarr)
```

[Try it Yourself »](#)

Note: Similar alternates to `vstack()` and `dstack()` are available as `vsplit()` and `dsplit()` .

[< Previous](#)[Next >](#)

COLOR PICKER



HOW TO

Tabs
Dropdowns
Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips

[Slideshow](#)

[Filter List](#)

[Sort List](#)

SHARE



CERTIFICATES

[HTML](#)

[CSS](#)

[JavaScript](#)

[SQL](#)

[Python](#)

[PHP](#)

[jQuery](#)

[Bootstrap](#)

[XML](#)

[Read More »](#)

[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

Top Tutorials

[HTML Tutorial](#)

[CSS Tutorial](#)

[JavaScript Tutorial](#)

[How To Tutorial](#)

[SQL Tutorial](#)

[Python Tutorial](#)

[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)
[Java Reference](#)
[Angular Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[jQuery Examples](#)
[Java Examples](#)
[XML Examples](#)

Web Certificates

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[jQuery Certificate](#)
[PHP Certificate](#)
[Bootstrap Certificate](#)
[XML Certificate](#)

[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

