



Machine Learning - Scale

[< Previous](#)[Next >](#)

Scale Features

When your data has different values, and even different measurement units, it can be difficult to compare them. What is kilograms compared to meters? Or altitude compared to time?

The answer to this problem is scaling. We can scale data into new values that are easier to compare.

Take a look at the table below, it is the same data set that we used in the [multiple regression chapter](#), but this time the **volume** column contains values in *liters* instead of *ccm* (1.0 instead of 1000).

Car	Model	Volume	Weight	CO2
Toyota	Aygo	1.0	790	99
Mitsubishi	Space Star	1.2	1160	95
Skoda	Citigo	1.0	929	95
Fiat	500	0.9	865	90
Mini	Cooper	1.5	1140	105
VW	Up!	1.0	929	105
Skoda	Fabia	1.4	1109	90
Mercedes	A-Class	1.5	1365	92
Ford	Fiesta	1.5	1112	98
Audi	A1	1.6	1150	99

Hyundai	120	1.1	980	99
---------	-----	-----	-----	----

It can be difficult to compare the volume 1.0 with the weight 790, but if we scale them both into comparable values, we can easily see how much one value is compared to the other.

There are different methods for scaling data, in this tutorial we will use a method called standardization.

The standardization method uses this formula:

$$z = (x - u) / s$$

Where **z** is the new value, **x** is the original value, **u** is the mean and **s** is the standard deviation.

If you take the **weight** column from the data set above, the first value is 790, and the scaled value will be:

$$(790 - 1292.23) / 238.74 = -2.1$$

If you take the **volume** column from the data set above, the first value is 1.0, and the scaled value will be:

$$(1.0 - 1.61) / 0.38 = -1.59$$

Now you can compare -2.1 with -1.59 instead of comparing 790 with 1.0.

You do not have to do this manually, the Python sklearn module has a method called `StandardScaler()` which returns a Scaler object with methods for transforming data sets.

Example

Scale all values in the Weight and Volume columns:

```
import pandas
from sklearn import linear_model
from sklearn.preprocessing import StandardScaler
scale = StandardScaler()

df = pandas.read_csv("cars2.csv")

X = df[['Weight', 'Volume']]

scaledX = scale.fit_transform(X)
```

```
print(scaledX)
```

Result:

Note that the first two values are -2.1 and -1.59, which corresponds to our calculations:

```
[[-2.10389253 -1.59336644]
 [-0.55407235 -1.07190106]
 [-1.52166278 -1.59336644]
 [-1.78973979 -1.85409913]
 [-0.63784641 -0.28970299]
 [-1.52166278 -1.59336644]
 [-0.76769621 -0.55043568]
 [ 0.3046118  -0.28970299]
 [-0.7551301  -0.28970299]
 [-0.59595938 -0.0289703 ]
 [-1.30803892 -1.33263375]
 [-1.26615189 -0.81116837]
 [-0.7551301  -1.59336644]
 [-0.16871166 -0.0289703 ]
 [ 0.14125238 -0.0289703 ]
 [ 0.15800719 -0.0289703 ]
 [ 0.3046118  -0.0289703 ]
 [-0.05142797  1.53542584]
 [-0.72580918 -0.0289703 ]
 [ 0.14962979  1.01396046]
 [ 1.2219378  -0.0289703 ]
 [ 0.5685001   1.01396046]
 [ 0.3046118   1.27469315]
 [ 0.51404696 -0.0289703 ]
 [ 0.51404696  1.01396046]
 [ 0.72348212 -0.28970299]
 [ 0.8281997   1.01396046]
 [ 1.81254495  1.01396046]
 [ 0.96642691 -0.0289703 ]
 [ 1.72877089  1.01396046]
 [ 1.30990057  1.27469315]
 [ 1.90050772  1.01396046]
 [-0.23991961 -0.0289703 ]
 [ 0.40932938 -0.0289703 ]
 [ 0.47215993 -0.0289703 ]
 [ 0.4302729   2.31762392]]
```

[Run example »](#)

Predict CO2 Values

The task in the [Multiple Regression chapter](#) was to predict the CO2 emission from a car when you only knew its weight and volume.

When the data set is scaled, you will have to use the scale when you predict values:

Example

Predict the CO2 emission from a 1.3 liter car that weighs 2300 kilograms:

```
import pandas
from sklearn import linear_model
from sklearn.preprocessing import StandardScaler
scale = StandardScaler()

df = pandas.read_csv("cars2.csv")

X = df[['Weight', 'Volume']]
y = df['CO2']

scaledX = scale.fit_transform(X)

regr = linear_model.LinearRegression()
regr.fit(scaledX, y)

scaled = scale.transform([[2300, 1.3]])

predictedCO2 = regr.predict([scaled[0]])
print(predictedCO2)
```


Result:

```
[107.2087328]
```

[Run example »](#)

[< Previous](#)[Next >](#)

COLOR PICKER



HOW TO

Tabs
Dropdowns
Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE



CERTIFICATES

HTML
CSS
JavaScript
SQL
Python
PHP
jQuery
Bootstrap
XML

[Read More »](#)

[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
jQuery Tutorial
Java Tutorial
C++ Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors

[jQuery Reference](#)[Java Reference](#)[Angular Reference](#)

Top Examples

[HTML Examples](#)[CSS Examples](#)[JavaScript Examples](#)[How To Examples](#)[SQL Examples](#)[Python Examples](#)[W3.CSS Examples](#)[Bootstrap Examples](#)[PHP Examples](#)[jQuery Examples](#)[Java Examples](#)[XML Examples](#)

Web Certificates

[HTML Certificate](#)[CSS Certificate](#)[JavaScript Certificate](#)[SQL Certificate](#)[Python Certificate](#)[jQuery Certificate](#)[PHP Certificate](#)[Bootstrap Certificate](#)[XML Certificate](#)[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

