



# Python Lists

[< Previous](#)[Next >](#)

## Python Collections (Arrays)

There are four collection data types in the Python programming language:

- **List** is a collection which is ordered and changeable. Allows duplicate members.
- **Tuple** is a collection which is ordered and unchangeable. Allows duplicate members.
- **Set** is a collection which is unordered and unindexed. No duplicate members.
- **Dictionary** is a collection which is unordered, changeable and indexed. No duplicate members.

When choosing a collection type, it is useful to understand the properties of that type. Choosing the right type for a particular data set could mean retention of meaning, and, it could mean an increase in efficiency or security.

## List

A list is a collection which is ordered and changeable. In Python lists are written with square brackets.

## Example

Create a List:

```
thislist = ["apple", "banana", "cherry"]  
print(thislist)
```

[Try it Yourself »](#)



## ACCESS ITEMS

You access the list items by referring to the index number:

### Example

Print the second item of the list:

```
thislist = ["apple", "banana", "cherry"]  
print(thislist[1])
```

[Try it Yourself »](#)

### Negative Indexing

Negative indexing means beginning from the end, **-1** refers to the last item, **-2** refers to the second last item etc.

### Example

Print the last item of the list:

```
thislist = ["apple", "banana", "cherry"]  
print(thislist[-1])
```

[Try it Yourself »](#)

### Range of Indexes

You can specify a range of indexes by specifying where to start and where to end the range.

When specifying a range, the return value will be a new list with the specified items.

### Example



HTML

CSS

MORE ▼



```
thislist = ["apple", "banana", "cherry", "orange", "kiwi", "melon",  
"mango"]  
print(thislist[2:5])
```

Try it Yourself »

**Note:** The search will start at index 2 (included) and end at index 5 (not included).

Remember that the first item has index 0.

By leaving out the start value, the range will start at the first item:

## Example

This example returns the items from the beginning to "orange":

```
thislist = ["apple", "banana", "cherry", "orange", "kiwi", "melon",  
"mango"]  
print(thislist[:4])
```

Try it Yourself »

By leaving out the end value, the range will go on to the end of the list:

## Example

This example returns the items from "cherry" and to the end:

```
thislist = ["apple", "banana", "cherry", "orange", "kiwi", "melon",  
"mango"]  
print(thislist[2:])
```



## Range of Negative Indexes

Specify negative indexes if you want to start the search from the end of the list:

### Example

This example returns the items from index -4 (included) to index -1 (excluded)

```
thislist = ["apple", "banana", "cherry", "orange", "kiwi", "melon",  
"mango"]  
print(thislist[-4:-1])
```

Try it Yourself »

## Change Item Value

To change the value of a specific item, refer to the index number:

### Example

Change the second item:

```
thislist = ["apple", "banana", "cherry"]  
thislist[1] = "blackcurrant"  
print(thislist)
```

Try it Yourself »

## Loop Through a List

You can loop through the list items by using a **for** loop:



HTML

CSS

MORE ▼



Print all items in the list, one by one:

```
thislist = ["apple", "banana", "cherry"]
for x in thislist:
    print(x)
```

Try it Yourself »

You will learn more about **for** loops in our [Python For Loops](#) Chapter.

## Check if Item Exists

To determine if a specified item is present in a list use the **in** keyword:

### Example

Check if "apple" is present in the list:

```
thislist = ["apple", "banana", "cherry"]
if "apple" in thislist:
    print("Yes, 'apple' is in the fruits list")
```

Try it Yourself »

## List Length

To determine how many items a list has, use the **len()** function:

### Example

Print the number of items in the list:



Try it Yourself »

## Add Items

To add an item to the end of the list, use the `append()` method:

### Example

Using the `append()` method to append an item:

```
thislist = ["apple", "banana", "cherry"]  
thislist.append("orange")  
print(thislist)
```

Try it Yourself »

To add an item at the specified index, use the `insert()` method:

### Example

Insert an item as the second position:

```
thislist = ["apple", "banana", "cherry"]  
thislist.insert(1, "orange")  
print(thislist)
```

Try it Yourself »

## Remove Item

There are several methods to remove items from a list:



The `remove()` method removes the specified item:

```
thislist = ["apple", "banana", "cherry"]  
thislist.remove("banana")  
print(thislist)
```

[Try it Yourself »](#)

## Example

The `pop()` method removes the specified index, (or the last item if index is not specified):

```
thislist = ["apple", "banana", "cherry"]  
thislist.pop()  
print(thislist)
```

[Try it Yourself »](#)

## Example

The `del` keyword removes the specified index:

```
thislist = ["apple", "banana", "cherry"]  
del thislist[0]  
print(thislist)
```

[Try it Yourself »](#)

## Example

The `del` keyword can also delete the list completely:



Try it Yourself »

## Example

The `clear()` method empties the list:

```
thislist = ["apple", "banana", "cherry"]
thislist.clear()
print(thislist)
```

Try it Yourself »

## Copy a List

You cannot copy a list simply by typing `list2 = list1`, because: `list2` will only be a *reference* to `list1`, and changes made in `list1` will automatically also be made in `list2`.

There are ways to make a copy, one way is to use the built-in List method `copy()`.

## Example

Make a copy of a list with the `copy()` method:

```
thislist = ["apple", "banana", "cherry"]
mylist = thislist.copy()
print(mylist)
```

Try it Yourself »

Another way to make a copy is to use the built-in method `list()`.





Make a copy of a list with the `list()` method:

```
thislist = ["apple", "banana", "cherry"]  
mylist = list(thislist)  
print(mylist)
```

[Try it Yourself »](#)

## Join Two Lists

There are several ways to join, or concatenate, two or more lists in Python.

One of the easiest ways are by using the `+` operator.

### Example

Join two list:

```
list1 = ["a", "b" , "c"]  
list2 = [1, 2, 3]  
  
list3 = list1 + list2  
print(list3)
```

[Try it Yourself »](#)

Another way to join two lists are by appending all the items from list2 into list1, one by one:

### Example

Append list2 into list1:

```
list1 = ["a", "b" , "c"]  
list2 = [1, 2, 3]
```



```
list1.append(x)
```

```
print(list1)
```

Try it Yourself »

Or you can use the `extend()` method, which purpose is to add elements from one list to another list:

## Example

Use the `extend()` method to add list2 at the end of list1:

```
list1 = ["a", "b" , "c"]  
list2 = [1, 2, 3]
```

```
list1.extend(list2)  
print(list1)
```

Try it Yourself »

## The list() Constructor

It is also possible to use the `list()` constructor to make a new list.

## Example

Using the `list()` constructor to make a List:

```
thislist = list(("apple", "banana", "cherry")) # note the double round-  
brackets  
print(thislist)
```

Try it Yourself »



## LIST METHODS

Python has a set of built-in methods that you can use on lists.

Method	Description
<u>append()</u>	Adds an element at the end of the list
<u>clear()</u>	Removes all the elements from the list
<u>copy()</u>	Returns a copy of the list
<u>count()</u>	Returns the number of elements with the specified value
<u>extend()</u>	Add the elements of a list (or any iterable), to the end of the current list
<u>index()</u>	Returns the index of the first element with the specified value
<u>insert()</u>	Adds an element at the specified position
<u>pop()</u>	Removes the element at the specified position
<u>remove()</u>	Removes the item with the specified value
<u>reverse()</u>	Reverses the order of the list
<u>sort()</u>	Sorts the list

## Test Yourself With Exercises

### Exercise:

Print the second item in the `fruits` list.

```
fruits = ["apple", "banana", "cherry"]  
print(      )
```



HTML

CSS

MORE ▼

[Start the Exercise](#)[◀ Previous](#)[Next ▶](#)

## COLOR PICKER



## HOW TO

Tabs  
Dropdowns  
Accordions  
Side Navigation  
Top Navigation  
Modal Boxes  
Progress Bars  
Parallax  
Login Form  
HTML Includes  
Google Maps  
Range Sliders  
Tooltips  
Slideshow  
Filter List  
Sort List

## SHARE

[HTML](#)[CSS](#)[MORE ▾](#)

## CERTIFICATES

HTML  
CSS  
JavaScript  
SQL  
Python  
PHP  
jQuery  
Bootstrap  
XML

[Read More »](#)

---

[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

---

## Top Tutorials

HTML Tutorial  
CSS Tutorial  
JavaScript Tutorial  
How To Tutorial  
SQL Tutorial  
Python Tutorial  
W3.CSS Tutorial  
Bootstrap Tutorial  
PHP Tutorial  
jQuery Tutorial  
Java Tutorial  
C++ Tutorial

## Top References

[HTML](#)[CSS](#)[MORE ▼](#)[JavaScript Reference](#)[SQL Reference](#)[Python Reference](#)[W3.CSS Reference](#)[Bootstrap Reference](#)[PHP Reference](#)[HTML Colors](#)[jQuery Reference](#)[Java Reference](#)[Angular Reference](#)

## Top Examples

[HTML Examples](#)[CSS Examples](#)[JavaScript Examples](#)[How To Examples](#)[SQL Examples](#)[Python Examples](#)[W3.CSS Examples](#)[Bootstrap Examples](#)[PHP Examples](#)[jQuery Examples](#)[Java Examples](#)[XML Examples](#)

## Web Certificates

[HTML Certificate](#)[CSS Certificate](#)[JavaScript Certificate](#)[SQL Certificate](#)[Python Certificate](#)[jQuery Certificate](#)[PHP Certificate](#)[Bootstrap Certificate](#)[XML Certificate](#)[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

