



NumPy Set Operations

[< Previous](#)[Next >](#)

What is a Set

A set in mathematics is a collection of unique elements.

Sets are used for operations involving frequent intersection, union and difference operations.

Create Sets in NumPy

We can use NumPy's `unique()` method to find unique elements from any array. E.g. create a set array, but remember that the set arrays should only be 1-D arrays.

Example

Convert following array with repeated elements to a set:

```
import numpy as np

arr = np.array([1, 1, 1, 2, 3, 4, 5, 5, 6, 7])

x = np.unique(arr)

print(x)
```

[Try it Yourself »](#)

Finding Union

To find the unique values of two arrays, use the `union1d()` method.

Example

Find union of the following two set arrays:

```
import numpy as np

arr1 = np.array([1, 2, 3, 4])
arr2 = np.array([3, 4, 5, 6])

newarr = np.union1d(arr1, arr2)

print(newarr)
```

Try it Yourself »

Finding Intersection

To find only the values that are present in both arrays, use the `intersect1d()` method.

Example

Find intersection of the following two set arrays:

```
import numpy as np

arr1 = np.array([1, 2, 3, 4])
arr2 = np.array([3, 4, 5, 6])

newarr = np.intersect1d(arr1, arr2, assume_unique=True)

print(newarr)
```

Try it Yourself »

Note: the `intersect1d()` method takes an optional argument `assume_unique`, which if set to True can speed up computation. It should always be set to True when dealing with sets.

Finding Difference

To find only the values in the first set that is NOT present in the second set, use the `setdiff1d()` method.

Example

Find the difference of the set1 from set2:

```
import numpy as np

set1 = np.array([1, 2, 3, 4])
set2 = np.array([3, 4, 5, 6])

newarr = np.setxor1d(set1, set2, assume_unique=True)

print(newarr)
```

Try it Yourself »

Note: the `setxor1d()` method takes an optional argument `assume_unique`, which if set to True can speed up computation. It should always be set to True when dealing with sets.

Finding Symmetric Difference

To find only the values that are NOT present in BOTH sets, use the `setxor1d()` method.

Example

Find the symmetric difference of the set1 and set2:

```
import numpy as np

set1 = np.array([1, 2, 3, 4])
set2 = np.array([3, 4, 5, 6])

newarr = np.setdiff1d(set1, set2, assume_unique=True)


print(newarr)
```

Try it Yourself »

Note: the `setdiff1d()` method takes an optional argument `assume_unique`, which if set to True can speed up computation. It should always be set to True when dealing with sets.

[< Previous](#)[Next >](#)

COLOR PICKER



HOW TO

Tabs
Dropdowns
Accordions

Side Navigation

Top Navigation

Modal Boxes

Progress Bars

Parallax

Login Form

HTML Includes

Google Maps

Range Sliders

Tooltips

Slideshow

Filter List

Sort List

SHARE



CERTIFICATES

HTML

CSS

JavaScript

SQL

Python

PHP

jQuery

Bootstrap

XML

[Read More »](#)

REPORT ERROR

PRINT PAGE

FORUM

ABOUT

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)
[Java Reference](#)
[Angular Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[jQuery Examples](#)
[Java Examples](#)
[XML Examples](#)

Web Certificates

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[jQuery Certificate](#)

PHP Certificate
Bootstrap Certificate
XML Certificate

[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

