



HTML

CSS

MORE ▾



NumPy Creating Arrays

[< Previous](#)[Next >](#)

Create a NumPy ndarray Object

NumPy is used to work with arrays. The array object in NumPy is called `ndarray`.

We can create a NumPy `ndarray` object by using the `array()` function.

Example

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5])

print(arr)

print(type(arr))
```

[Try it Yourself »](#)

type(): This built-in Python function tells us the type of the object passed to it. Like in above code it shows that `arr` is `numpy.ndarray` type.

To create an `ndarray`, we can pass a list, tuple or any array-like object into the `array()` method, and it will be converted into an `ndarray`:

Example

Use a tuple to create a NumPy array:

```
import numpy as np

arr = np.array((1, 2, 3, 4, 5))

print(arr)
```

Try it Yourself »

Dimensions in Arrays

A dimension in arrays is one level of array depth (nested arrays).

nested array: are arrays that have arrays as their elements.

0-D Arrays

0-D arrays, or Scalars, are the elements in an array. Each value in an array is a 0-D array.

Example

Create a 0-D array with value 42

```
import numpy as np

arr = np.array(42)

print(arr)
```

Try it Yourself »

1-D Arrays

An array that has 0-D arrays as its elements is called uni-dimensional or 1-D array.

These are the most common and basic arrays.

Example

Create a 1-D array containing the values 1,2,3,4,5:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5])

print(arr)
```

Try it Yourself »

2-D Arrays

An array that has 1-D arrays as its elements is called a 2-D array.

These are often used to represent matrix or 2nd order tensors.

NumPy has a whole sub module dedicated towards matrix operations called `numpy.mat`

Example

Create a 2-D array containing two arrays with the values 1,2,3 and 4,5,6:

```
import numpy as np

arr = np.array([[1, 2, 3], [4, 5, 6]])

print(arr)
```

Try it Yourself »

3-D arrays

An array that has 2-D arrays (matrices) as its elements is called 3-D array.

These are often used to represent a 3rd order tensor.

Example

Create a 3-D array with two 2-D arrays, both containing two arrays with the values 1,2,3 and 4,5,6:

```
import numpy as np

arr = np.array([[[1, 2, 3], [4, 5, 6]], [[1, 2, 3], [4, 5, 6]]])

print(arr)
```

Try it Yourself »

Check Number of Dimensions?

NumPy Arrays provides the `ndim` attribute that returns an integer that tells us how many dimensions the array have.

Example

Check how many dimensions the arrays have:

```
import numpy as np

a = np.array(42)
b = np.array([1, 2, 3, 4, 5])
c = np.array([1, 2, 3], [4, 5, 6])
d = np.array([[[1, 2, 3], [4, 5, 6]], [[1, 2, 3], [4, 5, 6]]])
```

```
print(a.ndim)
print(b.ndim)
print(c.ndim)
print(d.ndim)
```

Try it Yourself »

Higher Dimensional Arrays

An array can have any number of dimensions.

When the array is created, you can define the number of dimensions by using the `ndmin` argument.

Example

Create an array with 5 dimensions and verify that it has 5 dimensions:

```
import numpy as np

arr = np.array([1, 2, 3, 4], ndmin=5)

print(arr)
print('number of dimensions :', arr.ndim)
```

Try it Yourself »

In this array the innermost dimension (5th dim) has 4 elements, the 4th dim has 1 element that is the vector, the 3rd dim has 1 element that is the matrix with the vector, the 2nd dim has 1 element that is 3D array and 1st dim has 1 element that is a 4D array.

[< Previous](#)

[Next >](#)

COLOR PICKER



HOW TO

Tabs
Dropdowns
Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE



CERTIFICATES

HTML
CSS
JavaScript
SQL
Python
PHP
jQuery
Bootstrap
XML

[Read More »](#)

[REPORT ERROR](#)[PRINT PAGE](#)[FORUM](#)[ABOUT](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)
[Java Reference](#)
[Angular Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)

W3.CSS Examples
Bootstrap Examples
PHP Examples
jQuery Examples
Java Examples
XML Examples

Web Certificates

HTML Certificate
CSS Certificate
JavaScript Certificate
SQL Certificate
Python Certificate
jQuery Certificate
PHP Certificate
Bootstrap Certificate
XML Certificate

[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

