

COMSATS University Islamabad, Lahore Campus Department of Computer Engineering

$Microprocessor\ Systems\ and\ Interacting\ (CPE342)$

Course Instructor: Engr. Usman Rafique

AssignmentTWO	Section: _FA22-BCE-B_		
Submitted by: Abdullah Laeeq			
Reg. number:FA22-BCE-026			
Submitted on:			

	Q1	Q2	Q3	Total
Marks Obtained				



COMSATS UNIVERSITY ISLAMABAD, Lahore Campus

Department of Computer Engineering

Subject: Microprocessor Systems and Interfacing (CPE342) Batch: FA22-BCE-B

Assignment No. TWO Total Marks: 30

Handed over on: 20th March 2025 Submission Date: 27th March 2025

(In class)

Student's Name: Abdullah Laeeq

Registration Number: FA22-BCE-026

Instructions:

• Provide your solution in the space provided against each problem

- Back side of each leaf is for rough work only
- Submission after the deadline will not be graded
- Do not use lead pencil in your solution

Note: The CPU referred to in this problem sheet is Intel 8086-88.

Problem 1 10 Marks

Consider the following high-level language program structure. Construct complete assembly language program that can be generated from this program structure.

```
for (a=0; a<=250; a=a+2) {
    y = (x*a)-125;
        if (y>100) {
            pair();
            y++;
        } //end if
} //end for

void pair(j,k) {
    j = j/k;
} //end void
```

Assume all the variables **a**, **x**, **y**, **j** and **k** are 8-bit integers and are stored in BL, DL, DH, CL and CH, respectively. **Solution:**

Microprocessor Systems and Interfacing (CPE342) Course Instructor: Usman Rafique

;a => BL ;x => DL ;y => DH ;j => CL ;k => CH MOV BL,0 MOV DL,1 MOV DH,139 MOV CL,55 MOV CH,122 FOR: MOV AL,BL MUL DL MOV DH,AL SUB DH,125 CMP DH,100 JLE SKIP CALL PAIR INC DH SKIP: ADD BL,2 CMP BL,250 JBE FOR JMP END

PAIR: MOV AL,CL DIV CH MOV CL,AL

RET

END:

Construct an assembly language program that reads 1-byte data from 2000H and 1-byte data from 5000H. Place this data onto the stack, which is initially empty, such that the byte read from 1234H is the lower-byte and from ABCDH is the higher-byte of the 16-bit data that is to be placed onto the stack. Repeat this operation unless the stack segment becomes completely full. The stack segment starts from 9000H.

Solution:

MOV BX,1234H MOV DS,BX

MOV SI,2000H MOV [SI],55 MOV AL,[SI]

MOV BX,0ABCDH MOV DS,BX

MOV DI,5000H MOV [DI],25 MOV AH,[DI]

MOV BX,9000H MOV SS,BX MOV SP,0

MOV CX,8000H

COPY_LOOP:

PUSH AX

LOOP COPY_LOOP

Problem 3 10 Marks

Construct an assembly language program that reads a word from stack segment and check whether it is odd or even. Check entire stack segment for this operation. Place the count of even words in AX and count of odd words in BX. The stack starts at B000H. Make use of a subroutine that checks the odd/even property of the word.

Solution:

MOV BX,0B000H MOV SS,BX MOV SP,0 MOV CX,30

LOOP_STACK:

POP DX CALL CHECK

LOOP LOOP_STACK

JMP FINISH

CHECK: TEST DX,1 JC ODD INC AX JMP END ODD: INC BX END: RET

FINISH: