Abdullah Laeeq FA22-BCE-026

Q1

a) In Unity, we attach script to an empty object and in its Start() method, we run a loop from 0 to 8, insid the loop

Vector3 pos = new Vector3(0, 0, i*2), where is loop index and 2 is spacing/gap b/w cubes.
This keeps X, Y at 0 while stepping each cube further along Z axis
Then we call Instantiate(cubePrefab, pos, Quaternion.identity) to place each a cube the set its local size to new Vector3(2, 2, 2)

b) Rigidity + Physics Material with Bounciness value set to sphere's Collider

Q2 A prefab is a reusable template of a game object stored as an asset
Created by dragging Game Object from hierarchy panel into Project panel
Devs prefer it because any change made to original prefab auto propogates to all instances

manual duplication & inconsistency.

Q3

- Score (UI Canvas + Text): Add Canvas
  → Text Mesh Pro / Text Component
  → Reference in Script
  → update text string when score changes

- Background audio Loop:
  Add Audio Source Component
  → assign Clip → check loop
  → call play() in Start()

- Game Over Scene:
  Use OnCollisionEnter → call
  SceneManager.LoadScreen("GameOver")

Q4

(a) Bus moves 1 free only

(b) Destroy(col.gameObject) destroys the enemy; Destroy(transform.gameObject) Destroys bullet itself

(c) 3 coins instantiated.