greatlearning
Power Ahead

Front End Development - HTML

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

Table of Content

- What is HTML?
- Features
- HTML Editor
- HTML Skeleton
- Comments
- HTML Elements
- Basic Tags
- Attributes

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

What is HTML?

- Stands for HyperText Markup Language
- HyperText: Link between web pages.
- Markup Language: Text between tags which defines structure.
- It is a language to create web pages
- HTML defines how the web page looks and how to display content with the help of elements
- It forms or defines the structure of our Web Page
- Need to save your file with .html extension

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

Features Of HTML

- The learning curve is very easy (easy to modify)
- Create effective presentations
- Add links wherein we can add references
- Can display documents on platforms like Mac , Windows, Linux etc
- Add videos, graphics and audios making it more attractive.
- Case insensitive language

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

HTML Editors

- Simple editor: Notepad
- Notepad++
- Atom
- Best editor: Sublime Text.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

HTML Skeleton

```
<!DOCTYPE html>
<html>
<head>
        <title></title>
</head>
<body>

</body>
</html>
```

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

<!DOCTYPE html>

Instruction to the browser about the HTML version.

<html>

Root element which acts as a container to hold all the code
Browser should know that this a HTML document
Permitted content: One head tag followed by one body tag

<head>

Everything written here will never be displayed in the browser
It contains general information about the document
Title, definitions of css and script sheets
Metadata(information about the document)

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

<body>

- Everything written here will be displayed in the browser
- Contains text, images, links which can be achieved through tags.
- Examples:
  - This is our first paragraph.
  - Go To Google
  - <img src="photo.jpg">

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

HTML Comments

- Comments don’t render on the browser
- Helps to understand our code better and makes it readable.
- Helps to debug our code
- Three ways to comment:
  - Single line
  - Multiple line
  - Comment tag //Supported by IE

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

HTML Element

- Elements are created using tags
- Elements are used to define semantics
- Can be nested and empty

Basic Structure

 This is our first Paragraph

- Contains following things:
  - Start tag:
  - Attributes: color =”red”
  - End tag: // optional
  - Content: This is our first Paragraph

Proprietary content. ©Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.
This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

Element Types

- **Block Level** :
  - Takes up full block or width and adds structure in the web page
  - Always starts from new line
  - Always end before the new line
  - Example :
    - <p >
    -
    - <h1>...<h6>
    -
    -

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

Element Types

- **Inline Level**:
    - Takes up what is requires and adds meaning to the web page
    - Always starts from where the previous element ended
    - Example :
        -
        -
        -
        - <img>
        - <a>

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

Basic Tags:

- Enclosed within <>
- Different tags render different meaning .

- **<title> tag**
  - Whatever is written this tag comes up in the web page's tab
  - Defines the title of the page
  - Syntax: <title>Home </title>

- ** tag**
  - Defines the paragraph
  - Syntax: This is our first Paragraph

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

List of Self closing tags

- **<hr> tag**
  - Stands for horizontal rule
  - Dividing the web page

- **
 tag**
  - Stands for break line
  - Moving to next line

- **<img> tag**
  - To add images in the web page

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

- **<h1> tag …… <h6>tag**
  - Stands for heading tag
  - Defines heading of a page
  - h1 represents most important page in the page
  - h6 represents least important page in the page

- ** tag**
  - Defines the text to be bold
  - Replaced <b>tag //HTML5

- ** tag**
  - Defines the text to be bold
  - Replaced <i>tag //HTML5

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

- ** tag**
  - Stands for ordered list
  - To define series of events that take place in some order
  - Example making a tea (like a flow chart)
  - .....

- ** tag**
  - Stands for unordered list
  - To define series of events that take place where order is not important.
  - Example your hobbies
  - .....

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

- ** tag**
  - Defines the list item
  - Used inside the ‘ol’ and ‘ul’ tag to define the events
  -

- ** and tags**
  - Both of these are used to group different tags .
  - Acts like a container.
  - Effective while styling.
  - .....
  - ....
  - Difference   is block level and is inline level.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

- **<img> tag**
  - Used to add images in a web page
  - Syntax: <img src=”url”>
  - Self closing tag.

- **<a> tags**
  - Used to add links in a web page
  - Name of the link

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

- **<table> tag**

  - Used to create a table on a web page
  - Need other tags for completing the creation of a table
    - <tr> : for marking the table row
    - <th> : for table header
    - <td> : for table column data
  - Everything is always enclosed within <tr>
    - <thead> : to keep all header data
    - <tbody> : to keep all body data

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

- **<form> tag**
    - Action attribute: It specifies the URL to send form data to
    - Method attribute: specifies the type of HTTP request(GET or POST)
    - Example: <form action="/my-form-submitting-page" method="POST">
    - <input>: used to accept data from the user
    - Some types of inputs are:

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

- **Text**: used to store text data. Syntax: type="text"
- **Password**: used to enter a secure password. Syntax: type="password"
- **Placeholder**: temporary text in input fields. It is generally accompanied by "text" and "password" attributes. Syntax: placeholder="insert- text-here"
- **Button**: used to include buttons in the form. Syntax: type="button" value="insert-text-here"
- **Submit button**: For creating a submit button. All the data will get submitted when it is clicked. Syntax: type="submit"
- **Checkbox**: to provide the ability to check multiple options. Syntax: type="checkbox". To check options by default, set it with the checked attribute.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

- **Radio Button**: allows one to choose a single option. Syntax: type="radio". Keep the name attribute of all the options the same.
- **<select>**: For every possible option to select, use an <option> tag<option>
- **Text Areas**: multi-line plain-text editing control. Syntax: <textarea>. You can specify how large the text area is by using the "rows" and "cols" attributes
- **Labels**: add captions for individual items in a form. Syntax: <label>. A label can be used by placing the control element inside the <label> element, or by using the "for" and "id" attributes.
- Validations ensure that users fill out forms in the correct format, e.g.:
  a. **required**: The Boolean attribute which makes a field mandatory:
  b. **email**: the browser will ensure that the field contains an @ symbol.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.
This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

Attributes

- Properties associated with each tag.
- <tag name=”value”></tag> is the structure.
- Global Attribute:
  - Title : Add extra information (hover)
  - Style: Add style information(font,background,color,size)
- <img src=”url” width=”100”>
  - src is the attribute used in image tag to define path
  - Width is attribute used to define width in pixels
  - Alt i.e alternate text if image is not loaded

- Name of the link
  - href used to define path of the link.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

Conclusion

- Introduction to HTML
- Comments
- HTML Elements
- Basic Tags
- Attributes

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.

Thank You

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

This file is meant for personal use by abdullahshaikh150704@gmail.com only.
Sharing or publishing the contents in part or full is liable for legal action.