

CSEN1002 Compilers Lab, Spring Term 2024
Task 9: ANTLR Parsing I

Due: Week starting 07.05.2024

1 Objective

For this task you will use ANTLR (www.antlr.org) to implement an SDD for the following problem. ANTLR documentation is available here:

<https://github.com/antlr/antlr4/blob/master/doc/index.md>

2 Requirements

- You are required to use ANTLR to implement the SDD appearing below for a CFG that generates a language over $\{0, 1, \#\}$.

$$\begin{aligned} S &\longrightarrow F & S.check &= F.check * F.m \\ F &\longrightarrow DT & D.r &= 1; \quad D.c = 1 \\ & & T.r &= 2; \quad T.l = D.l \\ & & F.check &= D.check * T.check; \quad F.m = T.m \\ T &\longrightarrow \#N & N.r &= T.r; \quad N.c = 1 \quad N.l = T.l \\ & & T.check &= N.check; \quad T.m = N.m \\ T &\longrightarrow \varepsilon & T.check &= 1; \quad T.m = 1 \\ N &\longrightarrow DT & D.r &= N.r; \quad D.c = 1 \\ & & T.l &= N.l; \quad T.r = N.r + 1 \\ & & N.check &= D.check * T.check; \quad N.m = equals(D.l, N.l) * T.m \\ D &\longrightarrow 0D_1 & D_1.r &= D.r; \quad D_1.c = D.c + 1 \\ & & D.l &= D_1.l; \quad D.check = (1 - equals(D.c, D.r)) * D_1.check \\ D &\longrightarrow 1D_1 & D_1.r &= D.r; \quad D_1.c = D.c + 1 \\ & & D.l &= D_1.l; \quad D.check = equals(D.c, D.r) * D_1.check \\ D &\longrightarrow 0 & D.l &= D.c; \quad D.check = 1 - equals(D.c, D.r) \\ D &\longrightarrow 1 & D.l &= D.c; \quad D.check = equals(D.c, D.r) \end{aligned}$$

- The start variable S has an attribute *check* whose value is 1 if the generated string is a diagonal boolean matrix; otherwise, the value of *Check* is 0. A string over $\{0, 1, \#\}$ represents a boolean matrix if it is of the form $r_1\#r_2\#\dots\#r_n$, where $r_i \in \{0, 1\}^+$ and $|r_i| = |r_j|$, for every $1 \leq i, j \leq n$; the matrix is diagonal if, in addition, the j th bit of r_i , $1 \leq j \leq |r_i|$, is 1 if and only if $j = i$, for every $1 \leq i \leq n$.

- The only operations allowed on attributes are assignments, additions, subtraction, multiplications, and equality checks; an equality check is an expression of the form *equals(x,y)* whose value is 1 if *x* is equal to *y* and is 0 otherwise.
- The provided method `sCheckValue` uses the ANTLR grammar to get the value of *S.check* for a given input string. For example, for the string `10#01`, `sCheckValue` returns 1; and returns 0 for the string `11#01`.
- Important Details
 - Your implementation should be done within the template file uploaded to the CMS.
 - You are not allowed to change the grammar name, the rule name “s” or attribute “check”.
 - You are allowed to write as many helper parser and lexer rules within the same grammar file (if needed).
 - Public test cases have been provided on the CMS for you to test your implementation.
 - Please ensure that the public test cases run correctly without modification before coming to the lab to maintain a smooth evaluation process.
 - A Java file is provided in order to easily test your grammar with custom strings in addition to the public test cases.
 - Private test cases will be uploaded before your session and will have the same structure as the public test cases.

3 Evaluation

- Your SDD will be tested using ten inputs.
- You get one point for each correct output; hence, a maximum of ten points.

4 Online Submission

- You should submit your code at the following link.

<https://forms.gle/XiHwHwtrDdSSbG2r8>

- Submit one file “Task9.g4” containing the grammar.
- **Online submission is due by the end of your lab session.**