

(After Executing the command, Login in Hospice using “uid”: “00000” and “password”: “a12345678A”)

Execute the following commands in MySQL Server for Hospice (mysql id name “root”, Password “password”):

```
set global max_connections = 100000;
create database hospice;
use hospice;
create table login(
uid varchar(100),
password varchar(100)
);
INSERT INTO login (uid,password)
VALUES ("00000","a12345678A");
create table patient(
uid varchar(100),
name varchar(1000),
type int,
gender varchar(20),
age int,
mail varchar(100),
medicalhistory varchar(2000),
DoctorExpense Double(20,6),
PharmacyExpense Double(20,6),
LabExpense Double(20,6),
OtherExpense Double(20,6),
TotalBill Double(20,6)
);
INSERT INTO patient (uid)
VALUES ("10000");
create table employee(
uid varchar(100),
name varchar(1000),
type int,
gender varchar(20),
age int,
mail varchar(100),
MonthlySalary Double(20,6)
);
INSERT INTO employee (uid)
VALUES ("00000");
```

```
INSERT INTO employee (uid)
VALUES ("30000");
create table service(
uid varchar(100),
name varchar(1000),
type int,
description varchar(1000),
cost_unit Double(20,6),
discount Double(20,6)
);
INSERT INTO service (uid)
VALUES ("10");
create table providedservice(
ps_uid varchar(100),
s_uid varchar(100),
p_uid varchar(100),
e_uid varchar(100),
r_uid varchar(100),
s_type int,
quantity int,
payment_status int,
bill Double(20,6),
paid Double (20,6),
s_name varchar(1000)
);
INSERT INTO providedservice (ps_uid)
VALUES ("100000");
```