

Table of Contents

1. [Multidimensional Arrays](#)
 2. [Jagged Arrays \(Array of Arrays\)](#)
 3. [Comparison: Multidimensional vs Jagged](#)
 4. [Best Practices](#)
-

1. Multidimensional Arrays

Definition

A multidimensional array is a **rectangular array** where all rows have the same number of columns. It's stored as a single contiguous block in memory.

Syntax & Declaration

```
// Declaration - 2D array (4 rows x 3 columns)
int[,] arr = new int[4, 3];

// Declaration with initialization
int[,] arr1 = new int[4, 3]
{
    { 3, 4, 5 }, // Row 0
    { 4, 2, 3 }, // Row 1
    { 7, 8, 9 }, // Row 2
    { 5, 4, 5 }  // Row 3
};

// 3D array example
int[, ,] cube = new int[2, 3, 4]; // 2 layers x 3 rows x 4 columns
```

Memory Representation

Logical View (4x3 array):

	Col0	Col1	Col2
Row0	3	4	5
Row1	4	2	3

Row2	7	8	9
Row3	5	4	5

Physical Memory (Contiguous block):

3	4	5	4	2	3	7	8	9	5	4	5
---	---	---	---	---	---	---	---	---	---	---	---

↑Row0→→→ ↑Row1→→→ ↑Row2→→→ ↑Row3→→→

Stack:

arr1	0x1000
------	--------

Heap:

[3,4,5,4,2,3,7,8,9...	0x1000
-----------------------	--------

Single contiguous block

Accessing Elements

```
int[, ] arr1 = new int[4, 3]
{
    { 3, 4, 5 },
    { 4, 2, 3 },
    { 7, 8, 9 },
    { 5, 4, 5 }
};

// Reading element at row 2, column 1
Console.WriteLine(arr1[2, 1]); // Output: 8

// Modifying element at row 1, column 2
arr1[1, 2] = 4;
Console.WriteLine(arr1[1, 2]); // Output: 4
```

Important Methods & Properties

```
int[, ] matrix = new int[4, 3];

// Get number of dimensions
int dimensions = matrix.Rank; // Returns 2

// Get length of specific dimension
int rows = matrix.GetLength(0); // Returns 4 (dimension 0)
```

```

int cols = matrix.GetLength(1);    // Returns 3 (dimension 1)

// Get total number of elements
int total = matrix.Length;        // Returns 12 (4 × 3)

// Get upper bound of dimension (max index)
int maxRowIndex = matrix.GetUpperBound(0); // Returns 3
int maxColIndex = matrix.GetUpperBound(1); // Returns 2

```

Practical Example: Student Management System

```

// Scenario: Store student names across multiple tracks
// Each track has the SAME number of students

Console.WriteLine("Enter number of tracks:");
int numOfTracks = int.Parse(Console.ReadLine());

Console.WriteLine("Enter number of students per track:");
int numOfStudents = int.Parse(Console.ReadLine());

// Create 2D array: [tracks, students_per_track]
string[,] studentNames = new string[numOfTracks, numOfStudents];

// Input phase
for (int i = 0; i < studentNames.GetLength(0); i++)
{
    Console.WriteLine($"\\n--- Track {i + 1} ---");

    for (int j = 0; j < studentNames.GetLength(1); j++)
    {
        Console.Write($"Enter name of student {j + 1}: ");
        studentNames[i, j] = Console.ReadLine();
    }
}

// Output phase
Console.WriteLine("\\n===== STUDENT LIST =====");
for (int i = 0; i < numOfTracks; i++)
{
    Console.WriteLine($"\\n📁 Track {i + 1}:");
    Console.WriteLine("-----");

    for (int j = 0; j < numOfStudents; j++)
    {
        Console.WriteLine($"    {j + 1}. {studentNames[i, j]}");
    }
}

```

```
}  
}
```

Example Run:

```
Enter number of tracks: 2  
Enter number of students per track: 3
```

```
--- Track 1 ---
```

```
Enter name of student 1: Ahmed  
Enter name of student 2: Sara  
Enter name of student 3: Mohamed
```


```
--- Track 2 ---
```

```
Enter name of student 1: Fatma  
Enter name of student 2: Ali  
Enter name of student 3: Nour
```

```
===== STUDENT LIST =====
```

```
 Track 1:
```

-
1. Ahmed
 2. Sara
 3. Mohamed

```
 Track 2:
```

-
1. Fatma
 2. Ali
 3. Nour

Iteration Patterns

```
int[,] matrix = new int[3, 4];  
  
// Pattern 1: Using GetLength (Recommended)  
for (int i = 0; i < matrix.GetLength(0); i++) // Rows  
{  
    for (int j = 0; j < matrix.GetLength(1); j++) // Columns  
    {  
        Console.Write($"{matrix[i, j]} ");  
    }  
    Console.WriteLine();  
}
```

```

}

// Pattern 2: Using GetUpperBound
for (int i = 0; i <= matrix.GetUpperBound(0); i++)
{
    for (int j = 0; j <= matrix.GetUpperBound(1); j++)
    {
        matrix[i, j] = i * j;
    }
}

// Pattern 3: Foreach (read-only access)
foreach (int value in matrix)
{
    Console.WriteLine($"{value} ");
}

```

Advantages

1. **Simple syntax:** `arr[i, j]` is intuitive
2. **Memory efficient:** Stored as single contiguous block
3. **Cache-friendly:** Better CPU cache utilization
4. **Type-safe:** Strong compile-time checking
5. **Built-in bounds checking:** Prevents index out of range errors
6. **Easy to visualize:** Natural matrix/grid representation

Disadvantages

1. **Fixed rectangular shape:** All rows MUST have same column count
2. **Inflexible:** Cannot have rows with different lengths
3. **Harder to resize:** Cannot add/remove rows easily
4. **Memory waste:** If some rows need fewer columns, space is wasted
5. **Less intuitive for jagged data:** Not natural for variable-length rows

When to Use Multidimensional Arrays

Use when:

- Data forms a **perfect rectangle/grid** (e.g., chessboard, image pixels)
- All rows have **same number of columns**
- Need **maximum performance** (cache locality)
- Representing **mathematical matrices**
- Storing **tabular data** with uniform structure

Avoid when:

- Rows have **different lengths** (use jagged arrays)
- Need to **add/remove rows dynamically** (use List<List>)
- Data is **sparse** (many empty cells)

Real-world examples:

- 🎮 Game board (8×8 chess, 10×10 sudoku)
 - 🖼️ Image pixels (width × height)
 - 📊 Fixed-size spreadsheet
 - 📅 Calendar (7 days × 5 weeks)
 - 🎯 Seating chart (rows × seats per row)
-

By Abdullah Ali

Contact : +201012613453