

1 HTML Structure - Basic Structure

DOCTYPE and Head

html

```
<!DOCTYPE html>
```

- **Purpose:** Tells the browser this page is written in HTML5
- **Reference:** [W3Schools - HTML DOCTYPE](#)

html

```
<meta charset="UTF-8" />
```

- **Purpose:** Sets character encoding to support all languages (Arabic, English, Chinese...)
- **Without UTF-8:** Arabic characters will appear as weird symbols ❔❔❔❔

html

```
<meta name="viewport" content="width=device-width, initial-scale=1.0" />
```

- **Purpose:** Makes the page responsive on mobile devices
- **Without it:** Page will appear very small on phones

2 HTML Table - The Table

Basic Table Structure

html

```
<table border="1" cellpadding="15">
```

Attributes Explained:

- `border="1"` : Border thickness = 1 pixel
- `cellpadding="15"` : Space between cell content and borders = 15 pixels

- Reference: [W3Schools - HTML Tables](https://www.w3schools.com/html/html_tables.asp)

First Row - Main Header

html

```
<tr>
  <th colspan="9">Employee Database</th>
</tr>
` ``
```

****Detailed Explanation:****

- ``<tr>``: Table Row - a row in the table
- ``<th>``: Table Header - header cell (bold and centered text)
- ``colspan="9"``: Cell spans across 9 columns horizontally

****Visual Representation:****

` ``


Employee Database	(spans 9 columns)
-------------------	-------------------

Second Row - Column Headers

html

```
<tr>
  <td></td>
  <td>name</td>
  <td colspan="3">employee ID</td>
  <td colspan="2">phone</td>
  <td>email</td>
  <td>department</td>
</tr>
` ``
```

****Detailed Explanation:****

- Empty cell ``<td></td>`` at the beginning
- `employee ID` spans 3 columns
- `phone` spans 2 columns
- Total: 1 + 1 + 3 + 2 + 1 + 1 = ****9 columns**** 

****Visual:****
...

	name	employee ID	phone	email	department
--	------	-------------	-------	-------	------------

Data Rows (5 rows)

html

```
<tr>
  <td rowspan="5">name</td>
  <td>Fatima Ali</td>
  <td colspan="2">E001</td>
  <td colspan="2">01012763893</td>
  <td rowspan="5">email</td>
  <td>sara@gmail.com</td>
  <td>Hr</td>
</tr>
...
```

****Explaining `rowspan="5"`:**

- Cell spans **vertically** across 5 rows
- The words "name" and "email" appear only once for all 5 employees

****Visual:****
...

name	Fatima Ali	E001	01012763893	email	sara@gmail..	Hr
	Fatima Ali	E001	01012763893		sara@gmail..	Hr
	Fatima Ali	E001	01012763893		sara@gmail..	Hr
	Fatima Ali	E001	01012763893		sara@gmail..	Hr
	Fatima Ali	E001	01012763893		sara@gmail..	Hr

Empty Row + Total

html

```
<tr>
  <td colspan="9"></td>
</tr>
<tr>
  <td colspan="2">total employees</td>
  <td colspan="7" style="text-align: right">5</td>
</tr>
```

Explanation:

- Empty row to separate data from total
- `text-align: right` : Aligns text to the right
- Number "5" spans across 7 columns

3 JavaScript - Detailed Explanation

Variables - Variables

javascript

```
var x = 9
var y = "Abdullah"
var flag = true
var number = 9.8
```

Data Types:

Type	Example	typeof
Number	9	"number"
String	"sara"	"string"
Boolean	true	"boolean"
Undefined	undefined	"undefined"

Reference: [W3Schools - JS Variables](https://www.w3schools.com/js/variables.asp)

+ Arithmetic Operations

String Concatenation

javascript

```
console.log("ahmed" + 20) // "ahmed20"
```

- When adding string + number, the number converts to string

Type Coercion (Automatic Conversion)

javascript

```
console.log(20 + 30 + "10") // "5010"
```

Step-by-step Explanation:

1. `20 + 30 = 50` (number)
2. `50 + "10" = "5010"` (string)

Different Scenarios:

javascript

```
console.log("10" + 20 + 30) // "102030" ✗  
console.log(20 + 30 + "10") // "5010" ✓  
console.log("10" - 5) // 5 (minus converts to number)  
console.log("sara" - 5) // NaN (Not a Number)
```

Reference: [W3Schools - JS Type Conversion](https://www.w3schools.com/js/js_type_conversion.asp)

Boolean and Number Conversion

javascript

```
console.log(true == 1) // true  
console.log(false == 0) // true
```

```
console.log(12 + true)    // 13 (true = 1)
console.log(12 + false)   // 12 (false = 0)
```

Conversion Table:

Value	When Converted to Boolean	When Converted to Number
0	false	0
1	true	1
" "	false	0
"0"	true	0
null	false	0
undefined	false	NaN
NaN	false	NaN

Comparison Operators

== vs ===

javascript

```
// == Loose Equality (compares value only)
console.log(8 == "8")    // true
console.log(1 == true)   // true

// === Strict Equality (compares value and type)
console.log(8 === "8")   // false
console.log(1 === true)  // false
```

Advanced Examples:

javascript

```
console.log(null == undefined) // true (special case)
console.log(null === undefined) // false (different types)
console.log([] == [])          // false (different objects)
console.log(NaN === NaN)       // false (NaN ≠ anything, even itself!)
```

Reference: [W3Schools - JS Comparisons](https://www.w3schools.com/js/js_comparisons.asp)

Type Conversion Functions

javascript

```
Number(null)      // 0
Number(undefined) // NaN
Number(true)       // 1
Number("123")      // 123
Number("sara")     // NaN

String(123)        // "123"
String(true)       // "true"

Boolean(0)         // false
Boolean("")        // false
Boolean(89)        // true
Boolean("0")       // true
```


Special Cases

javascript

```
// null in operations
console.log(null + null)      // 0
console.log(null + 0)         // 0
console.log(20 + null)        // 20

// undefined in operations
console.log(undefined + undefined) // NaN
console.log(undefined + 5)         // NaN


// NaN in operations
console.log("sara" - 40)         // NaN
console.log("50" - 40)           // 10 (minus converts)
console.log(1 - NaN)             // NaN
console.log(40 - true)           // 39

// Check for NaN
console.log(Number.isNaN("sara" - 7)) // true 
console.log(Number.isNaN(123))       // false
```

Control Flow

If-Else Statement

javascript

```
var time = 12
if(time < 9) {
    console.log("Good Morning")
}
else if(time < 14) {
    console.log("Good Day")    //  Will print this
}
else {
    console.log("Good Evening")
}
```

Reference: [W3Schools - JS If Else](https://www.w3schools.com/js/js_if_else.asp)

Ternary Operator

javascript

```
var color = "red"
color == "red" ? console.log("red") : console.log("another color")
...

**Syntax:**
...

condition ? expressionIfTrue : expressionIfFalse
```

Examples:

javascript

```
var age = 20
var status = age >= 18 ? "adult" : "minor"    // "adult"

var score = 85
var grade = score >= 90 ? "A" : score >= 80 ? "B" : "C"    // "B"
```

Switch Statement

javascript

```
var day = 3
switch(day) {
  case 1:
    console.log("saturday")
    break;
  case 2:
    console.log("sunday")
    break;
  case 3:
    console.log("monday") // ✅ Will print this and stop
  case 4:
    console.log("tuesday") // ⚠️ Without break, will also print this!
    break;
  default:
    console.log("invalid day")
    break;
}
```

⚠️ Important Note:

- Without `break` in case 3, execution continues to case 4 (Fall-through)

Reference: [W3Schools - JS Switch](https://www.w3schools.com/js/js_switch.asp)

Loops

For Loop

javascript

```
for(var i = 0; i <= 3; i++) {
  console.log(i) // 0, 1, 2, 3
}
```

Different Forms:

javascript

```
// 1. Complete form
for(var i = 0; i <= 3; i++) {
    console.log(i)
}

// 2. Initialize i outside loop
var i = 0
for( ; i <= 3; ) {
    console.log(i)
    i++
}

// 3. Infinite Loop
for( ; ; ) {
    console.log("infinite loop")
    break; // Must stop it!
}
```

Reference: [W3Schools - JS For Loop](https://www.w3schools.com/js/js_for_loop.asp)

Continue & Break

javascript

```
// Continue: skip current iteration
for(var i = 0; i <= 5; i++) {
    if(i == 3) continue; // Will skip 3
    console.log(i)       // 0, 1, 2, 4, 5
}

// Break: stop loop completely
for(var i = 0; i <= 5; i++) {
    if(i == 3) break;    // Will stop at 3
    console.log(i)       // 0, 1, 2
}
```

User Interaction

Prompt - Input Data

javascript

```
var name = prompt("Enter Your Name");  
// Shows a dialog box for user input
```

Scenarios:

- User types "Ahmed" → name = "Ahmed"
- User clicks Cancel → name = null
- User clicks OK without typing → name = ""

Convert to Number:

javascript

```
var input = prompt("Enter a number")  
var number = Number(input)  
console.log(number + 10)
```

Reference: [W3Schools - JS Popup Boxes](https://www.w3schools.com/js/js_popup.asp)

Confirm - Confirmation Message

javascript

```
var x = confirm("Are you sure?")  
console.log(x)
```

Results:

- User clicks OK → x = true
 - User clicks Cancel → x = false
-



Summary of Possible Scenarios

Scenario 1: Opening the Page

1. HTML loads
2. Table displays with 5 employees

3. `script.js` loads (if exists)

Scenario 2: User Interaction

javascript

```
var name = prompt("Enter Your Name")
if(name) {
    alert("Welcome " + name)
} else {
    alert("No name entered")
}
```

Scenario 3: Data Validation

javascript

```
var age = prompt("Enter your age")
var ageNum = Number(age)

if(Number.isNaN(ageNum)) {
    alert("Please enter a valid number")
} else if(ageNum < 18) {
    alert("You are a minor")
} else {
    alert("You are an adult")
}
```

BY. Abdullah Ali