

VenQore

V1 Testing & Launch Checklist

Everything you need to test before a single real customer signs up.

Prepared April 2026 · Test locally first, then staging, then production

12 Test Sections	A → L covering every part of the system
Roles Covered	Owner, Admin, Manager, Cashier, Accountant, Purchasing Officer, Viewer
Data Isolation	Every test verifies Store A cannot see Store B
Final Sign-off	A sign-off checklist at the end before going live

How to Use This Document

■■ **Rule 1:** Test in this exact order: Local machine → Staging server → Production. Never skip local.

✓ **Rule 2:** A section is only done when every single checkbox in it is ticked. Not 'mostly done'. All of them.

■■ **Rule 3:** If something fails: fix it, then re-run the entire section from the top. Not just the failed item.

■ **Rule 4:** The data isolation tests (Section D) must pass before you go live. This is the most important section.

Testing Order Explained

Environment	What it is and when to use it
Local Machine	Your laptop/PC running VenQore with XAMPP or Laravel Herd. Free to break. Reset the database in seconds. Do ALL testing here first.
Staging Server	A cheap temporary server (even a \$6/month droplet) that mirrors production. Test the deployment process itself here.
Production (Hostinger)	Your real server. Only deploy here after local AND staging pass completely. Real users, real data, no mistakes.

What This Checklist Specifically Tests For Data Safety

The single biggest risk in a multi-tenant system is data leaking between stores. A customer at Store A should never see anything from Store B. This checklist tests this in 4 different ways:

- Database isolation — running commands to verify zero rows have NULL tenant_id
- Browser isolation — logging in as Store B user and confirming Store A data is invisible
- API isolation — directly calling a Store A URL while authenticated as Store B user
- Multi-tab isolation — two tabs open on two different stores simultaneously

A Before You Test Anything — Environment Check

Run every command below in your terminal before touching anything else. If any of these fail, fix them first. Everything else depends on this.

Run These Commands in Your Terminal

Check zero pending migrations

```
php artisan migrate:status | grep -c "Pending" # Must return: 0
```

Check all role types exist in database

```
php artisan tinker --execute="echo DB::select(\"SHOW COLUMNS FROM tenant_users LIKE 'role'\")[0]->Type;"
```

Check Horizon queue is running

```
php artisan horizon:status # Must say: Horizon is running
```

Test email sending works

```
php artisan tinker --execute="Mail::raw('test', fn(\$m) => \$m->to('your@email.com')->subject('test'));" # Check inbox – must arrive within 60 seconds
```

Test file storage (R2 or local) works

```
php artisan tinker --execute="Storage::disk('r2')->put('_test/ping.txt', 'ok'); echo Storage::disk('r2')->get('_test/ping.txt');" # Must print: ok
```

Check APP_DEBUG is off

```
grep APP_DEBUG .env # Must show: APP_DEBUG=false
```

Environment Checklist

- Zero pending migrations
- tenant_users.role column has all role types defined
- users.platform_role column exists
- store_activity_log table exists
- staff_invitations table exists
- Horizon is running (for background jobs)
- Test email arrived in inbox (not spam folder)
- File storage read/write/delete working
- APP_DEBUG=false confirmed in .env
- No hardcoded 'Rs.' currency symbols left in frontend code

B Creating a New Store — The Full Sign-Up Flow

This tests the complete journey from a stranger visiting your website to them being inside their own working store. Do this with a fresh email address you have never used before.

Step 1 — Register a New Account

- Go to venqore.com/register — form displays correctly
- Try submitting without ticking Terms of Service — must be blocked
- Try submitting with a password like '123' — must be blocked (too weak)
- Try submitting with an email already in the system — must show error
- Submit with valid details — account created successfully
- Redirected to the 'create or join a store' page (NOT the dashboard)
- Check the database: user was created with `platform_role = 'none'`
- Check the database: a trial `StoreLicense` was automatically created for this user

Step 2 — Create the First Store

- Click 'Create my first store' — form appears
- Try submitting with no store name — blocked
- Submit valid store name
- Tenant (store) record created in database with `status = 'trial'`
- `trial_ends_at` is set to 14 days from now
- You are set as the Owner in `tenant_users` with `role = 'owner'`
- `StoreLicense` updated: `status = 'consumed'`, `tenant_id` is filled in
- Chart of accounts seeded for the new store (check `accounts` table)
- Redirected to the Setup Wizard — NOT the dashboard yet

Step 3 — Complete the Setup Wizard

- Wizard shows business profile page: name, currency, timezone
- Select Pakistani Rupee — currency symbol changes to Rs. everywhere after
- Wizard shows industry selection page with all groups visible
- Select Fashion/Apparel — `feature_variants` flag turns ON in the database
- Select Electronics — `feature_serials` flag turns ON in the database
- Select Pharmacy — `feature_batches` flag turns ON in the database
- Industry-specific categories appear after selection (check `categories` table)
- Complete wizard — `setup_completed = true` in the `tenants` table
- Redirected to the dashboard
- Dashboard shows the correct store name and currency symbol
- Dashboard shows Rs. 0 / empty data (not another store's data)

- Log out and log in again — wizard does NOT appear a second time

Step 4 — Store Slug Safety

- Create a store named 'Admin' — the slug must NOT be 'admin' (gets a suffix like 'admin-3f9')
- Create a store named 'API' — slug must not be 'api'
- Create two stores with identical names — they get different slugs
- Store slug contains only lowercase letters, numbers, and hyphens

C Role Isolation — Does Each User See Only What They Should?

For each role below: create a fresh user, invite them to the test store with that role, log in AS that user, and verify the access. Do not skip any role.

Setup Before Role Testing

Create a test store called 'VQ Test Store' with this data pre-loaded:

- 5 products with prices and stock quantities
- 3 customers
- 2 completed sales
- 1 purchase order
- 1 manual journal entry

Owner Role

- Can open: Dashboard, POS, Sales, Purchases, Inventory, Finance, Reports, Staff, Settings, Billing
- Billing page shows subscription status and payment portal link
- Can invite staff — all V1 roles visible in the dropdown
- Can change a staff member's role
- Can remove a staff member from the store
- CANNOT see any /hq/* pages — trying to go there returns a 403 error

Admin Role

- Can open: Dashboard, POS, Sales, Purchases, Inventory, Finance, Reports, Staff, Settings
- CANNOT open the Billing page — gets a 'not allowed' error
- CANNOT delete the store
- CANNOT transfer ownership
- Can invite staff but CANNOT set the role to 'Owner'
- CANNOT change the actual Owner's role

Manager Role

- Can open: Dashboard, POS, Sales, Purchases, Inventory, All 38 Reports
- CANNOT open: Staff management, Billing, Settings
- Can create and edit products
- Can do a stock adjustment — creates a log entry with a reason
- Can open and close POS sessions

Cashier Role — Most Restricted

The Cashier is the most security-sensitive role. Test every restriction carefully.

- Dashboard shows: My Session stats, Open POS button, My Attendance only
- Dashboard does NOT show: Revenue totals, staff counts, financial numbers
- CANNOT open /sales page — gets blocked
- CANNOT open /inventory page — gets blocked
- CANNOT open /reports page — gets blocked
- CANNOT open /finance page — gets blocked
- CANNOT open /staff page — gets blocked
- CANNOT open /settings page — gets blocked
- CANNOT open /billing page — gets blocked
- Directly typing the URL /app/store/sales/create — blocked with error
- POS works: can search products, add to cart, complete a sale
- After sale: receipt is viewable
- After sale: stock quantity decreased in the database
- After sale: journal entry created in the database
- CANNOT sell more units than are in stock — blocked with error

Accountant Role

- Can open: Dashboard (finance view), Finance section, All 38 Reports
- CANNOT open POS
- CANNOT open Staff management
- Can create a journal entry (balanced debits and credits)
- Unbalanced journal entry (debits don't equal credits) is blocked
- Can reconcile a bank transaction
- CANNOT create a sale directly
- CANNOT change product prices

Purchasing Officer Role

- Can open: Dashboard (procurement), Purchases, Supplier management, Inventory (view only)
- CANNOT open Sales list or Customer list
- CANNOT open Finance/Accounting
- Can create a purchase order
- Can receive stock against a purchase order — stock increases correctly
- Stock receipt creates a movement record in the database

Viewer / Auditor Role

- Can open: Reports only (all 38 — read-only)

- CANNOT open POS, Sales, Inventory, Finance, Staff, Settings, Billing
- Directly typing any 'create' URL — blocked with error
- Reports load and show data (read access works)
- There are NO create, edit, or delete buttons anywhere visible

D DATA ISOLATION — The Most Critical Tests

■ **CRITICAL** If even one of these tests fails, you must NOT go live. A failure here means one customer's private business data is visible to another customer. This is a catastrophic breach of trust.

Setup for Isolation Testing

Create two completely separate stores:

- Store A: 'Ali Shoes' — add 3 products: 'Red Shoe', 'Blue Shoe', 'Sandal'
- Store A: add 1 customer named 'Ali Customer', make 1 sale for Rs. 5,000
- Store B: 'Zain Electronics' — add 3 products: 'TV', 'Phone', 'Laptop'
- Store B: add 1 customer named 'Zain Customer', make 1 sale for Rs. 15,000

Test 1 — Browser Isolation

Log in as a Store B user. Look everywhere.

- Products list shows: TV, Phone, Laptop — NOT Red Shoe, Blue Shoe, Sandal
- Customers list shows: Zain Customer — NOT Ali Customer
- Sales list shows: Rs. 15,000 sale — NOT the Rs. 5,000 sale
- Dashboard revenue shows Rs. 15,000 — NOT Rs. 20,000 (combined)
- All 38 reports show only Store B data — not combined totals
- Log back in as Store A — Store A's data is still intact (Store B didn't corrupt it)

Test 2 — Direct URL Attack Simulation

While logged in as a Store B user, try to access Store A's data directly by typing Store A's URL in the browser bar:

- Type Store A's URL /app/ali-shoes/dashboard — should get 403 error or redirect
- Type Store A's URL /app/ali-shoes/inventory — blocked
- Find a product UUID from Store A's database, request it via Store B's session — returns 404
- Find a sale UUID from Store A's database, request it via Store B's session — returns 404

Test 3 — Database Verification

Run this command and verify the output:

```
php artisan tinker --execute=" \$tables =
['products','sales','parties','accounts','journal_entries']; foreach(\$tables as \$t) { \$count
= DB::table(\$t)->whereNull('tenant_id')->count(); echo \$t . ' : ' . (\$count === 0 ? 'CLEAN' :
'FAIL - ' . \$count . ' rows') . PHP_EOL; }"
```

- products: shows CLEAN (zero rows without a store ID)
- sales: shows CLEAN
- parties (customers/suppliers): shows CLEAN

- accounts: shows CLEAN
- journal_entries: shows CLEAN

Test 4 — Multi-Tab Safety (Two Stores Open Simultaneously)

This tests that opening two stores in two browser tabs does not mix data.

- Open Tab 1: go to Ali Shoes POS (/app/ali-shoes/pos)
- Open Tab 2: go to Zain Electronics inventory (/app/zain-electronics/inventory)
- In Tab 1: complete a sale for Rs. 1,000
- In Tab 2: add a new product 'Smart Watch'
- Verify: the Rs. 1,000 sale is recorded in Ali Shoes (not Zain Electronics)
- Verify: Smart Watch appears in Zain Electronics (not Ali Shoes)
- Neither tab affected the other store — tabs are fully independent

E Staff Invite System

Inviting Staff by Email

- Owner opens Staff management page, clicks 'Invite Staff'
- Invite form shows: email field, role dropdown (V1 roles only, no Owner option)
- Submit with invalid email — blocked with error
- Submit with email of someone already in this store — shows 'already a member' error
- Submit valid invite — invitation record created in staff_invitations table
- Invite email arrives in the invitee's inbox within 60 seconds
- Invite email shows correct store name, correct role, and a secure link

Accepting an Invite

- Invitee clicks the link while NOT logged in — redirected to login with invite preserved
- After logging in — invite accepted, access to the store granted
- Invitee clicks link while logged in as WRONG email — blocked with clear error
- Invitee clicks link while logged in as CORRECT email — accepted immediately
- After acceptance: redirected to the store dashboard with a welcome message
- After acceptance: clicking the same link again shows 404 (token is gone, single-use)
- After acceptance: store appears in the invitee's store switcher if they have 2+ stores

Expired Invites and Security

- Invite older than 7 days: clicking the link shows 'invitation has expired'
- Owner can resend an expired invite — new token created, old one invalidated
- Join code (VQ-XXXX format) visible in store settings
- Entering wrong join code: shows 'invalid code' error
- Person already in the store enters their own store's join code: shows 'already a member'
- Owner regenerates join code — old code immediately stops working

F Core ERP Functions — Does the Business Logic Work?

F1 — Complete a Sale End-to-End

Setup before this test: Product 'Test Shoes', price Rs. 5,000, cost Rs. 3,000, stock 10. Customer 'Ahmed Ali'.

- Open POS, search 'Test Shoes' — appears in results within 1 second
- Add 2 units to cart — cart shows $2 \times \text{Rs. 5,000} = \text{Rs. 10,000}$
- Apply 10% discount — cart updates to Rs. 9,000
- Select customer 'Ahmed Ali'
- Select payment method: Cash, enter Rs. 10,000 received
- Change shown: Rs. 1,000
- Complete the sale — receipt appears

After Sale — Verify in Database:

- Sale record: correct tenant_id, correct total Rs. 9,000, correct discount Rs. 1,000
- Sale items: 2 items, correct product_id, correct price
- Stock: 'Test Shoes' now shows 8 in stock (was 10, sold 2)
- Stock movement record created: type = 'sale', quantity = -2
- Journal entry DEBIT: Cash Rs. 9,000 | CREDIT: Sales Revenue Rs. 9,000
- Journal entry DEBIT: Cost of Goods Sold Rs. 6,000 | CREDIT: Inventory Rs. 6,000
- Total debits equal total credits (the entry is balanced)
- Sale visible in today's Sales report
- Sale visible in P&L; report for current period

Edge Cases:

- Attempt to sell 11 units when stock is 10 — blocked with 'out of stock' error
- Attempt to sell 0 quantity — blocked
- Attempt to complete sale with empty cart — blocked

F2 — Purchase Order Flow

- Create supplier 'Ali Traders' with contact details
- Create purchase order: 5 units of 'Test Shoes' at Rs. 3,000 each
- PO status shows: Ordered
- Receive 3 units — stock increases by 3, PO status: Partially Received
- Journal entry created: Debit Inventory, Credit Accounts Payable
- Receive remaining 2 units — PO status: Fully Received
- Post payment to supplier — Accounts Payable decreases, Cash decreases
- Supplier balance updated correctly

F3 — Inventory Management

- Create product with all fields: name, SKU, barcode, price, cost, category, image
- Product image uploads and displays correctly
- Creating a duplicate SKU is blocked with an error
- Barcode search in POS finds the product instantly
- Delete product with NO sales history — succeeds
- Delete product WITH sales history — blocked with clear error
- Stock adjustment (manual increase) — reason is logged
- Stock adjustment (manual decrease) — reason is logged
- Create a category, then try to delete it WITH products — blocked
- Create a category with no products, then delete — succeeds

F4 — Reports

- All 38 reports open without a 500 server error
- P&L; report shows figures matching the test sales and purchases you created
- Balance Sheet: Assets column total equals Liabilities + Equity column total
- Trial Balance: total debits column equals total credits column
- Changing the date range filter changes the data shown
- Export to PDF: job runs in background, PDF is downloadable
- Export to Excel: job runs in background, Excel file is downloadable

G HQ Admin Panel — Your Command Center

The HQ panel at /hq/ is only for you (God Admin). Every other user must be completely blocked from it.

Access Control

- Log in as a regular store Owner, type /hq/ in the browser — must get a 403 error
- The 403 must NOT be a redirect to login — redirecting reveals the route exists
- Log in as God Admin — /hq/dashboard loads correctly
- HQ dashboard shows: total store count, MRR, trial count, active count

Store Management from HQ

- Can see all stores in /hq/stores with name, plan, status
- Suspend a store from HQ — store Owner gets an error when trying to log in
- The suspended store's cashiers also cannot log in
- Re-activate the store from HQ — store Owner can log in again
- Extend a trial from HQ — trial_ends_at updates in the database

Impersonation — Viewing a Store as the Owner

Impersonation lets you see what a store owner sees to help with support. It must be 100% read-only. No accidents. No corrupted data.

- Click 'Impersonate' on a store — you enter that store's view
- A red WARNING BANNER appears at the top of every page: 'You are viewing as [Store]. All write actions are blocked.'
- The banner cannot be dismissed or hidden
- While impersonating: try to create a product — must be blocked with 403
- While impersonating: try to edit a sale — must be blocked with 403
- While impersonating: browsing (GET requests) works — you can see their data
- End impersonation — banner disappears, you are back to your God Admin view
- After impersonation: check platform_activity_log — a record shows who impersonated, which store, when

H Payments, Subscriptions and AppSumo

H1 — Trial Expiry

Run this command to manually expire a trial for testing:

```
php artisan tinker --execute=" Tenant::withoutGlobalScopes() ->where('slug', 'your-test-store')
->update(['trial_ends_at' => now()->subMinute()]);"
```

- After running command: store Owner trying to log in sees 'Trial Expired' page
- Trial expired page shows an upgrade/payment link — not a blank 500 error
- Expired store data is preserved in the database (not deleted)
- Pay via Lemon Squeezy test card: 4242 4242 4242 4242 — webhook fires, access restored
- After payment: store Owner can log in immediately without doing anything extra

H2 — Lemon Squeezy Webhook Events

Event	Expected Result
subscription_created	New tenant created + welcome email sent + owner can log in
subscription_updated	Plan change updates tenant.plan immediately
subscription_cancelled	tenant.status → 'cancelled' (not suspended yet — access until end of period)
subscription_expired	tenant.status → 'suspended' — owner sees payment required page
subscription_payment_failed	Payment failure email sent to store owner
Invalid signature	Returns 401 — webhook is NOT processed

- Each event type above produces the correct result (test one by one)
- Webhook processing is asynchronous — fires a background job, does not block
- Same webhook sent twice: second one is ignored (idempotent — no duplicate stores)

H3 — AppSumo Code Redemption and Stacking

- Go to /redeem, enter a valid AppSumo code — code redeemed, Starter license created
- Try to redeem the same code again — blocked with 'already redeemed' error
- Redeem a second code — license upgrades to Growth plan automatically
- If store already exists when 2nd code redeemed — store.plan updates to Growth immediately
- Redeem a third code — upgrades to Business plan
- Try to redeem a 4th code — blocked with 'maximum 3 codes per account'
- Create a store with an LTD license — trial_ends_at is NULL (no expiry)
- LTD store status is 'active' not 'trial'

I Security Tests

Authentication Boundaries

- Unauthenticated user accessing /app/any-store/dashboard is redirected to login
- Store A user trying to access Store B's URL gets a 403 error
- Store user trying to access /hq/ gets a 403 error (not a redirect)
- Login brute force: 10+ wrong attempts from same IP triggers a block (429 error)
- Password reset token: using the same reset link twice fails (single-use)
- Password reset token: link expires after 60 minutes
- CSRF protection: submitting a form without the CSRF token returns 419 error

Plan Limit Enforcement at API Level

Limits must be enforced even if someone bypasses the UI and sends a direct API request. Test this by making the API call directly, not through the browser buttons.

- Starter store with 1,000 products: direct API call to create product 1,001 returns 403
- Starter store: direct API call to create 2nd warehouse returns 403
- Starter store: direct API call to invite 4th staff returns 403
- Cashier role: direct API call to POST /sales/create returns 403
- Viewer role: direct API call to any create endpoint returns 403
- The 403 response body includes an upgrade link (not just a generic error)

J Performance — Is It Fast Enough?

Run These Commands to Measure Speed

POS page load (must be under 1 second)

```
curl -w "Time: %{time_total}s\n" -o /dev/null -s \ https://venqore.com/app/your-store/pos
```

POS product search with 1,000 products (must be under 300ms)

```
time curl -s "https://venqore.com/app/your-store/pos/products?q=shoe" > /dev/null
```

Dashboard load (must be under 2 seconds)

```
time curl -s https://venqore.com/app/your-store/dashboard > /dev/null
```

- POS page loads in under 1 second — the page does NOT include the full product list
- POS product search returns results in under 300ms even with 1,000+ products
- Dashboard loads in under 2 seconds with real data
- All 38 reports load without a 500 server error (they can be slow, but must not crash)
- Horizon dashboard shows zero failed jobs after all tests completed
- Application error log shows no ERROR or CRITICAL entries after testing

K Clean Up Before Real Users Arrive

Run these cleanup steps after all tests pass. You do not want test data mixed in with real customer data when you go live.

Delete All Test Stores and Data

```
php artisan tinker --execute=" \$testSlugs = ['vq-test-store', 'ali-shoes', 'zain-electronics'];
foreach(\$testSlugs as \$slug) { \$t = Tenant::withoutGlobalScopes()->where('slug',
\$slug)->first(); if(\$t) { foreach(['products', 'sales', 'sale_items', 'parties', 'accounts',
'journal_entries', 'categories', 'warehouses', 'tenant_users'] as \$table) {
DB::table(\$table)->where('tenant_id', \$t->id)->delete(); } \$t->forceDelete(); echo 'Deleted:
' . \$slug . PHP_EOL; } }"
```

- All test store slugs deleted from database
- No test email addresses (test@, temp@) in the users table
- Queue cleared of test jobs: php artisan queue:clear --queue=default
- Failed jobs cleared: php artisan queue:flush
- Demo store reset to clean state: php artisan demo:reset
- Application logs cleared of test noise
- AppSumo test codes invalidated

L Document Known Gaps Before Going Live

There will always be things that are not perfect in V1. That is okay. The important thing is to know what they are and have decided they are acceptable for now. Write the answer to each question below.

1. Is the `store_activity_log` actually being written on every action? Test: create a product, check the `store_activity_log` table.

2. What happens if a Lemon Squeezy webhook fails to deliver? Is there a way to manually trigger it again?

3. Is there a database backup running automatically? When was the last backup tested by restoring it?

4. Is there a health check endpoint (`/health`) being monitored by UptimeRobot or similar?

5. Is there an error alert (Slack or email) set up for production 500 errors?

6. Has the ownership transfer flow been tested end-to-end?

✓ Final Sign-Off Checklist

Section A — Environment Check	ALL PASSED	_____
Section B — Store Creation	ALL PASSED	_____
Section C — Role Isolation	ALL PASSED	_____
Section D — Data Isolation	ALL PASSED	_____
Section E — Staff Invites	ALL PASSED	_____
Section F — Core ERP Functions	ALL PASSED	_____
Section G — HQ Admin Panel	ALL PASSED	_____
Section H — Payments & AppSumo	ALL PASSED	_____
Section I — Security Tests	ALL PASSED	_____
Section J — Performance	ALL PASSED	_____
Section K — Cleanup	ALL PASSED	_____
Section L — Known Gaps Documented	DOCUMENTED	_____

Known Issues Accepted for V1 Launch:

1. _____
2. _____
3. _____

System ready for real paying customers:

YES ☐ NO ☐

Tested on local machine:

YES ☐ NO ☐

Tested on staging server:

YES ☐ NO ☐

Date:

Signed off by:
