

Computer network

Binary exponential Backoff Algorithm

- * What do you mean by frame at LLC
(slide - 2) $\rightarrow$ ~~flag~~ part.
- * Draw byte stuffing and byte unstuffing technique in character oriented protocol
(slide 9 $\rightarrow$ just diagram)
- * Show the idea of bit stuffing and ~~bit~~ unstuffing under flag bits with bit stuffing. (slide - 12)
- * Compare the best and worst case of above technique (slide - 13)
- * Compare ~~the~~ error ^{connection} through retransmission and autonomous error connection.
(slide - 15)

* Example - 1 (slide - 22, 23)

How to avoid single bit error,
2 bit error, odd numbers of bit error
burst error. (slide - 29, 32) - (31 on)

* What will happen if $E(x) = G(x)$
(slide - 33)

* Give operating principles of
sliding window protocol. (slide - 45)

* Draw few steps of sliding window
protocol for the case of variable
window size. (slide - 50, 51, 52)

* Compare pure and slotted
ALOHA (slide - 63 to (page 65))

* Show that, maximum efficiency of
pure ALOHA is 0.184 max
and that of slotted ALOHA is
0.3684 (slide - 68, 69, 70, 71)

* Example - 1 (slide - 72)

* Compare adjustive service, gated service and limited service of token read protocol (slide - 77) no math, no figure

(
77 - a
78 - b
79 - c
) → No math, no figure,
just description

* why wireless LAN use carrier avoidance use CSMA/CA instead of CD (slide - 88)

[Tutorial only today's
List of question
date - 9]



Companz

utilization of transmission line

^ (~~slide~~) for smaller and larger frame

under stop and wait flow control

(slide - 42)