

Experiment No: 09

Write a simple PHP program on Introspection and Serialization.

Resources required:

Hardware	Software
Computer System	Any database tools such as XAMPP

Practical Significance:

Introspection

- Introspection in PHP offers the useful ability to examine an object's characteristics, such as its name, parent class (if any) properties, classes, interfaces and methods.
- PHP offers a large number functions that you can use to accomplish the task.
- In-built functions in PHP Introspection :

Function	Description
class_exists()	Checks whether a class has been defined.
get_class()	Returns the class name of an object.
get_parent_class()	Returns the class name of an object's parent class.
is_subclass_of()	Checks whether an object has a given parent class.
get_declared_classes()	Returns a list of all declared classes.
get_class_methods()	Returns the names of the class' methods.
get_class_vars()	Returns the default properties of a class.
interface_exists()	Checks whether the interface is defined.
method_exists()	Checks whether an object defines a method.

Program Code:

```
<?php
class Derived
{
    public function details()
    {
        echo "I am a Derived(super) class for the Child(sub) class. <BR>";
    }
}
class sub extends Derived
```

```
{
    public function details()
    {
        echo "I'm " .get_class($this) , " class.<BR>";
        echo "I'm " .get_parent_class($this) , "'s child.<BR>";
    }
}
//details of parent class
if (class_exists("Derived"))
{
    $der = new Derived();
    echo "The class name is: " .get_class($der) . "<BR>";
    $der->details();
}
//details of child class
if (class_exists("sub"))
{
    $s = new sub();
    $s->details();

    if (is_subclass_of($s, "Derived"))
    {
        echo "Yes, " .get_class($s) . " is a subclass of Derived.<BR>";
    }
    else
    {
        echo "No, " .get_class($s) . " is not a subclass of Derived.<BR>";
    }
}
}
```

Output :

The class name is: Derived
I am a Derived (super) class for the Child(sub) class.
I'm sub class.
I'm Derived's child.
Yes, sub is a subclass of Derived.

Serialization

- Serialization is a technique used by programmers to preserve their working data in a format that can later be restored to its previous form.

- Serializing an object means converting it to a byte stream representation that can be stored in a file. Serialization in PHP is mostly automatic, it requires little extra work from you, beyond calling the `serialize()` and `unserialize()` functions.

Serialize() :

- The `serialize()` converts a storable representation of a value.
- The `serialize()` function accepts a single parameter which is the data we want to serialize and returns a serialized string.
- A serialize data means a sequence of bits so that it can be stored in a file, a memory buffer or transmitted across a network connection link. It is useful for storing or passing PHP values around without losing their type and structure.

Syntax :

```
serialize(value1);
```

unserialize() : `unserialize()` can use string to recreate the original variable values i.e. converts actual data from serialized data.

Syntax :

```
unserialize(string1);
```

Program Code:

```
<?php
$s_data= serialize(array('Welcome', 'to', 'PHP'));
print_r($s_data . "<br>");
$us_data=unserialize($s_data);
print_r($us_data);
?>
```

Output :

```
a:3:{i:0;s:7:"Welcome";i:1;s:2:"to";i:2;s:3:"PHP";}
Array ( [0] => Welcome [1] => to [2] => PHP )
```

Practical related questions:

1. State the use of `unserialize()`.
`unserialize()` is converts serialized data to normal form
2. List the Magic Methods with PHP Object Serialization.
`serialize()` and `unserialize()`

Exercise:

1. Declare a class as "Test" with three user defined functions. List name of the class and functions declared in the class "Test".

```
<!-- print class name and its methods -->

<?php

class test {
    public function test1() {
        return "Test 1";
    }
}
```

```
}
public function test2() {
    return "Test 2";
}
public function test3() {
    return "Test 3";
}
}

$t = new test();
echo get_class($t);
echo "<br />";
print_r(get_class_methods($t));

?>

<!-- output -->
<!-- test
Array ( [0] => test1 [1] => test2 [2] => test3 ) -->
```

2. Declare an interface “MyInterface”. Write a script for whether interface exists or not.

```
<!-- Interface Exists -->

<?php

interface testI {
    public function test1();
    public function test2();
}

if(interface_exists('testI')) {
    echo "Interface testI exists";
} else {
    echo "Interface testI does not exists";
}

?>

<!-- Output -->
<!-- Interface testI exists -->
```

3. Write a script to based on unserialize().

```
<!-- Serialize and Unserialize -->

<?php

$s_data= serialize(array('I', 'am', 'Jayesh'));

print_r($s_data . "<br>");

$us_data=unserialize($s_data);

print_r($us_data);

?>

<!-- Output -->
<!-- a:3:{i:0;s:1:"I";i:1;s:2:"am";i:2;s:6:"Jayesh";}
Array ( [0] => I [1] => am [2] => Jayesh ) -->
```