

Module 5

DDL

Data Definition Language – create, remove, modify database structures (such as tables, indexes, views)

- Create
- Alter
- Drop

DML

Data Manipulation Language – create, remove and modify data values (the values stores in tables, indexes and views)

- Insert
- Update
- Delete
- Truncate

1- The Create Statement:

Used to create a new table or view

- Defines the table NAME and its COULMNS
- Defines the DATATYPE, LENGTH for each column
- Defines the CONSTRAINTS for each column.

Usually, we Drop a table if it exist (before creating)

DROP Statement

DROP TABLE IF EXISTS <table-name>

CREATE STATEMENT SYNTAX:

CREATE TABLE <table-name>

```
(  
    Column, Datatype (n) --n is the length of the field  
    Column, Datatype (n) NOT NULL,  
    Column, Datatype (n) NOT NULL Default 0,  
    Column, Datatype (n) CONSTRAINT <constraint name> TYPE,  
)
```

Example

CREATE TABLE Shippers

```
(  
    ShipperID          int          NOT NULL,  
    CompanyName        char(40)     NOT NULL,  
    PhoneNo            varchar(20)  NOT NULL  
)
```

2- SQL Constraints:

Constraints are the rules that are applied to rows and columns that allows the database software to maintain the data integrity within the database.

The database software will not allow the condition of the constraint to be violated.

Constraints can exist at the Table level/ or the Column level.

Table Level constraints (Primary Key, Foreign Key).

Column Level constraints (Not Null, Check, Default, Unique, Primary Key).

Column Level constraints

Create Table items

```
(
  itemID      INT      Not Null Primary Key,
  itemcode    varchar(4) Unique,
  itemname    varchar(40) Not Null Default '',

  quantity    INT      Not Null Default 0,
  price       Real      Not Null Default 0,

  (price      Decimal(7,2) check(price<1000))

  (check is available in Postgres not in MySQL)

)
```

Table Level Constraints

Create Table items

```
(
  itemID      INT      Not Null ,
  supplierID  INT      Not Null ,
  itemcode    varchar(4) Unique,
  itemname    varchar(40) Not Null Default '',
  quantity    INT      Not Null Default 0,
  price       Real      Not Null Default 0,

  OR

  price      Decimal(7,2) check(price<1000)

  PRIMARY KEY (itemID),
  CONSTRAINT fk_supplier FOREIGN KEY (supplierID) References
  suppliers (supplierID)

)
```

About Foreign Key:

A table level foreign key can indicate how to handle situation when a foreign key in parent table is deleted or updated.

```
CONSTRAINT fk_supplier FOREIGN KEY (supplierID),  
                References supplier (supplierID)  
    ON UPDATE  <action>  
    ON DELETE  <action>
```

Actions may be:

CASCADE	The change to the parent is cascaded to all the child rows
NO ACTION	The changes to the parent is prohibited.
SET NULL	The foreign key column in the child is set to null
SET DEFAULT	The foreign key column in the child is set to default
RESTRICT	The changes to the parent is prohibited

3- The ALTER Command:

The Alter command allows you to change many different characteristics of database structures (such as tables, columns, views).

- Rename a Table
- Rename a Column

- Rename a Constraint
- ADD or DROP a column
- ADD or DROP a Constraint
- Set or DROP a default (in column)
- Set a data_type (in column)

Renaming a Table using alter:

Alter Table items,
Rename to "alters";

Renaming a column using alter:

Alter Table items,
Rename Column "itemcode" to "itemunit"

Adding a column using alter:

Alter Table items,
ADD Column "itemName" varchar(20) NULL;