

TAP School MIS – API Documentation

Version 2.0.0

Updated: 2025-05-26

Maintained by: Trust And Pay (TAP) Technology Team

Table of Contents

Introduction.....	1
Authentication	1
Get Due Amount / Due Check.....	2
Payment Collection Confirmation.....	4
Get Transaction Status / Inquiry.....	6
Base URL.....	7
Credentials.....	7
Sample Test Data	7
Important Integration Notes.....	8

Introduction

It outlines the REST APIs for securely retrieving student bill details, confirming payments, and inquiring about transaction statuses.

Authentication

- Authentication Method: Basic Authentication
- Authorization: Basic <Base64Encoded(username:password)>

Get Due Amount / Due Check

Sample cURL

```
curl --location '{base_url}/bills/fetch' \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Basic YWRtaW46YWRtaW4xMjM=' \
  --data '{
    "school_code": "DRMC",
    "student_id": "334",
    "bill_month": "122023"
  }'
```

Endpoint

POST /bills/fetch

Headers

- Authorization: Basic <Base64Encoded(username:password)>
- Content-Type: application/json

Request Body

```
{
  "school_code": "DRMC",
  "student_id": "334",
  "bill_month": "122023"
}
```

Success Response

```
{
  "code": 2001,
  "message": "Success",
  "student_name": "Md. Mubin Rahman",
  "bill_month": "N/A",
  "bill_amount": 7025.00,
  "bill_due_date": "",
  "mis_tx_id": "MIS-SIDE-ID-ey6c2228-2cg1-5bh93973are2",
  "response_date_time": "2023-11-10 07:59:43"
}
```

Get Due Amount / Due Check - Success/Error Responses

Case	Code	Message
Bill fetch success	2001	Success
Institution not available	4001	Invalid Institute
Bill month not available	4002	Invalid Bill Date
Student ID not found	4003	Invalid ID
Invalid bill config	4004	Invalid Bill config
No due	4023	No Dues

Get Due Amount / Due Check - Request Body Data Structure

Field	Type	Description
school_code	String	Unique code of the school
student_id	String	Student identifier
bill_month	String	Billing month in MMYYYY format

Get Due Amount / Due Check - Response Body Data Structure

Field	Type	Description
code	Integer	Response status code
message	String	Response message
student_name	String	Name of the student
bill_month	String	Billed month
bill_amount	Double	Amount due
bill_due_date	String	Due date
mis_tx_id	String	Transaction ID on MIS side
response_date_time	String	Response timestamp

Payment Collection Confirmation

Sample cURL

```
curl --location '{base_url}/bills/pay' \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Basic YWRtaW46YWRtaW4xMjM=' \
  --data '{
    "school_code": "DRMC",
    "student_id": "334",
    "bill_month": "122023",
    "amount": 7025.00,
    "user_mobile_Number": "01792726811",
    "tap_tx_id": "SPNWRUHCIX24240XRG",
    "pay_time": "2023-11-10 08:20:43"
  }'
```

Endpoint

POST /bills/pay

Headers

- Authorization: Basic <Base64Encoded(username:password)>
- Content-Type: application/json

Request Body

```
{
  "school_code": "DRMC",
  "student_id": "334",
  "bill_month": "122023",
  "amount": 7025.00,
  "user_mobile_Number": "01792726811",
  "tap_tx_id": "SPNWRUHCIX24240XRG",
  "pay_time": "2023-11-10 08:20:43"
}
```

Success Response

```
{
  "code": 2001,
  "message": "Success",
  "mis_tx_id": "MIS-SIDE-ID-ey6c2228-2cg1-5bh93973are2",
  "response_date_time": "2023-11-10 08:20:43"
}
```

Payment Collection Confirmation – Success/Error Responses

Case	Code	Message
Payment success	2001	Success
Payment unsuccessful	4024	Payment Unsuccessful

Payment Collection Confirmation – Request Body Data Description

Field	Type	Description
school_code	String	School code
student_id	String	Student ID
bill_month	String	Billing month
amount	Double	Payment amount
user_mobile_Number	String	Payer's mobile number
tap_tx_id	String	Transaction ID from TAP
pay_time	String	Time of payment

Payment Collection Confirmation – Response Body Data Description

Field	Type	Description
code	Integer	Response status code
message	String	Response message
mis_tx_id	String	Transaction ID on MIS side
response_date_time	String	Response timestamp

Get Transaction Status / Inquiry

Sample cURL

```
curl --location '{base_url}/bills/status' \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Basic YWRtaW46YWRtaW4xMjM=' \
  --data '{
    "school_code": "DRMC",
    "tap_tx_id": "SPNWRUHCIX24240XRG"
  }'
```

Endpoint

POST /bills/status

Headers

- Authorization: Basic <Base64Encoded(username:password)>
- Content-Type: application/json

Request Body

```
{
  "school_code": "DRMC",
  "tap_tx_id": "SPNWRUHCIX24240XRG"
}
```

Success Response

```
{
  "code": 2001,
  "message": "Success",
  "mis_tx_id": "MIS-SIDE-ID-iofc2225-5cs8-5bh93965are2",
  "student_id": "334",
  "student_name": "Md. Mubin Rahman",
  "tran_date_time": "2023-11-10 08:20:43",
  "total_amount": 7025.00,
  "tran_status": "paid"
}
```

Get Transaction Status / Inquiry - Success/Error Responses

Case	Code	Message
Successful transaction	2001	Success
Transaction not found	4025	No transaction found with the core Id

Get Transaction Status / Inquiry – Request Body Data Description

Field	Type	Description
school_code	String	School code
tap_tx_id	String	Transaction ID from TAP

Get Transaction Status / Inquiry – Response Body Data Description

Field	Type	Description
code	Integer	Response status code
message	String	Response message
mis_tx_id	String	Transaction ID on MIS side
student_id	String	Student ID
student_name	String	Name of the student
tran_date_time	String	Transaction time
total_amount	Double	Total paid amount
tran_status	String	Transaction status

Base URL

Environment	Base URL
Test	https://api.tap.mis.test.com/api/v1
Production	https://api.tap.mis.com/api/v1

Credentials

Environment	Client ID / Username	Client Secret / Password
Test	tap_mis_prod	334&rtu\$22
Production	tap_mis_test	5464\$dawd#1&3

Sample Test Data

School Code	School Name	Sample Student ID
DRMC	Dhaka Residential Model College	334, 335,336,337,338,339,340
VNC	Viqarunnisa Noon School	1122,1123, 1124, 1125
MDC	Motijheel Ideal School	5501, 5502, 5503, 5504, 5505, 5506, 5507, 5508

Important Integration Notes

1. {base_url} should be dynamically replaced with the actual environment-specific domain. Please refer to the Base URL – Test Environment and Base URL – Production Environment tables above for the correct values.
2. All responses return HTTP 200 OK, regardless of success or failure. The response body contains a custom code field that should be used to determine the actual business outcome.
3. All amount fields are represented as double-precision floating-point numbers, and all code fields are integers.
4. All endpoints must be accessed over HTTPS to ensure secure communication and data protection.
5. While Basic Authentication is currently used, future implementations may introduce more advanced mechanisms such as OAuth 2.0, API Keys, or JWT (JSON Web Tokens) for enhanced security.

© 2025 Trust And Pay. All rights reserved.