

МИНОБРНАУКИ РОССИИ
САНКТ-ПЕТЕРБУРГСКИЙ ГОСУДАРСТВЕННЫЙ
ЭЛЕКТРОТЕХНИЧЕСКИЙ УНИВЕРСИТЕТ
«ЛЭТИ» ИМ. В.И. УЛЬЯНОВА (ЛЕНИНА)
Кафедра МО ЭВМ

ОТЧЕТ
по лабораторной работе №1
по дисциплине «Алгоритмы и структуры данных»
Тема: Рекурсия

Студент гр. 9304

Тиняков С.А.

Преподаватель

Фиалковский М. С.

Санкт-Петербург

2020

Цель работы.

Научиться применять рекурсию в программировании.

Задание.

Вариант 20.

Построить синтаксический анализатор понятия список_параметров.

список_параметров ::= параметр | параметр , список_параметров

параметр ::= имя=цифра цифра | имя=(список_параметров)

имя ::= буква буква буква

Выполнение работы.

Программа считывает данные из входного файла. Алгоритм в своей сути прост: он рекурсивно идёт по понятиям. Всё начинается с понятия список_параметров. Он, точно, начинается с понятия параметр. Алгоритм переходит к проверке понятия параметр. Он, точно, начинается с понятия имя, и алгоритм переходит к проверке этого понятия. Если после символа «=» в понятии параметр идет символ «(», то алгоритм идёт проверять понятие список_параметров. Аналогично, если в понятии список_параметров после понятия параметр идёт запятая, то вызывается проверка для понятия список_параметров.

На вход и выход программе подаются файлы через аргументы командной строки. Пробелы, символы табуляции и переноса строки и т. п. игнорируются. Во входном файле должно быть только то, что необходимо проанализировать. Никаких других предложений, символов и прочего быть не должно. В выходном файле выводится проанализированное понятие и то, что оно корректно, если понятие корректно. Иначе выводятся символы до ошибки(включая символ, на котором возникла она) и описание ошибки.

Класс *ReaderWriter* отвечает за ввод и вывод данных. В себе имеет два потока: один для входных данных, второй для выходных. Метод *GetNextChar*

возвращает следующий символ из входного потока. Если достигнут конец, то возвращается нулевой символ. Метод *GetAndWriteNextChar* делает тоже самое, только дополнительно записывает символ в выходной поток(нулевой символ не записывается). Метод *IsEOF()* сообщает, достигнут ли конец входного потока. Методы *WriteChar* и *WriteString* записывают в выходной файл соответственно символ и строку.

Класс *Analyzer* проверяет корректность понятия список_параметров. Метод *CheckListParam* проверяет корректность понятия список_параметров. Метод *ChecParam* проверяет корректность понятия параметр. Метод *ChecName* проверяет корректность понятия имя. Метод *StartAnalyz* запускает проверку входных данных.

Разработанный программный код см. в приложении А.

Результаты тестирования см. в приложении Б.

Выводы.

Научились применять рекурсию в программировании.

Была разработана программа для проверки понятия список_параметров. Реализация проверки сделана через рекурсию. Класс *ReaderWriter*, который отвечает за входные и выходные данные, сделан через потоки, что позволяет при помощи класса *Analyzer* проанализировать любой объект, с которым можно взаимодействовать через интерфейс потоков(например строки). Метод *WriteString* принимает аргумент типа *string_view*, что позволяет передовать методу как класс *string*, так и массив символов. Для проверки правильности работы программы были сделаны тесты.

ПРИЛОЖЕНИЕ А

ИСХОДНЫЙ КОД ПРОГРАММЫ

Название файла: Source/lab1.cpp

```
#include<iostream>
#include<fstream>
#include<string_view>
/* For analyz from string */
// #include<sstream>

class ReaderWriter{
private:
    std::istream& input;
    std::ostream& output;
public:
    ReaderWriter(std::istream& in, std::ostream& out):
        input(in),
        output(out)
    {
    }
    ~ReaderWriter(){
        output << '\n';
    }
    char GetNextChar(){
        char c;
        input >> c;
        if(IsEOF()) return '\0';
        return c;
    }

    char GetAndWriteNextChar(){
        char c;
        input >> c;
        if(IsEOF()) return '\0';
        output << c;
        return c;
    }

    bool IsEOF(){
        return input.eof();
    }

    void WriteChar(char c){
        output << c;
    }

    void WriteString(std::string_view str){
        output << str;
    }

};

class Analyzer{
private:
```

```

ReaderWriter* reader_writer;
char last_char;
std::string error_msg;

bool CheckListParam(){
    ;
    if(CheckParam()){
        char next = reader_writer->GetAndWriteNextChar();
        if(next == ',') return CheckListParam();
        else if(next == ')'){
            last_char = next;
            return true;
        }
        else if(!next) return true;
        error_msg = std::string("List of parameters Error:
Expected character '\',\'' but were given '\" + next + "\".\n";
        return false;
    }
    return false;
}

bool CheckParam(){
    ;
    if(CheckName()){
        char next = reader_writer->GetAndWriteNextChar();
        if(next == '='){
            next = reader_writer->GetAndWriteNextChar();
            if(next == '('){
                if(CheckListParam()){
                    if(last_char == ')'){
                        last_char = 0;
                        return true;
                    }
                }
                next = reader_writer->GetAndWriteNextChar();
                if(next == ')') return true;
                if(next) error_msg =
std::string("Parameter Error: Expected character '\')\'' but were given
'\')' + next + "\".\n";
                else error_msg = "Parameter Error:
Expected character '\')\'' but end of input were reached.\n";
                return false;
            }
            return false;
        }else{
            if(!(next >= '0' && next <= '9')){
                if(next) error_msg =
std::string("Parameter Error: Invalid define, character '\" + next +
"\" is not digit.\n";
                else error_msg = "Parameter Error:
Invalid define, expected digit, but end of input were reached.\n";
                return false;
            }
            next = reader_writer->GetAndWriteNextChar();
            if(!(next >= '0' && next <= '9')){

```

```

        if(next) error_msg =
std::string("Parameter Error: Invalid define, character '\"') + next +
"\"' is not digit.\n";
        else error_msg = "Parameter Error:
Invalid define, expected digit, but end of input were reached.\n";
        return false;
    }
    return true;
}
}
    if(next) error_msg = std::string("Parameter Error:
Expected character '\"='\", but were given '\"') + next + "\"'.\n";
    else error_msg = "Parameter Error: Expected character
\"'='\", but end of input were reached.\n";
    return false;
}
return false;
}

bool CheckName(){
    int count = 0;
    while(count < 3){
        char next = reader_writer->GetAndWriteNextChar();
        if(!(next >= 'A' && next <= 'z')){
            if(next) error_msg = std::string("Name Error:
Invalid name, character '\"') + next + "\"' is not letter.\n";
            else error_msg = "Name Error: Invalid name,
excepted letter, but end of input were reached.\n";
            return false;
        }
        count++;
    }
    return true;
}

public:
    Analyzer(ReaderWriter* reader_writer){
        this->reader_writer = reader_writer;
        last_char = 0;
    }
    ~Analyzer() = default;

    void StartAnalyz(){
        bool correct = CheckListParam();
        char next = reader_writer->GetNextChar();
        if(last_char != 0 && error_msg.empty()){
            error_msg = std::string("List of parameters Error:
Expected character '\"', '\"', but were given '\"') + last_char + "\"'.\n";
            correct = false;
        }
        if(!correct){
            reader_writer->WriteString("\nIncorrect. ");
            reader_writer->WriteString(error_msg);
        }else reader_writer->WriteString("\nCorrect.\n");
    }
};

```

```

int main(int argc, char** argv){
    if(argc < 3){
        std::cout << "Usage: param_analyzer /path/to/input
/path/to/output\n";
        return 1;
    }
    try{
        std::ifstream in(argv[1]);
        std::ofstream out(argv[2]);
        if(!in.is_open()){
            std::cout << "Can't open file " << argv[1] << "\n";
            return 2;
        }
        if(!out.is_open()){
            std::cout << "Can't open/create file " << argv[2] <<
"\n";

            return 2;
        }
        /* Example with string */
        // std::stringstream in("AAA = 15\n");
        {
            ReaderWriter rw(in, out);
            Analyzer analyzer(&rw);
            analyzer.StartAnalyz();
        }
        in.close();
        out.close();
    }catch(std::exception& e){
        std::cout << e.what() << "\n";
        return 3;
    }
    return 0;
}

```

Название файла: Makefile

```

lab1: Source/lab1.cpp
    g++ Source/lab1.cpp -std=c++17 -o lab1

run_tests: lab1
    python3 test.py

```

Название файла: test.py

```

import unittest
import subprocess
import os

class TestParamAnalyzer(unittest.TestCase):

    cwd = os.getcwd();

```

```

def test_0_basic(self):
    subtests = [
        ['AAA = 15', 'AAA=15\nCorrect.\n\n'],
        ['AA4 = 23', 'AA4\nIncorrect. Name Error: Invalid name, character \'4\' is not letter.\n\n'],
        ['AAw = 2P', 'AAw=2P\nIncorrect. Parameter Error: Invalid define, character \'P\' is not digit.\n\n'],
        ['BBB=      \n      (RRR      =\n56)', 'BBB=(RRR=56)\nCorrect.\n\n'],
        ['AAA = BBB = 45', 'AAA=B\nIncorrect. Parameter Error: Invalid define, character \'B\' is not digit.\n\n'],
        ['AAA = (BBB = 13)', 'AAA=(BBB=13)\nCorrect.\n\n'],
        ['AAA = (BBB = 13', 'AAA=(BBB=13\nIncorrect. Parameter Error: Expected character \')\'', but end of input were reached.\n\n'],
        ['AAA = (BBB = 1', 'AAA=(BBB=1\nIncorrect. Parameter Error: Invalid define, expected digit, but end of input were reached.\n\n'],
        ['AAA\n=      14)', 'AAA=14)\nIncorrect. List of parameters Error: Expected character \',\'', but were given \')\''. \n\n'],
        ['AAA\n=      14o', 'AAA=14o\nIncorrect. List of parameters Error: Expected character \',\'', but were given \'o\''. \n\n'],
        ['AAA\n=      14,', 'AAA=14,\nIncorrect. Name Error: Invalid name, expected letter, but end of input were reached.\n\n'],
        ['AAA 14', 'AAA1\nIncorrect. Parameter Error: Expected character \'=\'', but were given \'1\''. \n\n'],
        ['AAA ', 'AAA\nIncorrect. Parameter Error: Expected character \'=\'', but end of input were reached.\n\n']
    ]

    for test in subtests:
        with open('input', 'w') as f:
            f.write(test[0])
        p = subprocess.run(['./lab1', 'input', 'output'], cwd = self.cwd)

        with open('output', 'r') as f:
            line = f.read()
            self.assertEqual(line, test[1])

def test_1(self):
    subtests = [
        ['AAA = 15      ,      BBB =      (AaA = (AAA = (AAA = 12)), FFF =10)\n', 'AAA=15,BBB=(AaA=(AAA=(AAA=12)),FFF=10)\nCorrect.\n\n'],
        ['AAA = 15      ,      BBB =      (AaA = (AAA = (AAA = 12))), FFF =10\n', 'AAA=15,BBB=(AaA=(AAA=(AAA=12))),FFF=10\nCorrect.\n\n'],
        ['AAA = 15      ,      BBB =      (AaA = (AAA = (AAA = 12))), FFF      =10)\n', 'AAA=15,BBB=(AaA=(AAA=(AAA=12))),FFF=10)\nIncorrect. List of parameters Error: Expected character \',\'', but were given \')\''. \n\n'],
    ]

```



```

        ['AAA = 15      ,      BBB =      (AaA = (AAA = (AAA =
12)),      FFF      =10\n','AAA=15,BBB=(AaA=(AAA=(AAA=12)),FFF=10\nIncorrect.
Parameter Error: Expected character '\')\'', but end of input were
reached.\n\n'],

```

```

        ['AAA = 15      ,      BBB =      AaA = AAA = AAA =
12,      FFF      =10\n','AAA=15,BBB=A\nIncorrect.  Parameter Error: Invalid
define, character \'A\' is not digit.\n\n'],
    ]

```

```

        for test in subtests:
            with open('input', 'w') as f:
                f.write(test[0])
            p = subprocess.run(['./lab1','input','output'],
cwd = self.cwd)

            with open('output', 'r') as f:
                line = f.read()
                self.assertEqual(line, test[1])

```

```

    def test_2(self):
        subtests = [
            ['Ssf = (AOE = 12,\n          FWA = 14,\n
ASF = 16,\n          VER = 20\n          ),\nFFF = 04, QWE=(AFA = (aas =
13,\n          vsd = ( yet = (faw = ( ker = ( ort = 95, not = 00,\n          trr =
(          zzz          =          (kkk          =          (uuu          =
14)))))))]','Ssf=(AOE=12,FWA=14,ASF=16,VER=20),FFF=04,QWE=(AFA=(aas=1
3,vsd=(yet=(faw=(ker=(ort=95,not=00,trr=(zzz=(kkk=(uuu=14)))))))]\
nCorrect.\n\n'],
            ['asd = 00, fbk = 11, AAA = (OOO = 13),\nFFF
= 12, BBB = 94, QQQ = 93, KKK = 21,\nMMM = 21, NNN = 21, DDD = (EEE =
(kad = 94)),\nDDD = 64, VVV = 82,HHH=65, LLL = 08, ret =
42','asd=00,fbk=11,AAA=(OOO=13),FFF=12,BBB=94,QQQ=93,KKK=21,MMM=21,NNN
=21,DDD=(EEE=(kad=94)),DDD=64,VVV=82,HHH=65,LLL=08,ret=42\nCorrect.\n\
n']
        ]

```

```

        for test in subtests:
            with open('input', 'w') as f:
                f.write(test[0])
            p = subprocess.run(['./lab1','input','output'],
cwd = self.cwd)

            with open('output', 'r') as f:
                line = f.read()
                self.assertEqual(line, test[1])

```

```

    def test_3(self):
        p = subprocess.run(['./lab1','input'], cwd = self.cwd,
stdout = subprocess.PIPE)
        self.assertEqual(p.returncode, 1);
        p = subprocess.run(['./lab1','non_exist_file','output'],
cwd = self.cwd, stdout = subprocess.PIPE)
        self.assertEqual(p.returncode, 2);

```

```

    def tearDown(self):
        if os.path.isfile('./input'):
            os.remove('./input')
        if os.path.isfile('./output'):

```

```
os.remove('./output')

if __name__ == "__main__":
    unittest.main()
```

ТЕСТИРОВАНИЕ

Результаты тестирования представлены в таблице Б.1

Таблица Б.1 — Результаты тестирования

№ п/п	Входные данные	Выходные данные
1.	AAA = 15	AAA=15 Correct.
2.	AA4 = 23	AA4 Incorrect. Name Error: Invalid name, character '4' is not letter.
3.	AAw = 2P	Aaw=2P Incorrect. Parameter Error: Invalid define, character 'P' is not digit.
4.	BBB= (RRR = 56)	BBB=(RRR=56) Correct.
5.	AAA = BBB = 45	AAA=B Incorrect. Parameter Error: Invalid define, character 'B' is not digit.
6.	AAA = (BBB = 13)	AAA=(BBB=13) Correct.
7.	AAA = (BBB = 13	AAA=(BBB=13 Incorrect. Parameter Error: Expected character ')', but end of input were reached.
8.	AAA = (BBB = 1	AAA=(BBB=1 Incorrect. Parameter Error: Expected character ')', but end of input were reached.
9.	AAA = 14)	AAA=14) Incorrect. List of parameters Error: Expected character ',', but were given ')'. Correct.

10.	AAA = 14o	AAA=14o Incorrect. List of parameters Error: Expected character ',', but were given 'o'.
11.	AAA = 14,	AAA=14, Incorrect. Name Error: Invalid name, excepted letter, but end of input were reached.
12.	AAA 14	AAA1 Incorrect. Parameter Error: Expected character '=', but were given '1'.
13.	AAA	AAA Incorrect. Parameter Error: Expected character '=', but end of input were reached.
14.	AAA = 15 , BBB = (AaA = (AAA = (AAA = 12))), FFF =10	AAA=15,BBB=(AaA=(AAA=(AAA=12))), FFF=10) Correct.
15.	AAA = 15 , BBB = (AaA = (AAA = (AAA = 12))), FFF =10	AAA=15,BBB=(AaA=(AAA=(AAA=12))), FFF=10 Correct.
16.	AAA = 15 , BBB = (AaA = (AAA = (AAA = 12))), FFF =10)	AAA=15,BBB=(AaA=(AAA=(AAA=12))), FFF=10) Incorrect. List of parameters Error: Expected character ',', but were given ')'
17.	AAA = 15 , BBB = (AaA = (AAA = (AAA = 12))), FFF =10	AAA=15,BBB=(AaA=(AAA=(AAA=12))), FFF=10 Incorrect. Parameter Error: Expected character ')', but end of input were reached.
18.	AAA = 15 , BBB = AaA = AAA = AAA = 12, FFF =10	AAA=15,BBB=A Incorrect. Parameter Error: Invalid define, character 'A' is not digit.
19.	Ssf = (AOE = 12,	Ssf=(AOE=12,FWA=14,ASF=16,VER=20)

	FWA = 14, ASF = 16, VER = 20), FFF = 04, QWE=(AFA = (aas = 13, vsd = (yet = (faw = (ker = (ort = 95, not = 00, trr = (zzz = (kkk = (uuu = 14)))))))))	,FFF=04,QWE=(AFA=(aas=13,vsd=(yet=(faw=(ker=(ort=95,not=00,trr=(zzz=(kkk=(uuu=14)))))))))) Correct.
20.	asd = 00, fbk = 11, AAA = (OOO = 13), FFF = 12, BBB = 94, QQQ = 93, KKK = 21, MMM = 21, NNN = 21, DDD = (EEE = (kad = 94)), DDD = 64, VVV = 82,HHH=65, LLL = 08, ret = 42	asd=00,fbk=11,AAA=(OOO=13),FFF=12, BBB=94,QQQ=93,KKK=21,MMM=21,NNN=21,DDD=(EEE=(kad=94)),DDD=64,VVV=82,HHH=65,LLL=08,ret=42 Correct.