Group Member's Name:-

Muhammad Arsalan (2303.KHI.DEG.025)
Abdul Rehman (2303.KHI.DEG.035)
Arshad Shiwani (2303.KHI.DEG.026)

We add Docker Compose Services of phpmyadmin and wordpress.

```yaml
services:
  db:
    image: mariadb:10.6.4-focal
    command: '--default-authentication-plugin=mysql_native_password'
    volumes:
      - db_data:/var/lib/mysql
    restart: always
    environment:
      - MYSQL_ROOT_PASSWORD=somewordpress
      - MYSQL_DATABASE=wordpress
      - MYSQL_USER=wordpress
      - MYSQL_PASSWORD=wordpress

      #- MYSQL_ROOT_PASSWORD=notSecureChangeMe


    expose:
      - 3306


  wordpress:
    image: wordpress:latest
    volumes:
      - wp_data:/var/www/html
    ports:
      - 80:80
    restart: always
    environment:
      - WORDPRESS_DB_HOST=db
      - WORDPRESS_DB_USER=wordpress
      - WORDPRESS_DB_PASSWORD=wordpress
      - WORDPRESS_DB_NAME=wordpress


  phpmyadmin:
    image: phpmyadmin
    restart: always
    ports:
      - 5000:80



volumes:
  db_data:
  wp_data:
```

First we make docker container images of **phpmyadmin** and **wordpress**.

```
(base) abdulrehman@all-MS-7D35:~/Downloads/day_1_microservices$ cd docker_compose_example/
(base) abdulrehman@all-MS-7D35:~/Downloads/day_1_microservices/docker_compose_example$ docker compose up -d
[+] Running 3/0
 ✔ Container docker_compose_example-phpmyadmin-1   Running
 ✔ Container docker_compose_example-wordpress-1    Running
 ✔ Container docker_compose_example-db-1           Running
(base) abdulrehman@all-MS-7D35:~/Downloads/day_1_microservices/docker_compose_example$ docker compose logs >>logs1
(base) abdulrehman@all-MS-7D35:~/Downloads/day_1_microservices/docker_compose_example$ █
```

This is the screenshot of **phpmyadmin** panel.

This is the screenshot of **Wordpress** panel

This is the screenshot of **phpmyadmin** panel