

Practical 07 - Test and Load Test your WebService

Objectives:

- To interact with and test the WebService you created in Practical 06
- To load test the WebService you created in Practical 06

Tools to be used in this practical:

- Oracle Java JDK v1.7 (aka Java 7) - www.java.com (to support SOAPUI)
- SoapUI Tester - www.soapui.org
- Tomcat Application Server (assumed already running, and hosting your WebService application, as at the end of the last exercise)

Instructions:

1. Launch SOAPUI
 - 1.1. Locate folder where you unpacked SOAPUI, e.g. /home/usr/development/SoapUI-5.x.x
 - 1.2. Within that folder, locate the bin sub-directory
 - 1.3. Within the bin subdirectory, locate and launch the soapui.sh item
 - 1.4. Wait for SOAPUI to launch, and the desktop to appear
 - 1.5. If the "SOAPPUI Starter Page" appears, close it ([x] in top left of Window)
2. Create a "New SOAP project" within SoapUI
 - 2.1. Within SoapUI, select "File", then "New SOAP project"
 - 2.2. In the "New SOAP Project" window:
 - 2.2.1. Set "Project Name" to "ShapeAreas"
 - 2.2.2. Set "Initial WSDL" to the WSDL URL you noted at the end of Practical 06.
 - 2.2.3. Make sure that "Create Requests" is ticked.
 - 2.2.4. Make sure that "Create TestSuite" is ticked.
 - 2.2.5. Make sure that "Relative Paths" is ticked.
 - 2.2.6. Check again that all the settings above are correct, then click <OK>
 - 2.3. When asked to "Save project ShapeAreas", choose a suitable location (e.g. /home/user/development) then click <Save>
 - 2.4. Wait for the project to finish building.
 - 2.5. SOAPUI will attempt to generate a TestSuite based on the WSDL of the WebService.
 - 2.6. When "Generate Test Suite" appears
 - 2.6.1. Ensure that "TestSuite" is set to <create>
 - 2.6.2. Ensure that "Style" is set to "One TestCase for each operation"

- 2.6.3. Under "Request Content", ensure that "Create new empty requests" is selected.
- 2.6.4. Ensure that under "Operations" all of the Operations are selected
- 2.6.5. Ensure the "Generate LoadTest" is *not* selected.
- 2.6.6. Click <OK>
- 2.7. Under "Generate TestSuite", the default name is suitable, just click <OK>
- 2.8. Save the project so far by clicking on the "Save" icon on the tool bar.
- 3. Interact with the WebService:
 - 3.1. Locate and open the "ShapeAreasSoapBinding" item.
 - 3.2. Within the "ShapeAreasSoapBinding" item, locate and open each operation item (of 3).
 - 3.3. Within each Operation, locate and double click the "Request1" item
 - 3.4. Set the input fields in the "Request" side
 - 3.5. Click on "Submit Request" (green arrow to top left of request)
 - 3.6. Wait for the response to be returned
 - 3.7. Examine the response.
 - 3.8. Try the tests attempting to feed in bad data, e.g. a string where a numeric input is expected.
 - 3.8.1. What do you think of the error handling of this WebService?
 - 3.8.2. Did you write any code to produce SOAP faults?
 - 3.9. Break the request XML (e.g. remove one of the closing tags), and submit.
 - 3.9.1. Is this what we expected?
 - 3.9.2. Repeat these steps for the other operations...
- 4. Add further tests to the ShapeAreasSoapBinding TestSuite.
 - 4.1. Locate and open the "ShapeAreasSoapBinding TestSuite" item.
 - 4.2. Within the "ShapeAreasSoapBinding TestSuite" item select any one of the three TestCases for your operations, and open it.
 - 4.3. Within the opened operation, locate and open the "Test Steps (1)" item.
 - 4.4. Within the "Test Steps (1)" item, locate and double click on the operation name item.
 - 4.5. In the request editor, set the inputs and execute to ensure that the test passes.
 - 4.6. Note the response time of this test.
 - 4.7. Save the project.
 - 4.8. Add a response time test to the test suite
 - 4.8.1. Click on the "Assertions" button (bottom left below the request).
 - 4.8.2. Click the "+" item to add an assertion
 - 4.8.3. In the "Add Assertion" window:
 - 4.8.4. Select the "SLA" category.
 - 4.8.5. Under "SLA" select the "Response SLA" item - read the description of this assertion.
 - 4.8.6. Click <Add>
 - 4.8.7. Under "Configure Response SLA Assertion"

- 4.8.7.1. Set "Specify desired response time" to a reasonable time (e.g. 150% of the response time noted in the test above)
 - 4.8.7.2. Click <OK>
 - 4.8.8. Save the project
 - 4.8.9. Re-run the test a few times, noting the varying response times.
- 5. Load test your WebService.
 - 5.1. Below the "Test Steps(1)" item of the TestCase you selected above, locate the "Load Tests (0)" item.
 - 5.2. Right-click the "Load Tests (0)" item and select "New Load Test"
 - 5.3. In the "Specify name of LoadTest", accept the default name by pressing <OK>
 - 5.4. Wait a few seconds for the load test to build and open.
 - 5.5. Note the settings on the load test, in particular:
 - 5.5.1. Limit (the period the test will run for)
 - 5.5.2. Threads (number of simultaneous requests)
 - 5.5.3. Test Delay and Random (gaps between calls by each thread calling the web service, and variance in those gaps)
 - 5.6. Launch the test (green arrow in top left of the "LoadTest" windows)
 - 5.7. Note the max, min and average response times of the web service under load.
 - 5.8. Click on the "Graph" icons beside the "Launch Test" green arrow to see a graphical representation of the progress of the test.
- 6. Crank up the test rate
 - 6.1. Increase number of threads, decrease test delay.
 - 6.2. Re-run the test.
 - 6.3. Repeat until the SLA begins to be breached.
- 7. Add Additional Tests to the TestSuite to confirm that your WebService is working
 - 7.1. Add a test to check for "if we put in bad data, we get back a SOAP fault"
 - 7.1.1. Below the "Test Steps(1)" item of the TestCase you selected above, locate the "SOAP" item.
 - 7.1.1.1. Right click the SOAP item, and select "Clone"
 - 7.1.1.2. In the Clone TestStep window:
 - 7.1.2. Note the available options
 - 7.1.3. Set the name as you see fit
 - 7.1.4. Click <OK>
 - 7.1.5. Locate the Cloned SOAP test item, and double click it to edit it.
 - 7.1.6. Put in valid data, then run the Cloned SOAP test item - confirm that it passes
 - 7.1.7. Put in invalid data, then re-run the Cloned SOAP test item - does it pass or fail?
 - 7.1.8. As we've put in invalid data, we expect (want?) it to fail with a SOAP fault.
 - 7.1.8.1. Add an assertion of type "Compliance, Status and Standards" | "SOAP Fault"
 - 7.1.8.2. Remove any existing assertion of type "Not SOAP Fault"
 - 7.1.9. Run the test again - confirm that the test is passed (even though the WebService is returning a SOAP Fault)
 - 7.2. Add a test to check for "if we put in good data, we get back a correct answer"

- 7.2.1. Clone another copy of one of the SOAP Test Items
 - 7.2.2. Locate the Cloned SOAP test item, and double click it to edit it.
 - 7.2.3. Put in valid data
 - 7.2.4. Run the Cloned SOAP test item - confirm that it passes
 - 7.2.5. Note the name of the Attribute holding the answer.
 - 7.2.6. Look at the answer in the returned SOAP message - is it correct.
 - 7.2.7. Add an assertion of type "Property Content" | "XPath Match"
 - 7.2.8. Set the XPath Expression to "node()", and click "Select from Current" to set the Expected Result to the current returned result.
 - 7.2.9. You can try the "Select from Current" and "Test" buttons
 - 7.2.10. Also, note the other options
 - 7.2.11. Click Save
 - 7.2.12. Run this test again - confirm that the test is passed
8. Run the whole test case
 - 8.1. Locate the relevant test case item
 - 8.2. Double click on it to open in the editor
 - 8.3. You should be able to see each test step you have created
 - 8.4. Execute the test case (using the green "run" arrow button)
 - 8.5. Note the success or failure of the test case overall.