

Chapter 10: The Linear Search Theorem.

In which we introduce the simplest searching algorithm.

Suppose we are given an array $f[0..N)$ of integer, where $\{1 \leq N\}$, which is guaranteed to contain at least one occurrence of the value X , and we are asked to find the location of the leftmost X in f , i.e. the smallest index n where $f.n = X$.

We begin as usual with a problem specification.

$$\{ \langle \exists j : 0 \leq j < N : f.j = X \rangle \}$$

S

$$\{ \langle \forall j : 0 \leq j < n : f.j \neq X \rangle \wedge f.n = X \}$$

As usual, we begin by developing a model of the problem domain.

$$* (0) C.n \quad \equiv \quad \langle \forall j : 0 \leq j < n : f.j \neq X \rangle, \quad 0 \leq n \leq N$$

Appealing to the empty range and associativity we get the following theorems

Consider.

$$\begin{aligned} & C.0 \\ = & \quad \{ (0) \text{ in model } \} \\ & \langle \forall j : 0 \leq j < 0 : f.j \neq X \rangle \\ = & \quad \{ \text{empty range } \} \\ & \text{true} \end{aligned}$$

$$- (1) C.0 \quad \equiv \quad \text{true}$$

Consider

$$\begin{aligned} & C.(n+1) \\ = & \quad \{ (0) \text{ in model } \} \\ & \langle \forall j : 0 \leq j < n+1 : f.j \neq X \rangle \\ = & \quad \{ \text{split off } j = n \text{ term} \} \\ & \langle \forall j : 0 \leq j < n : f.j \neq X \rangle \wedge f.n \neq X \\ = & \quad \{ (0) \text{ in model } \} \\ & C.n \wedge f.n \neq X \end{aligned}$$

$$- (2) C.(n+1) \quad \equiv \quad C.n \wedge f.n \neq X, \quad 0 \leq n < N$$

Rewrite postcondition using the model.

$$\text{Post} : C.n \wedge f.n = X$$

Choose Invariants.

We choose as our invariants

$$P0: C.n$$

$$P1: 0 \leq n \leq N$$

Establish Invariants.

Theorem (1) in our model shows us that we can establish P0 by the assignment

$$n := 0$$

This also establishes P1.

Termination.

We note that

$$P0 \wedge P1 \wedge f.n = X \Rightarrow \text{Post}$$

Guard

We choose our loop guard to be

$$B : f.n \neq X$$

Variant.

As our variant function we choose

$$K - n$$

Where $0 \leq K < N$ and K is the (as yet unknown) index of the leftmost occurrence of X.

Calculate Loop body.

Decreasing the variant by the assignment $n := n+1$ is a standard step and maintains P1. Let us see what effect it has on P0

$$\begin{aligned} & (n := n+1). P0 \\ = & \quad \{ \text{textual substitution} \} \\ & C.(n+1) \\ = & \quad \{ (2) \text{ above} \} \\ & C.n \wedge f.n \neq X \\ = & \quad \{ f.n \neq X \text{ at start of loop body} \} \\ & C.n \\ = & \quad \{ P0 \text{ is invariant} \} \\ & \text{true} \end{aligned}$$

Finished program.

So our finished program is

```
    n := 0
; do f.n ≠ X →

        n := n+1

    od
{C.n ∧ f.n = X}
```

Generic Solution.

This problem is just one instance of a set of problems called the Linear Searches. We will now describe this family of problems and construct the generic solution.

Suppose we are given a finite, ordered domain, $f[\alpha..\beta)$ and a predicate Q defined on the elements of f . We are also given that Q holds true at at least one point in the domain. We are asked to find the lowest point at which this is the case. We begin with our specification.

$$\{ \langle \exists j : \alpha \leq j < \beta : \neg Q.(f.j) \rangle \}$$

S

$$\{ \langle \forall j : \alpha \leq j < n : \neg Q.(f.j) \rangle \wedge Q.(f.n) \}$$

As usual we develop our model

$$* (3) C.n \quad \equiv \quad \langle \forall j : \alpha \leq j < n : \neg Q.(f.j) \rangle, \alpha \leq n \leq \beta$$

Appealing to the empty range law and associativity we get the following theorems

Consider.

$$\begin{aligned} & C.\alpha \\ = & \quad \{ (0) \text{ in model } \} \\ & \langle \forall j : \alpha \leq j < \alpha : \neg Q.(f.j) \rangle \\ = & \quad \{ \text{empty range } \} \\ & \text{true} \end{aligned}$$

$$- (1) C.\alpha \quad \equiv \quad \text{true}$$

Consider

$$\begin{aligned} & C.(n+1) \\ = & \quad \{ (0) \text{ in model } \} \\ & \langle \forall j : \alpha \leq j < n+1 : \neg Q.(f.j) \rangle \\ = & \quad \{ \text{split off } j = n \text{ term} \} \\ & \langle \forall j : \alpha \leq j < n : \neg Q.(f.j) \rangle \wedge \neg Q.(f.n) \\ = & \quad \{ (0) \text{ in model } \} \\ & C.n \wedge \neg Q.(f.n) \end{aligned}$$

$$- (2) C.(n+1) \quad \equiv \quad C.n \wedge \neg Q.(f.n), \alpha \leq n < \beta$$

We can now rewrite our postcondition as

$$\text{Post} : C.n \wedge Q.(f.n)$$

Choose Invariants.

We choose as our invariants

$$P0: C.n$$

$$P1: \alpha \leq n \leq \beta$$

Termination.

We note that

$$P0 \wedge P1 \wedge Q.(f.n) \Rightarrow \text{Post}$$

Establish Invariants.

Our model (4) shows us that we can establish P0 by the assignment

$$n := \alpha$$

This also establishes P1.

Guard.

We choose our loop guard to be

$$B : \neg Q.(f.n)$$

Variant.

As our variant function we choose

$$K - n$$

Where $0 \leq K < N$ and K is the (as yet unknown) index of the leftmost point where Q holds.

Calculate Loop body.

Decreasing the variant by the assignment $n := n+1$ is a standard step and maintains P1. Let us see what effect it has on P0

$$\begin{aligned}
 & (n := n+1). P0 \\
 = & \quad \{\text{textual substitution}\} \\
 & C.(n+1) \\
 = & \quad \{(2) \text{ above}\} \\
 & C.n \wedge \neg Q.(f.n) \\
 = & \quad \{\neg Q.(f.n) \text{ at start of loop body}\} \\
 & C.n \\
 = & \quad \{ P0 \} \\
 & \text{true}
 \end{aligned}$$

Finished Program.

So our finished program is as follows

```

n := α
; do ¬Q.(f.n) →

        n := n+1

od

{C.n ∧ Q.(f.n)}

```

This is called the Linear Search Theorem.

Exercises.

Find the largest natural number i , where $i*i \leq 1023$.

Given $f[0..1000)$ of integer which is guaranteed to contain the value X more than once, construct programs to

- find the rightmost index i where $f.i = X$
- find the 2nd leftmost index i where $f.i = X$

Fred's appointment book is represented by a boolean array $f[0..N)$ and Mary's appointment book is represented by a boolean array $m[0..N)$. Fred is available to meet on day i if $f.i = \text{true}$ and is busy if $f.i = \text{false}$. Similarly with Mary. Given that there exists a day in the future when they both are free to meet, find out when the earliest day is that they can meet.

