ICS | International Chemical Supplier & Manufacturer

Safety Data Sheet (MSDS)

Print Thickener PT-500

Product Name	Print Thickener PT-500
Application	Pigment printing — textile auxiliary
Chemical Description	Synthetic thickener for pigment printing with sharp definition.

1. Hazard Summary

May cause mild irritation to eyes, skin, or the respiratory tract with prolonged or repeated contact. Avoid prolonged skin contact and inhalation of mist or vapor. Not classified as acutely hazardous under normal recommended use conditions.

2. First Aid Measures

Eyes: Flush immediately with clean water for at least 15 minutes; seek medical attention if irritation persists.
Skin: Wash thoroughly with soap and water.
Inhalation: Move to fresh air. Seek medical attention if discomfort continues.
Ingestion: Rinse mouth and seek medical advice; do not induce vomiting unless directed by a physician.

3. Personal Protective Equipment (PPE)

Chemical-resistant gloves, safety goggles, and protective clothing are recommended during handling. Ensure adequate ventilation in the work area.

4. Storage

Store in a cool, dry, well-ventilated area away from direct sunlight. Keep container tightly closed when not in use. Protect from freezing and excessive heat.

5. Fire Fighting Measures

Suitable extinguishing media: water spray, foam, dry chemical, or carbon dioxide (CO_2). No unusual fire or explosion hazards expected under normal use conditions.

6. Disposal Considerations

Dispose of in accordance with local, regional and national regulations. Do not discharge undiluted product directly into waterways or municipal drains.

This safety data sheet is provided for general handling guidance. It does not replace a full GHS/OSHA-format SDS — request the complete regulatory SDS for your destination market before industrial handling, storage or transport.
ICS — International Chemical Supplier & Manufacturer | info@ics-chemicals.com | +92 21 3567 8900