Search

home / study / engineering / computer science / computer science questions and answers / you have to design a c++ template function range, w...


Question: You have to design a C++ template function range, which tak...


Visual Studio c++

Add comments and send picture of output

You have to design a C++ template function range, which takes a dynamic two-dimensional square matrix, its dimensions (rows, columns) size. It returns the range of values in matrix.

- Range = ((max min)/4) + min.
- Note: No specialization is required for this function. Do not take input from user. Initialize a 2D array in main and call the function.
- Template <typename T> T range (T **array, int rows, int columns)






Write another template function that will Shift the columns of matrix by 1 and print the shifted matrix. What would be the prototype of this function?

С	A	В
D	Н	I
E	G	F

Show transcribed image text

Expert Answer (1)



Was this answer helpful?





Post a question

Answers from our experts for your tough homework questions

Enter question

Continue to post

4 questions remaining

My Textbook Solutions







9th Edition 7th Editio

2nd Edition View all solutions

```
//cout<<"MIN :"<<minValue<<"\nMAX :"<<maxValue<<"\n";
T result = ((maxValue - minValue) / 4) + minValue;
return result;
}
int main()
int ** arr = new int*[4];
for(int i = 0; i< 4; i++)
arr[i] = new int[4];
// make int array
int c = 0;
for(int i= 0; i< 4; i++)
for(int j = 0; j < 4; j++)
arr[i][j] = c++;
//make char array
char count = 'A';
char ** arr1 = new char*[3];
for(int i = 0; i < 3; i++)
arr1[i] = new char[3];
for(int i= 0; i< 3; i++)
for(int j = 0; j < 3; j++)
arr1[i][j] = count++;
cout<<"Result of int array : "<<range(arr,4,4);</pre>
cout<<"\nResult of char array : "<<range(arr1,3,3);</pre>
}
output:
Result of int array: 3
Result of char array : C
B)
#include<iostream>
using namespace std;
template <typename T>
void shift(T ** &array , int rows,int columns)
T *temp = new T[rows];
for(int i = 0 ; i < rows; i++)
temp[i] = array[i][columns - 1];
for(int i = columns - 1; i > 0; i--)
{
```

```
for(int j = 0; j < rows; j++)
array[j][i] = array[j][i-1];
}
for(int i = 0; i < rows; i++)
array[i][0] = temp[i];
int main()
int ** arr = new int*[4];
for(int i = 0; i< 4; i++)
arr[i] = new int[4];
// make int array
int c = 0;
for(int i= 0; i< 4; i++)
for(int j = 0; j < 4; j++)
arr[i][j] = c++;
shift(arr,4,4);
for(int i= 0; i< 4; i++){
for(int j = 0; j < 4; j++){
cout<<arr[i][j]<<" ";
}
cout<<"\n";
output:
3012
7456
11 8 9 10
15 12 13 14
Comment >
```

Questions viewed by other students

Q: Task 1: Write seperate C++ template functions for (i) and (ii) i) You have to design a C++ template function range, which takes a dynamic two-dimensional square matrix, its dimensions (rows, columns) size. It returns the range of values in matrix. Range = ((max - min)/4) + min. Note: No specialization is required for this function. Do not take input from user. Initialize a 2D array...

Advertising Choices
Cookie Notice
General Policies
Intellectual Property Rights
Terms of Use
Global Privacy Policy
DO NOT SELL MY INFO
Honor Code
Honor Shield

CHEGG PRODUCTS AND SERVICES

Cheap Textbooks Chegg Math Solver Chegg Coupon Mobile Apps Chegg Play Sell Textbooks Solutions Manual Chegg Study Help College Textbooks Study 101 eTextbooks Textbook Rental Flashcards Used Textbooks Learn Digital Access Codes Uversity Chegg Life

Chegg Writing

CHEGG NETWORK

EasyBib Internships.com Thinkful

CUSTOMER SERVICE

Customer Service Give Us Feedback Manage Subscription



Media Center

Site Map



© 2003-2022 Chegg Inc. All rights reserved.