```
[root@b5885d1b07cf /]# cksum /mydir/securecopy.txt
cksum: /mydir/securecopy.txt: No such file or directory
[root@b5885d1b07cf /]# cd ~/mydir
[root@b5885d1b07cf mydir]# cksum ~/mydir/securecopy.txt
2766876939 488142 /root/mydir/securecopy.txt
[root@b5885d1b07cf mydir]# nano ~/mydir/securecopy.txt
[root@b5885d1b07cf mydir]# cksum ~/mydir/securecopy.txt
683390707 488240 /root/mydir/securecopy.txt
[root@b5885d1b07cf mydir]# find ~/mydir -name Abeer.txt
/root/mydir/mydir2/Abeer.txt
[root@b5885d1b07cf mydir]#
```

```
[root@b5885d1b07cf mydir]# touch useradd-man.txt
[root@b5885d1b07cf mydir]# man useradd 1> useradd-man.txt
[root@b5885d1b07cf mydir]# grep password useradd-man.txt
        The number of days after a password expires until the account is permanently disabled. A
        value of 0 disables the account as soon as the password has expired, and a value of -1
        Example: -K PASS_MAX_DAYS=-1 can be used when creating system account to turn off password
        aging, even though system account has no password at all. Multiple -K options can be
    -p, --password PASSWORD
        The encrypted password, as returned by crypt(3). The default is to disable the password.
        Note: This option is not recommended because the password (or encrypted password) will be
        You should make sure the password respects the system's password policy.
        The number of days after a password has expired before the account will be disabled.
        started in /etc/group (with the same name, same password, and same GID).
        The maximum number of days a password may be used. If the password is older than this, a
        password change will be forced. If not specified, -1 will be assumed (which disables the
        The minimum number of days allowed between password changes. Any password changes attempted
        The number of days warning given before a password expires. A zero means warning is given
        Shadow password suite configuration.
        can't update password file
[root@b5885d1b07cf mydir]#
```

```
[root@b5885d1b07cf mydir]# diff /var/log/anaconda/syslog ~/mydir/securecopy.txt
208c208
< 14:16:33,624 INFO kernel:ACPI: PCI Root Bridge [PCI0] (domain 0000 [bus 00-ff])
---
> 14:16:33,624 INFO kernel:ACPI: PCI Abeer Bridge [PCI0] (domain 0000 [bus 00-ff])
241,245c241,245
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [io   0x0000-0x0cf7 window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [io   0x0d00-0xffff window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [mem 0x000a0000-0x000bffff window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [mem 0xc0000000-0xfebfffff window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [bus 00-ff]
---
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Abeer bus resource [io   0x0000-0x0cf7 window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Abeer bus resource [io   0x0d00-0xffff window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Abeer bus resource [mem 0x000a0000-0x000bffff window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Abeer bus resource [mem 0xc0000000-0xfebfffff window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Abeer bus resource [bus 00-ff]
448c448
< 14:16:33,659 INFO systemd:Reached target Initrd Root Device.
---
> 14:16:33,659 INFO systemd:Reached target Initrd Abeer Device.
519c519
< 14:16:38,726 WARNING rpc.statd:Running as root.  chown /var/lib/nfs/statd to choose different user
---
> 14:16:38,726 WARNING rpc.statd:Running as Abeer.  chown /var/lib/nfs/statd to choose different user
584c584
< 14:16:39,385 INFO NetworkManager:<info>  [1631715399.3855] auth[0x557aa18666a0]: create auth-manager: D
us connection not available. Polkit is disabled and only root will be authorized.
---
> 14:16:39,385 INFO NetworkManager:<info>  [1631715399.3855] auth[0x557aa18666a0]: create auth-manager: D
us connection not available. Polkit is disabled and only Abeer will be authorized.
645,646c645,646
< 14:16:49,128 INFO systemd:Reached target Initrd Root File System.
< 14:16:49,128 INFO systemd:Starting Reload Configuration from the Real Root...
---
> 14:16:49,128 INFO systemd:Reached target Initrd Abeer File System.
> 14:16:49,128 INFO systemd:Starting Reload Configuration from the Real Abeer...
649c649
< 14:16:49,216 INFO systemd:Started Reload Configuration from the Real Root.
---
> 14:16:49,216 INFO systemd:Started Reload Configuration from the Real Abeer.
662c662
< 14:16:50,382 INFO systemd:Starting Plymouth switch root service...
---
> 14:16:50,382 INFO systemd:Starting Plymouth switch Abeer service...
669c669
< 14:16:50,384 INFO systemd:Stopped target Initrd Root Device.
---
```